

```
1 CREATE TABLE workers (  
2     worker_id INT PRIMARY KEY,  
3     worker_name VARCHAR(50),  
4     dep_id INT,  
5     dep_name VARCHAR(50),  
6     gender VARCHAR(10),  
7     working_place VARCHAR(50)  
8 );  
9  
10 INSERT INTO workers VALUES  
11 (1, 'niveditha', 101, 'IT', 'Female', 'Bengaluru'),  
12 (2, 'nive', 102, 'Finance', 'Female', 'Mumbai'),  
13 (3, 'Varshitha', 103, 'Marketing', 'Female', 'Delhi'),  
14 (4, 'Neha', 104, 'Sales', 'Female', 'Chennai'),  
15 (5, 'niranjana', 101, 'IT', 'Female', 'Bengaluru'),  
16 (6, 'Navya', 103, 'Marketing', 'Female', 'Mumbai'),  
17 (7, 'Tom', 106, 'Finance', 'Male', 'Chennai'),  
18 (8, 'Ram', 109, 'Marketing', 'Male', 'Bengaluru');  
19  
20 SELECT  
21     worker_name,  
22     UPPER(worker_name) AS Uppercase_Name,  
23     dep_id,  
24     dep_name,  
25     gender,  
26     working_place  
27 FROM workers;
```

Output:

worker_name	Uppercase_Name	dep_id	dep_name	gender	working_place
niveditha	NIVEDITHA	101	IT	Female	Bengaluru
nive	NIVE	102	Finance	Female	Mumbai
Varshitha	VARSHITHA	103	Marketing	Female	Delhi
Neha	NEHA	104	Sales	Female	Chennai
niranjana	NIRANJANA	101	IT	Female	Bengaluru
Navya	NAVYA	103	Marketing	Female	Mumbai
Tom	TOM	106	Finance	Male	Chennai
Ram	RAM	109	Marketing	Male	Bengaluru

Output:

worker_name	Lowercase_Name	dep_id	dep_name	gender	working_place
niveditha	niveditha	101	IT	Female	Bengaluru
nive	nive	102	Finance	Female	Mumbai
Varshitha	varshitha	103	Marketing	Female	Delhi
Neha	neha	104	Sales	Female	Chennai
niranjana	niranjana	101	IT	Female	Bengaluru
Navya	navya	103	Marketing	Female	Mumbai
Tom	tom	106	Finance	Male	Chennai
Ram	ram	109	Marketing	Male	Bengaluru

```
CREATE TABLE workers (  
    worker_id INT PRIMARY KEY,  
    worker_name VARCHAR(50),  
    dep_id INT,  
    dep_name VARCHAR(50),  
    gender VARCHAR(10),  
    working_place VARCHAR(50)  
);
```

```
INSERT INTO workers VALUES  
(1, 'niveditha', 101, 'IT', 'Female', 'Bengaluru'),  
(2, 'nive', 102, 'Finance', 'Female', 'Mumbai'),  
(3, 'Varshitha', 103, 'Marketing', 'Female', 'Delhi'),  
(4, 'Neha', 104, 'Sales', 'Female', 'Chennai'),  
(5, 'niranjana', 101, 'IT', 'Female', 'Bengaluru'),  
(6, 'Navya', 103, 'Marketing', 'Female', 'Mumbai'),  
(7, 'Tom', 106, 'Finance', 'Male', 'Chennai'),  
(8, 'Ram', 109, 'Marketing', 'Male', 'Bengaluru');
```

```
SELECT  
    worker_name,  
    LOWER(worker_name) AS Lowercase_Name,  
    dep_id,  
    dep_name,  
    gender,  
    working_place  
FROM workers;
```

```
CREATE TABLE workers (  
    worker_id INT PRIMARY KEY,  
    worker_name VARCHAR(50),  
    dep_id INT,  
    dep_name VARCHAR(50),  
    gender VARCHAR(10),  
    working_place VARCHAR(50)  
);
```

```
INSERT INTO workers VALUES  
(1, 'niveditha', 101, 'IT', 'Female', 'Bengaluru'),  
(2, 'nive', 102, 'Finance', 'Female', 'Mumbai'),  
(3, 'Varshitha', 103, 'Marketing', 'Female', 'Delhi'),  
(4, 'niranjana', 104, 'Sales', 'Female', 'Chennai'),  
(5, 'Spoorthi', 101, 'IT', 'Female', 'Bengaluru'),  
(6, 'Navya', 103, 'Marketing', 'Female', 'Mumbai');
```

```
SELECT  
    worker_name,  
    LENGTH(worker_name) AS Length_Name,  
    dep_id,  
    dep_name,  
    gender,  
    working_place  
FROM workers;
```

Output:

worker_name	Length_Name	dep_id	dep_name	gender	working_place
niveditha	9	101	IT	Female	Bengaluru
nive	4	102	Finance	Female	Mumbai
Varshitha	9	103	Marketing	Female	Delhi
niranjana	9	104	Sales	Female	Chennai
Spoorthi	8	101	IT	Female	Bengaluru
Navya	5	103	Marketing	Female	Mumbai

```
1 CREATE TABLE workers (  
2     worker_id INT PRIMARY KEY,  
3     worker_name VARCHAR(50),  
4     dep_id INT,  
5     dep_name VARCHAR(50),  
6     gender VARCHAR(10),  
7     working_place VARCHAR(50)  
8 );  
9  
10 INSERT INTO workers VALUES  
11 (1, 'niveditha', 101, 'IT', 'Female', 'Bengaluru'),  
12 (2, 'nive', 102, 'Finance', 'Female', 'Mumbai'),  
13 (3, 'Varshitha', 103, 'Marketing', 'Female', 'Delhi'),  
14 (4, 'Neha', 104, 'Sales', 'Female', 'Chennai'),  
15 (5, 'niranjana', 101, 'IT', 'Female', 'Bengaluru'),  
16 (6, 'Navya', 103, 'Marketing', 'Female', 'Mumbai');  
17  
18 SELECT  
19     worker_name,  
20     CONCAT(worker_name, ' - ', working_place) AS Name_Place,  
21     dep_id,  
22     dep_name,  
23     gender  
24 FROM workers;
```

Output:

worker_name	Name_Place	dep_id	dep_name	gender
niveditha	niveditha - Bengaluru	101	IT	Female
nive	nive - Mumbai	102	Finance	Female
Varshitha	Varshitha - Delhi	103	Marketing	Female
Neha	Neha - Chennai	104	Sales	Female
niranjana	niranjana - Bengaluru	101	IT	Female
Navya	Navya - Mumbai	103	Marketing	Female

```
CREATE TABLE workers (  
    worker_id INT PRIMARY KEY,  
    worker_name VARCHAR(50),  
    dep_id INT,  
    dep_name VARCHAR(50),  
    gender VARCHAR(10),  
    working_place VARCHAR(50)  
);
```

```
INSERT INTO workers VALUES  
(1, 'niveditha', 101, 'IT', 'Female', 'Bengaluru'),  
(2, 'nive', 102, 'Finance', 'Female', 'Mumbai'),  
(3, 'Varshitha', 103, 'Marketing', 'Female', 'Delhi'),  
(4, 'niranjana', 104, 'Sales', 'Female', 'Chennai'),  
(5, 'Spoorthi', 101, 'IT', 'Female', 'Bengaluru'),  
(6, 'Navya', 103, 'Marketing', 'Female', 'Mumbai');
```

```
SELECT  
    worker_name,  
    SUBSTRING(worker_name, 1, 3) AS Substring_Name,  
    dep_id,  
    dep_name,  
    gender,  
    working_place  
FROM workers;
```

worker_name	Substring_Name	dep_id	dep_name	gender	working_place
niveditha	niv	101	IT	Female	Bengaluru
nive	niv	102	Finance	Female	Mumbai
Varshitha	Var	103	Marketing	Female	Delhi
niranjana	nir	104	Sales	Female	Chennai
Spoorthi	Spo	101	IT	Female	Bengaluru
Navya	Nav	103	Marketing	Female	Mumbai

```
CREATE TABLE workers (  
    worker_id INT PRIMARY KEY,  
    worker_name VARCHAR(50),  
    salary DECIMAL(10,3)  
);
```

```
INSERT INTO workers VALUES  
(1, 'niveditha', 76000.567),  
(2, 'Tanisha', 58000.789),  
(3, 'Varshitha', 55000.456),  
(4, 'Neha', 62000.678),  
(5, 'Spoorthi', 66000.345),  
(6, 'Navya', 79000.891);
```

```
SELECT  
    worker_name,  
    salary,  
    ROUND(salary) AS Rounded_Salary  
FROM workers;
```

```
CREATE TABLE workers (  
    worker_id INT PRIMARY KEY,  
    worker_name VARCHAR(50),  
    salary DECIMAL(10,3)  
);
```

```
INSERT INTO workers VALUES  
(1, 'niveditha', 76000.567),  
(2, 'Tanisha', 58000.789),  
(3, 'Varshitha', 55000.456),  
(4, 'Neha', 62000.678),  
(5, 'Spoorthi', 66000.345),  
(6, 'Navya', 79000.891);
```

```
SELECT  
    worker_name,  
    salary,  
    CEIL(salary) AS Ceiling_Salary  
FROM workers;
```

Output:

worker_name	salary	Rounded_Salary
niveditha	76000.567	76001
Tanisha	58000.789	58001
Varshitha	55000.456	55000
Neha	62000.678	62001
Spoorthi	66000.345	66000
Navya	79000.891	79001

Output:

worker_name	salary	Ceiling_Salary
niveditha	76000.567	76001
Tanisha	58000.789	58001
Varshitha	55000.456	55001
Neha	62000.678	62001
Spoorthi	66000.345	66001
Navya	79000.891	79001

```
CREATE TABLE workers (  
    worker_id INT PRIMARY KEY,  
    worker_name VARCHAR(50),  
    salary DECIMAL(10,3)  
);
```

```
INSERT INTO workers VALUES  
(1, 'niveditha', 76000.567),  
(2, 'Tanisha', 58000.789),  
(3, 'Varshitha', 55000.456),  
(4, 'Neha', 62000.678),  
(5, 'Spoorthi', 66000.345),  
(6, 'Navya', 79000.891);
```

```
SELECT  
    worker_name,  
    salary,  
    FLOOR(salary) AS Floor_Salary  
FROM workers;
```

Output:

worker_name	salary	Floor_Salary
niveditha	76000.567	76000
Tanisha	58000.789	58000
Varshitha	55000.456	55000
Neha	62000.678	62000
Spoorthi	66000.345	66000
Navya	79000.891	79000

```
CREATE TABLE workers (  
    worker_id INT PRIMARY KEY,  
    worker_name VARCHAR(50),  
    salary DECIMAL(10,3)  
);
```

```
INSERT INTO workers VALUES  
(1, 'niveditha', 76000.567),  
(2, 'Tanisha', 58000.789),  
(3, 'Varshitha', 55000.456),  
(4, 'Neha', 62000.678),  
(5, 'Spoorthi', 66000.345),  
(6, 'Navya', 79000.891);
```

```
SELECT  
    worker_name,  
    salary,  
    MOD(salary, 100) AS Salary_Remainder  
FROM workers;
```

Output:

worker_name	salary	Salary_Remainder
niveditha	76000.567	0.567
Tanisha	58000.789	0.789
Varshitha	55000.456	0.456
Neha	62000.678	0.678
Spoorthi	66000.345	0.345
Navya	79000.891	0.891

```
CREATE TABLE workers (  
    worker_id INT PRIMARY KEY,  
    worker_name VARCHAR(50),  
    salary DECIMAL(10,3)  
);
```

```
INSERT INTO workers VALUES  
(1, 'niveditha', 76000.567),  
(2, 'Tanisha', -58000.789),  
(3, 'Varshitha', 55000.456),  
(4, 'Neha', -62000.678),  
(5, 'Spoorthi', 66000.345),  
(6, 'Navya', 79000.891);
```

```
SELECT  
    worker_name,  
    salary,  
    ABS(salary) AS Absolute_Salary  
FROM workers;
```

Output:

worker_name	salary	Absolute_Salary
niveditha	76000.567	76000.567
Tanisha	-58000.789	58000.789
Varshitha	55000.456	55000.456
Neha	-62000.678	62000.678
Spoorthi	66000.345	66000.345
Navya	79000.891	79000.891

```
CREATE TABLE STUDENT (  
    Student_ID INT PRIMARY KEY,  
    Student_Name VARCHAR(50),  
    Date_of_Birth DATE  
);
```

```
INSERT INTO STUDENT VALUES  
(1, 'Manya', '2005-05-15'),  
(2, 'Tanisha', '2008-08-20'),  
(3, 'Varshitha', '2005-01-18'),  
(4, 'Neha', '2004-11-25'),  
(5, 'Spoorthi', '2005-03-18'),  
(6, 'Navya', '2004-07-12');
```

```
SELECT  
    Student_Name,  
    Date_of_Birth,  
    YEAR(Date_of_Birth) AS Birth_Year  
FROM STUDENT;
```

Output:

Student_Name	Date_of_Birth	Birth_Year
Manya	2005-05-15	2005
Tanisha	2008-08-20	2008
Varshitha	2005-01-18	2005
Neha	2004-11-25	2004
Spoorthi	2005-03-18	2005
Navya	2004-07-12	2004

```
CREATE TABLE STUDENT (  
    Student_ID INT PRIMARY KEY,  
    Student_Name VARCHAR(50),  
    Date_of_Birth DATE  
);
```

```
INSERT INTO STUDENT VALUES  
(1, 'niveditha', '2005-05-15'),  
(2, 'Tanisha', '2008-08-20'),  
(3, 'Varshitha', '2005-01-18'),  
(4, 'Neha', '2004-11-25'),  
(5, 'Spoorthi', '2005-03-18'),  
(6, 'Navya', '2004-07-12');
```

```
SELECT  
    Student_Name,  
    Date_of_Birth,  
    MONTH(Date_of_Birth) AS Birth_Month  
FROM STUDENT;
```

Output:

Student_Name	Date_of_Birth	Birth_Month
niveditha	2005-05-15	5
Tanisha	2008-08-20	8
Varshitha	2005-01-18	1
Neha	2004-11-25	11
Spoorthi	2005-03-18	3
Navya	2004-07-12	7

```
CREATE TABLE STUDENT (  
    Student_ID INT PRIMARY KEY,  
    Student_Name VARCHAR(50),  
    Date_of_Birth DATE  
);
```

```
INSERT INTO STUDENT VALUES  
(1, 'niveditha', '2005-05-15'),  
(2, 'Tanisha', '2008-08-20'),  
(3, 'Varshitha', '2005-01-18'),  
(4, 'Neha', '2004-11-25'),  
(5, 'Spoorthi', '2005-03-18'),  
(6, 'Navya', '2004-07-12');
```

```
SELECT  
    Student_Name,  
    Date_of_Birth,  
    DAY(Date_of_Birth) AS Birth_Day  
FROM STUDENT;
```

```
CREATE TABLE STUDENT (  
    Student_ID INT PRIMARY KEY,  
    Student_Name VARCHAR(50),  
    Date_of_Birth DATE  
);
```

```
INSERT INTO STUDENT VALUES  
(1, 'niveditha', '2005-05-15'),  
(2, 'Tanisha', '2008-08-20'),  
(3, 'Varshitha', '2005-01-18'),  
(4, 'Neha', '2004-11-25'),  
(5, 'Spoorthi', '2005-03-18'),  
(6, 'Navya', '2004-07-12');
```

```
SELECT  
    Student_Name,  
    Date_of_Birth,  
    TIMESTAMPDIFF(YEAR, Date_of_Birth, CURDATE()) AS Age  
FROM STUDENT;
```

+-----+-----+-----+		
Student_Name	Date_of_Birth	Birth_Day
+-----+-----+-----+		
niveditha	2005-05-15	15
Tanisha	2008-08-20	20
Varshitha	2005-01-18	18
Neha	2004-11-25	25
Spoorthi	2005-03-18	18
Navya	2004-07-12	12
+-----+-----+-----+		

Output:

Student_Name	Date_of_Birth	Age
niveditha	2005-05-15	21
Tanisha	2008-08-20	18
Varshitha	2005-01-18	21
Neha	2004-11-25	21
Spoorthi	2005-03-18	21
Navya	2004-07-12	22

```
CREATE TABLE STUDENT (  
    Student_ID INT PRIMARY KEY,  
    Student_Name VARCHAR(50),  
    Date_of_Birth DATE  
);  
  
INSERT INTO STUDENT VALUES  
(1, 'niveditha', '2005-05-15'),  
(2, 'Tanisha', '2008-08-20'),  
(3, 'Varshitha', '2005-01-18'),  
(4, 'Neha', '2004-11-25'),  
(5, 'Spoorthi', '2005-03-18'),  
(6, 'Navya', '2004-07-12');  
  
SELECT CURDATE() AS Todays_Date;
```

STDIN

Input for the program (Optional)

Output:

```
+-----+  
| Todays_Date |  
+-----+  
| 2026-10-02 |  
+-----+
```

```
1 CREATE TABLE STUDENT (  
2     Student_ID INT PRIMARY KEY,  
3     Student_Name VARCHAR(50),  
4     Date_of_Birth DATE  
5 );
```

```
7 INSERT INTO STUDENT VALUES  
8 (1, 'niveditha', '2005-05-15'),  
9 (2, 'Tanisha', '2008-08-20'),  
0 (3, 'Varshitha', '2005-01-18'),  
1 (4, 'Neha', '2004-11-25'),  
2 (5, 'Spoorthi', '2005-03-18'),  
3 (6, 'Navya', '2004-07-12');
```

```
5 SELECT COUNT(*) AS Total_Students  
6 FROM STUDENT;
```

STDIN
Input for the program (Optional)

Output:

```
— +-----+  
  | Total_Students |  
  +-----+  
  |              6 |  
  +-----+
```

```

CREATE TABLE STUDENT (
    Student_ID INT PRIMARY KEY,
    Student_Name VARCHAR(50),
    Date_of_Birth DATE,
    Marks INT
);

INSERT INTO STUDENT VALUES
(1, 'niveditha', '2005-05-15', 85),
(2, 'Tanisha', '2008-08-20', 78),
(3, 'Varshitha', '2005-01-18', 92),
(4, 'Neha', '2004-11-25', 74),
(5, 'Spoorthi', '2005-03-18', 88),
(6, 'Navya', '2004-07-12', 81);

SELECT SUM(Marks) AS Total_Marks
FROM STUDENT;

```

STDIN

Input for the program (

Output:

```

+-----+
| Total_Marks |
+-----+
|           498 |
+-----+

```

```
CREATE TABLE STUDENT (  
    Student_ID INT PRIMARY KEY,  
    Student_Name VARCHAR(50),  
    Date_of_Birth DATE,  
    Marks INT  
);  
  
INSERT INTO STUDENT VALUES  
(1, 'niveditha', '2005-05-15', 85),  
(2, 'Tanisha', '2008-08-20', 78),  
(3, 'Varshitha', '2005-01-18', 92),  
(4, 'Neha', '2004-11-25', 74),  
(5, 'Spoorthi', '2005-03-18', 88),  
(6, 'Navya', '2004-07-12', 81);  
  
SELECT AVG(Marks) AS Average_Marks  
FROM STUDENT;
```

STDIN

Input for the program (Optional)

Output:

```
+-----+  
| Average_Marks |  
+-----+  
|      83.0000 |  
+-----+
```

```

CREATE TABLE STUDENT (
    Student_ID INT PRIMARY KEY,
    Student_Name VARCHAR(50),
    Date_of_Birth DATE,
    Marks INT
);

INSERT INTO STUDENT VALUES
(1, 'niveditha', '2005-05-15', 85),
(2, 'Tanisha', '2008-08-20', 78),
(3, 'Varshitha', '2005-01-18', 92),
(4, 'Neha', '2004-11-25', 74),
(5, 'Spoorthi', '2005-03-18', 88),
(6, 'Navya', '2004-07-12', 81);

SELECT MAX(Marks) AS Highest_Marks
FROM STUDENT;

```

STDIN

Input for the program (Op

Output:

```

+-----+
| Highest_Marks |
+-----+
|                | 92 |
+-----+

```

```
CREATE TABLE STUDENT (  
    Student_ID INT PRIMARY KEY,  
    Student_Name VARCHAR(50),  
    Date_of_Birth DATE,  
    Marks INT  
);
```

```
INSERT INTO STUDENT VALUES  
(1, 'niveditha', '2005-05-15', 85),  
(2, 'Tanisha', '2008-08-20', 78),  
(3, 'Varshitha', '2005-01-18', 92),  
(4, 'Neha', '2004-11-25', 74),  
(5, 'Spoorthi', '2005-03-18', 88),  
(6, 'Navya', '2004-07-12', 81);
```

```
SELECT MIN(Marks) AS Lowest_Marks  
FROM STUDENT;
```

STDIN

Input for the program (Optional)

Output:

```
+-----+  
| Lowest_Marks |  
+-----+  
|           74 |  
+-----+
```