

Grading Instructions — CDMP (Canadian Donation Map)

These are the steps a TA needs to run and grade the system. The recommended path uses Docker with a pre-built Mongo dump, so no manual data pipeline needs to be run. Full background is in [DOCKER.md](#) and [README.md](#) in the repo root; this page is the condensed grading path.

1. Prerequisites

- Docker Desktop installed and running
- The data handoff zip from Google Drive (contains the MongoDB dump and raw data). The current package name is referenced in [README.md](#) under "Docker and Data Handoff"; check that section for the most recent Google Drive link, since the package is refreshed periodically.

2. Clone and start the app

```
bash
git clone <repo-url>
cd course-project-nacss
```

Download the current handoff zip from Google Drive into the project root and unzip it:

```
bash
unzip -n course-project-nacss-drive-upload-<date>.zip
```

Confirm this file exists after unzipping:

```
text
mongo-dump/course_project_nacss.archive
```

Start the containers:

```
bash
docker compose up --build -d
```

3. Restore the database

```
bash
docker compose run --rm mongo-tools mongorestore --host mongo --drop
--archive=/dump/course_project_nacss.archive
```

Confirm the restore:

```
bash
docker compose --profile tools run --rm data-importer npm run check:data
```

Expected key counts:

```
text
Donation records: 5374039
Region stats: 8159
Postal-riding mappings: 3347996
Donation riding assignments: 5374039
```

4. Open and verify the app

- Frontend: <http://localhost:8080>
- Backend health check: <http://localhost:5001/api/health>

Stop the app when done grading:

```
bash
docker compose down
```

Do **not** run the "Full Data Rebuild Path" in [DOCKER.md](#) for grading; it is only needed to validate the raw data pipeline end to end and takes much longer. The Mongo dump restore above is the intended grading/demo path.

5. Testing public features

No login is required for:

- The national donation map, province drill-down, and riding-level maps
- Filters: party, year, donor type, and boundary-vintage bucket
- Search (national and riding views)
- Per-capita view toggle
- The riding summary panel (total donations, donor count, party breakdown, longitudinal trend)

6. Testing research features

There is no seeded researcher account in the Mongo dump, so create one through the app itself:

1. Go to [Research Login](#) and Click on "Sign Up"
2. Enter any email ending in [.ca](#) or [.edu](#) (e.g. [ta@utoronto.ca](#)) and a password (8+ characters).
3. Log in with those credentials you made in step 2.
4. Accept the privacy agreement when prompted; this is required before any individual-level data is shown.

5. You now have access to the research dashboard, where you can:
 - Filter individual donation records by donor type, province, party, year, riding, and donor name search
 - Page through results
 - View the analytics panel (top ridings by donation count, donation amount/concentration distribution) for the current filter set
 - Export the current filtered result set as a CSV
 - View and update account info, including changing your password

All logins, queries, and exports are written to the activity log for audit purposes; there is no dedicated admin UI to view this log in the current release, but the underlying records live in the [ActivityLog](#) collection in MongoDB if you want to inspect them directly (e.g. via [mongosh](#) or [mongo-tools](#)).

`server/.env` needs `JWT_SECRET=<any string>` set for authentication to work; this is already configured for the Docker setup and does not need to be touched for grading (Docker does not use `server/.env` at all, see [DOCKER.md](#)).

7. Running the automated test suites

These do not require Docker or a database connection.

```
bash
# Backend (Jest + Supertest)
cd server
npm install
npm test
bash
# Frontend unit tests (Jest)
cd client
npm install
npm test
```

End-to-end tests require the app to be running via Docker on `http://localhost:8080` first:

```
bash
docker compose up -d
cd client
npx cypress run
```

8. Troubleshooting

- **Restore fails with "archive not found"** — confirm the file is at [mongo-dump/course_project_nacss.archive](#).
- **Map or dashboard APIs return empty data** — restore the Mongo dump again.

- **Docker build fails in `client`** — run `cd client && npm install` locally to refresh dependencies, then rebuild.
- **Need to reset all data** — `docker compose down -v`, then restore the dump again.

Full detail on every command above, plus the full pipeline rebuild path, is in [DOCKER.md](#).