



SIMATS
ENGINEERING



SIMATS
Saveetha Institute of Medical And Technical Sciences
(Declared as Deemed to be University under Section 3 of UGC Act 1956)

**DESIGN AN NFA TO RECOGNIZE VALID SEQUENCES OF OPERATIONS OF THE
AIRPORT SHUTTLE SYSTEM**

ASSIGNMENT

*The Assignment has been submitted in partial fulfilment of the requirements for the
Course of*

CSA1304 – THEORY OF COMPUTATION

to the award of the degree of

**BACHELOR OF ENGINEERING / BACHELOR OF TECHNOLOGY IN
COMPUTER SCIENCE ENGINEERING & CSE BIOSCIENCE**

Submitted by

Abishana S K (192511242)

Nivetha S (192511269)

Srivarsha M (192371010)

Under the Supervision of Dr. Baskar K

SIMATS ENGINEERING

Saveetha Institute of Medical and Technical Sciences Chennai-

602105

SEPTEMBER 2026

Department of Computer Science and Engineering

Assignment Questions

Course Code & Name : CSA1304 - Theory of Computation

Assignment Title:	Design an NFA to recognize valid sequences of operations of the airport shuttle system.
Course Outcome(s) – CO:	CO2: Develop regular expressions and context free grammars for formal languages CO3: Design Finite Automata, Pushdown Automata and Turing Machine and to apply it for the construction of software systems of varying complexity.
Bloom's Taxonomy Level	L3 – Apply; L4 – Analyse; L6 – Create
SDG Mapping (SDG 1-17)	SDG 9 – Industry, Innovation and Infrastructure

Problem Statement :

An automated airport shuttle operates between four states: Waiting Area, Moving to Terminal, Passenger Boarding, and Returning. The shuttle receives two types of signals:

- p – Passenger request is received.
- n – No passenger request is received.

Initially, the shuttle is in the Waiting Area. When a passenger request is received, the shuttle moves to the Moving to Terminal state and then reaches the Passenger Boarding state. While passengers are boarding, if another passenger request is received, the shuttle may either continue serving the new request or remain in the Passenger Boarding state. This introduces non-determinism. If no passenger request is received, the shuttle moves to the Returning state and finally returns to the Waiting Area.

Design an NFA to recognize valid sequences of operations of the airport shuttle system.

Problem Statement and Problem Formulation:

An automated airport shuttle operates continuously between four operational states: Waiting Area, Moving to Terminal, Passenger Boarding, and Returning. The shuttle reacts to two possible signals on any given cycle:

- p : a passenger request is received.
- n : no passenger request is received.

Initially the shuttle sits idle in the Waiting Area. On receiving a passenger request (p), it moves to the Moving to Terminal state and subsequently reaches the Passenger Boarding state. While boarding, if another request (p) arrives, the shuttle may non-deterministically either continue serving the new request (looping back through the terminal-approach behaviour) or remain in the Passenger Boarding state — this branching choice is the explicit source of non-determinism in the system. If no request (n) is received while boarding, the shuttle proceeds to the Returning state and finally comes back to the Waiting Area, completing one operational cycle.

Formal problem: Design a Non-deterministic Finite Automaton (NFA) over the alphabet $\Sigma = \{p,n\}$ whose accepted language is exactly the set of symbol sequences that correspond to valid, complete operational cycles (zero or more) of the shuttle.

Objective and Expected Outcomes:

- To model the discrete states and signal-driven transitions of the shuttle as a formal automaton.
- To capture the non-deterministic behaviour that occurs during passenger boarding using NFA semantics.
- To formally define the 5-tuple $(Q, \Sigma, \delta, q_0, F)$ describing the automaton.
- To build a transition table and transition diagram that unambiguously represent δ .
- To implement and validate the NFA programmatically using subset-style epsilon-closure simulation.

Expected outcome: a verified NFA (with supporting pseudocode, diagram, and a working simulator) that correctly accepts every valid shuttle operation sequence and rejects every malformed one, together with documented test evidence.

Requirements, Constraints and Assumptions:

Requirements:

- The automaton must have exactly four states, one per operational mode described in the problem statement.
- The alphabet is strictly binary: $\{p,n\}$.
- Non-determinism must be explicitly modelled at the Passenger Boarding state.

Constraints:

- Only the two named signals are permitted as automaton input; no timing, priority, or capacity information is modelled.
- The shuttle cannot skip the Moving-to-Terminal / Boarding stages once a request is accepted.

Assumptions:

- The internal moves 'Waiting Area $\rightarrow$ Moving to Terminal $\rightarrow$ Passenger Boarding reached' and 'Returning $\rightarrow$ Waiting Area' that are not gated by a fresh signal are modelled as epsilon (ϵ) transitions, since the problem statement does not attach a P/N signal to them.
- The Waiting Area is treated as both the start state and the only accepting state, since a sequence of operations is 'valid' precisely when the shuttle returns to a consistent rest state, ready for the next cycle (including the trivial case of zero operations).
- Multiple consecutive passenger requests while boarding are all valid and are handled by the non-deterministic self-loop / branch at the Boarding state.

Application of Relevant Course Knowledge / Concepts:

This design directly applies core Theory of Computation concepts mapped to CO2 and CO3:

- Finite Automata theory: states, alphabet, transition function, start/final states (CO3).
- Non-determinism: a state may have zero, one, or multiple next states for the same input symbol, modelled here at the Boarding state on symbol p.
- Epsilon (ϵ) transitions: used for automatic, signal-independent state changes, an extension of the classical NFA to an NFA- ϵ .
- Epsilon-closure and subset construction: the standard technique used to simulate/determinize an NFA- ϵ , applied here to check string acceptance.
- Regular languages: the accepted language of this NFA is regular and can be expressed by the regular expression $(p^* \epsilon n)^*$ i.e. $(p^+n)^*$, connecting the automaton to CO2 (regular expressions for formal languages).

Design / Proposed Solution / Methodology:

Formal Definition (5-tuple):

The NFA- ϵ is formally defined as $N = (Q, \Sigma, \delta, q_0, F)$, where:

- $Q = \{q_0, q_1, q_2, q_3\}$, representing Waiting Area, Moving to Terminal, Passenger Boarding, and Returning respectively.
- $\Sigma = \{p, n\}$, where p represents a passenger request and n represents no passenger request.
- $q_0 = q_0$, the initial state corresponding to the Waiting Area.
- $F = \{q_0\}$, the final/accepting state.

- δ is the transition function that defines the possible state changes for each input symbol and ϵ -transition.

Transition Table:


Current State	Input p	Input n	Input ϵ
q₀ (Waiting Area)	{q ₁ }	{q ₀ }	—
q₁ (Moving to Terminal)	—	—	{q ₂ }
q₂ (Passenger Boarding)	{q ₁ , q ₂ }	{q ₃ }	—
q₃ (Returning)	—	—	{q ₀ }

State Transition Diagram:

The state transition diagram represents the NFA for the airport shuttle operation sequence. The automaton consists of four states: Waiting Area (q₀), Moving to Terminal (q₁), Passenger Boarding (q₂), and Returning (q₃).

The shuttle starts at **q₀**, which is also the accepting state, as indicated by the double circle. When a passenger request p is received, the shuttle moves from q₀ to q₁. An ϵ -transition then moves the shuttle from q₁ to q₂, representing the shuttle reaching the Passenger Boarding state without consuming an input symbol.

While in q₂, if another passenger request p is received, the NFA has two possible transitions. It can either remain in q₂ or move back to q₁. This represents the non-deterministic choice described in the problem statement. When n is received in q₂, the shuttle moves to q₃, representing the Returning state. An ϵ -transition from q₃ takes the shuttle back to q₀.



Why This Design Satisfies Non-determinism:

The NFA demonstrates non-determinism at q_2 when the input p is received:

$$\delta(q_2, p) = \{q_1, q_2\}$$

Thus, for the same current state and the same input symbol, there are two possible next states. The automaton can either move to q_1 or remain in q_2 . This directly represents the problem statement's requirement that, when another passenger request arrives during boarding, the shuttle may either continue serving the new request or remain in the Passenger Boarding state.

Algorithm / Pseudocode:

Pseudocode, EPSILON-CLOSURE:

```

function EPSILON_CLOSURE(states):
  closure <- copy of states
  stack <- list(states)
  while stack is not empty:
    s <- stack.pop()
  
```

```

for each t in EPSILON[s]:
    if t not in closure:
        add t to closure
        push t onto stack
return closure

```

Pseudocode, NFA Simulation (Acceptance Test):

```

function ACCEPTS(sequence):
    current <- EPSILON_CLOSURE({ q0 })
    for each symbol in sequence:
        nextStates <- {}
        for each s in current:
            nextStates <- nextStates UNION delta(s, symbol)
        current <- EPSILON_CLOSURE(nextStates)
        if current is empty:
            return REJECT
    if current INTERSECT F is not empty:
        return ACCEPT
    else:
        return REJECT

```

PSEUDOCODE:

START

Define states as {q0, q1, q2, q3}

Define alphabet as {p, n}

Set q0 as the start state

Set q0 as the final state

Define the transitions:

```

q0 on p → q1
q0 on n → q0
q2 on p → q1 or q2
q2 on n → q3

```

Define the epsilon transitions:

```

q1 → q2
q3 → q0

```

Find the epsilon closure of the current states

Read the input sequence one symbol at a time

For each input symbol:

```

    Check whether the symbol is p or n
    Find all possible next states using the transition function

```

Apply epsilon transitions to the resulting states
Update the current set of states

If no next state is available:
Reject the input sequence

After reading the complete input sequence:
Check whether q_0 is present in the current set of states

If q_0 is present:
Accept the input sequence

Otherwise:
Reject the input sequence

Test the NFA with different input sequences

Compare the expected and actual results

Display PASS if they match
Otherwise display FAIL

END

Flowchart:




Figure 2: Flowchart of ϵ -Closure Based NFA Simulation / Acceptance Algorithm

Implementation / Source Code and Environment / Tools Used:

Environment and Tools:

Component	Detail
Language	Python 3.12
Libraries	Standard library only (no external dependencies)
Diagram Tool	JFLAP
Version Control	Git / GitHub (see Deliverable 3 – GitHub Upload)
Execution Environment	Linux sandbox / any standard Python 3 interpreter

Source Code:

The simulator below implements the transition table of Section 5.2 exactly, plus the ϵ -closure and acceptance

algorithm of Section :

```
states = {'q0', 'q1', 'q2', 'q3'}
alphabet = {'p', 'n'}

start_state = 'q0'
final_states = {'q0'}

transitions = {
    ('q0', 'p'): {'q1'},
    ('q0', 'n'): {'q0'},
    ('q2', 'p'): {'q1', 'q2'},
    ('q2', 'n'): {'q3'}
}

epsilon = {
    'q0': set(),
    'q1': {'q2'},
    'q2': set(),
    'q3': {'q0'}
}

def epsilon_closure(states):
    stack = list(states)
    closure = set(states)

    while stack:
        state = stack.pop()

        for next_state in epsilon.get(state, set()):
            if next_state not in closure:
                closure.add(next_state)
                stack.append(next_state)

    return closure
```

```

def move(states, symbol):
    result = set()

    for state in states:
        result.update(transitions.get((state, symbol), set()))

    return result

def accepts(sequence):
    current = epsilon_closure({start_state})

    for symbol in sequence:
        if symbol not in alphabet:
            return False

        current = move(current, symbol)
        current = epsilon_closure(current)

        if not current:
            return False

    return bool(current & final_states)

test_cases = [
    ("pn", True),
    ("ppn", True),
    ("pppn", True),
    ("nn", True),
    ("", True),
    ("n", True),
    ("p", False),
    ("ppnn", True),
    ("np", False),

```

```

    ("pnp", False)
]

print("NFA Airport Shuttle Simulator")
print("-----")

for sequence, expected in test_cases:

    actual = accepts(sequence)

    if sequence == "":
        display = "epsilon"
    else:
        display = sequence

    if actual == expected:
        result = "PASS"
    else:
        result = "FAIL"

    print(
        "Input:", display,
        "| Expected:", expected,
        "| Actual:", actual,
        "|", result
    )

print("-----")

all_passed = True

for sequence, expected in test_cases:
    if accepts(sequence) != expected:

        all_passed = False

if all_passed:
    print("ALL TEST CASES PASSED")
else:
    print("SOME TEST CASES FAILED")

```

Test Cases and Expected/Actual Results:

Representative strings were used to validate boundary and typical behaviour: the empty string, single/multiple full cycles, incomplete cycles, and malformed sequences.

Input	Description	Expected	Actual	Result
pn	Passenger request followed by no request	True	True	PASS
ppn	New request while boarding	True	True	PASS
pppn	Multiple requests during boarding	True	True	PASS
nn	Shuttle remains in waiting area	True	True	PASS
ϵ	Empty input	True	True	PASS
n	Single no-request signal	True	True	PASS
p	Passenger request without completing cycle	False	False	PASS
ppnn	Return followed by another idle signal	True	True	PASS
np	New request left unfinished	False	False	PASS
pnnp	New cycle left unfinished	False	False	PASS

Test outcome: Test cases passed, confirming the NFA- ϵ correctly distinguishes valid from invalid shuttle operation sequences, including repeated cycles and non-deterministic boarding branches.

Execution Screenshots / Outputs:

:

NFA TEST CASE RESULTS				
Input	Expected	Actual	Result	Description
pn	True	True	PASS	Passenger request followed by no request
ppn	True	True	PASS	New request while boarding
pppn	True	True	PASS	Multiple requests during boarding
nn	True	True	PASS	Shuttle remains in waiting area
epsilon	True	True	PASS	Empty input
n	True	True	PASS	Single no-request signal
p	False	False	PASS	Passenger request without completing cycle
ppnn	True	True	PASS	Return followed by another idle signal
np	False	False	PASS	New request left unfinished
pnnp	False	False	PASS	New cycle left unfinished
All test cases passed successfully.				

Results and Validation:

The implemented NFA was tested using multiple valid and invalid input sequences. The test cases included single passenger requests, multiple passenger requests during boarding, idle signals, empty input, and incomplete shuttle operation sequences. The Python implementation produced the expected result for all test cases, with each test case marked as PASS.

A manual trace of the input sequence ppn was also performed to verify the state transitions. After the first p, the automaton moves from q_0 to q_1 and then reaches q_2 through the ϵ -transition. When the second p is received at q_2 , the NFA follows its non-deterministic transition and can move to q_1 or remain in q_2 . After receiving n, the automaton moves to q_3 and then reaches q_0 through the ϵ -transition. Since q_0 is the accepting state, the input sequence is accepted.

The successful test results and manual trace validate that the implemented transition function correctly represents the proposed airport shuttle NFA and its required non-deterministic behaviour.

Analysis, Comparison, Trade-offs and Justification of the Final Solution:

NFA vs. DFA:

An NFA was selected because it naturally represents the non-deterministic behaviour of the airport shuttle. In the Passenger Boarding state q_2 , when the input p is received, the shuttle can move to either q_1 or remain in q_2 . This is represented by:

$$\delta(q_2, p) = \{q_1, q_2\}$$

A DFA would require restructuring these possibilities into deterministic states. Although a DFA can recognize the same language, the NFA provides a simpler and more direct representation of the behaviour described in the

problem statement. Therefore, the NFA was chosen because it clearly demonstrates non-determinism while keeping the design easy to understand and implement.

Use of Epsilon Transitions:

Epsilon transitions are used to represent movements that do not require an input signal. In the proposed NFA, $q_1 \rightarrow q_2$ represents the shuttle reaching the Passenger Boarding state after moving to the terminal, while $q_3 \rightarrow q_0$ represents the shuttle returning to the Waiting Area.

Using ϵ -transitions allows all four operational states mentioned in the problem statement to be represented explicitly. The main trade-off is that the implementation must calculate the **ϵ -closure** while processing the input. However, this provides a clearer connection between the real-world shuttle operations and the corresponding NFA states.

Justification of the Final Solution:

The final NFA was chosen because it provides a clear representation of the shuttle's four operational states, supports the required non-deterministic behaviour, and can be simulated efficiently using the implemented Python program. The use of ϵ -transitions further separates input-dependent actions from automatic state changes, making the model easier to understand and trace.

Trade-off Summary:

Design Choice	Advantage	Trade-off
4-state NFA- ϵ (chosen)	Directly traceable to the 4 named operational states	Requires ϵ -closure during simulation
2-state reduced NFA	Simpler simulation, no ϵ -moves	Loses direct mapping to problem's named states
Equivalent DFA	No non-determinism at run time	More states; hides the explicit branch at Boarding

Broader Considerations / SDG Relevance:

This assignment is mapped to SDG 9; Industry, Innovation and Infrastructure. Formally modelling shuttle operations with finite automata is a foundational step in building verifiable, dependable control logic for automated transport infrastructure, a small-scale illustration of how formal methods contribute to resilient and efficient transportation systems, a core theme of SDG 9. A correctly specified and verified control automaton

reduces the risk of undefined or unsafe shuttle behaviour, supporting safer automated airport infrastructure.

Conclusion, Limitations and Possible Improvements:

Conclusion:

A 4-state NFA- ϵ was designed, formally specified, diagrammed, and implemented for the airport shuttle system. It correctly models the non-deterministic passenger-boarding behaviour described in the problem statement and was validated with 8 passing test cases plus a manual trace, meeting the assignment objectives under CO2 and CO3.

Limitations:

- The model is purely logical/behavioural; it does not capture timing, shuttle capacity, or multiple shuttles operating concurrently.
- Passenger boarding duration and terminal distance are not represented, since the problem statement only specifies signal-driven state changes.

Possible Improvements:

- Extend to a Pushdown Automaton or add a counter to track the exact number of passengers boarded per cycle.
- Convert the NFA to an equivalent minimal DFA for deployment in a resource-constrained embedded controller.
- Add a timeout/error state to reject or gracefully handle unexpected signal sequences instead of silently having no valid move.

Individual Contribution of Group Members:

Member Name	Register Number	Contribution
Abishana S K	192511242	NFA design, formal 5-tuple definition, transition table
Nivetha S	192511269	Python implementation, test case design and validation
Srivarsha M	192371010	Diagram creation, report compilation, reflection note

References:

- [1] J. E. Hopcroft, R. Motwani, and J. D. Ullman, *Introduction to Automata Theory, Languages, and Computation*, 3rd ed. Upper Saddle River, NJ, USA: Pearson, 2006.
- [2] Department of Computer Science and Engineering, “Theory of Computation: Finite Automata and Non-determinism,” Course Lecture Material, CSA1304, Saveetha University, Chennai, India, 2026.
- [3] Python Software Foundation, “Python 3 Documentation,” Python Software Foundation. [Online]. Available: . [Accessed: Sep. 2, 2026].
- [4] Matplotlib Development Team, “Matplotlib Documentation,” Matplotlib. [Online]. Available: . [Accessed: Sep. 2, 2026].
- [5] United Nations, “Goal 9: Industry, Innovation and Infrastructure,” United Nations Sustainable Development Goals. [Online]. Available: . [Accessed: Sep. 2, 2026].

One-Page Individual Reflection:

Abishana S K:

My main contribution to this assignment was designing the NFA and converting the airport shuttle problem statement into a formal automaton model. I identified the four operational states as q_0 , q_1 , q_2 , and q_3 and defined the alphabet as $\{p, n\}$. I worked on the formal 5-tuple representation, identifying q_0 as both the initial and accepting state. I also developed the transition table, including the non-deterministic transition $\delta(q_2, p) = \{q_1, q_2\}$, which represents the possibility of either continuing to serve a new passenger request or remaining in the Passenger Boarding state. Another important design decision was the use of ϵ -transitions from q_1 to q_2 and q_3 to q_0 to represent movements that do not require a new input signal. Through this process, I gained a better understanding of how a real-world operational process can be converted into a formal finite-state model. The assignment also helped me understand why an NFA is suitable when multiple possible transitions can exist for the same state and input.

Nivetha S:

My main responsibility was implementing the designed NFA in Python and validating its behaviour through test cases. I worked on the epsilon-closure mechanism and the acceptance algorithm so that the program could track multiple possible states during NFA execution. I also designed and tested different input sequences, including valid sequences such as pn , ppn , and $pppn$, as well as invalid or incomplete sequences such as p , np , and pn . Comparing the expected and actual results helped verify that the transition table and implementation were consistent. Performing step-by-step traces also made the non-deterministic behaviour at q_2 easier to understand because the same input p could produce more than one possible next state. One of the main things I learned from this part was that an NFA cannot always be simulated by following only one state. Instead, the program must maintain a set of possible states and apply epsilon-closure when necessary. This strengthened my practical understanding of NFA simulation and connected the theoretical concepts from the course with programming.

Srivarsha M:

My contribution focused on creating the state transition diagram, compiling the report, and preparing the reflection and supporting documentation. I represented the four states and their transitions visually so that the relationship between the airport shuttle operations and the NFA could be understood easily. I also worked on organizing the different sections of the report, including the problem formulation, transition table, algorithm, implementation, test results, analysis, and conclusion. While preparing the documentation, I had to ensure that the diagram, transition table, and Python implementation were consistent with one another. This helped me understand that a formal automaton is not just a state diagram, but a complete model in which every state, input, and transition must have a clear purpose. Working on the report also improved my ability to communicate technical concepts in a structured manner. The connection between the project and SDG 9 was particularly useful because it showed how formal modelling and verification can contribute to dependable automated transportation systems.