Untitled0.ipynb - Colab
Google Colab support | PyCharm
Ask Gemini
colab.research.google.com/drive/1XVR9SXRE4qXvelwanErFW_QPnVtEgKfc#scrollTo=Ts4QMbwtE6lo
Colab is now part of Google AI Plans. Get upgraded compute power and a suite of new AI tools all in one bundle.
Explore the Plans

Untitled0.ipynb

[11] ✓ 0s

```
jug4 = 0
jug3 = 0

print("Initial State:", (jug4, jug3))

# Step 1: Fill the 3-gallon jug
jug3 = 3
print("Fill 3-gallon jug:", (jug4, jug3))

# Step 2: Pour water into the 4-gallon jug
jug4 = jug4 + jug3
jug3 = 0
print("Pour into 4-gallon jug:", (jug4, jug3))

# Step 3: Fill the 3-gallon jug again
jug3 = 3
print("Fill 3-gallon jug:", (jug4, jug3))

# Step 4: Pour until the 4-gallon jug is full
transfer = min(4 - jug4, jug3)
jug4 = jug4 + transfer
jug3 = jug3 - transfer
print("Pour water:", (jug4, jug3))

# Step 5: Empty the 4-gallon jug
jug4 = 0
print("Empty 4-gallon jug:", (jug4, jug3))

# Step 6: Pour the remaining water into the 4-gallon jug
jug4 = jug3
jug3 = 0
print("Final State:", (jug4, jug3))

print("Water in 4-gallon jug:", jug4, "gallons")
```

```
Initial State: (0, 0)
Fill 3-gallon jug: (0, 3)
Pour into 4-gallon jug: (3, 0)
```


28°C Light rain
Search
ENG IN
20:31 15-10-2026

Untitled0.ipynb - Colab
Google Colab support | PyCharm
Ask Gemini
colab.research.google.com/drive/1XVR9SXRE4qXvelwanErFW_QPnVtEgKfc#scrollTo=Ts4QMbwtE6lo
Colab is now part of Google AI Plans. Get upgraded compute power and a suite of new AI tools all in one bundle.
Explore the Plans
Commands
+ Code
+ Text
Run all
RAM
Disk

[12]
✓ 0s

```python
class MarsRover:
    def __init__(self):
        self.position = 0
        self.battery = 100
        self.samples = []

    def perceive(self, terrain, sample):
        print("Terrain:", terrain)
        print("Sample detected:", sample)

    def move(self):
        if self.battery >= 10:
            self.position += 1
            self.battery -= 10
            print("Rover moved to position:", self.position)
        else:
            print("Low battery! Rover cannot move.")

    def collect_sample(self, sample):
        if sample:
            self.samples.append(sample)
            print("Sample collected:", sample)
        else:
            print("No sample available.")

    def analyze_sample(self):
        if self.samples:
            print("Analyzing sample:", self.samples[-1])
            print("Sample analysis completed.")
        else:
            print("No samples to analyze.")

    def status(self):
        print("Position:", self.position)
        print("Battery:", self.battery, "%")
        print("Samples collected:", len(self.samples))


rover = MarsRover()

rover.perceive("Rocky", "Rock")
```

Variables
Terminal
8:30 PM
Python 3
28°C
Light rain
Search
ENG
IN
20:32
15-10-2026

Untitled0.ipynb - Colab
Google Colab support | PyCharm
Ask Gemini
colab.research.google.com/drive/1XVR9SXRE4qXvelwanErFW_QPnVtEgKfc#scrollTo=Ts4QMbwtE6lo
Colab is now part of Google AI Plans. Get upgraded compute power and a suite of new AI tools all in one bundle.
Explore the Plans
Commands
+ Code
+ Text
Run all
RAM
Disk

[12] ✓ 0s

```
rover.move()
rover.collect_sample("Rock")
rover.analyze_sample()
rover.status()
```

```
Terrain: Rocky
Sample detected: Rock
Rover moved to position: 1
Sample collected: Rock
Analyzing sample: Rock
Sample analysis completed.
Position: 1
Battery: 90 %
Samples collected: 1
```

[13] ✓ 0s

```
N = 8
board = [-1] * N

def is_safe(row, col):
    for previous_col in range(col):
        previous_row = board[previous_col]

        if previous_row == row:
            return False

        if abs(previous_row - row) == abs(previous_col - col):
            return False

    return True

def solve_queens(col):
    if col == N:
        return True

    for row in range(N):
        if is_safe(row, col):
            board[col] = row

            if solve_queens(col + 1):
                return True
```

Variables
Terminal
Start
8:30 PM
Python 3
28°C
Light rain
Search
ENG
IN
20:32
15-10-2026

Untitled0.ipynb - Colab
Google Colab support | PyCharm
Ask Gemini
colab.research.google.com/drive/1XVR9SXRE4qXvelwanErFW_QPnVtEgKfc#scrollTo=Ts4QMbwtE6lo
Colab is now part of Google AI Plans. Get upgraded compute power and a suite of new AI tools all in one bundle.
Explore the Plans
Commands
+ Code
+ Text
Run all
RAM
Disk

[13]
✓ 0s

```
            board[col] = -1

    return False

if solve_queens(0):
    print("Solution for 8 Queens Problem:")
    for row in range(N):
        for col in range(N):
            if board[col] == row:
                print("Q", end=" ")
            else:
                print(".", end=" ")
        print()

    print("\nQueen positions (row, column):")
    for col in range(N):
        print((board[col] + 1, col + 1))
else:
    print("No solution found.")
```

```
Solution for 8 Queens Problem:
Q . . . . . . .
. . . . . . Q .
. . . . Q . . .
. . . . . . . Q
. Q . . . . . .
. . . Q . . . .
. . . . . Q . .
. . Q . . . . .

Queen positions (row, column):
(1, 1)
(5, 2)
(8, 3)
(6, 4)
(3, 5)
(7, 6)
(2, 7)
(4, 8)
```

Untitled0.ipynb - Colab

Google Colab support | PyCha

Ask Gemini

colab.research.google.com/drive/1XVR9SXRE4qXvelwanErFW_QPnVtEgKfc#scrollTo=Ts4QMbwtE6lo

Colab is now part of Google AI Plans. Get upgraded compute power and a suite of new AI tools all in one bundle. Explore the Plans

Commands + Code + Text Run all

RAM Disk

[14] 1m

```
def ola_cab_booking():
    print("Welcome to OLA Cab Booking")

    source = input("Enter starting location: ")
    destination = input("Enter destination: ")

    cabs = {
        "Mini": 100,
        "Micro": 80,
        "Sedan": 150,
        "Shared": 60,
        "Prime": 200
    }

    print("\nAvailable Cab Types:")
    for cab, fare in cabs.items():
        print(cab, "- Rs.", fare)

    choice = input("\nEnter your preferred cab: ").title()

    if choice in cabs:
        print("\nBooking Details")
        print("Starting Location:", source)
        print("Destination:", destination)
        print("Selected Cab:", choice)
        print("Estimated Fare: Rs.", cabs[choice])

        confirm = input("Confirm booking? (yes/no): ").lower()

        if confirm == "yes":
            print("Cab booked successfully!")
            print("Your cab is on the way.")
        else:
            print("Booking cancelled.")
    else:
        print("Invalid cab type.")

ola_cab_booking()
```

```
Welcome to OLA Cab Booking
```

Variables Terminal

8:30 PM Python 3

28°C Light rain

Search

ENG IN

20:33 15-10-2026

Untitled0.ipynb - Colab
Google Colab support | PyCha
Ask Gemini
colab.research.google.com/drive/1XVR9SXRE4qXvelwanErFW_QPnVtEgKfc#scrollTo=Ts4QMbwtE6lo
Colab is now part of Google AI Plans. Get upgraded compute power and a suite of new AI tools all in one bundle.
Explore the Plans
Commands
+ Code
+ Text
Run all
RAM
Disk

```
Welcome to OLA Cab Booking
Enter starting location: salem
Enter destination: chennai

Available Cab Types:
Mini - Rs. 100
Micro - Rs. 80
Sedan - Rs. 150
Shared - Rs. 60
Prime - Rs. 200

Enter your preferred cab: mini

Booking Details
Starting Location: salem
Destination: chennai
Selected Cab: Mini
Estimated Fare: Rs. 100
Confirm booking? (yes/no): yes
Cab booked successfully!
Your cab is on the way.
```

Double-click (or enter) to edit

[15] ✓ 0s

```python
import heapq

def uniform_cost_search(graph, start, goal):
    priority_queue = [(0, start, [start])]
    visited = set()

    while priority_queue:
        cost, node, path = heapq.heappop(priority_queue)

        if node in visited:
            continue

        visited.add(node)

        print("Visiting:", node, "| Cost:", cost)

        if node == goal:
```

Variables
Terminal
8:30 PM
Python 3
28°C
Light rain
Search
ENG
IN
20:33
15-10-2026

Untitled0.ipynb - Colab
Google Colab support | PyCha
Ask Gemini
colab.research.google.com/drive/1XVR9SXRE4qXvelwanErFW_QPnVtEgKfc#scrollTo=Ts4QMbwtE6lo
Colab is now part of Google AI Plans. Get upgraded compute power and a suite of new AI tools all in one bundle.
Explore the Plans
Commands
+ Code
+ Text
Run all
RAM
Disk

[15]
0s

```
            print("Total cost:", cost)
            return path, cost

        for neighbor, edge_cost in graph.get(node, []):
            if neighbor not in visited:
                new_cost = cost + edge_cost
                new_path = path + [neighbor]

                heapq.heappush(
                    priority_queue,
                    (new_cost, neighbor, new_path)
                )

    print("No path found.")
    return None, float("inf")


# Example weighted graph
graph = {
    'S': [('A', 2), ('B', 5)],
    'A': [('B', 1), ('G', 7)],
    'B': [('G', 3)],
    'G': []
}

uniform_cost_search(graph, 'S', 'G')
```

```
Visiting: S | Cost: 0
Visiting: A | Cost: 2
Visiting: B | Cost: 3
Visiting: G | Cost: 6

Least-cost path: S -> A -> B -> G
Total cost: 6
(['S', 'A', 'B', 'G'], 6)
```

Variables
Terminal
8:30 PM
Python 3
28°C
Light rain
Search
ENG
IN
20:34
15-10-2026