# **Ansible Task-2**

# 1. Install Ansible-Navigator.

yum install python3-pip

python3 -m pip install ansible-navigator –user

echo 'export PATH=\$HOME/.local/bin:\$PATH' >> ~/.profile source ~/.profile

#### ansible-navigator

#### vim ansible-navigatoryml

```
ansible-navigator:
    execution-environment:
        image: ghcr.io/ansible/creator-ee:v0.22.0
        pull:
            policy: missing
        playbook-artifact:
        enable: false
```

2. Create a file called packages.yml in/home/sandy/ansible to install packages httpd, mod\_ssl, and mariadb.

## cd /home/sandy/ansible

vim packages.yml

```
ansible-navigator run -m stdout packages.yml
```

```
| Content | Cont
```

3. Create a playbook that changes the default target on all nodes to multi-user target. Do this in playbook file called target.yml in/home/sandy/ansible

### cd /home/sandy/ansible

vim target.yml

```
ansible-navigator run -m stdout target.yml
```

4. Create a playbook called issue.yml in /home/sandy/ansible which changes the file /etc/issue on all managed nodes and write "Development"

## cd /home/sandy/ansible

vim issue.yml

```
---
- name: lineinfile
hosts: all
tasks:
- name: add line to issue file
lineinfile:
    path: /etc/issue
    line: Development
```