Input and output instructions for the Agricultural Water Use (AG) Package for GSFLOW

The AG was developed for GSFLOW to simulate irrigation and water use by cultivated and natural plants. The AG Package works with the Streamflow-Routing (SFR2) and the Unsaturated Flow (UZF1) Packages and includes capabilities for simulating pumping wells like the WELL Package. Input required for simulating agricultural diversions, supplementary pumping, irrigation, and demand calculations are all specified within the AG Package input file. All exchanges between different packages (SFR2, UZF1, and AG) are calculated within the AG Package; however, the SFR2 and UZF1 Packages must be active to use their capabilities in conjunction with the AG Package. Diversion segments must be specified within the SFR2 Package to apply diverted water as irrigation. All data for supplementary and irrigation wells is specified within the AG Package input file; the AG Package calculates and applies its own boundary conditions to the groundwater flow equation for representing irrigation and/or supplementary wells.

The AG Package is activated by specifying a file type of "AG" within the MODFLOW-NWT Name file. The AG input file contains 4 different blocks of data, including 1) Options, 2) Time series, 3) Segment and Well Lists, and 4) Stress Period. Stress period data is used to vary agricultural practices during a simulation represented mechanically as the connectivity between segments and irrigation cells, supplemental wells and diversion segments, and wells and irrigation cells, as well as other input values that control agricultural water use.

Block 1: Simulation options

AG Package character variables can be specified in any order and must be proceeded and followed by the character variables OPTIONS and END, respectively.

```
Item 1: OPTIONS
Item 2: [NOPRINT]
       [IRRIGATION DIVERSION
                                   Numirrdiversions
                                                         Maxcellsdiversion]
       [IRRIGATION WELL
                                    Numirrwells
                                                         Maxcellswell]
       [IRRIGATION POND
                                   Numirrponds
                                                         Maxcellspond]
       [SUPPLEMENTAL WELL
                                   Numsupwells
                                                         Maxdiversions]
       [MAXWELL
                                    Nummaxwell]
       [MAXPOND
                                    Nummaxpond]
       [TABFILESWELL
                                           Numtabwell
                                                                Maxvalwell]
       [TABFILESPOND
                                           Numtabpond
                                                                Maxvalpond]
       [PHIRAMP]
                                    Accel]
       [ETDEMAND
       [TRIGGER]
       [TIMESERIES DIVERSION]
       [TIMESERIES WELL]
       [TIMESERIES POND]
       [TIMESERIES DIVERSIONET]
       [TIMESERIES_WELLET]
       [TIMESERIES PONDET]
       [DIVERSIONLIST
                                    Unit diversionlist]
       [WELLLIST
                                    Unit welllist]
       [WELLIRRLIST
                                    Unit wellirrlist]
       [PONDLIST
                                    Unit pondlist]
       [PONDIRRLIST
                                    Unit pondirrlist]
                                    Unit diversionirrlist]
       [DIVERSIONIRRLIST
                                    Unitcbc]
       [WELLCBC
```

Item 3: END

OPTIONS Character variable specified to indicate the beginning of the key word options.

NOPRINT Character variable that suppresses the printing of well lists.

IRRIGATION DIVERSION An optional character variable. When IRRIGATION DIVERSION is specified,

the option to use surface water (SW) for irrigation is activated.

Numirrdiversions An optional integer variable. When IRRIGATION DIVERSION is specified, the integer

variable Numirrdiversions also is specified. Numirrdiversions is the maximum number of

SFR2 diversion segments in any stress period that will be used for irrigation.

Maxcellsdiversion An optional integer variable. When IRRIGATION DIVERSION is specified, the integer

variable Maxcellsdiversion also is specified. Maxcellsdiversion is the maximum number of MODFLOW cells or PRMS HRUs that will receive irrigation from a single SFR2

diversion segment in any stress period.

IRRIGATION WELL An optional character variable. When IRRIGATION WELL is specified, the option to

use groundwater for irrigation is active.

Numirrwells An optional integer variable. When IRRIGATION WELL is specified, the integer

variable Numirrwells also is specified. Numirrwells is the maximum number of AG wells

in any stress period that will be used for irrigation.

IRRIGATION_POND An optional character variable. When IRRIGATION_POND is specified, the option to

use PRMS detention reservoirs for irrigation is active.

Numirrponds An optional integer variable. When IRRIGATION POND is specified, the integer

variable Numirrponds also is specified. Numirrponds is the maximum number of PRMS

detention reservoirs in any stress period that will be used for irrigation.

Maxcellspond An optional integer variable. When IRRIGATION_POND is specified, the integer

variable Maxellspond also is specified. Maxcellspond is the maximum number of PRMS HRUs that will receive irrigation from a single PRMS detention reservoir in any stress

period.

SUPPLEMENTAL WELL An optional character variable. When SUPPLEMENTAL WELL is specified,

the option to simulate supplemental groundwater for irrigation is active. The AG Package calculates supplemental GW pumping using the difference between the irrigation demand

and the surface water diversion.

Numsupwells An optional integer variable. When SUPPLEMENTAL_WELL is specified, the integer

variable Numsupwells also is specified. Numsupwells is the maximum number of

supplemental wells in any stress period that will pump groundwater.

Maxdiversions An optional integer variable. When SUPPLEMENTAL WELL is specified, the integer

variable Maxdiversions also is specified. Maxdiversions is the maximum number of

SFR2 diversion segments that are supplemented by a well.

MAXWELL An optional character variable. If IRRIGATION WELL or SUPPLEMENTAL WELL is

specified, then MAXWELL also is specified. MAXWELL is included to indicate that the maximum number of unique supplemental and irrigation wells used during a simulation

(Nummaxwell) also will be read.

Nummaxwell The maximum number of unique supplemental and irrigation wells used during a

simulation.

MAXPOND An optional character variable. If IRRIGATION POND is specified, then MAXPOND

also is specified. MAXPOND is included to indicate that the maximum number of unique PRMS detention reservoirs used during a simulation (Nummaxpond) also will be read.

Nummaxpond The maximum number of unique supplemental and irrigation wells used during a

simulation.

TABFILESWELL is included in order set pumping rates

using time series input files.

Numtabwell An integer variable equal to the number of individual TABFILES used to set pumping

rates. Numtabwell can be less than MAXWELL when using a single TABFILE for

multiple wells.

Maxvalwell An integer variable equal to the maximum number of values specified for any TABFILE.

TABFILESPOND An optional character variable. TABFILESPOND is included in order set pond maximum

withdrawal rates using time series input files.

Numtabpond An integer variable equal to the number of individual TABFILES used to set withdrawal

rates. Numtabpond can be less than MAXPOND when using a single TABFILE for

multiple ponds.

Maxvalpond An integer variable equal to the maximum number of values specified for any TABFILE.

PHIRAMP An optional character variable. PHIRAMP is included to specify the smoothing interval

used to change negative pumping rates to zero when the groundwater cell dewaters. This

variable only is used when the Newton Solver is active.

ETDEMAND An optional character variable. ETDEMAND is included in order to activate automatic

calculation of the net irrigation water requirement. ETDEMAND and TRIGGER cannot

be used in the same simulation.

Accel An real variable that controls the maximum change in the irrigation diversion or pumped

amount between iterations. Values between 0.5 and 10 work well.

TRIGGER An optional character variable. TRIGGER is included to activate the irrigation trigger

option. TRIGGER and ETDEMAND cannot be used in the same simulation.

TIMESERIES DIVERSION An optional character variable that activates the option for outputting diversions

flow rates for specified SFR2 segments used for irrigation. Additional details are

specified in the time series data input.

TIMESERIES_WELL An optional character variable for outputting well pumping rates for specified wells used

for irrigation. Additional details are specified in the time series data input.

TIMESERIES_POND An optional character variable for outputting detention reservoir diversion rates for

specified ponds used for irrigation. Additional details are specified in the time series data

input.

TIMESERIES DIVERSIONET An optional character variable for outputting irrigation applied to all cells/HRUs

supplied by 1 or more specified diversion segments. Additional details are specified in

the time series data input.

TIMESERIES_WELLET An optional character variable for outputting irrigation applied to all cells/HRUs supplied

by 1 or more specified wells. Additional details are specified in the time series data input.

TIMESERIES PONDET An optional character variable for outputting irrigation applied to all HRUs supplied by 1

or more specified ponds. Additional details are specified in the time series data input.

DIVERSIONLIST An optional character variable for outputting a list of all diversion segments and

diversion amounts used for irrigation in the AG Package when "SAVE BUDGET" or a

non-zero value for ICBCFL is specified in Output Control.

Unit diversionlist An optional integer variable that is the file unit number to which DIVERSIONLIST

output is written. This unit number must correspond to a file of type Data specified in the MODFLOW Name file. A negative value indicates output will be written to the LIST

file.

WELLLIST An optional character variable for outputting a list of all active wells in the AG Package

and pumped amounts when "SAVE BUDGET" or a non-zero value for ICBCFL is

specified in Output Control.

Unit_welllist An optional integer variable that is the file unit number to which WELLLIST output is

written. This unit number must correspond to a file of type Data specified in the MODFLOW Name file. A negative value indicates output will be written to the LIST

file.

PONDLIST An optional character variable for outputting a list of all active PRMS detention

reservoirs used for irrigation in the AG Package and diverted amounts when "SAVE

BUDGET" or a non-zero value for ICBCFL is specified in Output Control.

Unit_pondlist An optional integer variable that is the file unit number to which PONDLIST output is

written. This unit number must correspond to a file of type Data specified in the MODFLOW Name file. A negative value indicates output will be written to the LIST

file.

WELLIRRLIST An optional character variable for outputting a list of MODFLOW cells or PRMS HRUs

that are irrigated by AG wells and the irrigated amounts when "SAVE BUDGET" or a

non-zero value for ICBCFL is specified in Output Control.

Unit_wellirrlist An optional integer variable that is the file unit number to which WELLIRRLIST output

is written. This unit number must correspond to a file of type Data specified in the MODFLOW Name file. A negative value indicates output will be written to the LIST

file.

PONDIRRLIST An optional character variable for outputting a list of PRMS HRUs that are irrigated by

PRMS detention reservoirs and the irrigated amounts when "SAVE BUDGET" or a non-

zero value for ICBCFL is specified in Output Control.

Unit pondirrlist An optional integer variable that is the file unit number to which PONDIRRLIST output

is written. This unit number must correspond to a file of type Data specified in the MODFLOW Name file. A negative value indicates output will be written to the LIST

file.

DIVERSIONIRRLIST An optional character variable for outputting a list of MODFLOW cells or PRMS HRUs

irrigated by irrigation segments and the irrigated amounts when "SAVE BUDGET" or a

non-zero value for ICBCFL is specified in Output Control.

Unit diversionirrlist An optional integer variable that is the file unit number to which DIVERSIONIRRLIST

output is written. This unit number must correspond to a file of type Data specified in the MODFLOW Name file. A negative value indicates output will be written to the LIST

file.

WELLCBC An optional character variable for outputting cell-by-cell flow terms when "SAVE

BUDGET" or a non-zero value for ICBCFL is specified in Output Control.

Unit_cbc An optional integer variable that is the file unit number to which cell-by-cell unformatted

list output is written. This unit number must correspond to a file of type Data(binary)

specified in the MODFLOW Name file.

END Character variable specified to indicate the end of the character options.

Block 2: Time series output

Time series data can be written to separate formatted output files for selected SFR segments and AG wells used for irrigation. These files are of type "Data" and must be included in the MODFLOW Name file. Time series data are read only if time series character variables are specified in the character options section.

```
Item 4: [TIME SERIES]
```

Item 5: [DIVERSION Segmentnum₁ Unit diversion₁]

.

[DIVERSION Segmentnum_{numtimeseriesdiversion} Unit_diversion_{numtimeseriesdiversion}]

Item 6: [DIVERSIONET Segmentnum₁ Unit_diversionet₁]

.

[DIVERSIONET Segmentnum_{numtimeseriesdiversionet} Unit diversionet_{numtimeseriesdiversionet}]

Item 7: [WELL Wellnum₁ Unit well₁]

.

[WELL Wellnum_{numtimeserieswell} Unit_well_{numtimeserieswell}]

Welletnum Item 8: [WELLET Unit wellet]

Wellnum_{numtimeserieswellet} Unit wellet_{numtimeserieswellet}] [WELLET

Item 11: [WELLALL Unitwellall]

Item 12: [WELLETALL Unitwelletall]

Item 13: [POND Pondnum₁ Unit pond₁]

 $\lceil POND \ Pondnum_{numtimeseriespond}$ Unit_pond_{numtimeseriespond}]

Item 14: [PONDET Pondetnum Unit pondet]

[PONDET $Pondnum_{numtimeseries pondet} \\$

Unit_pondetnumtimeseriespondet]

Item 15: [PONDALL Unitpondall]

Item 16: [PONDETALL Unitpondetall]

Item 17: [END]

TIME SERIES Character variable specified to indicate the beginning of the time series data block.

DIVERSION Character variable indicating that irrigation information for a diversion will be written to a time series output file.

Segmentnum Integer variable that is the SFR2 segment number.

Unitdiversion Integer variable that is the formatted output file unit number.

DIVERSIONET Character variable indicating that crop ET for all cells/HRUs irrigated by a diversion will be written to a time series output file.

Segmentnum Integer variable that is the SFR2 segment number.

Unitdiversionet Integer variable that is the formatted output file unit number.

WELL Character variable indicating that irrigation information for a well will be written to a time series output file.

Wellnum Integer variable that is the AG well number.

Unitwell Integer variable that is the formatted output file unit number. This file is of type "Data" and is included in the MODFLOW Name file.

WELLET Character variable indicating that evapotranspiration information for a well will be written to a time series output file.

Welletnum Integer variable that is the AG well number.

Unitwellet Integer variable that is the formatted output file unit number. This file is of type "Data" and is included in the MODFLOW Name file.

WELLETALL Character variable indicating that evapotranspiration information summed for all wells will be written to a time series output file.

Unitwelletall Integer variable that is the formatted output file unit number. This file is of type "Data" and is included in the MODFLOW Name file.

WELLALL Character variable indicating that irrigation information summed for all wells will be written to a time series output file.

Unitwellall Integer variable that is the formatted output file unit number. This file is of type "Data" and is included in the MODFLOW Name file.

POND Character variable indicating that irrigation information for a pond will be written to a time series output file.

Pondnum Integer variable that is the HRU ID for the PRMS open detention reservoir for timeseries output.

Unitpond Integer variable that is the formatted output file unit number. This file is of type "Data" and is included in the MODFLOW Name file.

PONDET Character variable indicating that evapotranspiration information for a PRMS open detention reservoir will be written to a time series output file.

Pondetnum Integer variable that is the HRU ID number that contains the PRMS open detention reservoir.

Unitpondet Integer variable that is the formatted output file unit number. This file is of type "Data" and is included in the MODFLOW Name file.

PONDETALL Character variable indicating that evapotranspiration information summed for all open detention reservoirs will be written to a time series output file.

Unitpondetall Integer variable that is the formatted output file unit number. This file is of type "Data" and is included in the MODFLOW Name file.

PONDALL Character variable indicating that irrigation information summed for all open detention reservoirs will be written to a time series output file.

Unitpondall Integer variable that is the formatted output file unit number. This file is of type "Data" and is included in the MODFLOW Name file.

END Character variable specified to indicate the end of the time series data block.

Block 3: Segment, Well, and Pond lists

SFR segments used for irrigation during any stress period of a simulation must be listed within the SEGMENT LIST data block. Maximum segment diversion rates can be set for each time step using SFR TABFILES, and maximum diversion rates can be set for each stress period using the SFR input variable Q.

Item 12: [SEGMEMNT LIST]

Item 13: [SEGMENTNUMBER₁]

.

[SEGMENTNUMBER_{MAXNUMSEGS}]

Item 14: [END]

SEGMEMNT LIST Character variable specified to indicate irrigation diversion segments will be included in

simulation. All irrigation segments used in a simulation must be listed.

SEGMENTNUMBER₁ Integer value equal to the first irrigation segment used in a simulation.

SEGMENTNUMBER_{MAXNUMSEGS} Integer value equal to the last irrigation segment used in a simulation.

END Character variable specified to indicate the end segment list data block.

Wells used for irrigation, including those used to supplement surface water diversions, are defined within the WELL LIST. Well numbering is implicitly defined according to the order of wells in the WELL LIST, the first entry is well 1, numbered consecutively to the total number of wells used during a simulation. There are 2 options for specifying information in the WELL LIST. The first option uses TABFILES to vary the maximum pumping rate during a simulation, and the second option uses a single specified value for the maximum pumping rate that does not vary during the simulation.

Input instructions for AG Package TABFILES are included at the end of this document.

Item 15: [WELL LIST]

If character variable TABFILESWELL is specified in the OPTIONS block, then item 16a is read as a space delimited list in free format. Otherwise, item 16b is read.

```
Item 16a: [TABWELLUNIT<sub>1</sub> TABWELLVAL<sub>1</sub> TABWELLLAY<sub>1</sub> TABWELLROW<sub>1</sub>
```

 $TABWELLCOL_1$

.

If character variable TABFILES is not specified in the OPTIONS block then item 16b is read as a space delimited list in free format.

Item 16b: [WELLLAY₁ WELLROW₁ WELLCOL₁ Q₁]

.

 $[WELLAY_{Maxwell} \qquad WELLROW_{Maxwell} \qquad WELLCOL_{Maxwell} \qquad Q_{Maxwell}]$

Item 17: [END]

WELL LIST Character variable specified to indicate that AG wells will be included in a simulation.

TABWELLUNIT Integer variable equal to the unit number for the TABFILE used to specify pumping rates

for a well.

TABWELLVAL Integer variable equal to the maximum number of rows to be read from a TABFILE.

TABWELLLAY Integer variable equal to the layer number of the cell containing a well set using

TABFILES.

TABWELLROW Integer variable equal to the row number of the cell containing a well set using

TABFILES.

.

TABWELLCOL Integer variable equal to the column number of the cell containing a well set using

TABFILES.

WELLLAY Integer variable equal to the layer number of the cell containing a well.

WELLROW Integer variable equal to the row number of the cell containing a well.

WELLCOL Integer variable equal to the column number of the cell containing a well.

Q Real variable equal to the maximum pumping rate or applied pumping rate.

END Character variable specified to indicate the end of the well list data block.

PRMS open depression storage ponds used for irrigation are defined within the POND LIST. Pond identification numbers are equal to the HRU_ID. There are 2 options for specifying information in the POND LIST. The first option uses TABFILES to vary the maximum pond irrigation rates during a simulation, and the second option uses a single specified value for the maximum pond irrigation rate that does not vary during the simulation.

Input instructions for AG Package TABFILES are included at the end of this document.

Item 18: [POND LIST]

If character variable TABFILESPOND is specified in the OPTIONS block, then item 19a is read as a space delimited list in free format. Otherwise, item 19b is read.

```
Item 19a: [TABPONDUNIT<sub>1</sub> TABPONDVAL<sub>1</sub> TABPONDHRU<sub>1</sub>, TABPONDSEG<sub>1</sub>]
```

.

```
[TABPONDUNIT_{Numtabpond} \quad TABPONDVAL_{Numtabpond} \quad TABPONDHRU_{Numtabpond} \\ \quad TABPONDSEG_{Numtabpond}]
```

If character variable TABFILESPOND is not specified in the OPTIONS block, then item 19b is read as a space delimited list in free format.

```
Item 19b: [PONDHRU<sub>1</sub> QPOND<sub>1</sub> PONDSEG<sub>1</sub>]
```

.

[PONDHRU Maxpond QPONDMaxpond PONDSEG Maxpond]

Item 20: [END]

POND LIST Character variable specified to indicate that AG ponds will be included in a simulation.

TABPONDUNIT Integer variable equal to the unit number for the TABFILE used to specify maximum

pond irrigation rates.

TABPONDVAL Integer variable equal to the maximum number of rows to be read from a TABFILE.

TABPONDHRU Integer variable equal to the HRU ID that contains an open detention reservoir (pond)

used for irrigation.

TABPONDSEG SFR segment diversion number that supplies inflow to pond. TABPONDSEG is specified

when using TABFILES to set maximum pond irrigation amounts. This segment number

should not be included in the AG Package SEGMENT LIST. A value of zero

indicates that there is no segment inflow to pond during a simulation.

PONDHRU Integer variable equal to the HRU ID that contains an open detention reservoir (pond)

used for irrigation.

QPOND Real variable equal to the maximum irrigation rate provided by a pond.

PONDSEG SFR segment diversion number that supplies inflow to the pond. PONDSEG is specified

when TABFILES are NOT used to set maximum pond irrigation amounts. This segment number should not be included in the AG Package SEGMENT LIST. A value of zero

indicates that there is no segment inflow to pond during a simulation.

END Character variable specified to indicate the end of the well list data block.

Block 4: Stress period information

Character variables "STRESS PERIOD" and "END" are required for each stress period. There are 3 options for specifying stress period information: 1) use stress period data for irrigation segments, irrigation wells, irrigation ponds, or supplemental wells from previous stress period; 2) specify data for all active irrigation segments, irrigation wells, irrigation ponds, or supplemental wells for the stress period; or 3) set all irrigation segments, irrigation wells, or supplemental wells to inactive for the stress period. Combinations of these 3 options can be used for any stress period.

Items 21a and 25a are specified for MODFLOW simulations; items 21b and 25b are specified for GSFLOW simulations. Some values are not used for a simulation due to specifications in the OPTIONS block; dummy values must be specified for unused input variables.

STRESS PERIOD

Item 18: [IRRDIVERSION]

Item 19: [NUMIRRSEGSP]

Item 20: [SEGID NUMCELLSEG IRRPERIODSEG TRIGGERFACTSEG DUM]

```
Item 21a: [IRRROW DIVERSION 1
                                     IRRCOL DIVERSION 1 EFF FACT DIVERSION 1
FIELD FACT DIVERSION 1]
      FIELD FACT_ DIVERSION numcellseg]
                                            DUM DIVERSION 1
                                                                  EFF_FACT_ DIVERSION 1
Item 21b: [HRU ID DIVERSION 1
FIELD FACT DIVERSION 1]
      [HRU ID DIVERSION numhruseg DUM DIVERSION numhruseg EFF FACT DIVERSION numhruseg
FIELD FACT DIVERSION<sub>numhruseg</sub>]
Item 22: [IRRWELL]
Item 23: [NUMIRRWELLSP]
Item 24: [IRRWELLID NUMCELLWELL
                                           IRRPERIODWELL
                                                                 TRIGGERFACTWELL DUM]
Item 25a [IRRROW WELL<sub>1</sub>
                                 IRRCOL_WELL<sub>1</sub>
                                                           EFF_FACT_WELL<sub>1</sub>
FIELD_FACT_WELL 1]
     \lceil IRRROW\_WELL_{numcellwell}
                               IRRCOL WELL numcellwell
                                                          EFF_FACT_WELL numcellwell
FIELD_FACT_WELL numcellwell]
Item 25b [HRU ID WELL<sub>1</sub>
                                DUM WELL<sub>1</sub>
                                                      EFF FACT WELL<sub>1</sub>
FIELD_FACT_WELL 1]
     [HRU ID WELL numhruwell
                              DUM WELL numhruwell
                                                   EFF FACT WELL numbruwell
FIELD_FACT_WELL numhruwell]
Item 26: [SUPWELL] [SEG/POND]
Item 27: [NUMSUPWELLSP]
Item 28: [SUPWELLNUM
                            NUMSEGWELL/ NUMPONDWELL]
Item 29: [SEGWELLID<sub>1</sub>
                            FRACSUP<sub>1</sub>
                                            FRACSUPMAX<sub>1</sub>]
       \lceil SEGWELLID_{numsegwell}
                                                   FRACSUPMAX_{numsegwell}
                            FRACSUP<sub>numsegwell</sub>
Item 30: [IRRPOND]
Item 31: [NUMIRRPONDSP]
```

Item 32: [IRRPONDID NUMCELLPOND IRRPERIODPOND TRIGGERFACTPOND FLOWTHROUGHPOND]

Item 33a [IRRHRUID_POND₁ EFF_FACT_POND₁] FIELD_FACT_POND₁]

.

.

[IRRHRUID_POND numcellpond EFF_FACT_POND numcellpond FIELD_FACT_POND numcellpond]

 $Item \ 33b \ [HRU_ID_POND_1 \qquad \qquad DUM_POND_1 \qquad \qquad EFF_FACT_POND_1$

FIELD_FACT_POND 1]

.

 $[HRU_ID_POND_{numhrupond} \quad DUM_POND_{numhrupond} \quad EFF_FACT_POND_{numhrupond} \\ FIELD_FACT_POND_{numhrupond}]$

END

IRRDIVERSION An optional character variable. IRRDIVERSION can be specified if character variable IRRIGATION_DIVERSION is specified in the OPTIONS block.

NUMIRRSEGSP An integer variable equal to the number of SFR2 segments active during a stress period that will divert water to cells. If NUMIRRSEGSP < 0, irrigation segment data from the previous stress period will be used. If NUMIRRSEGSP = 0, all irrigation segments will be set to inactive.

SEGID An integer variable equal to the SFR2 segment number for the diversion used for irrigation.

NUMCELLSEG An integer variable equal to the total number of MODFLOW cells or PRMS HRUs that will be irrigated by SFR2 diversion segment SEGID.

IRRPERIODSEG A real variable equal to the length of time water will be diverted for a single irrigation event. Although this variable is specified for each SEGID, it only is used if the character variable TRIGGER is specified in the options block. Units for this variable are determined from the DIS file input variable ITMUNI. Values should be greater than or equal to the length of the largest model time step during irrigation periods.

TRIGGERFACTSEG A real variable between 0 and 1 that triggers an irrigation event. If TRIGGERFACTSEG is set to 0.5 then an irrigation event will start when ETa/ETo = 0.5. Although this variable is specified for each SEGID, it only is used if the character variable TRIGGER is specified in the options block.

IRRROW_DIVERSION An integer variable equal to the cell row number that will be irrigated by segment SEGID. This variable only is specified for MODFLOW-only simulations.

IRRCOL_DIVERSION An integer variable equal to the cell column number that will be irrigated by segment SEGID. This variable only is specified for MODFLOW-only simulations.

HRU_ID_ DIVERSION An integer variable equal to the HRU ID number that will be irrigated by segment SEGID. This variable only is specified for PRMS-only and GSFLOW simulations.

DUM DIVERSION An integer variable that must be specified but is not used and can be set to zero.

EFF_FACT_DIVERSION A real variable equal to the fraction of surface water applied to a cell that can be used to represent crop evapotranspiration and other field losses. If evapotranspiration is being simulated explicitly then set EFF_FACT_DIVERSION to zero.

FIELD_FACT_ DIVERSION A real variable equal to the fraction of the diverted water applied to a cell that is used to distribute a diversion among multiple cells. The sum of all FIELD_FACT_ DIVERSION values for a diversion should sum to 1.

IRRWELL An optional character variable. IRRWELL can be specified if character variable IRRIGATION WELL is specified in the OPTIONS block.

NUMIRRWELLSP An integer variable equal to the number of AG wells active during a stress period that will pump water for irrigation on MODFLOW cells or PRMS HRUs. If NUMIRRWELLSP < 0, irrigation well data from the previous stress period will be used. If NUMIRRWELLSP = 0, all irrigation wells will be set to inactive.

IRRWELLID An integer variable equal to the well identification number used to pump groundwater for irrigation.

NUMCELLWELL An integer variable equal to the total number of MODFLOW cells or PRMS HRUs that receive water from a well.

IRRPERIODWELL A real variable equal to the length of time water will be pumped for a single irrigation event. Although this variable is specified for each WELL, it only is used if the character variable TRIGGER is specified in the options block and for wells that are not SUP wells. Units for this variable are determined from the DIS file input variable ITMUNI. Values should be greater than or equal to the length of the largest model time step during irrigation periods.

TRIGGERFACTORWELL A real variable between 0 and 1.0 that triggers an irrigation event. If TRIGGERFACTORWELL is set to 0.5 then an irrigation event will start when ETa/ETo = 0.5. Although this variable is specified for each WELL, it only is used if the character variable TRIGGER is specified in the options block.

IRRROW_WELL An integer variable equal to the cell row number to which pumped water will be applied as irrigation. This variable only is specified for MODFLOW-only simulations.

IRRCOL_WELL An integer variable equal to the cell column number to which pumped water will be applied as irrigation. This variable only is specified for MODFLOW-only simulations.

HRU_ID_ WELL An integer variable equal to the HRU ID to which pumped water will be applied as irrigation. An integer variable that must be specified but is not used and can be set to zero. This variable only is specified for PRMS-only and GSFLOW simulations.

DUM DIVERSION An integer variable that must be specified but is not used and can be set to zero.

EFF_FACT_WELL A real variable equal to the fraction of groundwater applied to a cell that can be used to represent crop evapotranspiration and other field losses. If evapotranspiration is being simulated explicitly then set EFF_FACT_WELL to zero.

FIELD_FACT_WELL A real variable equal to the fraction of the groundwater applied to a cell that is used to distribute water pumped from a well among multiple cells. The sum of all FIELD_FACT_WELL values for a well should sum to 1.

SUPWELL An optional character variable indicating that supplemental well stress period data will be specified.

NUMSUPWELLSP An integer variable equal to the number of active supplementary wells during a stress period that will pump groundwater to meet the surface water shortfall for irrigation. If NUMSUPWELLSP < 0,

supplementary well data from the previous stress period will be used. If NUMSUPWELLSP =0, all supplementary wells will be set to inactive.

SUPWELLNUM An integer variable equal to the AG well number that supplements one or more surface water diversions.

NUMSEGWELL An integer variable equal to the number of SFR2 segments that will be supplemented by a well.

SEGWELLID An integer variable equal to the SFR2 segment number that will be supplemented by a well.

FRACSUP A real variable between 0 and 1 that is equal to the fraction of the surface water shortfall for segment SEGWELLID that will be supplemented by a well.

FRACSUPMAX A real variable between 0 and 1 that is equal to the fraction of the surface water demand that is used to calculate the net irrigation water requirement with supplemental groundwater pumping. Supplemental groundwater pumping (Q_{sup}) will be calculated as $Q_{sup} = FRACSUP * [FRACSUPMAX * <math>Q_{demand} - Q_{div}]$, where Q_{demand} is the specified surface water diversion rate for irrigation.

IRRPOND An optional character variable. IRRPOND can be specified if character variable IRRIGATION POND is specified in the OPTIONS block.

NUMIRRPONDSP An integer variable equal to the number of PRMS open detention reservoirs active during a stress period that will supply water for irrigation on PRMS HRUs. If NUMIRRPONDSP < 0, irrigation pond data from the previous stress period will be used. If NUMIRRPONDSP =0, all irrigation ponds will be set to inactive.

IRRPONDID An integer variable equal to the HRU_ID identification number for the HRU that contains an open detention reservoir used for irrigation.

NUMCELLPOND An integer variable equal to the total number of HRUs that receive irrigation from a pond.

IRRPERIODPOND A real variable equal to the length of time water will be supplied from a pond for a single irrigation event. Although this variable is specified for each pond, it only is used if the character variable TRIGGER is specified in the options block. Units for this variable are determined from the DIS file input variable ITMUNI. Values should be greater than or equal to the length of the largest model time step during irrigation periods.

TRIGGERFACTORPOND A real variable between 0 and 1.0 that triggers an irrigation event. If TRIGGERFACTORPOND is set to 0.5 then an irrigation event will start when ETa/ETo = 0.5. Although this variable is specified for each POND, it only is used if the character variable TRIGGER is specified in the options block.

FLOWTHROUGHPOND An integer flag that is used to select an option for calculating segment inflow to a pond. A value of zero means segment inflow to the pond is specified through the SFR variable "FLOW." A value of 1 means segment inflow to the pond will be calculated using the irrigation demand. Outflow from the pond will be set equal to inflow minus shortfall and applied to fields for irrigation. A value of 1 only can be used if ETDEMAND is specified in the Options block.

IRRROW_POND An integer variable equal to the cell row number to which pumped water will be applied as irrigation. This variable only is specified for MODFLOW-only simulations.

IRRCOL_POND An integer variable equal to the cell column number to which pumped water will be applied as irrigation. This variable only is specified for MODFLOW-only simulations.

HRU_ID_ POND An integer variable equal to the HRU ID to which pumped water will be applied as irrigation. An integer variable that must be specified but is not used and can be set to zero. This variable only is specified for PRMS-only and GSFLOW simulations.

DUM POND An integer variable that must be specified but is not used and can be set to zero.

EFF_FACT_POND A real variable equal to the fraction of groundwater applied to a cell that can be used to represent crop evapotranspiration and other field losses. If evapotranspiration is being simulated explicitly then set EFF_FACT_POND to zero.

FIELD_FACT_POND A real variable equal to the fraction of the groundwater applied to a cell that is used to distribute water diverted from a pond among multiple cells. The sum of all FIELD_FACT_POND values for a pond should sum to 1.

END Character variable specified to indicate the end of each stress period data block.

Input data for TABFILES

```
 \begin{array}{cccc} \text{Item 1: } [\text{TIME}_1 & & Q_1] \\ & \cdot & \\ & \cdot & \\ & \cdot & \\ & \cdot & \\ & [\text{TIME}_{\text{TABVAL}} & Q_{\text{TABVAL}}] \end{array}
```

TIME A real variable equal to the simulation time that the pumping rate Q will be used to interpolate the maximum or applied pumping rate for a time step. The pumping rate for a time step is calculated using linear interpolation. The units for TIME must be consistent with the DIS Package input variable ITMUNI. Q A real variable equal to the maximum pumping rate for supplementary wells or for simulations that include the character variable ETDEMAND, otherwise Q is the applied pumping rate that can be used for setting the irrigation demand for wells used for irrigation (IRRWELL). Pumping rates are set equal to the pumping rate at the end of the time interval

Water budget table

Table 1: Water budget for agricultural water use package, where inflows ("IN") are sources of groundwater from wells ("AG WELLS") and surface water diversions ("DIVERSION SEGMENTS") used for irrigation, and outflows ("OUT") are consumptive use of groundwater ("GW IRRIGATION") and surface water ("SW IRRIGATION"), groundwater return flows ("SYSTEM LOSSES GW") and surface water return flows ("SYSTEM LOSSES SW").

1	VOLUMETRIC BUDGET FOR ENT	IRE MODEL AT END	OF TIME STEP 15, STRESS	PERIOD 8
2				
3				
4	CUMULATIVE VOLUMES	L**3 RATE	S FOR THIS TIME STEP	L**3/T
5				
6				
7	IN:		IN:	
8				
9	AG WELLS =	11775075.0000	AG WELLS	= 8.9560
10	DIVERSION SEGMENTS =	153412592.0000	DIVERSION SEGMENTS	= 50.8780
11	GW IRRIGATION =	0.0000	GW IRRIGATION	= 0.0000
12	SW IRRIGATION =	0.0000	SW IRRIGATION	
13	SYSTEM LOSSES GW =	0.0000	SYSTEM LOSSES GW	= 0.0000
14	SYSTEM LOSSES SW =	0.0000	SYSTEM LOSSES SW	= 0.0000
15				
16	TOTAL IN =	165187664.0000	TOTAL IN	= 59.8340
17				
18	OUT:		OUT:	
19				
20	AG WELLS =	0.0000	AG WELLS	= 0.0000
21	DIVERSION SEGMENTS =	0.0000	DIVERSION SEGMENTS	= 0.0000
22	GW IRRIGATION =	11775075.0000	GW IRRIGATION	= 8.9560
23	SW IRRIGATION =	153415664.0000	SW IRRIGATION	= 50.8790
24	SYSTEM LOSSES GW =	0.0000	SYSTEM LOSSES GW	= 0.0000
25	SYSTEM LOSSES SW =	0.0000	SYSTEM LOSSES SW	= 0.0000
26				
27	TOTAL OUT =	165190736.0000	TOTAL OUT	= 59.8350
28				
29	IN - OUT =	-3072.0000	IN - OUT	= -1.0185E-03
30				
31	PERCENT DISCREPANCY =	-0.00	PERCENT DISCREPANCY	-0.00