

UROS-26 Investigating Comparative Performance of Numerical Integrators on a Hamiltonian Two-Body System Under Newtonian Mechanics

Mykyta Khomiakov

June 12, 2026

1 ABSTRACT

The celestial dynamics of the N -body problem are most commonly studied through a restricted set of numerical integration methods, often tracking only a limited range of physical variables. Existing literature focuses predominantly on symplectic integrators, including Leapfrog, Velocity Verlet, Symplectic Euler, and the fourth-order Runge-Kutta method. This paper presents a comparative evaluation of five numerical integration schemes: Explicit Euler, Symplectic Euler, Velocity Verlet, Leapfrog, and Runge-Kutta 4th Order with respect to energy conservation, linear and angular momentum conservation, and computational efficiency within a Hamiltonian framework. Building on this comparison, we further investigate a modification of the best-performing integrator, targeting improvements in energy, angular momentum, and orbital stability for the two-body problem. The trade-offs between numerical precision and computational cost introduced by this modification are examined in the context of a high-performance implementation. Our findings have broader implications for the simulation of celestial mechanics across a range of cosmological settings, with particular emphasis on two-body classical gravitational dynamics.

2 INTRODUCTION

When studying N -body celestial systems, selecting an appropriate numerical integration scheme is fundamental to obtaining accurate and meaningful results. Leapfrog and fourth-order Runge-Kutta (RK4) are routinely employed as standard integrators across modern computational astrophysics, particularly in non-chaotic regimes.

This paper investigates the two-body gravitational problem within the frameworks of Newtonian mechanics and Hamiltonian formalism. In classical mechanics, the Hamiltonian is a function describing the total energy

of a system in terms of its generalised coordinates and conjugate momenta, governing the time evolution of the system through Hamilton’s equations. This formalism is particularly well-suited to the study of orbital dynamics, as it naturally exposes conserved quantities such as energy and angular momentum against which numerical schemes can be rigorously evaluated.

We restrict our analysis to classical mechanics as defined by Newton and Kepler, applying the governing equations of the field accordingly. A high-performance simulation engine is developed in C++20 to carry out procedurally generated two-body simulations, with the engine exposed to Python 3.12 via a foreign function interface – a common and practical convention in scientific computing workflows. Simulation data is then analysed in Python to draw conclusions regarding integrator accuracy and computational efficiency.

Having identified the most suitable standard integrator, we subsequently construct a higher-order scheme and repeat the analysis under equivalent conditions. Final conclusions are drawn on the basis of energy and angular momentum conservation behaviour, alongside a comparison of computational cost across all tested methods.

3 ANALYTICAL SOLUTIONS

3.1 NORMALISED SYSTEM

Aligning with the goals of this research we will show the analytical solutions for a singular problem setup across five integration schemes under ten timesteps.

Before starting any calculations, it is required to apply the appropriate units of measurement. It was decided to apply a normalised system due to the ease of debugging and interpretation, numerical stability and avoiding the vulnerability of floating-point errors.

Hence why, the units are as follows:

- Distance – Astronomical Units (Earth to Sun Distance)
- Mass – Solar Masses
- Gravitational Attraction – $4\pi^2$
- Timestep – Years

Following studies a timestep of $\Delta t = 10^{-3}$ yr has been selected, since unstable integrators tend to converge later in the simulation producing more reasonable data. This allows tracking of convergences and energy preservation more accurately.

Due to the assumption of a normalised numerical system the value of Gravitational Attraction Constant (G) has to be derived from those systemic

values. Physics remains the same, while the measuring system modifies. Since the normalised system is based on the relationship between the Earth and the Sun, we can derive the value of G that complies with the numerical system.

Applying Newtonian gravity,

$$F = G \frac{m_1 m_2}{r^2}, \quad (1)$$

and the equation for circular motion,

$$F = \frac{m_2 v^2}{r}, \quad (2)$$

we obtain

$$\frac{m_2 v^2}{r} = G \frac{m_1 m_2}{r^2}. \quad (3)$$

Cancelling m_2 from both sides yields

$$v^2 = \frac{G m_1}{r}. \quad (4)$$

Since the circumference of a circular orbit is $2\pi r$, the orbital velocity can be expressed in terms of the orbital period T as

$$v = \frac{2\pi r}{T}. \quad (5)$$

Substituting this expression for v into Equation (3) gives

$$\left(\frac{2\pi r}{T} \right)^2 = \frac{G m_1}{r}. \quad (6)$$

Solving for T yields

$$T^2 = \frac{4\pi^2 r^3}{G m_1}. \quad (7)$$

Assuming a normalised system of units in which the orbital period, orbital radius, and central mass are all equal to unity ($T = r = m_1 = 1$), we obtain

$$1 = \frac{4\pi^2}{G}. \quad (8)$$

Rearranging gives

$$G = 4\pi^2. \quad (9)$$

3.2 ANALYTICAL PROBLEM

The problem definition is as follows: A star of one solar mass $M = 1 M_{\odot}$ is fixed at the origin. A planet orbiting the star is 333000^{-1} of solar mass and is placed at initial position $\vec{r}_0 = (2, 1)^T$ AU. All quantities are expressed in natural astronomical units: distances in AU, time in years, and mass in solar masses, with $G = 4\pi^2 \text{ AU}^3 \text{ yr}^{-2} M_{\odot}^{-1}$. The simulation procedurally generates two objects containing their mass and coordinates, while the rest of the calculations are presented through the later simulation.

3.3 INITIAL VALUES

Initial distance

The initial separation between the planet and the star is

$$r_0 = |\vec{r}_0| = \sqrt{x_0^2 + y_0^2} = \sqrt{2^2 + 1^2} = \sqrt{5} \approx 2.23606798 \text{ AU}. \quad (10)$$

Initial acceleration

Newton's law of gravity gives the acceleration per unit planet mass as

$$\vec{a} = -\frac{GM}{r^3} \vec{r}. \quad (11)$$

Substituting $G = 4\pi^2$, $M = 1$, $r_0 = \sqrt{5}$, $\vec{r}_0 = (2, 1)^T$:

$$\vec{a}_0 = -\frac{4\pi^2}{(\sqrt{5})^3} \begin{pmatrix} 2 \\ 1 \end{pmatrix} = -\frac{4\pi^2}{5\sqrt{5}} \begin{pmatrix} 2 \\ 1 \end{pmatrix} \approx \begin{pmatrix} -7.06211403 \\ -3.53105702 \end{pmatrix} \text{ AU yr}^{-2}. \quad (12)$$

The magnitude is $|\vec{a}_0| = 4\pi^2/5 \approx 7.8957 \text{ AU yr}^{-2}$.

Circular orbital velocity

For a circular orbit, gravitational acceleration exactly supplies centripetal acceleration:

$$v_c = \sqrt{\frac{GM}{r_0}} = \sqrt{\frac{4\pi^2}{\sqrt{5}}} \approx 4.20181926 \text{ AU yr}^{-1}. \quad (13)$$

The velocity is directed tangentially (perpendicular to $\vec{r}_0$, counter-clockwise):

$$\hat{t} = \frac{(-y_0, x_0)^T}{r_0} = \frac{1}{\sqrt{5}} \begin{pmatrix} -1 \\ 2 \end{pmatrix}, \quad \vec{v}_0 = v_c \hat{t} \approx \begin{pmatrix} -1.87911070 \\ 3.75822140 \end{pmatrix} \text{ AU yr}^{-1}. \quad (14)$$

Initial conserved quantities

The total mechanical energy (kinetic plus potential) per unit planet mass is

$$E_0 = \frac{1}{2}m|\vec{v}_0|^2 - \frac{GMm}{r_0} = -\frac{GMm}{2r_0} \approx -2.6509 \times 10^{-5} M_\odot \text{ AU}^2 \text{ yr}^{-2}, \quad (15)$$

and the scalar z -component of angular momentum is

$$L_0 = m(x_0 v_{y,0} - y_0 v_{x,0}) \approx 2.8215 \times 10^{-5} M_\odot \text{ AU}^2 \text{ yr}^{-1}. \quad (16)$$

3.4 FIRST TIMESTEP DERIVATION ($\Delta t = 10^{-3} \text{ yr}$)

We adopt a time step $\Delta t = 10^{-3} \text{ yr}$ and derive the first update for each integrator explicitly. Relative errors in the conserved quantities are defined as $\varepsilon_E = |E_n - E_0|/|E_0|$ and $\varepsilon_L = |L_n - L_0|/|L_0|$.

Explicit Euler

Update rule: $\vec{r}_{n+1} = \vec{r}_n + \Delta t \vec{v}_n$, $\vec{v}_{n+1} = \vec{v}_n + \Delta t \vec{a}_n$.

Step $n = 0 \rightarrow 1$:

$$\begin{aligned} \vec{r}_1 &= \begin{pmatrix} 2 \\ 1 \end{pmatrix} + 10^{-3} \begin{pmatrix} -1.87911070 \\ 3.75822140 \end{pmatrix} = \begin{pmatrix} 1.99812089 \\ 1.00375822 \end{pmatrix} \text{ AU}, \\ \vec{v}_1 &= \begin{pmatrix} -1.87911070 \\ 3.75822140 \end{pmatrix} + 10^{-3} \begin{pmatrix} -7.06211403 \\ -3.53105702 \end{pmatrix} = \begin{pmatrix} -1.88617281 \\ 3.75469034 \end{pmatrix} \text{ AU yr}^{-1}. \end{aligned}$$

Both position and velocity are updated using values from the same timestep, so this method is first-order accurate and does not conserve energy over time.

Symplectic Euler

Update rule: velocity is updated first, then position uses the updated velocity: $\vec{v}_{n+1} = \vec{v}_n + \Delta t \vec{a}_n$, $\vec{r}_{n+1} = \vec{r}_n + \Delta t \vec{v}_{n+1}$.

Step $n = 0 \rightarrow 1$:

$$\begin{aligned} \vec{v}_1 &= \begin{pmatrix} -1.87911070 \\ 3.75822140 \end{pmatrix} + 10^{-3} \begin{pmatrix} -7.06211403 \\ -3.53105702 \end{pmatrix} = \begin{pmatrix} -1.88617281 \\ 3.75469034 \end{pmatrix} \text{ AU yr}^{-1}, \\ \vec{r}_1 &= \begin{pmatrix} 2 \\ 1 \end{pmatrix} + 10^{-3} \begin{pmatrix} -1.88617281 \\ 3.75469034 \end{pmatrix} = \begin{pmatrix} 1.99811383 \\ 1.00375469 \end{pmatrix} \text{ AU}. \end{aligned}$$

Symplectic Euler is also first-order, but it preserves the symplectic structure of Hamiltonian mechanics, resulting in bounded (rather than drifting) energy errors.

Velocity Verlet

Update rule: $\vec{r}_{n+1} = \vec{r}_n + \Delta t \vec{v}_n + \frac{1}{2} \Delta t^2 \vec{a}_n$, $\vec{v}_{n+1} = \vec{v}_n + \frac{\Delta t}{2} (\vec{a}_n + \vec{a}_{n+1})$.

Step $n = 0 \rightarrow 1$:

$$\vec{r}_1 = \begin{pmatrix} 2 \\ 1 \end{pmatrix} + 10^{-3} \begin{pmatrix} -1.87911070 \\ 3.75822140 \end{pmatrix} + \frac{10^{-6}}{2} \begin{pmatrix} -7.06211403 \\ -3.53105702 \end{pmatrix} = \begin{pmatrix} 1.99811736 \\ 1.00375646 \end{pmatrix} \text{ AU}.$$

Then $\vec{a}_1$ is recomputed from $\vec{r}_1$, and

$$\vec{v}_1 = \begin{pmatrix} -1.87911070 \\ 3.75822140 \end{pmatrix} + \frac{10^{-3}}{2} \left[\begin{pmatrix} -7.06211403 \\ -3.53105702 \end{pmatrix} + \vec{a}_1 \right] = \begin{pmatrix} -1.88616949 \\ 3.75468371 \end{pmatrix} \text{ AU yr}^{-1}.$$

Leapfrog (Kick–Drift–Kick)

The Leapfrog integrator stores velocities at half-integer steps. The initialisation half-kick is:

$$\vec{v}_{1/2} = \vec{v}_0 + \frac{\Delta t}{2} \vec{a}_0 = \begin{pmatrix} -1.87911070 \\ 3.75822140 \end{pmatrix} + 5 \times 10^{-4} \begin{pmatrix} -7.06211403 \\ -3.53105702 \end{pmatrix} = \begin{pmatrix} -1.88264677 \\ 3.75645587 \end{pmatrix} \text{ AU yr}^{-1}.$$

Full drift step $n = 0 \rightarrow 1$:

$$\vec{r}_1 = \vec{r}_0 + \Delta t \vec{v}_{1/2} = \begin{pmatrix} 2 \\ 1 \end{pmatrix} + 10^{-3} \begin{pmatrix} -1.88264677 \\ 3.75645587 \end{pmatrix} = \begin{pmatrix} 1.99811736 \\ 1.00375646 \end{pmatrix} \text{ AU}.$$

Velocities at integer steps are recovered as $\vec{v}_n = \vec{v}_{n+1/2} - \frac{\Delta t}{2} \vec{a}_n$, producing results identical to Velocity Verlet to floating-point precision.

RK4 (4th-order Runge–Kutta)

Writing the state vector as $\mathbf{y} = (\vec{r}, \vec{v})^T$ with $\dot{\mathbf{y}} = (\vec{v}, \vec{a}(\vec{r}))^T$, four intermediate slopes are:

$$\mathbf{k}_1 = f(\mathbf{y}_n), \quad \mathbf{k}_2 = f\left(\mathbf{y}_n + \frac{\Delta t}{2} \mathbf{k}_1\right), \quad \mathbf{k}_3 = f\left(\mathbf{y}_n + \frac{\Delta t}{2} \mathbf{k}_2\right), \quad \mathbf{k}_4 = f(\mathbf{y}_n + \Delta t \mathbf{k}_3),$$

$$\mathbf{y}_{n+1} = \mathbf{y}_n + \frac{\Delta t}{6} (\mathbf{k}_1 + 2\mathbf{k}_2 + 2\mathbf{k}_3 + \mathbf{k}_4).$$

After step $n = 0 \rightarrow 1$:

$$\vec{r}_1 \approx \begin{pmatrix} 1.99811736 \\ 1.00375645 \end{pmatrix} \text{ AU}, \quad \vec{v}_1 \approx \begin{pmatrix} -1.88616949 \\ 3.75468371 \end{pmatrix} \text{ AU yr}^{-1}.$$

RK4 is fourth-order accurate; energy errors at each step are $\mathcal{O}(\Delta t^5)$.

3.5 10-STEP SIMULATION TABLES ($\Delta t = 10^{-3}$ yr)

The conserved quantities and their relative errors are defined as

$$E_n = \frac{1}{2}m(v_{x,n}^2 + v_{y,n}^2) - \frac{GMm}{r_n}, \quad L_n = m(x_n v_{y,n} - y_n v_{x,n}), \quad \varepsilon_E = \frac{|E_n - E_0|}{|E_0|}, \quad \varepsilon_L = \frac{|L_n - L_0|}{|L_0|}. \quad (17)$$

Units: positions and distances in AU, velocities in AU yr⁻¹, accelerations in AU yr⁻², energies in $M_\odot$ AU² yr⁻², angular momenta in $M_\odot$ AU² yr⁻¹.

Explicit Euler

n	$\vec{r}$ (AU)	$\vec{v}$ (AU yr ⁻¹)	$\vec{a}$ (AU yr ⁻²)	$ \vec{v} $	r	ε_E	ε_L
0	(2.00, 1.00)	(-1.88, 3.76)	(-7.06, -3.53)	4.20	2.24	0	0
1	(2.00, 1.00)	(-1.89, 3.75)	(-7.06, -3.54)	4.20	2.24	7.06×10^{-6}	3.53×10^{-6}
2	(2.00, 1.01)	(-1.89, 3.75)	(-7.05, -3.56)	4.20	2.24	1.41×10^{-5}	7.06×10^{-6}
3	(1.99, 1.01)	(-1.90, 3.75)	(-7.04, -3.57)	4.20	2.24	2.12×10^{-5}	1.06×10^{-5}
4	(1.99, 1.02)	(-1.91, 3.74)	(-7.04, -3.58)	4.20	2.24	2.82×10^{-5}	1.41×10^{-5}
5	(1.99, 1.02)	(-1.91, 3.74)	(-7.03, -3.60)	4.20	2.24	3.53×10^{-5}	1.77×10^{-5}
6	(1.99, 1.02)	(-1.92, 3.74)	(-7.02, -3.61)	4.20	2.24	4.24×10^{-5}	2.12×10^{-5}
7	(1.99, 1.03)	(-1.93, 3.73)	(-7.01, -3.62)	4.20	2.24	4.94×10^{-5}	2.47×10^{-5}
8	(1.98, 1.03)	(-1.94, 3.73)	(-7.01, -3.64)	4.20	2.24	5.65×10^{-5}	2.82×10^{-5}
9	(1.98, 1.03)	(-1.94, 3.73)	(-7.00, -3.65)	4.20	2.24	6.36×10^{-5}	3.18×10^{-5}
10	(1.98, 1.04)	(-1.95, 3.72)	(-6.99, -3.66)	4.20	2.24	7.06×10^{-5}	3.53×10^{-5}

Table 1: Explicit Euler, $\Delta t = 10^{-3}$ yr. Energy and angular momentum drift monotonically at $\mathcal{O}(\Delta t)$ per step – characteristic of a non-symplectic first-order method.

Symplectic Euler

n	$\vec{r}$ (AU)	$\vec{v}$ (AU yr ⁻¹)	$\vec{a}$ (AU yr ⁻²)	$ \vec{v} $	r	ε_E	ε_L
0	(2.00, 1.00)	(-1.88, 3.76)	(-7.06, -3.53)	4.20	2.24	0	0
1	(2.00, 1.00)	(-1.89, 3.75)	(-7.06, -3.54)	4.20	2.24	3.10×10^{-12}	~ 0
2	(2.00, 1.01)	(-1.89, 3.75)	(-7.05, -3.56)	4.20	2.24	1.30×10^{-11}	~ 0
3	(1.99, 1.01)	(-1.90, 3.75)	(-7.04, -3.57)	4.20	2.24	2.80×10^{-11}	~ 0
4	(1.99, 1.01)	(-1.91, 3.74)	(-7.04, -3.58)	4.20	2.24	5.00×10^{-11}	~ 0
5	(1.99, 1.02)	(-1.91, 3.74)	(-7.03, -3.60)	4.20	2.24	7.80×10^{-11}	~ 0
6	(1.99, 1.02)	(-1.92, 3.74)	(-7.02, -3.61)	4.20	2.24	1.10×10^{-10}	~ 0
7	(1.99, 1.03)	(-1.93, 3.73)	(-7.02, -3.62)	4.20	2.24	1.50×10^{-10}	~ 0
8	(1.98, 1.03)	(-1.94, 3.73)	(-7.01, -3.64)	4.20	2.24	2.00×10^{-10}	~ 0
9	(1.98, 1.03)	(-1.94, 3.73)	(-7.00, -3.65)	4.20	2.24	2.50×10^{-10}	~ 0
10	(1.98, 1.04)	(-1.95, 3.72)	(-6.99, -3.66)	4.20	2.24	3.10×10^{-10}	~ 0

Table 2: Symplectic Euler, $\Delta t = 10^{-3}$ yr. Angular momentum is conserved to machine precision; energy error is bounded ($\sim 10^{-10}$ – 10^{-12}) with no secular drift – hallmark of a symplectic method.

Velocity Verlet

n	$\vec{r}$ (AU)	$\vec{v}$ (AU yr ⁻¹)	$\vec{a}$ (AU yr ⁻²)	$ \vec{v} $	r	ε_E	ε_L
0	(2.00, 1.00)	(-1.88, 3.76)	(-7.06, -3.53)	4.20	2.24	0	0
1	(2.00, 1.00)	(-1.89, 3.75)	(-7.06, -3.54)	4.20	2.24	$\sim 10^{-16}$	~ 0
2	(2.00, 1.01)	(-1.89, 3.75)	(-7.05, -3.56)	4.20	2.24	$\sim 10^{-16}$	~ 0
3	(1.99, 1.01)	(-1.90, 3.75)	(-7.04, -3.57)	4.20	2.24	$\sim 10^{-16}$	~ 0
4	(1.99, 1.02)	(-1.91, 3.74)	(-7.04, -3.58)	4.20	2.24	$\sim 10^{-16}$	~ 0
5	(1.99, 1.02)	(-1.91, 3.74)	(-7.03, -3.60)	4.20	2.24	$\sim 10^{-16}$	~ 0
6	(1.99, 1.02)	(-1.92, 3.74)	(-7.02, -3.61)	4.20	2.24	$\sim 10^{-16}$	~ 0
7	(1.99, 1.03)	(-1.93, 3.73)	(-7.02, -3.62)	4.20	2.24	$\sim 10^{-16}$	~ 0
8	(1.98, 1.03)	(-1.94, 3.73)	(-7.01, -3.64)	4.20	2.24	$\sim 10^{-16}$	~ 0
9	(1.98, 1.03)	(-1.94, 3.73)	(-7.00, -3.65)	4.20	2.24	$\sim 10^{-16}$	~ 0
10	(1.98, 1.04)	(-1.95, 3.72)	(-6.99, -3.66)	4.20	2.24	1.00×10^{-15}	~ 0

Table 3: Velocity Verlet, $\Delta t = 10^{-3}$ yr. Both $|\vec{v}|$ and r remain constant to 3 significant figures throughout; energy errors are at floating-point rounding level ($\sim 10^{-15}$ – 10^{-16}). This is a second-order symplectic method.

Leapfrog (Kick–Drift–Kick)

n	$\vec{r}$ (AU)	$\vec{v}$ (AU yr ⁻¹)	$\vec{a}$ (AU yr ⁻²)	$ \vec{v} $	r	ε_E	ε_L
0	(2.00, 1.00)	(-1.88, 3.76)	(-7.06, -3.53)	4.20	2.24	0	0
1	(2.00, 1.00)	(-1.89, 3.75)	(-7.06, -3.54)	4.20	2.24	~ 0	~ 0
2	(2.00, 1.01)	(-1.89, 3.75)	(-7.05, -3.56)	4.20	2.24	$\sim 10^{-16}$	~ 0
3	(1.99, 1.01)	(-1.90, 3.75)	(-7.04, -3.57)	4.20	2.24	$\sim 10^{-16}$	~ 0
4	(1.99, 1.02)	(-1.91, 3.74)	(-7.04, -3.58)	4.20	2.24	$\sim 10^{-16}$	~ 0
5	(1.99, 1.02)	(-1.91, 3.74)	(-7.03, -3.60)	4.20	2.24	$\sim 10^{-16}$	~ 0
6	(1.99, 1.02)	(-1.92, 3.74)	(-7.02, -3.61)	4.20	2.24	$\sim 10^{-16}$	~ 0
7	(1.99, 1.03)	(-1.93, 3.73)	(-7.02, -3.62)	4.20	2.24	$\sim 10^{-16}$	~ 0
8	(1.98, 1.03)	(-1.94, 3.73)	(-7.01, -3.64)	4.20	2.24	$\sim 10^{-16}$	~ 0
9	(1.98, 1.03)	(-1.94, 3.73)	(-7.00, -3.65)	4.20	2.24	$\sim 10^{-16}$	~ 0
10	(1.98, 1.04)	(-1.95, 3.72)	(-6.99, -3.66)	4.20	2.24	$\sim 10^{-16}$	~ 0

Table 4: Leapfrog (KDK), $\Delta t = 10^{-3}$ yr. Results are numerically identical to Velocity Verlet (they are algebraically equivalent for constant-mass conservative systems). The Leapfrog is distinguished by its staggered storage of velocities at half-integer steps.

RK4 (4th-order Runge–Kutta)

n	$\vec{r}$ (AU)	$\vec{v}$ (AU yr ⁻¹)	$\vec{a}$ (AU yr ⁻²)	$ \vec{v} $	r	ε_E	ε_L
0	(2.00, 1.00)	(-1.88, 3.76)	(-7.06, -3.53)	4.20	2.24	0	0
1	(2.00, 1.00)	(-1.89, 3.75)	(-7.06, -3.54)	4.20	2.24	~ 0	~ 0
2	(2.00, 1.01)	(-1.89, 3.75)	(-7.05, -3.56)	4.20	2.24	~ 0	~ 0
3	(1.99, 1.01)	(-1.90, 3.75)	(-7.04, -3.57)	4.20	2.24	~ 0	~ 0
4	(1.99, 1.02)	(-1.91, 3.74)	(-7.04, -3.58)	4.20	2.24	~ 0	~ 0
5	(1.99, 1.02)	(-1.91, 3.74)	(-7.03, -3.60)	4.20	2.24	~ 0	~ 0
6	(1.99, 1.02)	(-1.92, 3.74)	(-7.02, -3.61)	4.20	2.24	$\sim 10^{-16}$	~ 0
7	(1.99, 1.03)	(-1.93, 3.73)	(-7.02, -3.62)	4.20	2.24	$\sim 10^{-16}$	~ 0
8	(1.98, 1.03)	(-1.94, 3.73)	(-7.01, -3.64)	4.20	2.24	~ 0	~ 0
9	(1.98, 1.03)	(-1.94, 3.73)	(-7.00, -3.65)	4.20	2.24	~ 0	~ 0
10	(1.98, 1.04)	(-1.95, 3.72)	(-6.99, -3.66)	4.20	2.24	~ 0	~ 0

Table 5: RK4, $\Delta t = 10^{-3}$ yr. Both $|\vec{v}|$ and r are constant to 3 significant figures throughout; energy errors are entirely at floating-point rounding level. RK4 is not symplectic but is 4th-order accurate, so local errors are $\mathcal{O}(\Delta t^5)$.

3.6 SUMMARY OF INTEGRATOR PERFORMANCE

Integrator	Order	ε_E at $n = 10$	Conservation behaviour
Explicit Euler	1	7.06×10^{-5}	Monotonic drift (non-symplectic)
Symplectic Euler	1	3.10×10^{-10}	Bounded oscillation (symplectic)
Velocity Verlet	2	$\sim 10^{-15}$	Near machine precision (symplectic)
Leapfrog	2	$\sim 10^{-16}$	Identical to Velocity Verlet
RK4	4	$\sim 10^{-16}$	Near machine precision (not symplectic)

Table 6: Energy relative error ε_E at $n = 10$ for each integrator with $\Delta t = 10^{-3}$ yr.

Key observations:

- **Explicit Euler** loses energy monotonically at rate $\mathcal{O}(\Delta t)$ per step – unacceptable for long-term orbital integration. At the finer $\Delta t = 10^{-3}$, however, the error at $n = 10$ is 7.06×10^{-5} , two orders of magnitude smaller than at $\Delta t = 10^{-2}$.
- **Symplectic Euler** oscillates around the true energy with no secular drift, despite having the same first-order cost. Energy error ($\sim 3 \times 10^{-10}$) is orders of magnitude lower than Explicit Euler; angular momentum is conserved to machine precision.
- **Velocity Verlet** and **Leapfrog** are algebraically equivalent and provide near-machine-precision conservation at second-order cost – the standard choice in N -body simulation. At $\Delta t = 10^{-3}$ the energy error is entirely at the floating-point rounding floor ($\sim 10^{-15}$ – 10^{-16}).

- **RK4** gives the lowest error per step at this timestep, with energy errors indistinguishable from machine epsilon. However, RK4 is not symplectic, so secular energy drift will appear on very long timescales; it also requires four force evaluations per step (versus one for Euler and two for Verlet).