

Tendo — Local Setup

NGA Discipline & Attendance · run it on your own laptop · about 15 minutes

Tendo is a React app (`client/`, `http://localhost:3000`) and an Express API (`server/`, `http://localhost:5171`) in one repository. It stores data in a local SQLite file it creates itself, and you sign in with your NGA MIS account — nothing else to install or run.

Before you start

You need **Node.js 20 or newer** and **Git** (nodejs.org · git-scm.com), and two things from your team lead:

Your NGA MIS login	the same account you use at mis.amashuri.com
The Tendo client secret	one shared value for the team — goes into <code>SSO_CLIENT_SECRET</code> in step 3

1 · Get the code

```
git clone https://github.com/niyongaboemmy/nga-discipline-attendance.git
cd nga-discipline-attendance
npm run install:all
```

Installing takes a few minutes the first time. Warnings are normal; only `npm ERR!` lines matter.

2 · Create your settings files

```
Copy-Item client\.env.example client\.env
Copy-Item server\.env.example server\.env
```

On macOS or Linux use `cp client/.env.example client/.env` and the same for `server`.

3 · Fill in `server/.env`

Open `server/.env` in your editor and change these two lines. Leave everything else as it is; `client/.env` needs no changes.

Setting	Value
<code>SSO_CLIENT_SECRET</code>	the client secret from your team lead
<code>JWT_SECRET</code>	any long random text (30+ characters) of your own — a password generator works well

Optional: add `ADMIN_USERNAMES=your_mis_username` to see every screen as an admin.

4 · Run it

```
npm run dev
```

Both parts start together and reload as you edit. Open **`http://localhost:3000`**, click **Sign in**, log in on the MIS page, and you are sent back to Tendo signed in. Stop with `Ctrl+C`.

5 · Working on a feature

Pushing to main deploys to production. Always work on a branch and open a Pull Request:

```
git checkout -b feature/short-description
# make and test your changes, then
git push -u origin feature/short-description
```

If something goes wrong

You see	Do this
<i>Port 3000 is already in use</i>	Close the other app using port 3000 (<code>netstat -ano findstr :3000</code> shows it) and run <code>npm run dev</code> again.
<i>Failed to authorize application</i>	Tell your team lead — the MIS needs <code>http://localhost:3000/sso/callback</code> on its allowed list for Tendo. One-time fix on their side.
<i>Failed to exchange SSO code</i>	<code>SSO_CLIENT_SECRET</code> in <code>server/.env</code> is wrong. Fix it and restart.
Signed in but nothing is allowed	Add <code>ADMIN_USERNAMES=your_mis_username</code> to <code>server/.env</code> , restart, sign in again.
Want to start with a clean database	Stop the app and delete <code>server/data/attendance.db</code> . It is recreated on the next start.

Checks: `curl http://localhost:5171/health` · `npm test --prefix server` · `npm run lint --prefix client`