



ANDROID STATIC ANALYSIS REPORT



 COVID Defense (1.9.1)

File Name:	org.pathcheck.la.bt_1.9.1-2661_minAPI23(arm64-v8a,armeabi-v7a,x86,x86_64)(nodpi)_apkmirror.com.apk
Package Name:	org.pathcheck.la.bt
Average CVSS Score:	0
App Security Score:	100/100 (LOW RISK)
Trackers Detection:	2/421
Scan Date:	Feb. 20, 2022, 6:08 p.m.

FILE INFORMATION

File Name: org.pathcheck.la.bt_1.9.1-2661_minAPI23(arm64-v8a,armeabi-v7a,x86,x86_64)(nodpi)_apkmirror.com.apk
Size: 64.72MB
MD5: 9ca7904e21c160a4ddbb30d3e6b24145

SHA1: fb0f39708860809dfe3b2657d6b40934e28e87a5

SHA256: b413b5b7d15cacacc0b7a09294ac62c71c908c28e7b6bc9cf18caa91e1c56642

APP INFORMATION

App Name: COVID Defense

Package Name: org.pathcheck.la.bt

Main Activity: org.pathcheck.covidsafepaths.SplashActivity

Target SDK: 30

Min SDK: 23

Max SDK:

Android Version Name: 1.9.1

Android Version Code: 2661

APP COMPONENTS

Activities: 3

Services: 5

Receivers: 10

Providers: 1

Exported Activities: 1

Exported Services: 2

Exported Receivers: 3

Exported Providers: 0

CERTIFICATE INFORMATION

APK is signed

v1 signature: True

v2 signature: True

v3 signature: True

Found 1 unique certificates

Subject: C=US, ST=California, L=Mountain View, O=Google Inc., OU=Android, CN=Android

Signature Algorithm: rsassa_pkcs1v15
Valid From: 2020-08-19 16:53:47+00:00
Valid To: 2050-08-19 16:53:47+00:00
Issuer: C=US, ST=California, L=Mountain View, O=Google Inc., OU=Android, CN=Android
Serial Number: 0x5c0ddeb0e391f69b39df3a4cdb22bde27d76dc12
Hash Algorithm: sha256
md5: 0146b0937373daff29c353c3cb2ea4da
sha1: aeb36f335826cd5f11d2426b1863694a6f549437
sha256: 5836fe0251e77d8c44818ef7d1e0b9980346072187191a18259648de788fe775
sha512: 52379f08f1753d9fedfe73c927f76dca715dc87a5a8f9c593fe375ab52508453b3ba05c144ff640100b36a4385317a7934d97a1d42bdc9c60317ed7524e7b560
PublicKey Algorithm: rsa
Bit Size: 4096
Fingerprint: 07a749fd00217b095db29c84bcabb2e8572954659f64528d950f7398e2d1ab93

STATUS	DESCRIPTION
secure	Application is signed with a code signing certificate
warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

≡ APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.BLUETOOTH	normal	create Bluetooth connections	Allows applications to connect to paired bluetooth devices.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.FOREGROUND_SERVICE	normal		Allows a regular application to use Service.startForeground.

APKID ANALYSIS

FILE	DETAILS
------	---------

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check possible Build.SERIAL check Build.TAGS check network operator name check
	Compiler	r8

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
org.pathcheck.covidsafepaths.MainActivity	Schemes: pathcheck://, https://, Hosts: exposureHistory, us-la.en.express,

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

MANIFEST ANALYSIS

NO	ISSUE	SEVERITY	DESCRIPTION
1	Activity (org.pathcheck.covidsafepaths.MainActivity) is not Protected. [android:exported=true]	high	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
2	Broadcast Receiver (org.pathcheck.covidsafepaths.exposurenotifications.nearby.ExposureNotificationBroadcastReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.nearby.exposurenotification.EXPOSURE_CALLBACK [android:exported=true]	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
3	<p>Service (com.google.android.gms.nearby.exposurenotification.WakeUpService) is Protected by a permission, but the protection level of the permission should be checked.</p> <p>Permission: com.google.android.gms.nearby.exposurenotification.EXPOSURE_CALLBACK [android:exported=true]</p>	high	<p>A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.</p>
4	<p>Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked.</p> <p>Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]</p>	high	<p>A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.</p>

NO	ISSUE	SEVERITY	DESCRIPTION
5	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
6	Broadcast Receiver (org.matomo.sdk.extra.InstallReferrerReceiver) is not Protected. [android:exported=true]	high	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

CODE ANALYSIS

NO	ISSUE	SEVERITY	STANDARDS	FILES
----	-------	----------	-----------	-------

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	lib/arm64-v8a/libbugsnag-ndk.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>True info</p> <p>The shared object has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk', '__memmove_chk', '__read_chk', '__strchr_chk', '__vsprintf_chk', '__strcpy_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	lib/arm64-v8a/libbugsnag-plugin-android-anr.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	lib/arm64-v8a/libc++_shared.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	lib/arm64-v8a/libfb.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	lib/arm64-v8a/libfbjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	lib/arm64-v8a/libfolly_futures.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	lib/arm64-v8a/libfolly_json.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	lib/arm64-v8a/libglog.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	lib/arm64-v8a/libglog_init.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	lib/arm64-v8a/libhermes-executor-debug.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	lib/arm64-v8a/libhermes-executor-release.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	lib/arm64-v8a/libhermes-inspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	lib/arm64-v8a/libhermes.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	lib/arm64-v8a/libimagepipeline.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>No RELRO high</p> <p>This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	lib/arm64-v8a/libjscexecutor.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	lib/arm64-v8a/libjsijni profiler.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	lib/arm64-v8a/libjsinspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	lib/arm64-v8a/libnative-filters.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>No RELRO high</p> <p>This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	lib/arm64-v8a/libnative-image-transcoder.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>No RELRO high</p> <p>This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	lib/arm64-v8a/libreactnativeblob.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	lib/arm64-v8a/libreactnativejni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	lib/arm64-v8a/librealm-jni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>True info</p> <p>The shared object has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__read_chk', '__vsprintf_chk', '__strchr_chk', '__memcpy_chk', '__vsnprintf_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	lib/arm64-v8a/libyoga.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
24	lib/armeabi-v7a/libbugsnag-ndk.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	lib/armeabi-v7a/libbugsnag-plugin-android-anr.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
26	lib/armeabi-v7a/libc++_shared.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
27	lib/armeabi-v7a/libfb.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
28	lib/armeabi-v7a/libfbjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
29	lib/armeabi-v7a/libfolly_futures.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
30	lib/armeabi-v7a/libfolly_json.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
31	lib/armeabi-v7a/libglog.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
32	lib/armeabi-v7a/libglog_init.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
33	lib/armeabi-v7a/libhermes-executor-debug.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
34	lib/armeabi-v7a/libhermes-executor-release.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
35	lib/armeabi-v7a/libhermes-inspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
36	lib/armeabi-v7a/libhermes.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
37	lib/armeabi-v7a/libimagepipeline.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
38	lib/armeabi-v7a/libjscexecutor.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
39	lib/armeabi-v7a/libjsijniProfiler.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
40	lib/armeabi-v7a/libjsinspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
41	lib/armeabi-v7a/libnative-filters.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
42	lib/armeabi-v7a/libnative-imagetranscoder.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
43	lib/armeabi-v7a/libreactnativeblob.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
44	lib/armeabi-v7a/libreactnativejni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
45	lib/armeabi-v7a/librealm-jni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
46	lib/armeabi-v7a/libyoga.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
47	lib/x86/libbugsnag-ndk.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
48	lib/x86/libbugsnag-plugin-android-anr.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
49	lib/x86/libc++_shared.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
50	lib/x86/libfb.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
51	lib/x86/libfbjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
52	lib/x86/libfolly_futures.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
53	lib/x86/libfolly_json.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
54	lib/x86/libglog.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
55	lib/x86/libglog_init.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
56	lib/x86/libhermes-executor-debug.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
57	lib/x86/libhermes-executor-release.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
58	lib/x86/libhermes-inspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
59	lib/x86/libhermes.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
60	lib/x86/libimagepipeline.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
61	lib/x86/libjscexecutor.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
62	lib/x86/libjsijni profiler.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
63	lib/x86/libjsinspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
64	lib/x86/libnative-filters.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
65	lib/x86/libnative-imagetranscoder.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
66	lib/x86/libreactnativeblob.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
67	lib/x86/libreactnativejni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
68	lib/x86/librealm-jni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
69	lib/x86/libyoga.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
70	lib/x86_64/libbugsnag-ndk.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>True info</p> <p>The shared object has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strcpy_chk', '__strchr_chk', '__memcpy_chk', '__memmove_chk', '__read_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
71	lib/x86_64/libbugsnag-plugin-android-anr.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
72	lib/x86_64/libc++_shared.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
73	lib/x86_64/libfb.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
74	lib/x86_64/libfbjni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
75	lib/x86_64/libfolly_futures.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
76	lib/x86_64/libfolly_json.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
77	lib/x86_64/libglog.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
78	lib/x86_64/libglog_init.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
79	lib/x86_64/libhermes-executor-debug.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
80	lib/x86_64/libhermes-executor-release.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
81	lib/x86_64/libhermes-inspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
82	lib/x86_64/libhermes.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
83	lib/x86_64/libimagepipeline.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
84	lib/x86_64/libjscexecutor.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
85	lib/x86_64/libjsijniprofiler.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
86	lib/x86_64/libjsinspector.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
87	lib/x86_64/libnative-filters.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
88	lib/x86_64/libnative-imagetranscoder.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
89	lib/x86_64/libreactnativeblob.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
90	lib/x86_64/libreactnativejni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
91	lib/x86_64/librealm-jni.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>True info</p> <p>The shared object has the following fortified functions: ['__memmove_chk', '__strlen_chk', '__read_chk', '__vsprintf_chk', '__sprintf_chk', '__memcpy_chk', '__strchr_chk']</p>	<p>True info</p> <p>Symbols are stripped.</p>

NO	SHARED OBJECT	NX	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
92	lib/x86_64/libyoga.so	<p>True info</p> <p>The shared object has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p>	<p>True info</p> <p>This shared object has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p>	<p>Full RELRO info</p> <p>This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.</p>	<p>False info</p> <p>The shared object does not have run-time search path or RPATH set.</p>	<p>False info</p> <p>The shared object does not have RUNPATH set.</p>	<p>False warning</p> <p>The shared object does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions.</p>	<p>True info</p> <p>Symbols are stripped.</p>

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
notify.bugsnag.com	good	IP: 35.186.205.6 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map
coviddefensela.com	good	IP: 34.193.204.92 Country: United States of America Region: Virginia City: Ashburn Latitude: 39.043720 Longitude: -77.487488 View: Google Map
bugsnag.com	good	IP: 65.8.68.99 Country: United States of America Region: Washington City: Seattle Latitude: 47.606209 Longitude: -122.332069 View: Google Map

DOMAIN	STATUS	GEOLOCATION
issuetracker.google.com	good	IP: 172.217.14.206 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
github.com	good	IP: 140.82.114.3 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
ldh.la.gov	good	IP: 3.94.39.96 Country: United States of America Region: Virginia City: Ashburn Latitude: 39.043720 Longitude: -77.487488 View: Google Map
apiserver.encv.org	good	IP: 34.107.223.222 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map

DOMAIN	STATUS	GEOLOCATION
prod.exposurenotification.health	good	IP: 13.107.246.70 Country: Netherlands Region: Noord-Holland City: Amsterdam Latitude: 52.374031 Longitude: 4.889690 View: Google Map
www.coviddefensela.com	good	IP: 184.73.183.75 Country: United States of America Region: Virginia City: Ashburn Latitude: 39.043720 Longitude: -77.487488 View: Google Map
sessions.bugsnag.com	good	IP: 35.190.88.7 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map
cdn.projectaurora.cloud	good	IP: 35.244.172.56 Country: United States of America Region: Missouri City: Kansas City Latitude: 39.099731 Longitude: -94.578568 View: Google Map

DOMAIN	STATUS	GEOLOCATION
apps.apple.com	good	IP: 23.73.34.217 Country: Canada Region: Alberta City: Calgary Latitude: 51.050110 Longitude: -114.085289 View: Google Map
docs.bugsnap.com	good	IP: 138.68.50.15 Country: United States of America Region: California City: Santa Clara Latitude: 37.354111 Longitude: -121.955238 View: Google Map
play.google.com	good	IP: 142.250.217.110 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.cdc.gov	good	IP: 23.6.53.73 Country: Canada Region: Alberta City: Calgary Latitude: 51.050110 Longitude: -114.085289 View: Google Map

DOMAIN	STATUS	GEOLOCATION
ldhcovid19.my.salesforce.com	good	IP: 96.43.153.168 Country: United States of America Region: California City: San Francisco Latitude: 37.788464 Longitude: -122.394608 View: Google Map
realm.io	good	IP: 99.86.146.90 Country: Korea (Republic of) Region: Gyeonggi-do City: Incheon Latitude: 37.279171 Longitude: 127.442497 View: Google Map
encdn.prod.exposurenotification.health	good	IP: 104.212.67.47 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map

URLs

URL	FILE
https://github.com/bugsnag/bugsnag-js	com/bugsnag/android/BugsnagReactNativePlugin.java

URL	FILE
https://notify.bugsnag.com https://sessions.bugsnag.com	com/bugsnag/android/EndpointConfiguration.java
https://docs.bugsnag.com/platforms/android/ndk-link-errors	com/bugsnag/android/NdkPlugin.java
https://bugsnag.com	com/bugsnag/android/Notifier.java
https://github.com/software-mansion/react-native-screens/issues/17#issuecomment-424704067	com/swmansion/rnscreens/ScreenFragment.java
https://github.com/software-mansion/react-native-screens/issues/17#issuecomment-424704067	com/swmansion/rnscreens/ScreenStackFragment.java
https://%s/	com/terveystalo/react_native/matomo_sdk/RNMatomoSdkModule.java
https://issuetracker.google.com/issues/36918154	io/realm/Realm.java
https://realm.io/news/android-installation-change/	io/realm/RealmConfiguration.java

URL	FILE
https://cdn.projectaurora.cloud/la/cfg/android/v1.6.config.json https://play.google.com/store/apps/details?id=org.pathcheck.la.bt https://cdn.projectaurora.cloud/la/cfg/ios/v1.config.json https://cdn.projectaurora.cloud/la/cfg/ios/v2.config.json https://www.cdc.gov/coronavirus/2019-ncov/if-you-are-sick/quarantine.html https://ldhccovid19.my.salesforce.com/services/data/v49.0/subjects/PathCheck_Staging_c https://ldhccovid19.my.salesforce.com/services/oauth2/ https://ldhccovid19.my.salesforce.com https://www.cdc.gov/coronavirus/2019-ncov/if-you-are-sick/steps-when-sick.html https://www.cdc.gov/coronavirus/2019-ncov/symptoms-testing/symptoms.html https://encdn.prod.exposurenotification.health https://cdn.projectaurora.cloud/cfg https://cdn.projectaurora.cloud/cfg/v1.config.json https://cdn.projectaurora.cloud/cfg/v1.6.config.json https://ldh.la.gov/index.cfm/page/3934 https://apiserver.encv.org https://apps.apple.com/us/app/covid-defense/id1528363969 https://coviddefensela.com/privacy-policy https://prod.exposurenotification.health https://www.coviddefensela.com/ https://www.coviddefensela.com/faqs	org/pathcheck/covidsafepaths/BuildConfig.java
https://encdn.prod.exposurenotification.health/	org/pathcheck/covidsafepaths/exposurenotifications/nearby/DiagnosisKeyFileSubmitter.java

EMAILS

EMAIL	FILE
help@realm.io	lib/arm64-v8a/librealm-jni.so

EMAIL	FILE
help@realm.io	lib/armeabi-v7a/librealm-jni.so
help@realm.io	lib/x86/librealm-jni.so
help@realm.io	lib/x86_64/librealm-jni.so

TRACKERS

TRACKER	CATEGORIES	URL
Bugsnap	Crash reporting	https://reports.exodus-privacy.eu.org/trackers/207
Matomo (Piwik)	Analytics	https://reports.exodus-privacy.eu.org/trackers/138

PLAYSTORE INFORMATION

Title: COVID Defense

Score: 3.66 **Installs:** 100,000+ **Price:** 0 **Android Version Support:** 6.0 and up **Category:** Health & Fitness **Play Store URL:** [org.pathcheck.la.bt](https://play.google.com/store/apps/details?id=com.pathcheck.la.bt)

Developer Details: State of Louisiana, 8181680172265163636, Louisiana Division of Administration 1201 N 3rd St. Baton Rouge, LA 70802-5243, <https://www.coviddefensela.com/>, COVIDDefenseSupport@la.gov,

Release Date: Jan 7, 2021 **Privacy Policy:** [Privacy link](#)

Description:

COVID Defense is an easy-to-use app created by the Louisiana Department of Health. COVID Defense protects your privacy while helping protect you from COVID-19. You will get an alert if you are in close contact with someone who tests positive for COVID-19. By adding this free app to your phone, you join thousands of people helping to protect one another from COVID by knowing if you've been exposed. The COVID Defense app was built using an open-source project developed by PathCheck Foundation.

App Security Score Calculation

Every app is given an ideal score of 100 to begin with.

For every findings with severity **high** we reduce 15 from the score.

For every findings with severity **warning** we reduce 10 from the score.

For every findings with severity **good** we add 5 to the score.

If the calculated score is greater than 100, then the app security score is considered as 100.

And if the calculated score is less than 0, then the app security score is considered as 10.

Risk Calculation

APP SECURITY SCORE	RISK
0 - 15	CRITICAL
16 - 40	HIGH
41 - 70	MEDIUM
71 - 100	LOW

Report Generated by - MobSF v3.4.5 Beta

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2022 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).