

Final Migration Report

Cisco ASA → Palo Alto PAN-OS · job SAMPLE-0001 · host lab-edge-fw01 · generated 2026-08-27 10:00 UTC · RuleForge

REVIEW NEEDED — walk the partial/manual items before cut-over

6 partial and 10 manual-review items — walk the conversion process report before deploying

Before / after by category

Category	Source elements	Converted	Partial	Manual	Failed	Distribution
interface	11	11	0	0	0	
zone	7	7	0	0	0	
object	35	35	0	0	0	
service	9	9	0	0	0	
group	12	12	0	0	0	
rule	43	41	2	0	0	
nat	13	9	4	0	0	
route	6	6	0	0	0	
captured	10	0	0	10	0	

Round-trip verification

The generated configuration was re-parsed by RuleForge's own Palo Alto PAN-OS parser and compared against the intermediate model: PASS

Metric	Source	Re-parsed output	Check	Note
rules	43	43	ok	
NAT rules	13	13	ok	
static routes	6	6	ok	

network objects	35	42	ok	generated config carries helper objects / expanded entries — expected
interfaces	11	11	ok	

Source inventory (deep analysis)

Context	Interfaces	Zones	Objects	Services	Groups	Rules	NAT	Routes	Captured
lab-edge-fw01	11	7	35	9	12	43	13	6	10

lab-edge-fw01: 6 VPN configuration blocks captured — site-to-site VPNs must be rebuilt on the target (v1 reports them with full source lines)

Mapping applied

Kind	Context	Source	Target	Note
interface	lab-edge-fw01	GigabitEthernet0/0	ethernet1/1	
interface	lab-edge-fw01	GigabitEthernet0/1	ethernet1/2	
interface	lab-edge-fw01	GigabitEthernet0/4	ethernet1/3	
interface	lab-edge-fw01	GigabitEthernet0/5	ethernet1/4	
interface	lab-edge-fw01	Port-channel10	ae10	
interface	lab-edge-fw01	GigabitEthernet0/2	ethernet1/5	
interface	lab-edge-fw01	GigabitEthernet0/2.20	ethernet1/5.20	
interface	lab-edge-fw01	GigabitEthernet0/2.30	ethernet1/5.30	
interface	lab-edge-fw01	GigabitEthernet0/2.40	ethernet1/5.40	
interface	lab-edge-fw01	GigabitEthernet0/2.50	ethernet1/5.50	
interface	lab-edge-fw01	Management0/0	ethernet1/6	
zone	lab-edge-fw01	outside	outside	
zone	lab-edge-fw01	dmz	dmz	
zone	lab-edge-fw01	inside	inside	

zone	lab-edge-fw01	voice	voice
zone	lab-edge-fw01	guest	guest
zone	lab-edge-fw01	oob-mgmt	oob-mgmt
zone	lab-edge-fw01	mgmt	mgmt

Unconverted-item register

Context	Element	Status	What to do
lab-edge-fw01	GRP-PROTO-VPN	manual review	other: object-group protocol — review on target — not auto-converted in v1; source lines preserved in the report
lab-edge-fw01	GRP-ICMP-OK	manual review	other: object-group icmp-type — review on target — not auto-converted in v1; source lines preserved in the report
lab-edge-fw01	ikev2 policy 10	manual review	vpn: crypto configuration — not auto-converted in v1; source lines preserved in the report
lab-edge-fw01	ipsec ikev2 ipsec-proposal AES256-SHA256	manual review	vpn: crypto configuration — not auto-converted in v1; source lines preserved in the report
lab-edge-fw01	map OUTSIDE-MAP 10 match address VPN-MUC	manual review	vpn: crypto configuration — not auto-converted in v1; source lines preserved in the report
lab-edge-fw01	map OUTSIDE-MAP 10 set peer 203.0.113.10	manual review	vpn: crypto configuration — not auto-converted in v1; source lines preserved in the report
lab-edge-fw01	map OUTSIDE-MAP 10 set ikev2 ipsec-proposal AES256-SHA256	manual review	vpn: crypto configuration — not auto-converted in v1; source lines preserved in the report
lab-edge-fw01	map OUTSIDE-MAP interface outside	manual review	vpn: crypto configuration — not auto-converted in v1; source lines preserved in the report
lab-edge-fw01	ca trustpoint ASDM-TrustPoint-0	manual review	certificate: PKI trustpoint/certificate — not auto-converted in v1; source lines preserved in the report

Recommended cut-over checklist

#	Step
1	Load the generated configuration into a lab or maintenance-window device and verify it applies without syntax errors.
2	Walk every PARTIAL item in the process report and confirm the chosen translation is acceptable.
3	Rebuild every MANUAL item (VPN, certificates, dynamic routing, URL/app profiles) using the captured source lines in the process report.
4	Verify interface/zone mapping against the physical cabling plan (see Mapping applied table).
5	Confirm NAT behaviour with test flows: one per NAT rule kind (static, PAT, pool, twice).
6	Compare hit counters / traffic logs for the top 10 rules after cut-over against the source device baseline.
7	Keep the source device configuration archived; do not decommission until the target has passed a full business cycle.