

WidgetKit

> Widgets and watch complications

> Live Activities

> Controls

Presentation

Creating views for widgets, Live Acti...

> SwiftUI views for widgets

Interactivity

Adding interactivity to widgets and L...

Animating data updates in widgets...

Linking to specific app scenes from ...

Accessibility

Adding accessible descriptions to wi...

Previews and debugging

Previewing widgets and Live Activiti...

> WidgetPreviewContext

> Preview macros

Filter

/

WidgetKit / Animating data updates in widgets and Live Activities

Article

Animating data updates in widgets and Live Activities

Use SwiftUI animations to indicate data updates in your widgets and Live Activities.

Overview

Animations bring your widgets and Live Activities to life and alert a person when new information is available. Widgets and Live Activities animate data updates with default animations or SwiftUI animations you choose, bringing a person's attention to updated data. In earlier OS versions, widgets don't animate, and Live Activities only use a subset of SwiftUI transitions and animations.

Note

Animations in widgets and Live Activities have a maximum duration of two seconds.

For example, text views animate content changes with blurred content transitions by default, and changes to images and SF Symbols animate with default content transitions. If you add or remove views from the interface based on timeline updates or other state changes, views fade in and out.

Related session from WWDC23

[Session 10028: Bring widgets to life](#)

To replace default animations and transitions:

- Configure built-in transitions like [opacity](#), [move\(edge:\)](#), [slide](#), [push\(from:\)](#), or combinations of them.
- Add [transition\(_:\)](#), [contentTransition\(_:\)](#), or [animation\(_:value:\)](#) to views.
- Request animations for timer text with [numericText\(countsDown:\)](#).

Important

On devices that include an Always-On display, the system doesn't perform animations to preserve battery life in Always On. Check the [isLuminanceReduced](#) environment value to detect reduced luminance before animating content changes.

For Live Activities that appear on devices that run iOS 16 or earlier, the system ignores any animation modifiers — for example, [withAnimation\(_: :\)](#) and [animation\(_:value:\)](#) — and uses the system's animation timing instead. However, you can use built-in transitions like [opacity](#), [move\(edge:\)](#), [slide](#), [push\(from:\)](#), or combinations of them.

For more information about SwiftUI animations, refer to [Animations](#).

Add transitions and animations to views that update their data

In addition to the default transitions and animations that the system performs when views update their data, you can choose other built-in SwiftUI transitions and animations. Widgets and Live Activities support all built-in SwiftUI transitions and animations. For example, you could configure a content transition for numeric text as shown in this example:

```
Text(totalCaffeine.formatCaffeine())
    .font(.title)
    .minimumScaleFactor(0.8)
    .contentTransition(.numericText())
```

Additionally, you could add a spring animation to the transition:

```
Text (totalCaffeine.formatCaffeine())
    .font(.title)
    .minimumScaleFactor(0.8)
    .contentTransition(.numericText())
    .animation(.spring(duration: 0.2), value: totalCaffeine)
```

To use custom text animations, use [contentTransition\(_:\)](#) as shown in the example above. To use the default text animation, use [transition\(_:\)](#), and customize its speed and delay as shown in the following example:

```
Text("Some text with \(entry.value) that changes.")
    .animation(.default.speed(0.25).delay(0.5), value: entry.value)
```

Add transitions and animations to additional views

In addition to adding transitions or animations to a view that changes its data, you can animate a view when other widget information changes. To animate a view when a certain value changes, first associate the view you want to animate with that value's data model object. This is easiest when your data model conforms to the [Hashable](#) protocol. If your data model doesn't conform to Hashable, change its code accordingly. Then, associate the view with the data model using the [id\(_:\)](#) view modifier. Finally, add a transition or animation.

The following example shows how the LastDrinkView adds a push transition when the associated log changes.

```
struct LastDrinkView: View {
    let log: CaffeineLog
    var dateFormatStyle: Date.FormatStyle {
        Date.FormatStyle(date: .omitted, time: .shortened)
    }

    var body: some View {
        VStack(alignment: .leading) {
            Text(log.drink.name)
                .bold()

            Text ("\(log.date, format: .dateFormatStyle) • \(log.drink.name)")
                .font(.caption)
                .id(log) // Associate the view with the data model.
                .transition(.push(from: .bottom))
        }
    }
}
```

Disable animations

If a content update changes many views in your widget or Live Activity, consider disabling transitions and animations for some views to direct a person's attention to the most important updates. To disable animations for a view, including default animations, pass [identity](#) to [transition\(_:\)](#) or nil to the animation parameter of [withAnimation\(_: :\)](#) and [animation\(_:value:\)](#).

Note

[Transaction](#) isn't available to widgets and Live Activities, so you can't cancel or deactivate an animation by setting the transaction's [animation](#) property to nil.

See Also

Interactivity

- [Adding interactivity to widgets and Live Activities](#)
Include buttons or toggles in a widget or Live Activity to offer app functionality without launching the app.
- [Linking to specific app scenes from your widget or Live Activity](#)
Add deep links to your widgets and Live Activities that enable people to open a specific scene in your app.

Platforms

[iOS](#)

[iPadOS](#)

[macOS](#)

[tvOS](#)

[visionOS](#)

[watchOS](#)

Tools

[Swift](#)

[SwiftUI](#)

[Swift Playground](#)

[TestFlight](#)

[Xcode](#)

[Xcode Cloud](#)

[SF Symbols](#)

Topics & Technologies

[Accessibility](#)

[Accessories](#)

[App Extension](#)

[App Store](#)

[Audio & Video](#)

[Augmented Reality](#)

[Design](#)

[Distribution](#)

[Education](#)

[Fonts](#)

[Games](#)

[Health & Fitness](#)

[In-App Purchase](#)

[Localization](#)

[Maps & Location](#)

[Machine Learning & AI](#)

[Open Source](#)

[Security](#)

[Safari & Web](#)

Resources

[Documentation](#)

[Tutorials](#)

[Downloads](#)

[Forums](#)

[Videos](#)

Support

[Support Articles](#)

[Contact Us](#)

[Bug Reporting](#)

[System Status](#)

Account

[Apple Developer](#)

[App Store Connect](#)

[Certificates, IDs, & Profiles](#)

[Feedback Assistant](#)

Programs

[Apple Developer Program](#)

[Apple Developer Enterprise Program](#)

[App Store Small Business Program](#)

[MFI Program](#)

[News Partner Program](#)

[Video Partner Program](#)

[Security Bounty Program](#)

[Security Research Device Program](#)

Events

[Meet with Apple](#)

[Apple Developer Centers](#)

[App Store Awards](#)

[Apple Design Awards](#)

[Apple Developer Academies](#)

[WWDC](#)