

FluoroSeal® CONTROL VALVE SIZING

CUSTOMER		EXP Canada		
Project		RFO- Plug valve		
VALVE TAG ID		103000R073000B0S0WB004		
Valve Type		Plug		
Model No.		4"R302F/B-WCB/316-1-P		
Trim		Reduced		
Flow characteristic		Equal %		
ANSI/DIN Class		300		
Valve Size (in)		4"		
Description		4in. Reduced Port, ANSI Class 300, 2 Way, Flanged Raised Face, Sleeved Plug Valve, Body in ASTM A216 Gr. WCB, Plug in ASTM A351 Gr. CF8M PTFE Sleeved, Cover in ASTM A216 Gr. WCB, Cover Bolts in ASTM A193 Grade B7, Bare Stem		
Break Torque (Nm)		311		
MAST (Nm)		531		
Valve Cv(Rated)		548.0		
Inlet Pipe (in)		4		
Outlet Pipe (in)		4		
Seat Material/Style		PTFE (316)		
Fluid Name		Sulphur		
Fluid Phase		liquid		
	Unit	Min	Norm	Max
Flow (Volume)	m3/h	4.26	17.03	19.74
Flow (Mass)	Kg/Hr	1794.07	1794.07	1794.07
Fluid Temp.	C	135	135	135
P1	Kpa-g	1357.578	1210.719	1496.162
P2	Kpa-g	1146.874	740.152	1346.822
ΔP	Kpa	210.7	470.57	149.34
Viscosity	cP	9	9	9
SP Gravity		1.80	1.80	1.80
Critical Pressure	kg/cm2			
Vapour Pressure	kg/cm2			
Allowable P	kg/cm2			
Required Cv		4.549	12.169	25.039
Valve Opening	%	16.27	23.4	30.6
Noise	dBA	<80	<80	<80
Actuator Model #		135U-S080		
Actuator Model		MORIN B Actuator		
Actuator Model code		B135U-S080-JSO		
FAIL ACTION		Fail Close		
Fisher Positioner Model:		DVC6200 (Aluminum Housing)/HC tier		
Fisher 67CFSR set point		60 psig		

Notes :

- 1) Calculations are based on the provided data sheets .
- 2) Tag No: 1540-FCV-2602
- 3) Service Description: LIQUID SULFUR TO SULFUR SPRAY NOZZLES