

Copy and main specifications

Copy/Print Mode		Laser electrostatic transfer method
Photosensitive materials		OPC
Development system		Dry two-component developer
Memory		Standard 3.5GB
Solid State Drive		Standard: 256GB, 1TB
Warm-up time	Host power supply When open	10 seconds or less
	Sleep Mode When recovering	10 seconds or less
	Quick Start Mode	4 seconds or less
Maximum original size		A3
First page output time		5.5 seconds
Grayscale		256 levels
Resolution	copy	600dpi×600dpi
	Print	1,200 dpi × 600 dpi, 1,200 dpi × 1,200 dpi (half speed)
	scanning	600dpi×600dpi
Copy ratio	Fixed magnification	25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%
	Manual zoom	25% to 400% (in 1% units)
Continuous output speed		35 pages/minute
Continuous copying number		1y9,999
Paper supply (A4, 80gsm)	standard	550 sheets x 2 (paper cassette) + 100 sheets (bypass tray)
	Optional	550 sheets x 2 (dual paper tray assembly-AW1), 2450 sheets (large capacity paper tray-E1)

Contact Us

Back to top

Paper size	Paper Box	<p>Tray 1:</p> <p>Standard sizes: A4, A5, A5R, A6R, B5, 16K Custom sizes:</p> <p>105.0×148.0mm~297.0×215.9mm Envelope: ISO-C5 Tray 2: Standard sizes: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, 8K, 16K, 16KR</p> <p>Custom size: 105.0×148.0mmj304.8×457.2mm Envelope: COM10 No.10, Monarch 30 sheets, DL</p>
	Manual feed tray	<p>Standard sizes: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, 8K, 16K, 16KR Custom sizes: 98.4×139.7mm~320.0×457.2mm</p> <p>Custom sizes: 100.0×148.0mm~304.8×457.2mm Envelopes: COM10 No.10, Monarch 30 sheets, ISO-C5, DL Custom envelope sizes:</p> <p>98.0×98.0mm~320.0×457.2mm</p>
Paper thickness	Paper Box	52~256g/ŷ
	Manual feed tray	<p>52~300gsm *</p> <p>* SRA3 is not suitable for coated paper (257~300gsm) and thick paper (257gsm~300gsm) Paper expansion kit - A1: 60ŷ300gsm</p>
Paper type	Paper Box	<p>Tray 1: Thin paper, Plain paper, Thick paper, Recycled paper, Color paper, Bond paper, Pre-punched paper, Letterhead, Envelope</p> <p>Tray 2: Thin paper, Plain paper, Thick paper, Recycled paper, Color paper, Bond paper, Pre-punched paper, Letterhead, Envelope</p> <p>seal up</p>
	Manual feed tray	<p>Thin paper, Plain paper, Thick paper, Recycled paper, Coated paper*, Colored paper, Tracing paper, Bond paper, Labels, Pre-punched paper, Letterhead paper, Envelopes</p> <p>* SRA3 is not suitable for coated paper (257~300gsm) and thick paper (257gsm~300gsm)</p>
power supply		220-240V 50/60Hz 5A
Maximum power consumption		No more than 1.5kw
Sleep mode energy consumption		<p>0.8W *</p> <p>*Due to certain settings, 0.8W sleep mode may not be available in all situations</p>
Host size (width x depth x height)		<p>With double-sided automatic document feeder BA1: 565×719×891mm</p> <p>With double-sided scanning document feeder C1: 565×722×897mm</p>
Installation space (width x depth)		<p>Basic dimensions:</p> <p>978×1,116mm (with BA1 Duplex Automatic Document Feeder installed + multi-purpose tray pulled out + paper drawer opened) 978×1,119mm (with C1 Duplex Automatic Document Feeder installed + multi-purpose tray pulled out + paper drawer opened) Fully</p> <p>expanded dimensions: 1,651×1,116mm (with BA1 Duplex Automatic Document Feeder installed + finisher/saddle stitcher AE1 + copy tray T2 + paper drawer opened) 1,651 ×</p> <p>1,119 mm (with duplex scanning feeder C1 + finisher/saddle stitcher installed)</p> <p>AE1+copy tray T2+paper box open)</p>

Contact Us

Back to top

Main unit weight (including toner bottle)		Approx. 69kg (including BA1 automatic document feeder) Approx. 75kg (with C1 automatic document feeder)
Standard Duplex Automatic Document Feeder-BA1		
Original scanning speed	Single-sided copying:	51 pages/minute (A4, black and white/color, 600×600dpi)
	Double-sided copying:	25.5 pages/minute (A4, black and white/color, 600×600dpi)
	Single-sided scanning	70 pages/minute (A4, black and white/color, 300×300dpi)
	Duplex scanning	35 pages/minute (A4, black and white/color, 300×300dpi)
Optional Duplex Simultaneous Scanning Feeder-C1		
Original scanning speed	Single-sided copying	80 pages/minute (A4, black and white, 600×600 dpi) 80 pages/minute (A4, color, 600×600 dpi)
	Double-sided copying	160 pages/minute (A4, black and white, 600×600 dpi) 90 pages/minute (A4, color, 600×600 dpi)
	Single-sided scanning	135 pages/minute (A4, black and white, 300×300 dpi) 135 pages/minute (A4, color, 300×300 dpi)
	Duplex Scanning	270 pages/minute (A4, black and white, 300×300 dpi) 270 pages/minute (A4, color, 300×300 dpi)

复印及主要规格

复印/打印方式		激光静电转印方式
感光材料		OPC
显影系统		干式双组分显影
内存		标配3.5GB
固态硬盘		标配：256GB，1TB
预热时间	主机电源 打开时	10秒或更少
	睡眠模式 恢复时	10秒或更少
	快速启动 模式时	4秒或更少
最大原稿尺寸		A3
首页输出时间		5.5秒
灰度等级		256级
分辨率	复印	600dpi×600dpi
	打印	1,200dpi×600dpi, 1,200dpi×1,200dpi（半速）
	扫描	600dpi×600dpi
复印倍率	固定倍率	25%， 50%， 61%， 70%， 81%， 86%， 100%（1:1）， 115%， 122%， 141%， 200%， 400%
	手动缩放	25% ~ 400%（以1%为单位）
连续输出速度		35页/分钟
连续复印张数		1 ~ 9,999张
供纸量（A4， 80gsm）	标准	550张×2（纸盒供纸）+100张（手送托盘）
	可选	550张×2（双纸盒组件-AW1）， 2450张（大容量纸盒-E1）

[联系我们](#)

[返回顶部](#)

纸张尺寸	纸盒	纸盒1: 标配尺寸: A4, A5, A5R, A6R, B5, 16K 自定义尺寸: 105.0×148.0mm ~ 297.0×215.9mm 信封: ISO-C5 纸盒2: 标配尺寸: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, 8K, 16K, 16KR 自定义尺寸: 105.0×148.0mm ~ 304.8×457.2mm 信封: COM10 No.10, Monarch 30 sheets, DL
	手送纸盘	标配尺寸: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, 8K, 16K, 16KR 定制尺寸: 98.4×139.7mm~320.0×457.2mm 自定义尺寸: 100.0×148.0mm~304.8×457.2mm 信封: COM10 No.10, Monarch 30 sheets, ISO-C5, DL 信封自定义尺寸: 98.0×98.0mm~320.0×457.2mm
纸张厚度	纸盒	52~256g/m ²
	手送纸盘	52~300gsm* * SRA3不适用于涂层纸 (257~300gsm) 和厚纸 (257gsm~300gsm) 纸张类扩组件-A1: 60 ~ 300gsm
纸张类型	纸盒	纸盒1: 薄纸, 普通纸, 厚纸, 再生纸, 彩色纸, 证券纸, 预先穿孔纸, 信签纸、信封 纸盒2: 薄纸, 普通纸, 厚纸, 再生纸, 彩色纸, 证券纸, 预先穿孔纸, 信签纸、信封
	手送纸盘	薄纸, 普通纸, 厚纸*, 再生纸, 涂层纸*, 彩色纸, 描图纸, 证券纸, 标签纸, 预先穿孔纸, 信签纸, 信封 * SRA3不适用于涂层纸 (257~300gsm) 和厚纸 (257gsm~300gsm)
电源		220-240V 50/60Hz 5A
最大功耗		不超过1.5kw
睡眠模式能耗		0.8W* *由于某些设置, 0.8W睡眠模式并非在所有情况下都可用
主机尺寸 (宽×深×高)		含双面自动输稿器BA1: 565×719×891mm 含双面同步扫描输稿器C1: 565×722×897mm
安装空间 (宽×深)		基本尺寸: 978×1,116mm (安装双面自动输稿器BA1+多功能托盘拉出+纸盒打开时) 978×1,119mm (安装双面同步扫描输稿器C1+多功能托盘拉出+纸盒打开时) 全展开尺寸: 1,651×1,116mm (安装双面自动输稿器BA1+分页装订器/鞍式装订处理器AE1+复印托盘T2+纸盒打开时) 1,651×1,119mm (安装双面同步扫描输稿器C1+分页装订器/鞍式装订处理器AE1+复印托盘T2+纸盒打开)

[联系我们](#)

[返回顶部](#)

主机重量（含墨粉瓶）		约69kg（含双面自动输稿器BA1） 约75kg（安装双面同步扫描输稿器C1）
标配双面自动输稿器-BA1		
原稿扫描速度	单面复印	51页/分钟（A4，黑白/彩色，600×600dpi）
	双面复印	25.5页/分钟（A4，黑白/彩色，600×600dpi）
	单面扫描	70页/分钟（A4，黑白/彩色，300×300dpi）
	双面扫描	35页/分钟（A4，黑白/彩色，300×300dpi）
选配双面同步扫描输稿器-C1		
原稿扫描速度	单面复印	80页/分钟（A4，黑白，600×600dpi） 80页/分钟（A4，彩色，600×600dpi）
	双面复印	160页/分钟（A4，黑白，600×600dpi） 90页/分钟（A4，彩色，600×600dpi）
	单面扫描	135页/分钟（A4，黑白，300×300dpi） 135页/分钟（A4，彩色，300×300dpi）
	双面扫描	270页/分钟（A4，黑白，300×300dpi） 270页/分钟（A4，彩色，300×300dpi）

