

Functions You'll Love



Bluetooth
5.0



Dual band 2.4/5G Wi-
Fi



Low Noise



3D
Supported



Play 3

Display

Product Classification	Portable Projector
Display Technique	DLP
Display Chip	0.23" DMD
Supported Formats	HDR 10
Brightness	400 ISO Lumens ¹
Standard Resolution	1920 × 1080 pixels
Lamp Life	25000 Hours ⁵

Lens	High Light Transmission Coated Lens
3D	3D (Top and Bottom(Including Frame Packing) & Side by Side)

Projection

Throw Ratio	1.2:1
Auto Focus	ISA 2.0 uninterrupted auto focus
Auto Keystone Correction	ISA 2.0 uninterrupted auto keystone
Intelligent Screen Alignment	Yes
Intelligent Obstacle Avoidance	Yes
Intelligent Eye Protection	Yes
Projection Method	Front, Rear, Front Ceiling, Rear Ceiling
Image Size	40" – 200" ²

Audio

Speaker	2 x 8W
Dolby Audio	Yes
Dolby Digital (DD)	Yes
Dolby Digital Plus (DD+)	Yes

System

RAM	2GB
Storage	16GB ⁶

System	GMUI 5.0
--------	----------

Fast Boot	Yes
-----------	-----

Connectivity

Input Ports	USB type-C × 1, USB type-A × 1, HDMI 2.0 × 1
-------------	--

Output Ports	AUX 3.5mm × 1
--------------	---------------

WiFi	Wifi 5 Dual-band 2.4/5GHz, 802.11a/b/g/n/ac ⁴
------	---

Bluetooth	Bluetooth 5.0
-----------	---------------

Electrical

Noise	< 30dB ⁷
-------	---------------------

Power Dissipation	65W
-------------------	-----

Power	AC100–240V, 50/60Hz
-------	------------------------

Measurements

Product Size (H x W x D)	161 × 119 × 108mm (6.33 × 4.68 × 4.25 Inch) ⁸
--------------------------	--

Product Weight	1.1kg (2.42lb) ⁹
----------------	-----------------------------

What's in the Box

Power Plug	x1
------------	----

Warranty Card	x1
---------------	----

Manual	x1
--------	----

Bluetooth Remote Control	Bluetooth Remote Control × 1, AAA Batteries × 2
--------------------------	---

Product Notes:

1. Product brightness values and marks are generated by the XGIMI laboratories and enterprise. According to local standards and regulations, starting from the new MoGo 2 series, we have chosen to use ISO as our standard for brightness labeling. For relevant XGIMI laboratory standards, refer to: us.xgimi.com/pages/luminance-testing-method.

2. For the best viewing experience, we recommend using a projection size of 60–120 inches. Exceeding this range may affect the quality of your projected content. The display quality may vary based on product usage habits and environmental conditions.

3. Android TV is a trademark of Google LLC.

4. Router required.

5. 25,000 hours is the theoretical lifespan of the light source. The actual lifespan may vary due to differences in environmental conditions, product usage habits and the mode selected.

6. The actual storage capacity is subject to change based on various factors, such as system usage, software version, and settings used.

7. Measured under an ambient temperature of 25°C with a 1-meter distance from the machine. Results may vary based on different testing environments, conditions, and the product being evaluated. This data comes from XGIMI laboratories.

8. The measured size may vary based on configuration, manufacturing, and measurement method.

9. The measured weight may vary based on configuration, manufacturing process, and measurement method.

* Actual product features and specifications (including appearance, color, and size) and actual display aspects (including backgrounds, interface, and icons) may vary by country. Please consult the point of sale for further information.

* All performance data in the preceding pages are theoretical values obtained by XGIMI internal laboratories through tests conducted under particular conditions. Refer to the aforementioned product details for more information on the specific testing conditions. Actual performance may vary based on individual product configurations, software versions, application conditions, and environmental factors. All data is subject to actual usage.

* XGIMI makes every effort at the time of publication to ensure the accuracy of product information it provides. Due to subsequent changes involving product batches, production, and supply factors, it may be necessary for XGIMI to make changes and adjustments to text and images so that they match the performance, specifications, indexes, and components of the actual product. Product information is subject to such changes and adjustments without notice.

* Operating temperature: 0°C to 40°C.

* All parameters listed on this page are measured in an XGIMI internal test environment for mass production. User experiences may vary in different settings, usage conditions, software versions, etc. Please check the official XGIMI website for detailed test standards and data.

* The product will be attached with a printed manual. However, the electronic manual will be updated on the XGIMI website. If there is any discrepancy or conflict between the printed and the electronic manual, please refer to the latest electronic manual on the official website: us.xgimi.com/pages/mogo-2-pro-support.

* The 90% color gamut mentioned here is based on the area ratio.