Copy and main specifications

Copy/Print Mode		Laser electrostatic transfer method
Photosensitive materials		**OPC**
Development system		**Dry two-component developer**
Fixing system		**Advanced color fast fixing technology**
Memory	**Standard**	**3.5GB**
SSD Solid State Drive		**256GB**
Warm-up time	**Host power supply** **When open**	**10 seconds or less**
	Sleep Mode **When recovering**	**10 seconds or less**
	Fast boot up in 4 seconds or less	
Maximum original size		**A3**
First page output time		**6.1 s/8.4 s or less**
Grayscale		**256 levels**
Resolution	**copy**	**600dpi x 600dpi**
	Print	**1200dpi x 600dpi** **1200dpi x 1200dpi (half-speed)**
Copy ratio	**Fixed ratio: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%**	
	Manual zoom 25% ~ 400% (in 1% units)	
Continuous output speed		**30ppm**
Continuous copying number		**1 ~ 999 sheets**
Paper supply ÿ80g/m ÿ **2**	**Standard double paper** **box**	**550 sheets x 2+100 sheets (multi-purpose tray)**
	Optional	**550 sheets x 2(with Cassette Feeding Unit-AW1)**
Paper thickness Tray 1 & 2 52 ~ 256 gsm		

Paper type	Tray 1	A4, A5, A5R, A6R, B5, 16K, ISO-C5 Customized: 105.0 x 148.0 mm ~ 297.0 x 215.9 mm
	Tray 2	A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, 8K, 16K, 16KR, COM10 No.10, Monarch, DL Customized: 105.0 x 148.0 mm ~ 304.8 x 457.2 mm
power supply		220-240V 50/60Hz 5A
Maximum power consumption		No more than 1.5kw
Energy consumption in sleep mode		0.8W*Due to certain settings, 0.8W sleep mode may not be available in all situations.
Host size (width x depth x height)		565 x 719 x 891 mm (including duplex automatic document feeder)
Host weight		78 kg (including toner and duplex automatic document feeder)

Main Components

Duplex automatic scanning document feeder-BA1 (standard)	
Original feeding method	Automatic Document Feeder
Original size	A3, A4, A4R, A5, A5R, B4, B5, B5R, B6, 8K, 16K Customized size: 128.0 x 139.7 mm ~ 297.0 x 431.8 mm
Original scanning speed	Single-sided: 70/70 (300 x300 dpi, send), 51/51 (600 x600 dpi, copy)
	Duplex: 35/35 (300 x300 dpi, send), 25.5/25.5 (600 x600 dpi, copy)
Scanning resolution (dpi)	600x 600
Original tray capacity	100 pages (80gsm)

Duplex scanning document feeder-C1 (optional)	
Original feeding method	Automatic Document Feeder
Original size	A3, A4, A4R, A5, A5R, B4, B5, B5R, B6, 8K, 16K Customized size: 69.9 x 139.7 mm ~ 304.8 x 431.8 mm
Original scanning speed	Single-sided: 135/135 (300 x300 dpi, send), 80/80 (600 x600 dpi, copy)
	Duplex: 270/270 (300 x300 dpi, send), 160/90 (600 x600 dpi, copy)
Scanning resolution (dpi)	600x 600

复印及主要规格

复印/打印方式		激光静电转印方式
感光材料		OPC
显影系统		干式双组分显影
定影系统		高级彩色快速定影技术
内存	标配	3.5GB
SSD固态硬盘		256GB
预热时间	主机电源打开时	10秒以内或更少
	睡眠模式恢复时	10秒以内或更少
	快速启动	4秒或更少
最大原稿尺寸		A3
首页输出时间		6.1 s/8.4 s或更少
灰度等级		256级
分辨率	复印	600dpi x 600dpi
	打印	1200dpi x 600dpi 1200dpi x 1200dpi(half-speed)
复印倍率	固定倍率	25%, 50%, 61%, 70%, 81%, 86%, 100%（1:1），115%, 122%, 141%, 200%, 400%
	手动缩放	25%～400%（以1%为单位）
连续输出速度		30ppm
连续复印张数		1～999张
供纸量（80g/m²）	标准双纸盒	550张 x 2+100张（多功能托盘）
	选配	550张 x 2(with Cassette Feeding Unit-AW1)
纸张厚度	纸盒1&2	52～256 gsm

激光静电转印方式

纸张类型	纸盒1	A4, A5, A5R, A6R, B5, 16K, ISO-C5 自定义：105.0 x 148.0 mm ~ 297.0 x 215.9 mm
	纸盒2	A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, 8K, 16K, 16KR, COM10 No.10, Monarch, DL 自定义：105.0 x 148.0 mm ~ 304.8 x 457.2 mm
电源		220-240V 50/60Hz 5A
最大功耗		不超过1.5kw
"睡眠"模式能耗		0.8W*由于某些设置，0.8W睡眠模式并非在所有情况下都可用。
主机尺寸（宽×深×高）		565 x 719 x 891 mm (含双面自动扫描输稿器)
主机重量		78 kg（包含墨粉含双面自动扫描输稿器）

主要组件

双面自动扫描输稿器-BA1（标配）

原稿输送方式	自动文档输稿器
原稿尺寸	A3, A4, A4R, A5, A5R, B4, B5, B5R, B6, 8K, 16K 自定义尺寸: 128.0 x 139.7 mm ~ 297.0 x 431.8 mm
原稿扫描速度	单面: 70/70 (300 x300 dpi, send), 51/51 (600 x600 dpi, copy) 双面: 35/35 (300 x300 dpi, send), 25.5/25.5 (600 x600 dpi, copy)
扫描分辨率(dpi)	600x 600
原稿托盘容量	100页（80gsm）

双面同步扫描输稿器-C1（选配）

原稿输送方式	自动文档输稿器
原稿尺寸	A3, A4, A4R, A5, A5R, B4, B5, B5R, B6, 8K, 16K 自定义尺寸: 69.9 x 139.7 mm ~ 304.8 x 431.8 mm
原稿扫描速度	单面: 135/135 (300 x300 dpi, send), 80/80 (600 x600 dpi, copy) 双面: 270/270 (300 x300 dpi, send), 160/90 (600 x600 dpi, copy)
扫描分辨率(dpi)	600x 600