

Fast Graph Kernel with Optical Random Features



Hashem GHANEM

Nicolas KERIVEN Nicolas TREMBLAY

IEEE ICASSP 2021

June 06/2021



Outline

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

1 Introduction to the graph classification problem

Introduction to
the graph
classification
problem

2 Background: the graphlet kernel

Background:
the graphlet
kernel

3 GSA- φ algorithm with optical random features

GSA- φ
algorithm with
optical random
features


4 Results and Discussion

Results and
Discussion


References

Graphs

- Model: (objects \rightarrow nodes) , (relations \rightarrow edges).




(a) Chemical reactions




(b) Social networks

- Adjacency matrix to represent a graph of v nodes:
 - $\mathbf{A} \in \mathbb{R}^{v \times v}$: $a_{i,j} = 1$ if nodes (i,j) have edge, 0 otherwise.



Graph classification & applications

- Supervised classification:
 - Pre-labeled dataset: $(\{\mathcal{G}_1, \dots, \mathcal{G}_n\}, \{y_1, \dots, y_n\})$.
 - Each graph \mathcal{G}_i belongs to class y_i .
 - Task: a classification algorithm that, given in input a new graph, output the class to which it belongs.
- Graphs have different sizes (#nodes), so a classifier has 2 blocks:



- Applications in real world: Marketing, Banking, Biology.
- Example in biology:
 - amino acids are linked to form a protein.
 - enzymes are specific type of proteins
 - predict whether a protein is an enzyme or not.

- Graph kernels based algorithms:
 - Fixed graph representation is computed.
 - **Graphlet kernel** is based on counting subgraphs.

Our Contribution: inspired by the graphlet kernel, we propose a fast and efficient graph classification framework, which leverages optical random features.

Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

GSA- φ
algorithm with
optical random
features

Results and
Discussion

References

Outline

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

1 Introduction to the graph classification problem

Introduction to
the graph
classification
problem

2 Background: the graphlet kernel

Background:
the graphlet
kernel

3 GSA- φ algorithm with optical random features

GSA- φ
algorithm with
optical random
features


4 Results and Discussion

Results and
Discussion


References

Necessary tools and definitions

- Graphlet kernel needs an integer parameter k to be fixed.
- Also, the set of all different graphs of size k .
 - these graphs are called *graphlets*.




- Definition: to get a sub-graph \mathcal{F} from a graph \mathcal{G} :



Graphlet kernel illustration

Goal: compute representation vectors for graphs, for example:



The **probability mass function $\mathbf{f}_{\mathcal{G}}$** is the representation vector of \mathcal{G} .

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

GSA- φ
algorithm with
optical random
features

Results and
Discussion

References

Graphlet kernel cost

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM


Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

GSA- φ
algorithm with
optical random
features

Results and
Discussion

References



$f_{\mathcal{G}}$ cost **exponential** in k : $C_{gk} = \mathcal{O}(\#subgraphs * \#graphlets * C_{comp})$

Acceleration: estimate \mathbf{f}_G with s subgraphs

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

GSA- φ
algorithm with
optical random
features


Results and
Discussion

References

A graph G from the dataset.



Randomly sample $s = 6$ sub-graphs of size $k = 3$ from G



$$\hat{\mathbf{f}}_G = \frac{1}{6} * \begin{bmatrix} 1 & 3 & 1 & 1 \end{bmatrix}$$

$$\left. \begin{array}{l} \hat{\mathbf{f}}_G \text{ cost:} \\ \mathcal{O}(6 * 4 * C_{comp}) \end{array} \right\}$$

$\hat{\mathbf{f}}_G$ cost is lower but still **exponential** in k :

$$C_{gk+gs} = \mathcal{O}(s * \#graphlets * C_{comp})$$

\Rightarrow must deal with the matching stage for a lower cost.

Outline

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

1 Introduction to the graph classification problem

Introduction to
the graph
classification
problem

2 Background: the graphlet kernel

Background:
the graphlet
kernel

3 GSA- φ algorithm with optical random features

GSA- φ
algorithm with
optical random
features

4 Results and Discussion


Results and
Discussion

References

Proposed classification framework $GSA - \varphi$

Replace subgraph-to-graphlet matching with a fast user-defined map:

$\varphi : \{\text{size-}k \text{ subgraphs}\} \mapsto \mathbb{R}^m$, m is user-chosen.



$\mathbf{z}_{\mathcal{G}}$ is the representation vector of \mathcal{G} , with cost: $C_{GSA-\varphi} = \mathcal{O}(s * C_{\varphi})$.

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

$GSA-\varphi$
algorithm with
optical random
features

Results and
Discussion

References

$GSA - \varphi$ with kernel random features

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

- Kernels with random features are functions that:

$$\kappa(\mathbf{x}, \mathbf{x}') = \mathbb{E}_{\mathbf{w} \sim p} \xi_{\mathbf{w}}(\mathbf{x})^* \xi_{\mathbf{w}}(\mathbf{x}')$$

- Defining : $\varphi_{RF}(\mathbf{x}) = \frac{1}{\sqrt{m}} (\xi_{\mathbf{w}_j}(\mathbf{x}))_{j=1}^m$
we can write: $\kappa(\mathbf{x}, \mathbf{x}') \approx \varphi_{RF}(\mathbf{x})^* \varphi_{RF}(\mathbf{x}')$

- Example: Gaussian kernel $\kappa_G(\mathbf{x}, \mathbf{x}') = \exp^{-\frac{\|\mathbf{x} - \mathbf{x}'\|^2}{2\sigma^2}}$ corresponds to:

$$\varphi(\mathbf{x}) = \frac{\sqrt{2}}{\sqrt{m}} \cos(\mathbf{W}^T \mathbf{x} + b), \quad \mathbf{x} \in \mathbb{R}^d, \mathbf{W} \in \mathbb{R}^{m \times d}$$

- \mathbf{x} is a subgraph adjacency matrix $\Rightarrow \varphi_{RF}(\mathbf{x})$ costs: $\mathcal{O}(mk^2)$
- Computation cost of $GSA - \varphi_{RF} = \mathcal{O}(smk^2)$

Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

$GSA - \varphi$
algorithm with
optical random
features

Results and
Discussion

References

Concentration analysis

- Recall: $(\mathcal{G} + \text{subgraph sampling}) \rightarrow \mathbf{f}_{\mathcal{G}}$: discrete prob. dist. of graphlets.
- Recall: $\mathbf{z}_{\mathcal{G}}$ is the graph representation of $GSA - \varphi$.
- The Euclidean metric $\|\mathbf{z}_{\mathcal{G}} - \mathbf{z}_{\mathcal{G}'}\|^2$ converges to the **MMD metric**: $MMD(\mathbf{f}_{\mathcal{G}}, \mathbf{f}_{\mathcal{G}'})^2$
- MMD is a true metric on distributions for many schemes of kernel random features


Theorem

Let \mathcal{G} and \mathcal{G}' be two graphs. Assume that $|\xi_{\mathbf{w}}(F)| \leq 1$.
Then, for all $\delta > 0$, with probability at least $1 - \delta$:

$$\left| \|\mathbf{z}_{\mathcal{G}} - \mathbf{z}_{\mathcal{G}'}\|^2 - MMD(\mathbf{f}_{\mathcal{G}}, \mathbf{f}_{\mathcal{G}'})^2 \right| \leq \frac{4\sqrt{\log(6/\delta)}}{\sqrt{m}} + \frac{8\left(1 + \sqrt{2\log(3/\delta)}\right)}{\sqrt{s}}$$

GSA – φ with optical random features

- Model: $\varphi_{OPU}(\mathbf{x}) = |\mathbf{W}\mathbf{x} + \mathbf{b}|^2$; $\mathbf{W} \in \mathbb{R}^{m \times d}$, $\mathbf{b} \in \mathbb{R}^m$, $\mathbf{x} \in \mathbb{R}^d$
- When $m \mapsto \infty$ then: $\varphi_{OPU}(\mathbf{x}_1)^T \varphi_{OPU}(\mathbf{x}_2) \approx \kappa_{OPU}(\mathbf{x}_1, \mathbf{x}_2)$



OPU's Experimental setup [Saade et al., 2016].

- $C_{\varphi_{OPU}} = \mathcal{O}(1)$ in the input and output dimensions.
- The computation cost $C_{GSA-\varphi_{OPU}} = \mathcal{O}(s)$

Comparison between computation costs

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

GSA- φ
algorithm with
optical random
features

Results and
Discussion

References

Graphlet kernel		$O(s * (\#graphlets) * C_{comp})$
GSA- φ with:	φ_{Gs}	$O(sm k^2)$
	φ_{Gs+eig}	$O(s(mk + k^3))$
	φ_{OPU}	$O(s)$

Outline

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

1 Introduction to the graph classification problem

Introduction to
the graph
classification
problem

2 Background: the graphlet kernel

Background:
the graphlet
kernel

3 GSA- φ algorithm with optical random features

GSA- φ
algorithm with
optical random
features


4 Results and Discussion

Results and
Discussion

References

$GSA - \varphi_{OPU}$ Vs. graphlet kernel and GCN models

- Dataset:
 - 300 2-classes labeled graphs.
 - generated based on SBM model.
 - inter-class similarity r controls the problem difficulty.




Fixed parameters: $s = 2000$, $m = 5000$

k -graphlet Kernel for $k = 3$

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM



Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

GSA- ϕ
algorithm with
optical random
features

Results and
Discussion

References


Fixed parameters: $r = 1.1$, $s = 2000$, $m = 5000$ and $\sigma = 0.1$.

$GSA - \varphi_{OPU}$ on the Reddit dataset

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

- $k = 7, s = 4000$.
- For every m , the experiment is repeated 4 times (red dots), then averaged (blue curve).



Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

$GSA-\varphi$
algorithm with
optical random
features

Results and
Discussion

References

Conclusion and future work

Conclusion:

- 1 GSA- φ with RF maps separates well between graphs.
- 2 GSA- φ with optical RF maps is faster than traditional graphlet kernel.
- 3 GSA- φ with optical RF maps performs better than the graphlet kernel, and better than a particular graph convolutional networks on graph classification.

Future work:

- 1 Combine our algorithm with GCNs when we have node features.
- 2 Further analysis of the MMD metric properties on particular graph models.

Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

GSA- φ
algorithm with
optical random
features

Results and
Discussion

References

References I

- Hashem Ghanem, Nicolas Keriven, and Nicolas Tremblay. Fast graph kernel with optical random features. *ICASSP*, 2021.
- Alaa Saade, Francesco Caltagirone, Igor Carron, Laurent Daudet, Angélique Drémeau, Sylvain Gigan, and Florent Krzakala. Random projections through multiple optical scattering: Approximating kernels at the speed of light. In *2016 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 6215–6219. IEEE, 2016.
- Nino Shervashidze, SVN Vishwanathan, Tobias Petri, Kurt Mehlhorn, and Karsten Borgwardt. Efficient graphlet kernels for large graph comparison. In *Artificial Intelligence and Statistics*, pages 488–495, 2009.
- Johannes Kobler, Uwe Schöning, and Jacobo Torán. *The graph isomorphism problem: its structural complexity*. Springer Science & Business Media, 2012.
- Aman Sinha and John C Duchi. Learning kernels with random features. In *Advances in Neural Information Processing Systems*, pages 1298–1306, 2016.

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

GSA- φ
algorithm with
optical random
features

Results and
Discussion

References

References II

Fast Graph
Kernel with
Optical
Random
Features

Hashem
GHANEM

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *International Conference on Learning Representations*, 2019. URL <https://openreview.net/forum?id=ryGs6iA5Km>.

Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. In *Advances in neural information processing systems*, pages 1177–1184, 2008.

Introduction to
the graph
classification
problem

Background:
the graphlet
kernel

GSA- φ
algorithm with
optical random
features

Results and
Discussion

References