




# Factory Manipulation with Cooperative Multi-agent Reinforcement Learning


28. May 2024

Kirschstein, Köck



# The Setting

- 2 or more robot arms
- basket in reach for each arm
- conveyor belt (with increasing speed)
- cubes transported on the conveyor belt  
→ shall be put into the basket
- arms must not hit each other
- arms must not hit the environment
- 8 degrees of freedom
- Arms use RL to learn movements



# The Reward Function



Which reward should we use?

# The Reward Function

Which reward should we use?

1st intention:

**Reward of 1, if a block is thrown in the basket**

# The Reward Function

Which reward should we use?

1st intention:

**Reward of 1, if a block is thrown in the basket**

Sparse reward

- → **Almost no learning possible**

*Hier könnt ihr Foto stehen*

# The Reward Function

Which reward should we use?

2nd intention:

Function **increases monotonously** with *progress to target*

# The Reward Function

Which reward should we use?

2nd intention:

Function **increases monotonously** with *progress to target*

Parameters to include:

- $N$ : Number of cubes in basket
- $d_c$ : Distance to closest cube
- $d_r$ : Distance to closest robot arm
- $d_b$ : Distance to basket
- $g$ : Gripper state
- $a \in [-1, 1]^{\text{DOF}}$ : action vector

# The Reward Function

Which reward should we use?

2nd intention:

Function **increases monotonously** with *progress to target*

Desirable Incentives:

- Reward vicinity to closest cube
- Punish distance to other robot arms
- Reward grasping while very close to cube
- Reward vicinity to basket with grasped cube
- Reward relaxing grasp over basket
- Punish hectic motion



# The Reward Function

Which reward should we use?

2nd intention:

Function **increases monotonously** with *progress to target*

Possible reward function with Incentives  $l_0, \dots, l_6$ :

$$r = \sum_{i=0}^6 \varepsilon_i l_i$$

with  $\varepsilon_i$  scaling factor as hyperparameter

Start with equal  $\varepsilon_i$ , goal:  $\varepsilon_0 \gg \varepsilon_i$ , ideally most  $\varepsilon_i = 0$