

# kmul user manual



<b>Title</b>	kmul (Constant multiplication routine generator)
<b>Author</b>	Nikolaos Kavvadias
<b>Contact</b>	<a href="mailto:nikolaos.kavvadias@gmail.com">nikolaos.kavvadias@gmail.com</a>
<b>Website</b>	<a href="http://www.nkavvadias.com">http://www.nkavvadias.com</a>
<b>Release Date</b>	17 October 2020
<b>Version</b>	0.1.4
<b>Rev. history</b>	
<b>v0.1.4</b>	2020-10-17 Add a binary decomposition algorithm.
<b>v0.1.3</b>	2016-07-29 Add support for C99, GNU89 data types, fix support for ANSI C ones.
<b>v0.1.2</b>	2016-04-12 Cumulative update; flag management cleanup, cleanup scripts.
<b>v0.1.1</b>	2014-11-29 Added project logo in README.
<b>v0.1.0</b>	2014-10-16 Documentation updates and fixes.
<b>v0.0.7</b>	2014-06-13 Changed README to README.rst.
<b>v0.0.6</b>	2014-06-12 Updated contact information. Replaced COPYING.BSD by LICENSE.
<b>v0.0.5</b>	2013-04-28 Converted documentation to RestructuredText.
<b>v0.0.4</b>	2012-03-17 Split build-and-test scripts to "build" and "test".
<b>v0.0.3</b>	2011-12-03 Minor README updates regarding multiple releases, tutorial usage.

<b>v0.0.2</b>	2011-11-20 Minor README, Makefile updates.
<b>v0.0.1</b>	2011-06-07 Initial release.

## 1. Introduction

`kmul` is a generator of routines for optimized multiplication by an integer constant. In order to calculate a constant integer multiplication, it uses the public domain routines presented in the work: Preston Briggs and Tim Harvey, "Multiplication by integer constants," Technical report, Rice University, July 1994. This technical report implements Bernstein's algorithm documented in: R. Bernstein, "Multiplication by integer constants," Software - Practice and Experience, Vol. 16, No. 7, pp. 641-652, July 1986.

A simpler algorithm based on binary decomposition can also be used for comparison.

`kmul` emits either a NAC (generic assembly language) or an ANSI C/C99 implementation of the multiplication.

## 2. File listing

The `kmul` distribution includes the following files:

/kmul	Top-level directory
LICENSE	Description of the Modified BSD license.
Makefile	Makefile for generating the <code>kmul</code> executable.
README.html	HTML version of README.rst.
README.pdf	PDF version of README.rst.
README.rst	This file.
build.sh	Build script for <code>kmul</code> .
clean.sh	Clean the files produced from <code>test.sh</code> .
clean2.sh	Clean the files produced from <code>test2.sh</code> .
kmul.c	The source code for the application.
kmul.png	PNG image for the <code>kmul</code> project logo.
rst2docs.sh	Bash script for generating the HTML and PDF versions.
test.c	Sample test file.
test.opt.c	Expected optimized version of <code>test.c</code> .
test.sh	Perform some sample runs.
test2.sh	Another test script to perform more sample runs.

### 3. Installation

There exists a quite portable Makefile (`Makefile` in the current directory). Running `make` from the command prompt should compile `kmul`.

### 4. Prerequisites

- [mandatory for building] Standard UNIX-based tools (`make`)
- `gcc` (tested with `gcc-3.4.4+` on `cygwin/x86` and `gcc-4.6+` on `linux/x64`)
- `bash`

### 5. `kmul` usage

The `kmul` program can be invoked with several options (see complete option listing below). The usual tasks that can be accomplished with `kmul` are:

- generate a NAC optimized software routine for the multiplication
- generate an ANSI C optimized software routine for the multiplication.

ANSI C routines are emitted only for a width of 32-bits (see option below).  
`kmul` can be invoked as:

```
$ ./kmul.exe [options]
```

The complete `kmul` options listing:

- h** Print this help.
- d** Enable debug/diagnostic output.
- bindecomp** Use binary decomposition instead of the Bernstein-Briggs algorithm.
- mul <num>** Set the value of the multiplier. Default: 1.
- width <num>** Set the bitwidth of all operands: multiplier, multiplicand and product. Default: 32.
- signed** Construct optimized routine for signed multiplication.
- unsigned** Construct optimized routine for unsigned multiplication (default).
- nac** Emit software routine in the NAC general assembly language (default).
- ansic** Emit software routine in ANSI C (for widths up to 32 bits).
- gnu89** Emit software routine in ANSI C with GNU extensions (for widths up to 64 bits).
- c99** Emit software routine in C99 (for widths up to 64 bits).

Here follow some simple usage examples of `kmul`.

1. Generate the ANSI C implementation of the optimized routine for  $n * 11$ .

```
$ ./kmul.exe -mul 11 -width 32 -unsigned -ansic
```

2. Generate the NAC implementation of the optimized routine for  $n * (-7)$ .

```
$ ./kmul.exe -mul -7 -width 32 -signed -ansic
```

3. Generate the ANSI C implementation of the optimized routine for  $n * 23$  with debugging output.

```
$ ./kmul.exe -mul 23 -width 32 -unsigned -ansic -d
```

4. Generate the C99 implementation of the optimized routine for the signed  $n * 23$  multiplication and for a data width of 17 bits.

```
$ ./kmul.exe -mul 23 -width 17 -signed -c99
```

## 6. Quick tutorial

kmul can be used for arithmetic optimizations in user programs. Assume the following user program (test.c):

```
// test.c
#include <stdio.h>
#include <stdlib.h>
int main(int argc, char *argv[]) {
    int a, b;
    a = atoi(argv[1]);
    b = a * 23;
    printf("b = %d\n", b);
    return b;
}
```

This file is compiled and run as follows with one additional argument:

```
$ gcc -Wall -O2 -o test.exe test.c
$ ./test.exe 155
```

and the expected result is:

```
$ b = 3565
```

The user can apply kmul for generating a constant multiplication routine for  $a * 23$ :

```
$ ./kmul -mul 23 -width 32 -signed -ansic
```

and the corresponding routine is produced (local variables  $t_5$  to  $t_{15}$  can be deleted by the user; the compiler will be optimize them away eventually). Then, the user should

edit a new file, let's say `test.opt.c` and include the produced routine. The resulting optimized source file should be as follows:

```
// test.opt.c
#include <stdio.h>
#include <stdlib.h>

long kmul_o_s32_p_23 (long x)
{
    long t0;
    long t1;
    long t2;
    long t3;
    long t4;
    long t5;
    long t6;
    long t7;
    long t8;
    long t9;
    long t10;
    long t11;
    long t12;
    long t13;
    long t14;
    long t15;
    long y;
    t0 = x;
    t1 = t0 << 1;
    t2 = t1 + x;
    t3 = t2 << 3;
    t4 = t3 - x;
    y = t4;
    return (y);
}

int main(int argc, char *argv[])
{
    int a, b;
    a = atoi(argv[1]);
    b = kmul_o_s32_p_23(a);
    printf("b = %d\n", b);
    return b;
}
```

This file is compiled and run as follows with one additional argument:

```
$ gcc -Wall -O2 -o test.opt.exe test.opt.c
$ ./test.opt.exe 155
```

The target platform compiler (e.g., gcc or llvm) is expected to inline the `kmul_o_s32_p_23` function at its call site.

## 7. Running tests

In order to build and run a series of sample tests do the following:

```
$ ./build.sh
$ ./test.sh
```

or for a more extensive set of tests:

```
$ ./test2.sh
```

To clean-up the produced files and only these use:

```
$ ./clean.sh
```

or

```
$ ./clean2.sh
```

for `test.sh` and `test2.sh`, correspondingly.