

ChatScript PostgreSQL
© Bruce Wilcox, gowilcox@gmail.com
Revision 3/22/2014 cs4.2

ChatScript ships with code and WINDOWS libraries for accessing PostgreSQL but you need a database somewhere.

On Linux, ChatScript ships with PostgreSQL client built-in, but if you want to rebuild the system for some reason, then while standing in /src type either

make server – build ordinary CS server w/o PostgreSQL client

make pgserver – build CS server w PostgreSQL client (you had to install postgres first)

On Mac and IOS #define DISCARDDATABASE is on by default.

If you have access to a PostgreSQL server remotely, that's fine. If you need one installed on your machine, see the end for how to install one.

Access A PostgreSQL Database

There are only a couple of functions you need.

^DBINIT(xxx) xxx is the parameter string you want to pass PostgreSQL. The default minimal would be something like this:

```
u: (open) if (^dbinit( dbname = postgres port = 5432 user = postgres password = mypassword ))
    {db opened}
    else {db failed}
```

Once the named database is open, it becomes the current database the server uses *until you close it* no matter how many volleys later that is. Currently you can only have one database open at a time.

By the way, if a call to ^DBINIT fails, the system will both write why to the user log and set it onto the value of **\$\$db_error**.

^DBCLOSE() closes the currently open database.

^DBEXEC(“xxx” 'myfunc) executes database commands. You may omit the 2nd argument if those commands do not generate answers, otherwise it names a function you have defined whose argument count matches the number of pieces of information coming from the database. Typically a database query like **SELECT** will return multiple rows containing multiple columns of values. The number of values per row must match your function, which is called once for each row. If any call to your function fails, ^DBEXEC stops and fails. When you want to use multiple commands to the database, you must separate them with ; and only answers from the last command are returned (per PostgreSQL standards and behavior).

Note: for any direct calls, the format string “^”xxx” is your friend, as it will generally preserve the contents of the string unchanged to pass to DBEXEC.

So, after this, you can read whatever commands PostgreSQL supports because they all funnel through ^DBEXEC.

By the way, if a call to ^DBEXEC fails, the system will both write why to the user log and set it onto the value of `$$db_error`.

PostgreSQL Commands

The basic commands you most likely need are:

Creating Data

CREATE DATABASE name – to make a new database

CREATE TABLE weather – to define a new table

```
(
  city          varchar(80),
  stateAbbr     char[2],
  temp_lo       int,
  temp_hi       int,
  prcp          real,
  date          date
)
```

DROP TABLE weather - to delete a table

Note that the weather table, while shown all nicely laid out, has to be a single string to ^DBEXEC which will NOT span multiple lines (but could have been created by ^join(...) whose arguments could have been neatly laid out. Field names are case insensitive (per std).

INSERT INTO weather VALUES ('San Francisco', 'CA', 46, 50, 0.25, '1994-11-27')

Note that text values must be encased in ' xxx ' (per std).

Better style is to name the fields and values, omitting any you don't want to supply:

```
INSERT INTO weather (date, city, temp_hi, temp_lo)
VALUES ('1994-11-29', 'Hayward', 54, 37)
```

or with lots of data and a file on the same machine as the database server,
COPY weather FROM '/home/user/weather.txt'

Retrieving Data

SELECT * FROM weather - retrieves all fields and all rows of table weather (rows in arbitrary order)

You can name the fields and order with this:

```
SELECT city, temp_lo, temp_hi, prcp, date FROM weather
```

assuming the function of yours named expects 5 arguments.

And a constrained query like:

```
SELECT * FROM weather WHERE city = 'San Francisco' AND prcp > 0.0
```

And of course there are other things the database can do, including joins and other searches, but you can go read the PostgreSQL manual for that. The above is enough to do many simple things.

Creating A PostgreSQL Database

It's never as easy as you'd hope. Maybe I've hit all the stumbles for you.

Installation on Windows

While in theory you can install a 64-bit version of PostgreSQL on a 64-bit machine, I found there were problems in compiling ChatScript with it, so I use only the 32-bit version, which works on either 32-bit or 64-bit Windows machines. Note that the 32-bit dll that is needed is at the top level of ChatScript, so the system will automatically find it. For reference, the compilation header files and library for loading are in src/postgre/WIN32

First, you need to download the 32-bit Windows PostgreSQL. I used version 9.3.3 from this page: <http://www.enterprisedb.com/products-services-training/pgdownload#windows> win-x86-32. Download that and run it. You can default everything. ChatScript will just work with it.

Installation on Mac

Sorry. Don't have a mac. You have to figure it out yourself.

Installation on Linux

So many choices. You probably have to read docs for your system. I went wrong in so many directions I lost track of whether I was logged in as me, su, sudo, postgres, etc. If you have problems installing, here is my best knowledge... After that go search the internet or documentation, don't come to me to get postgres installed.

On my amazon AMI server I used

```
sudo yum -y install postgresql postgresql-server postgresql-devel postgresql-contrib
```

My 64-bit machine worked fine, my 32-bit machine had issues. Nominally you need to:

```
#0 set a password for your postgres user (the user that runs the db)
```

```
#1 initialize the database in PGDATA via
```

```
service postgresql initdb
```

or

```
su - postgresql
initdb -D /var/lib/pgsql9/data/
```

Confirm there is now stuff installed in /var/lib/pgsql9.

You may need to edit /var/lib/pgsql9/pg_hba.conf to change the local validation from peer to trust - e.g.

```
local    all             all                                trust
Sometimes it was already trust, and sometimes it was peer.
```

On a 32-bit AMI I tried to launch the postgres server but it wanted it to have been installed in /var/lib/pgsql for some reason. So I had to create a symbolic link to make it happy:

```
ln -s /var/lib/pgsql9 /var/lib/pgsql
```

#2 launch the server via

```
service postgresql start
```

or

```
su - postgres - log in as postgres user
pg_ctl start - starts server in background
```

#3 make it auto restart on reboot

```
chkconfig postgresql on
```

You can confirm a server is running by typing

```
psql
```

which is a tool to log into the server. You may have to be logged in as postgres.

There's a bunch more about setting up login passwords, etc. RTFM.