



Trailhead



[Lightning Web Components for Aura Developers \(/content/learn/modules/lightning-web-components-for-aura-developers?trailmix_creator_id=srebello7&trailmix_slug=salesforce-platform-developer\)](/content/learn/modules/lightning-web-components-for-aura-developers?trailmix_creator_id=srebello7&trailmix_slug=salesforce-platform-developer)



Compose Components

Compose Components

Learning Objectives

After completing this unit, you'll be able to:

- Compose components.
- Use a slot.
- List differences between data binding behavior for the two programming models.

You can add components within the body of another component. This component composition enables you to build complex components from simpler building-block components.

In a large application, it's useful to compose the app with a set of smaller components to make the code more reusable and maintainable.

The lightning namespace contains many base components, such as lightning-button, that you can use to build your components. For more details, see the [Component Library \(https://developer.salesforce.com/docs/component-library\)](https://developer.salesforce.com/docs/component-library).

Understand Component Relationships

Let's start by looking at a simple example and defining some of the terminology we use for composed components. This discussion can seem like an unnecessary diversion, but it's important to have consistent terminology when you're talking with other developers.

```
1 <!-- owner.html -->
2 <template>
3     <c-child first-name="Moonbeam"></c-child>
4 </template>
```



Hi NELLURI, ask me about products, features, and pricing, or connect to a sale...





The owner is the component that owns the template. In this example, the owner is the c-owner component. The owner controls all the composed components that it contains. The owner can:

[Lightning Web Components for Aura Developers \(7 content/learn/modules/lightning-web-components-for-aura-developers?trailmix_creator_id=srebello7&trailmix_slug=salesforce-platform-developer\)](https://trailhead.salesforce.com/content/learn/modules/lightning-web-components-for-aura-developers/compose-components?trailmix_creator_id=srebello7&trailmix_slug=salesforce-platform-developer)

Compose Components

- Set public properties on composed components.
- Call public methods on composed components.
- Listen for any events fired by the composed components.

Parent and Child

When a component contains another component, which, in turn, can contain other components, we have a containment hierarchy. In the documentation, we sometimes talk about parent and child components. A parent component contains a child component. A parent component can be the owner or a container component that's also part of the owner's template. In this example, c-parent-container is a container component because it contains c-child. The c-parent-container component is not the owner because it's in the template of the owner component, c-owner.

```
1 <!-- owner.html -->
2 <template>
3     <c-parent-container>
4         <c-child first-name="Moonbeam"></c-child>
5     </c-parent-container>
6 </template>
```



DreamHouse Example

Let's look at an example of composing components. The PropertyTileList Aura component contains the PropertyTile component.

```
1 <aura:component>
2     ...
3     <div class="slds-card">
4         <lightning:layout horizontalAlign="center"
5         multipleRows="true">
```





```
</lightning:layout>
</div>
```

[Lightning Web Components for Aura Developers \(/content/learn/modules/lightning-web-components-for-aura-developers?trailmix_creator_id=srebello7&trailmix_slug=salesforce-platform-developer\)](https://trailhead.salesforce.com/content/learn/modules/lightning-web-components-for-aura-developers?trailmix_creator_id=srebello7&trailmix_slug=salesforce-platform-developer)

The PropertyTile component has an attribute called property. Don't be distracted by that name. DreamHouse is a real-estate app, so we're talking about real-estate properties rather than JavaScript properties here!

Here's the HTML for the propertyTileList Lightning web component:

```
1 <template>
2   <div class="slds-card tile-list">
3     <template for:each={filteredProperties}
4     for:item="property">
5       <c-property-tile property={property} key=
6       {property.Id}></c-property-tile>
7     </template>
8   </div>
9 </template>
```



The markup looks similar for the two programming models, except for the syntax for referencing a composed component. We saw earlier how the Aura model and the Lightning Web Components model each have a different syntax for references to components in markup.

- In the Aura component, we use c:PropertyTile.
- In the Lightning web component, we use c-property-tile. A dash separates the namespace, c, from the component name. The camel-case propertyTile Lightning web component is referenced as property-tile in the HTML file of another Lightning web component that contains it.

Lightning Web Component Contains a Lightning Web Component

Let's look at composition with two Lightning web components, lwcContainerComponent and lwcComponent.





To use a Lightning web component, `LwcComponent`, in another Lightning web component:

[Lightning Web Components for Aura Developers \(/content/learn/modules/lightning-web-components-for-aura-developers?trailmix_creator_id=srebello78&trailmix_slug=salesforce-platform-developer\)](https://developer.salesforce.com/docs/lightning-web-components/for-aura-developers/?trailmix_creator_id=srebello78&trailmix_slug=salesforce-platform-developer)

- Use a dash to separate the namespace, c, from the component name.

Compose Components

- **Expose Components**
 - Change the camel case name, `lwcComponent`, to a kebab case (dash-separated) reference, `lwc-component`. We use the dash-separated reference for consistency with Web Components standards.
 - The HTML spec mandates that tags for custom elements aren't self-closing. Self-closing tags end with `</>`. A Lightning web component is essentially a custom element. Therefore, you need opening and closing tags for the component reference:

```
1 <c-lwc-component></c-lwc-component>
```



Aura Component Contains a Lightning Web Component

Now let's look at an Aura component, auraWrapper, that contains a Lightning web component, lwcContainerComponent.

```
1  <!-- auraWrapper.cmp -->
2  <aura:component>
3      <c:lwcContainerComponent />
4  </aura:component>
```



To use a Lightning web component, `lwcContainerComponent` in an Aura component:

- Use a colon to separate the namespace, c, from the component name.
- Use the camel case component name, lwcContainerComponent.
- Self-closing tags are allowed in Aura markup so we use <c:lwcContainerComponent />.

Facets Become Slots

In Aura, a *facet* is any attribute of type `Aura.Component[]`. That's just a fancy way of saying you can set an array of components for the attribute. In even less fancy terms





that a parent component passes into a component's body. The HTML `<slot>` element is part of the Web Components standard.

[Lightning Web Components for Aura Developers \(/content/learn/modules/lightning-web-components-for-aura-developers/trailmix_creator_id=sp00h07&trailmix_slug=salesforce-platform-developer\)](#)
Here's an example of an Aura component that contains a header facet and the body facet that every component has by default.

Compose Components

```
1 <aura:component>
2     <aura:attribute name="header" type="Aura.Component[]" />
3     <div>
4         <span>{!v.header}</span><br/>
5         <span>{!v.body}</span>
6     </div>
7 </aura:component>
```



A similar Lightning web component looks like this.

```
1 <template>
2     <div>
3         <slot name="header"></slot><br/>
4         <slot></slot>
5     </div>
6 </template>
```



The slot named header replaces the header facet. The unnamed slot replaces the body facet.

You can see a deeper dive in the Lightning Web Components Developer Guide.

Anything Else to Consider About Facets?

Yes, I'm glad you asked! Remember that Lightning web components can't contain Aura components. If you're migrating an Aura component that contains a facet, you must also migrate any subcomponents that you want to stuff into the facet. That way, you ensure that you never put an Aura component into a Lightning web component.





via the one-way data binding.

[Lightning Web Components for Aura Developers \(/content/learn/modules/lightning-web-components-for-aura-developers?trailmix_creator_id=srebello7&trailmix_slug=salesforce-platform-developer\)](#)

Resources

Compose Components

- [Lightning Aura Components Developer Guide: Component Facets](#)
(https://developer.salesforce.com/docs/atlas.en-us.lightning.meta/lightning/components_facets.htm).
- [Lightning Aura Components Developer Guide: Data Binding Between Components](#)
(https://developer.salesforce.com/docs/atlas.en-us.lightning.meta/lightning/expr_data_binding.htm).
- [Lightning Web Components Developer Guide: Compose Components](#)
(https://developer.salesforce.com/docs/component-library/documentation/lwc/lwc.create_components_compose).
- [Lightning Web Components Developer Guide: Set Properties on Child Components](#)
(https://developer.salesforce.com/docs/component-library/documentation/lwc/lwc.create_components_data_binding).

Quiz

To complete this unit, you need to answer all the quiz questions correctly.

+100 Points

1 Which character separates the namespace from the component name in Lightning web components?

A An exclamation point

B A smiley emoji

C A colon





In the Lightning Web Components programming model, the data binding for property values in composed Lightning web components is?

[Lightning Web Components for Aura Developers \(Compose Lightning web components for aura developers?trailmix_creator_id=srebello7&trailmix_slug=salesforce-platform-developer\)](https://trailhead.salesforce.com/content/learn/modules/lightning-web-components-for-aura-developers/compose-components?trailmix_creator_id=srebello7&trailmix_slug=salesforce-platform-developer)

Compose Components

- A** One way
- B** Two way
- C** Three way
- D** Omni-directional

Second attempt earns 50 points. Three or more earns 25 points.

Check the Quiz to Earn 100 Points

Learn

Badges
Trails
Trailmixes
Superbadges
Trailhead Academy
Career Paths

Certifications

Certifications
Maintain Certifications
Verify Certifications

Community

Trailblazer Community
Events
Agentblazers
Salesforce Developers
Salesforce Admins
Code of Conduct

Extras

Trailhead Login
Sales Enablement
Trailblazer Store
Salesforce Help





salesforce

© 2026 Salesforce, Inc. All rights reserved.

[Privacy Statement](#) [Terms of Use](#) [Use of Cookies](#) [Trust](#) [Accessibility](#) [Cookie Preferences](#)[Lightning Web Components for Aura Developers \(/content/learn/modules/lightning-web-components-for-aura-developers?trailmix_creator_id=srebello7&trailmix_slug=salesforce-platform-developer\)](#)

Engli



Compose Components

