Developer Guide

GetPassengerListRQ v4 Web Service

Version 1.0

September 2017

Sabre Airline Solutions®

Software version 2015

Document Edition 1.0 (March 2017)

This documentation is the confidential and proprietary intellectual property of the *Sabre Airline Solutions®* business. Any unauthorized use, reproduction, preparation of derivative works, performance or display of this document or software represented by this document, without the express written permission of *Sabre Airline Solutions* is strictly prohibited.

Sabre Airline Solutions, the Sabre Airline Solutions logo, Sabre Holdings, the Sabre Holdings logo and SabreSonic are trademarks and/or service marks of an affiliate of Sabre Holdings Corp. All other trademarks, service marks and trade names are the property of their respective owners.

© 2013 Sabre Inc. All rights reserved. 01_2013

Committed to minimizing the environmental impact of our global operations and to promoting sustainable business practices in travel and tourism. **www.sabre-holdings.com**

DOCUMENT REVISION HISTORY

Version	Date	Who	Description
V4.0	Jul-2017	Savitha Suresh	Initial Draft
V4.0	Sep-2017	Arun Bright	Reviewed by Arun, incorporated the changes.

Table of Contents

1 Introduction

1.1 Overview 5

2 Prerequisites

2.1 EPR Information 6
2.2 Pre-requisites 6
2.3 Web Services SOAP Syntax 6
2.4 Specifying a Minor Version 8

3 Usage

3.1 Summary 10
3.2 Minor Versions 8
3.3 Listing of Passengers on Priority Lists 12

4 Error Messages

4.1 Error Code Table 14

5 Appendix

5.1 Glossary 19

Introduction 1

1.1 Overview

The ***SabreSonic Check-In®*** (SSCI) *GetPassengerListRQ* web service retrieves the list of passengers matching specific passenger characteristics in the requested flight. Caller can retrieve the list of passenger in a flight having specific edit code or specific SSR. *GetPassengerListRQ* support combination of one or more Edit code/ SSR code in the request, giving the flexibility to the caller to narrow down to list of passenger having specific characteristics.

Prerequisites 2

2.1 EPR Information

Authorization and authentication of a Sabre web service consumer is controlled by security attributes, keywords and other credentials. For this web service the following minimum requirements must be met.

EPR duty codes required are: 4, 5, 6, and 7

EPR UAT keywords required are: GDSPLY, SELECT

The agent AAA city, duty code and partition ID are setup by Universal Services Gateway (USG) / Sabre Web Services (SWS) when the user is authenticated and the web service session is created.

2.2 Pre-requisites

The flight provided must be initialized in SabreSonic Check-In. Flight initialization runs approximately 72 hours prior to departure. If the flight requested is not initialized the service will return the error 'FLIGHT NOT INITIALIZED - INVALID DATE OR CITY'.

2.3 Web Services SOAP Syntax

The web service request must include a SOAP envelope element, a SOAP header element and a SOAP body element. Additionally, a properly formatted web service request requires certain application specific attributes and constructs in each of these elements. The purpose of this section is to provide a detailed understanding of these requirements.

All of the following examples assume the client wants to consume version 4 of the web service. These examples would have to change accordingly in order to consume other versions or services by either specifying a different version, a different service or both.

First, the SOAP envelope element must include a namespace declaration that defines the type and the version of the web service that the client wants to consume. As an example, the following is a SOAP envelope header that defines that the client wants to consume version 4 of the *GetPassengerListRQ* service by declaring the namespace n1.

```
<soapenv:Envelope xmlns:soap="http://www.w3.org/2001/12/soap-envelope"
soap:encodingStyle="http://www.w3.org/2001/12/soap-encoding" xmlns:n1="
http://services.sabre.com/checkin/getPassengerList/v4 ">
```

Second, the SOAP body element must use the namespace declared in the SOAP envelope as shown below:

```
<soapenv:Body>
<n1:GetPassengerListRQ>
.
.
</n1:GetPassengerListRQ>
</soapenv:Body>
```

If not done correctly, then SSCI Web Services will not be able parse and validate the request correctly which will result in the request being rejected.

Lastly, the SOAP header element must declare the “Action” element as shown below:

```
<soapenv:Header>
<eb:MessageHeader eb:id="" eb:version="4.0"
xmlns:eb="http://www.ebxml.org/namespaces/messageHeader">
<eb:Action>GetPassengerListRQ</eb:Action>
.
.
</eb:MessageHeader>
</soapenv:Header>
```

This element is used for proper routing of the request to the SSCI Web Services and without this element the request will be rejected and not even reach the SSCI Web Services for processing.

Versions 3

3.1 Schema and WSDL

An overview of the WSDL and schema can be found in the following documents:

- WSDL – GetPassengerListRQ_v4.wsdl
- Request/Response Schema – GetPassengerListRQRS_v4.xsd

3.2 Minor Versions

The following enhancement(s) are available in minor versions of the request/response schema.

Version	Description
4.0.0	No minor versions have been released

The above enhancement(s) require that the Version attribute be specified in the *GetPassengerListRQ* element of the request; otherwise, only those features in the base version (4.0.0) will be available

3.3 Specifying a Minor Version

When making enhancements to an existing response schema version, backward compatibility is maintained by making new response elements and/or attributes optional as well as adding an optional Version attribute to the top level element of the request payload. The Version attribute is used to request that the response payload be constructed according to a specific minor version of the response schema (e.g. 4.0.0). If the Version attribute is not specified, then the response payload is constructed according to the original version of the response schema (e.g. 4.0.0). This allows these new elements and/or attributes to be added to the request schema without requiring all existing clients to rebuild their applications with the new schema unless they want to use them.

In order for a client to request that the response payload be constructed according to a specific minor version of the response schema (e.g. 4.1.0), the Version attribute must be added to the top level element of the request payload as shown below:

```
<soapenv:Body>
<n1:GetPassengerListRQ Version="4.0.0">
…
</n1:GetPassengerListRQ>
</soapenv:Body>
```

The Version attribute is only used to request that the response payload be constructed according to a specific minor version of the response schema. If a client does not need the response payload to be constructed according to a specific minor version of the response schema, but instead wants the

response payload to be constructed according to the original version of the response schema (e.g. 4.0.0), then the Version attribute should not be specified at all.

Usage 4

4.1 Summary

GetPassengerListRQ service retrieves the list of passenger matching the display codes. The display codes are also referred as Edit Codes / SSR. The list of Edit Codes is provided in the Appendix 6.1.Current version of the service supports only below functionalities:

- Revenue Passengers (RV)
- Non-Revenue Passengers(XRV)
- Boarded Passengers(ON)
- Not –Boarded Passengers(XON)
- Priority List (P)
- All Priority List (PALL)

The below table indicates the minimum information required to call *GetPassengerListRQ*:

Request			
Element		**Mandatory**	**Comments**
GetPassengerListRQ/Itinerary/			
	Airline	Y	Airline code: 2-3 Char
	Flight	Y	Flight number
	DepartureDate	N	Flight departure date If not provided, the service will default to the current date of the city assigned in the EPR
	Origin	Y	Origin airport code
	Destination #	N	Destination Airport code. If the destination is provided, the listing will for destination provided in the request, else it will be till the final destination of the flight.
	ClassOfService	N	Class of service for which listing is required for. Class of service is not supported on some types of listing.(for example : on Priority lists – P and PALL)
GetPassengerListRQ/DisplayCodeRequest /DisplayCodes			
	@condition	N	Supports “AND” or “OR” AND : Matches **all** DisplayCodes enterd to retrieve Passenger list OR : Matches **any** DisplayCodes enterd to retrieve Passenger list
	DisplayCode	M	List of Display codes supported. – Appendix 6.1

GetPassengerListRQ/DisplayCodeRequest /SortSequence	N	Sorting the passenger list. Always sorts in ascending order. Below sort options are supported: - Name (by last name) - Seat (by seat no.) - Sequence (by check-in sequence) - Group Number (by group code) * If not provided, default sorting is by “Name”

Response		
Element		**Description**
GetPassengerListRS/ItineraryInfo/Itinerary/		Information related to the Itinerary
	Airline	Airline 2 letter code
	Flight	Flight number
	DepartureDate	Flight departure date
	Origin	Origin airport code
	Destination	Destination Airport code
	ClassOfService	Class of Service requested
	AircraftType	The Aircraft Type of the flight.
GetPassengerListRS/ItineraryInfo/DepartureArrival_Dates/		
	Scheduled_Departure Date	Scheduled Departure Dates
	Estimated_DepartureDate	Estimated Departure Dates
	DepartureTime	Estimated Departure Time
	Scheduled_ArrivalDate	Scheduled Arrival Date
	Estimated_ArrivalDate	Estimated Arrival date
	ArrivalTime	Estimated Arrival Time
GetPassengerListRS/ItineraryInfo/DepartureGate		Display the Deparuture gate
GetPassengerListRS/ItineraryInfo/CabinInfoList/CabinInfo/		Repeats for all the cabins returned in the result
	Cabin	Cabin class available on the flight
	Count	Seat count in the cabin Count of the passengers matching the DisplayCode in the request.
	Authorized	Total authorized seats in the cabin

	Available	Total available seats in the cabin
GetPassengerListRS/PassengerInfoList/PassengerInfo/		Information related to Passenger
	ThruIndicator	In case of multileg flights, the passenger who is Checked-in on the first leg, gets this indicator turned on the 2nd leg of the flight.
	GroupCode	Group code for the Group PNR
	BookingClass	Passenger booking class
	Cabin	Booked cabin
	Seat	Seat number
	Destination	Destination of the passenger
	BoardingPassFlag	Is set to “True” if the boarding pass has been issued, else “False” For stand by passengers this indicator will be false, though the passenger has a stand by boarding pass.
	PassengerType	Type of the passenger: F - Full fare passenger E - Employee Passenger
	BagCount	Number of bags the passenger is carrying

4.2 Retrieving Passengers from Priority Lists

GetPassengerListRQ supports retrieving passengers placed on priority list, caller can either retrieve all the passengers on the priority lists (PALL) or retrieve list of unaccommodated passengers on the Priority lists (P)

P and PALL cannot be combined with any other display codes.

Functions	Description
Listing of ALL passengers on the Priority list	GetPassengerListRQ/DisplayCodeRequest/DisplayCodes/Display Code = “PALL”
Listing of passengers on the Priority list, who are not yet accommodated	GetPassengerListRQ/DisplayCodeRequest/DisplayCodes/Display Code = “P”

Below options are **NOT** supported on the priority list request (RQ) :

- GetPassengerListRQ/Itinerary/ClassOfService
- GetPassengerListRQ/DisplayCodeRequest/SortSequence

Apart from the above mentioned common elements, Priority list requests return the following response elements.

Response		
Element		**Description**
GetPassengerListRS/PassengerInfoList/PassengerInfo/		
	PriorityCode	Priority code assigned to the passenger
	UpgradeCode	Upgrade code assigned to the passenger
	CorpID	“T” will be displayed if the passenger has an Electronic ticket, else it will be blank.
	DesiredBookingClass	Desired booking class passenger has requested to be accommodated
	SeniorityDate	Company employment seniority date

Request and Response Sample: GetPassengerListRQ_v4_SamplePayload_4_2_a.xml

GetPassengerListRQ_v4_SamplePayload_4_2_b.xml

GetPassengerListRQ_v4_SamplePayload_4_2_c.xml

Error Messages 5

5.1 Error Code Table

The error messages listed here are only a sampling of possible responses. Additional error messages may exist.

Error Code	Error Message	Error Description
14000	Validation Failed	Parsing of request failed because invalid content was found in the request.
14001	Timeout	Response timed out.
14002	Varies	An application error that varies depending upon the specific nature of the exception that occurred while processing the request.
14003	PNR Error Message	PNR service timed out.
14004	Multiple Passengers Not Allowed When Flight Number Is Omitted	When flight number is not included, multiple passengers in the request are not allowed.
14005	Unmarshall Failure	Trip search response could not be unmarshalled.
14006	TripSearchRS Passenger Not Found In PNR	No passenger matching the request was found in the PNR database.
14007	Passenger Not Found In PNR Locator	No passenger matching the request was found in the PNR response.
14008	Marshall Failure	A request could not be marshaled correctly.
14009	Unmarshall Failure	A response could not be unmarshalled correctly.
14010	Future	n/a
14011	Future	n/a
14012	Did not find a hosted air segment in reservation	Returned for lookup by PNR locator only. Indicates that when trying to retrieve passenger information a hosted air segment could not be found in the reservation, so there is no data to retrieve since it's not hosted by Sabre.
14013	Missing required element <Itinerary> or <PassengerList>	For legacy lookup by itinerary and passenger list; both the <Itinerary> element and the <PassengerList> element are required.

Error Code	Error Message	Error Description
14014	Missing required attribute Version	Returned for lookup by PNR locator only. The Version attribute is required for lookup by PNR locator.
-2825	DATABASE ERROR	AAA city is not done
-304	DATABASE ERROR	Database Error
-303	$SYSTEM ERROR (MEMORY ALLOCATION ERROR - CALL SABRE	Database Error
-303	DATABASE ERROR	Database Error
-300	DATABASE ERROR	Database Error
-300	DATABASE ERROR	Database Error
-37	DATABASE ERROR	Database Error: LV19AA
-30	DATABASE ERROR	Database Error: Not able to Open File Maintenance Control File
-27	DATABASE ERROR	Database Error
-25	DATABASE ERROR	Database Error: Lf31aa
-25	DATABASE ERROR	Database Error: Lf31aa
-22	DATABASE ERROR	Database Error: Lf23aa
-21	DATABASE ERROR	Database Error: Lf22aa
-2	$DISPLAY SIMILAR NAME LIST PRIOR TO THIS ENTRY	Display similar name list prior to this entry
-2	DATABASE ERROR	Database Error: Lw10aa
-1	DATABASE ERROR	Database Error: Lw10aa
0	BAGGAGE ROUTE MISSING INDICATOR	
621	$NO PASSENGER DATA EXISTS $PNR ACTIVITY IN PROGRESS $NO PASSENGER DATA EXISTS	Database Error: Passenger record not found
650	$NO NAME MATCH FOUND	No such name in the list
653	$INVALID DISPLAY OPTION	Display option is not correct
655	$DISPLAY CODE INCORRECT	Display code omitted
658	$NONE LISTED	Database Error: Lw10aa
705	$NONE LISTED	Database Error: Airline work file not opened
706	$INVALID LINE NUMBER SELECTED	Line number is not correct
806	$ASSIGN BAG TAG PRINTER	Bagtag printer is needed
813	$USE BASE FLIGHT NUMBER	Use funnel flight number instead of base flight number

Error Code	Error Message	Error Description
883	$CODE NOT ALLOWED IN COMBINATION	Display code not allowed to be used in combination
1010	$CHECK DATE - DDMMYY	Date format is not correct
1576	$ACS NOT AVAILABLE	Database Error: Maintenance control file not available
1617	$SECONDARY ENTRY NOT ALLOWED FROM OA LIST	Entry GE*N1 is not for Other Airline
2550	$ENTRY CANNOT DEFAULT CLASS OF SERVICE	Class of service is required for this entry
2551	$FLIGHT NUMBER NOT FOUND	Flight number not found
2552	$INCORRECT DATE OR DATE REQUIRED	Incorrect date entered or no date provided
2553	$INVALID INPUT DATE	Invalid date entered
2554	$DEDICATE FLIGHT	Flight not dedicated - dedicate the flight before this entry
2555	$FLIGHT DEDICATED - REMOVE AIRLINE CODE	Flight already dedicated - remove the airline code from entry
2556	$ENTER FLIGHT/DATE OR REDEDICATE	Reenter flight / date or rededicate
2557	AIRLINE CODE NOT FOUND	Airline code not entered / present in the entry
2558	$FLIGHT NUMBER NOT FOUND	Flight number not entered / present in the entry
2559	$FLIGHT NUMBER OR BOARD-POINT INCORRECT	Check the flight number or board point entered in the entry
2560	$INCORRECT BOARD-POINT	Incorrect board point entered
2561	$OFF-POINT NOT FOUND	Off point not found for flight
2563	$NEED PROPER DUTY CODE OR KEYWORD	Proper duty code / keyword required for the entry
2564	DATABASE ERROR	Database Error: Lw10aa
2566	$FLIGHT NOT INITIALIZED - INVALID DATE OR CITY	Flight not initialized - invalid date or city code
2570	$THIS CRT CANNOT DISPLAY A MASK	Mask not supported on this entry for this agent
2571	DATABASE ERROR	Database Error
2572	$INCORRECT ENTRY LENGTH	Incorrect length of entry
2574	DATABASE ERROR	Database Error
2576	$BEGINNING CHARACTERS IN ENTRY INVALID	Invalid characters at the beginning of entry

Error Code	Error Message	Error Description
2577	$INVALID FOR CONVERSATION MODE	Invalid conversation ID / Mode found in table
2578	$INVALID CLASS OF SERVICE	Database Error: Passenger with this class of service is not available
2579	$INVALID BOOKING CODE	Booking code or class of service is not valid
2580	$CANNOT VALIDATE BOOKING CODE OR CLASS OF SERVICE	Booking code or class of service is not valid
2581	BOARD CITY NOT AAA	Board city and AAA do not match
2585	$USE NEW ENTRY GABP	Use correct boarding pass printer number to assign boarding pass printer
2591	$CANNOT USE DEDICATED FLT- RE-ENTER ACTUAL FLIGHT NUMBER	Cannot use dedicated flight - re-enter the actual flight number in the entry
2592	$MANDATORY DATE NOT PRESENT	Mandatory date not present in entry
2593	$REPLACE CLASS OF SERVICE WITH	Need to replace the class of service with '/' in the entry
2594	$DESTINATION CITY NOT ALLOWED	Destination city not allowed / found on this flight number used in the entry
2595	$ORIGINATION CITY NOT ALLOWED	Origination city not allowed / found on this flight number used in the entry
2599	$USE W* ENTRIES TO ASSIGN BP PRINTER	Need to use the W* entries to assign boarding pass printer
2854	$MULTIPLE EDITS NOT ALLOWED	Multiple edits cannot be combined / allowed together
3073	$MAXIMUM 10 LINE NBRS MAY BE SELECTED	Maximum of 10 line numbers can be selected per entry
3074	$MAXIMUM 10 PSGRS PER ENTRY	Maximum of 10 passengers allowed per entry
3076	$ON AND XON MAY NOT BE COMBINED WITH ANY OTHER EDITS	ON & XON edits cannot be combined with any other edits
3077	$ENTER GLFLT-NAME$PRIORITY CODE	Check the format of the entry
3092	$PASSENGER ITINERARIES MUST MATCH - ENTER SEPARATELY	More than one passenger is included in entry
3102	$MAX 50 SEQUENCE NUMBERS	Maximum of 50 sequence numbers are allowed per entry
3357	$FLIGHT RESTRICTED	Flight restriction is not overridden for this agent
3545	$CHECK-IN MAXIMUM 99 PASSENGERS	Maximum of 99 passengers allowed in check-in

Error Code	Error Message	Error Description
4070	$FLIGHT RESTRICTED - REBUILD IN PROGRESS	Flight restricted - rebuild in progress
4678	$FLIGHT RESTRICTED-EQUIPMENT CHANGE IN PROGRESS	Flight restricted - equipment change in progress
4679	$FLIGHT RESTRICTED-BUILD IN PROGRESS	Flight restricted - build in progress
5532	$REISSUE IN PROGRESS *WFR OR IGNORE	Reissue in progress, use *WFR or ignore before this entry
5710	$ENTRY NOT SUPPORTED FOR OA OPERATED FLIGHT	Entry not supported for flight operated by other carrier
5714	$CODESHARE DATABASE PROCESSING ERROR	Database processing error while processing for codeshare
7114	ALT SPACE OR TRF OA NOT ALLOW	ALT space or transfer not allowed on other carrier flight
7148	NST MAY NOT BE COMBINED WITH ANY OTHER EDITS	NST edit cannot be combined with other edits

Appendix 6

6.1 Edit Code Characteristic

The edit codes listed here are only a sampling of possible codes. Additional edit codes may exist.

Display Code	Description
AA	List all passengers at-airport on a given flight. Use XAA to list passengers not at-airport on a given flight.
AC	List all passengers who have “add collect due” a given flight. Use XAC to list passengers with no “add collect due” on a given flight.
AE	List all passengers with air extras on a given flight.
ARMD	List all passengers travelling with weapon on a given flight. Use XARMD to list passengers travelling with no weapon on a given flight.
AVIH	List all passengers with pet or animal in kennel on a given flight. Use XAVIH to list passengers without pet or animal in kennel on a given flight.
BLND	List all passengers who are vision-impaired on a given flight. Use X BLND to list passengers who are not vision-impaired on a given flight.
BP	List all passengers who have boading pass on a given flight. Use XBP to list passengers who have no boading pass on a given flight.
BT	List all passengers who have checked bags on a given flight. Use XBT to list passengers who have no checked bags on a given flight.
CHD	List all passengers identified as child on a given flight. Use XCHD to list passengers not identified as child on a given flight.
CM	List all passengers who have comments or notes on a given flight. Use XCM to list passengers who have no comments or notes on a given flight.
DEAF	List all passengers who are hearing-impaired on a given flight. Use XDEAF to list passengers who are not hearing-impaired on a given flight.
DEPA	List all passengers who are accompanied deportee on a given flight. Use DEPA to list passengers who are not accompanied deportee on a given flight.
DEPU	List all passengers who are unaccompanied deportee on a given flight. Use DEPU to list passengers who are not unaccompanied deportee on a given flight.
DG	List all passengers who are downgraded on a given flight. Use XDG to list passengers who are not downgraded on a given flight.

Display Code	Description
DOCA	List all passengers who have address documentation on a given flight. Use XDOCA to list passengers who have no address documentation on a given flight.
DOCO	List all passengers who have other documentation provided on a given flight. Use XDOCS to list passengers who have no other documentation provided on a given flight.
DOCS	List all passengers who have standard travel documentation on a given flight. Use XDOCS to list passengers who have no standard travel documentation on a given flight.
DOCV	List all passengers whose documentation have been verified on a given flight. Use XDOCV to list passengers whose documentation have not been verified on a given flight.
HAND	List all passengers who are handcuffed on a given flight. Use XHAND to list passengers who are not handcuffed on a given flight.
INF	List all passengers who are infant on a given flight. Use XINF to list passengers who are not infant on a given flight.
IB	List all passengers who have inbound segments on a given flight. Use XIB to list passengers who have no inbound segments on a given flight.
MAAS	List all passengers with meet-and-assist request on a given flight. Use XMAAS to list passengers with no meet-and-assist request on a given flight.
MEDA	List all passengers with medical clearance required on a given flight. Use XMEDA to list passengers with no medical clearance required on a given flight.
MILT	List all military passengers on a given flight. Use XMILT to list non-military passengers on a given flight.
OB	List all passengers who have an outbound connection on a given flight. Use XOB to list all passengers who have no outbound connection.
ON	List all passengers who have boarded a given flight. Use XON to list all passengers who have not boarded.
P	List all unaccommodated priority list passengers on a given flight.
PALL	List all priority list passengers on a given flight
PETC	List all passengers with pet in cabin on a given flight. Use XPETC to list passengers with no pet in cabin on a given flight.
PR	List all passengers with pre-reserved seat on a given flight. Use XPR to list passengers with no pre-reserved seat on a given flight.

Display Code	Description
PSPT	List all passengers with passport information on a given flight. Use XPSPT to list passengers with no passport information on a given flight.
RV	List all revenue passengers on a given flight. Use XRV to list all non-revenue passengers.
TKT	List all passengers with paper ticket on a given flight. Use XTKT to list passengers with no paper ticket on a given flight.
TWOV	List all passengers who are travelling without visa on a given flight. Use XTWOV to list passengers who are travelling with visa on a given flight.
UG	List all passengers who are upgraded on a given flight. Use XUG to list passengers who are not upgraded on a given flight.
UMNR	List all passengers who are unaccompanied minors on a given flight. Use XUMNR to list passengers who are not unaccompanied minors on a given flight.
UPID	List all passengers who have unique passenger id on a given flight. Use XUPID to list passengers who have no unique passenger id on a given flight.
WCHR	List all passengers who have wheelchair on a given flight. Use XWCHR to list passengers who have no wheelchair on a given flight.
WCHS	List all passengers who have wheelchair for distance on a given flight. Use XWCHS to list passengers who have no wheelchair for distance on a given flight.
WCHC	List all passengers who have wheelchair and need aisle chair on a given flight. Use XWCHC to list passengers who have no wheelchair and need aisle chair on a given flight.
XT	List all passengers with cancelled bag tags on a given flight. Use XXT to list passengers with no cancelled bag tags on a given flight.

6.2 Glossary

Term	Description
EPR	Acronym for *Employee Profile Record* Each user of PSS is provided with a unique ID that combined with a user-defined password, permits access to the system. The EPR also includes security access indicators, including cities permitted for sign in, duty codes, and application keywords.
PNR	Acronym for *Passenger Name Record*

Term	Description
	A file record in TPF used to store passenger specific information related to travel itinerary, payment, and other related information. The fundamental record in a reservation system containing the information.
PSS	Acronym for *Passenger Service System* This is the part of Sabre which handles Sabre Subscriber creation of PNRs, allows booking of airline flights, car rentals, and hotel nights, as well as providing airline prices and tickets, and other travel retail related products.
SSCI	Acronym for *SabreSonic Check-In*
XML	Acronym for *Extensible Markup Language* A specification developed by the W3C. XML is a pared-down version of SGML, designed especially for Web documents.
WSDL	Acronym for *Web Services Definition* WSDL uses a common format to describe and publish the formats, operations, and protocols of a Web service. WSDL elements describe data using one or more XML schemas. These schemas are passed to the Web service. The description of the data tells the receiver how to process the data, and the binding to a protocol or transport instructs the sender how to send the data. Both parties must have access to the same XML schema. WSDL is usually used with SOAP