Sabre APIs – PNR Services
Technical Documentation

User Guide

Trip_ReportsRQ

Schema Version 1.3.0
April 2018

Reference

Prepared for
Sabre Web Services – PNR Services Clients

Prepared by
Sabre Inc.

Date
3 April 2018

© 2018, Sabre Inc. All rights reserved.

This documentation is the confidential and proprietary intellectual property of Sabre Inc. Any unauthorized use, reproduction, preparation of derivative works, performance, or display of this document, or software represented by this document, without the express written permission of Sabre Inc. is strictly prohibited.

Sabre, the Sabre logo design, and Product Name are trademarks and/or service marks of an affiliate of Sabre Inc. All other trademarks, service marks, and trade names are owned by their respective companies.

• • •

Document Revision Information

Version	Date	Author	Comments
1.0	April 3, 2018	Sabre Team	Document created

Table of Contents

Document Revision Information ..... **iii**

Table of Contents ..... **iv**

Overview **8**

1.1. Introduction 8
1.2. Purpose 8
1.3. Availability 8

Specification **10**

2.1. Trip_ReportsRQ service version 10
2.2. Trip_ReportsRQ request and response structures 11
Trip_ReportsRQ request message (RQ) 11
Trip_ReportsRQ response message (RS) 11
2.3. Service Security 12

Passenger Lists **13**

3.1. General Information 13
3.2. MLJ – List of Confirmed Passengers with Married Segments 15
3.2.1 Native Sabre 15
3.2.2 Trip_ReportsRQ 15
3.2.3 Use Case – Native Sabre 16
3.2.4 Use Case – Trip_ReportsRQ 16
3.3. PFX – List of Confirmed Passengers with their SSRs/OSIs 18
3.3.1 Native Sabre 19
3.3.2 Trip_ReportsRQ 21
3.3.3 Use Case – Native Sabre 22
3.3.4 Use Case – Trip_ReportsRQ 22
3.4. MLB – List of Confirmed Passengers 24
3.4.1 Native Sabre 24
3.4.2 Trip_ReportsRQ 25
3.4.3 Use Case – Native Sabre 25
3.4.4 Use Case – Trip_ReportsRQ 26
3.5. MLBT – List of Confirmed Passengers with an e-Ticket 27
3.5.1 Native Sabre 28
3.5.2 Trip_ReportsRQ 28
3.5.3 Use Case – Native Sabre 29
3.5.4 Use Case – Trip_ReportsRQ 29

Sabre Inc. Confidential/All Rights Reserved

3.6. MLBS – Name List by Last Name 30
3.6.1 Native Sabre 31
3.6.2 Trip_ReportsRQ 32
3.6.3 Use Case – Native Sabre 33
3.6.4 Use Case – Trip_ReportsRQ 33
3.7. MLBO – List of Confirmed Passengers with an Outbound Connection from Specified Flight 35
3.7.1 Native Sabre 36
3.7.2 Trip_ReportsRQ 36
3.7.3 Use Case – Native Sabre 36
3.7.4 Use Case – Trip_ReportsRQ 37
3.8. MLBI – List of Confirmed Passengers with an Inbound Connection to the Specified Flight 39
3.8.1 Native Sabre 40
3.8.2 Trip_ReportsRQ 40
3.8.3 Use Case – Native Sabre 41
3.8.4 Use Case – Trip_ReportsRQ 41
3.9. MLC – List of Passengers Ever Booked on the Specified Flight 43
3.9.1 Native Sabre 44
3.9.2 Trip_ReportsRQ 44
3.9.3 Use Case – Native Sabre 45
3.9.4 Use Case – Trip_ReportsRQ 45
3.10. MLX – List of Cancelled Passengers on the Specified Flight 46
3.10.1 Native Sabre 47
3.10.2 Trip_ReportsRQ 47
3.10.3 Use Case – Native Sabre and Trip_ReportsRQ 48
3.11. TRI – Inbound Transfer Information List (Inbound Report) 49
3.11.1 Native Sabre 50
3.11.2 Trip_ReportsRQ 50
3.11.3 Use Case – Native Sabre 52
3.11.4 Use Case – Trip_ReportsRQ 53
3.12. TRO – Outbound Transfer Information List (Outbound Report) 56
3.12.1 Native Sabre 56
3.12.2 Trip_ReportsRQ 56
3.12.3 Use Case – Native Sabre 58
3.12.4 Use Case – Trip_ReportsRQ 59
3.13. TRIN – Inbound Transfer Information List with Names 64
3.13.1 Native Sabre 64
3.13.2 Trip_ReportsRQ 65
3.13.3 Use Case – Native Sabre and Trip_ReportsRQ 67
3.14. TRON – Outbound Transfer Information List with Names 70
3.14.1 Native Sabre 71
3.14.2 Trip_ReportsRQ 71
3.14.3 Use Case – Native Sabre and Trip_ReportsRQ 73

Inventory Reports 78

4.1. General Information 78

4.2. BSF – Full Flight Booking Report ... 78
4.2.1 Native Sabre ... 79
4.2.2 Trip_ReportsRQ ... 84
4.2.3 Use Case – Native Sabre and Trip_ReportsRQ ... 85
4.3. BGR – Full Flight Booking Report in XML ... 88
4.3.1 Trip_ReportsRQ ... 88
4.4. BSR – Flight Booking and Ticketing Report ... 88
4.4.1 Native Sabre ... 89
4.4.2 Trip_ReportsRQ ... 92
4.4.3 Use Case – Native Sabre and Trip_ReportsRQ ... 92
4.5. BST – Flight Summary Report ... 95
4.5.1 Native Sabre ... 95
4.5.2 Trip_ReportsRQ ... 97
4.5.3 Use Case – Native Sabre and Trip_ReportsRQ ... 97

Group/Corporate Name PNR Lists ... 99

5.1. General Information ... 99
5.2. MLE – Block Space Group (BSG) ... 99
5.2.1 Native Sabre ... 99
5.2.2 Trip_ReportsRQ ... 100
5.2.3 Use Case – Native Sabre and Trip_ReportsRQ ... 101
5.3. MLD – /C (corporate name) Group PNRs and the individuals in these PNRs ... 103
5.3.1 Native Sabre ... 103
5.3.2 Trip_ReportsRQ ... 104
5.3.3 Use Case – Native Sabre and Trip_ReportsRQ ... 105
5.4. MLG – /C (corporate name) Group PNRs ... 109
5.4.1 Native Sabre ... 109
5.4.2 Trip_ReportsRQ ... 109
5.4.3 Use Case – Native Sabre and Trip_ReportsRQ ... 110

Reaccommodated Passengers ... 112

6.1. MLR – Passenger Reaccommodation List ... 112
6.1.1 Native Sabre ... 113
6.1.2 Trip_ReportsRQ ... 113
6.1.3 Use Case Analysis ... 114
6.1.4 Use Case – Native Sabre and Trip_ReportsRQ ... 116

Error and warning messages ... 125

7.1. List of Codes – Native Sabre and Trip_ReportsRQ ... 125
7.2. Samples ... 126

Glossary **129**

Technical Support **131**

9.1. Telephone 131
9.2. Email 132
9.3. Links 132

Overview 1

1.1. Introduction

We address this guide mainly to architects and developers who need a mechanism of generating various lists or reports based on flights and PNRs stored in Sabre Open Systems. Business users can also benefit from this documentation to get familiar with the service capabilities.

This chapter contains general information about the service. In the next chapters, we describe the mechanisms implemented within the service, including all the reports offered and a list of error and warning messages. At the end of the User Guide you can find a glossary of the terms used, as well as how to reach Technical Support, if needed.

1.2. Purpose

Once a PNR has been created on the Sabre Host, the Native Sabre and Trip_ReportsRQ web service offers functionalities to airlines to generate reports. The Trip_ReportsRQ service allows displaying booking, ticketing and inventory data in form of reports for specific flights.

The user can generate reports through Native Sabre commands and via Trip_ReportsRQ API calls.

There are four main groups of reports:

1. Passenger Lists – group of reports that allow displaying passenger listswith specific information about flight and passengers.
2. Inventory Reports – ad hoc reports that allow retrieving details on flights
3. Group / Corporate Name PNR Lists – reports which display large party and group/corporate name PNRs to assist airlines in managing their group products.
4. Reacommodated Passengers – reports that allow retrieving historical reaccommodation information for all passengers on the flight, either for cancelled or active flights.

The next chapters describe reports from each presented group in more details.

1.3. Availability

An authorized airline user can benefit from Trip_ReportsRQ both through the Native Sabre channel (some host commands utilize our API in the background) and the web service one. We offer standard service functionalities to all airline clients.

The service runs in 24x7 mode. In case of any planned maintenance windows, we send the wide standard notifications in advance.

Sabre Inc. Confidential / All Rights Reserved

If you would like to start using the service, please contact us to activate the solution. We can also help you tuning the service fit for your purposes in case you plan to use the API with a high volume of requests.

In case of any doubts, we recommend contacting our Technical Support. Please find the contact details in chapter 9.1.

Sabre Inc. Confidential / All Rights Reserved

Specification 2

2.1. Trip_ReportsRQ service version

The correct Trip_ReportsRQ request needs version number provided. **1.3.0** is the current version and this is the only supported version now.

```
<Trip_ReportsRQ Version="1.3.0" ... >
```

Only digits and dots can compose the version number.

Although version 1.3.0 is the only supported version, some older versions are temporarily available.
Below you will find a list of historical versions that are not currently supported. Each version we described below shows the differences between that version and the version that is the current one.

Version	Reports in scope	Difference in the response in comparison to the supported 1.3.0 version
1.3.0 **Supported**	All reports	-
1.0.3 **Not supported**	MLR	Presents the same information as version 1.3.0
1.0.2 **Not supported**	BSF and BSR	Presents the same information as version 1.3.0, however does not present: 1. FlightEntry/CapacityRestriction tags 2. EntryHeader Section (MLR Report)
1.0.1 **Not supported**	BSF, BSR, MLJ, MLB, MLBT, MLBS, MLBO, MLBI, MLC, MLX, MLE, MLD, MLG, MLR	Presents the same information as version 1.3.0, however does not present: 1. EntryHeader Section (MLR Report) 2. ShareEntry tag
1.0.0 **Not supported**	All reports	Presents the same information as version 1.3.0, however does not present: 1. DepartureLegTime tags under EntryHeader tag 2. ShareEntry tag

		3. EntryHeader Section (MLR Report)

2.2. Trip_ReportsRQ request and response structures

Trip_ReportsRQ request message (RQ)

An overview on the Trip_ReportsRQ service design, with the key XML sections highlighted, is presented below. For more information please refer to next paragraphs.

HEADER:

It contains e.g. BinarySecurityToken obtained when authorizing user's web service session.

BODY:

<Trip_ReportsRQ> required block, some its attributes like Version are required too.

<Report> required block

<ReportName> required block

Each report is defined by ReportName, e.g. MLG, PFX.

<ReportFormat> optional block

Each report has a specific format defined, e.g. G.

<Criteria> required block, includes the following search criteria (some of them are mandatory for some reports):

FlightCriteria: AirlineCode, FlightNumber, DepartureAirport, ArrivalAirport, InboundAirport, OutboundAirport, DepartureDateTime, EndDateTime, StatusCode, ClassOfService, Frequency;

NameCriteria: LastName (can be used once per request);

PosCriteria (can be used once per request);

SSRCriteria (can be used once per request);

OSICriteria (can be used once per request);

DateCriteria: StartDate, EndDate (can be used once per request);

BookingCriteria: Station, AgentHomeCity, AgentSine (can be used once per request).

Trip_ReportsRQ response message (RS)

The response is an XML file that contains e.g. list of passengers or details of inventory per flight. Unless there are no PNRs (passengers) meeting the report criteria, an empty list is returned.

The RQ and RS samples as presented in the next chapters.

2.3. Service Security

The reports' generation is available only for authorized AS users that provided a valid token in the web service request.

Users can retrieve data only from the partitions they have access to. In a common case it means that a user of given airline cannot access data of any other carrier unless it is allowed in the native Sabre system too.

Passenger Lists

3

3.1. General Information

Passenger List Reports, also reffered to as Dynamic Reports, gather and present passenger specific information on flight.

All Passenger List Reports are available in Native Sabre and via Trip_ReportsRQ API.

NATIVE SABRE INPUT

Native Sabre Input follows the same logic for all Passenger List Reports, however there are minor differences which are described in the following chapters. The generic structure of the Native Sabre format is as follows:

RK/(ReportName)/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}{Offpoint}

Please check the next chapters for more details about the entry.

NATIVE SABRE OUTPUT

The Native Sabre Output presents the same information for all Passenger List Reports, except for the PFX Report. Below you will find description of all fields presented in Native Sabre display. For details about PFX Report display, please go to section 3.3.

SINGLE LEG FLIGHT

```
         123456789111111111122222222223333333333444444444455555555556666 6
                  012345678901234567890123456789012345678901234567890123 4
A        MULTI
B        LA704 /25DEC          C
C        SCLMAD    13AUG
D        001C  0GRUPOSKY               KBVGLB V HK1  SCLLA        22NOV10
E        002N  1GUTIERREZ/JOSE         KBVGUX V HK1  SCLLA        23NOV10
F        003N  1DUBOULOZBEL/PATRICIA   KLMPSY N HK1  PARLA        15NOV10
G        004N  1GENILLARD/CHRISTOPHER. KLMMIV N HK1  PARLA        15NOV10
H        005C  0HVS/GRP/INTLCL/ANTART. KLMEDS N HK1  PARLA        15NOV10
I        006C  0HVS/GRP/INTLCL/ANTART. KLMMQA N HK1  PARLA        15NOV10
J        007N  1HILLE/LUCAS            HKSSWF Q HK1  FRALA        10NOV10
K        008C  0SKYLINKTRAVEL/CHRISTM. HKSSTK Q HK1  FRALA        10NOV10
L        009N  2GUIN/RAPHAELLEMARCELL. JYZOST O HK10 SCLLA        14OCT10
M        010N  1HIRSCH/PATRICIA        JYFJYS O HK10 SCLLA        14OCT10
N        011N  1HITCE/BRIGITTEM        JYILPD O HK10 SCLLA        14OCT10
O        Warning     012C  0HVS/GRP/INTLCL/ANTART. KLMJWR O HK1  SCLLA        13NOV10
```

MULTI LEG FLIGHT

```
         123456789111111111122222222223333333333444444444455555555556666 6
                  012345678901234567890123456789012345678901234567890123 4
A        MULTI
B        LA704 /20DEC          C
```

```
C  SCLMAD    20DEC
D  001C  0HVS/GRP/INTLCL/ANTART. JYUSIR O HK10 SCLLA        26MAR10
E  002C  0HVS/GRP/INTLCL/ANTART. KLMOLT N HK1  PARLA        15NOV10
F  003C  0HVS/GRP/INTLCL/ANTART. KLMMPQ N HK1  PARLA        15NOV10
G  004C  0SKYLINKTRAVEL/CHRISTM. HKSSYG Q HK1  FRALA        10NOV10
H  005C  0HVS/GRP/INTLCL/ANTART. KLMJWR O HK1  SCLLA        13NOV10
I  006C  0HVS/GRP/INTLCL/ANTART. KDRSWF O HK4  SCLLA        14OCT10
J  SCLFRA    20DEC
K  007C  0CHILETOURISTIK/EASTER  JLYSHE Q HK4  SCLLA        28OCT10
L  008C  0CHILETOURISTIK/EASTER  JJMVEK Q HK4  SCLLA        20AUG10
M  009C  0WAVE/CHILEONE/II       HNFGHE Q HK8  SCLLA        15MAR10
N  MADFRA    21DEC
O  NIL
P  END
```

Col.#/ Range	Element	Definition
A1-5	MULTI	
B1-6	LA704	Airline Code (2 char) and Flight number (4 char)
B7	/	Delimiter
B8-12	30JUN	Flight date (5 char)
B21-25	BE	Report type indicator – Report Name less ML (4 char)
C1-6	SCLMAD	City Pair of the leg or segment as appropriate (6 char). Check EntryType. If equal to Segment, this is a segment of the complete flight. Repeat this field as often as a new Entry Type>Segment is included in the response data.
C11-15	30JUN	Segment Flight date (5 char)
D1-3	001	Line number
D4	H	PNR type indicator (1 char) B = BSG Master PNR H = BSG Child PNR C = Group PNR N =-Individual name in Group PNR Blank if not one of the above
D7	1	Number of party/passengers Number in party is the number of passengers with this last name, or number of passengers in the group, e.g., 30 passengers in the CCM group, 1 passenger with last name of CEBRIANCANTOS
D8-28	ALGORRIGARCIA/G	Name Truncated if the name is longer than the length possible on the user interface
D29	.	Indicates that the name is truncated.
D31-36	HLPRMT	Record Locator Sabre interface must allow for 6 alpha characters
D38	J	Booked class of service
D40	HK	Segment status code (2 char)
D42	1	Number of passengers
D45-57	MADIB	ID of creating office. Sabre user interface should allow for up to 12 characters
D58-64	27MAY10	Date of last PNR update DDMMMYY. (7 char)

Sabre Inc. Confidential / All Rights Reserved

WEB SERVICE INPUT AND OUTPUT

The Trip_ReportsRQ Input and Output is described in further chapters.

3.2. MLJ – List of Confirmed Passengers with Married Segments

The MLJ Report returns list of passengers for married segments with record locator and status code for all board points or specific board point.

Key characteristic:

Report returns only confirmed passengers, taking into consideration following status codes only: HK, KK, KL, BK, CG, DK, FG, GK, IG, NK, OB, OS, OX, PS, RR, SC, TK, CH, CR, LK, YG, ZB, ZH, ZK, ZR (Note: all these codes may not be used in all airlines partitions)

1. Data returned in response is ordered by departure point. For example, for a flight operating en route SCL-LIM-LAX, report returns passenger list for SCL-LIM, SCL-LAX and LIM-LAX. Please see Use Case 2 below.
2. Report does not return passenger type Infant.

MLJ Report is available in Native Sabre and Trip_ReportsRQ.

Note: the report requires a dedicated activation.

3.2.1 Native Sabre

The Native Sabre format to generate MLJ Report:

Report Type	Format Example
MLJ	**RK/MLJ/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}{OffPoint}** RK/MLJ/LA123Y/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Class Of Service, Board Point, Off Point

3.2.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter J as presented below:

<ReportFormat>J</ReportFormat>

Sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>MLJ</ReportName>                                    MANDATORY
       <ReportFormat>J</ReportFormat>                                  OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                     MANDATORY
                     <FlightNumber>639</FlightNumber>                  MANDATORY
                     <DepartureAirport>LIM</DepartureAirport>          OPTIONAL
                     <ArrivalAirport>SCL</ArrivalAirport>              OPTIONAL
                     <DepartureDateTime>2018-01-20</DepartureDateTime> MANDATORY
                     <ClassOfService>J</ClassOfService>                OPTIONAL
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                            MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLJ Report contains:

- Report Name and Format
- Header which presents indicated flight details by leg
- Details including passenger list

3.2.3 Use Case – Native Sabre

Given Sabre PNRs assigned with the given carrier, a flight operator needs a list of confirmed LA passengers for married connection, for LA flight number 704, departing on 14-FEB-2018, on V class of service.

Input: `RK/MLJ/LA704V/14FEB/SCLMAD`

Output:

```
MULTI
LA704  /14FEB       J
SCLMAD     14FEB
001   1BERNACCHIO/MARIA TER. ABCDEF V HK4               02JAN18
002   1ROSSI/ARMANDO         ABCDEF V HK4               02JAN18
003   1BERNACCHIO/MIRELLA    ABCDEF V HK4               02JAN18
004   1BIANCHI/BENVENUTO     ABCDEF V HK4               02JAN18
```

3.2.4 Use Case – Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, a flight operator needs a list of confirmed LA passengers for married connection, for LA flight number 123, departing on 26-NOV-2017, on O class of service.

Trip_ReportsRQ presents list of passengers ordered by departure point. Flight LA123 operates en route EZE-SCL-JFK. Each flight leg is presented separately in following order: EZE-SCL, EZE-JFK, SCL-JFK.

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLJ</ReportName>
<ReportFormat>J</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>123</FlightNumber>
              <DepartureDateTime>2017-11-26</DepartureDateTime>
              <ClassOfService>O</ClassOfService>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
  </Criteria>
</Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>MLJ</ReportName>
<ReportFormat>J</ReportFormat>
<ReportResult>
<Header>
    <AirlineCode>LA</AirlineCode>
    <FlightNumber>123</FlightNumber>
    <DepartureDateTime>2017-11-26T23:30:00</DepartureDateTime>
    <DepartureDayOfWeek>SUN</DepartureDayOfWeek>
    <DisplayType>J</DisplayType>
</Header>
<Details>
<Entry>
<Entry>
       <EntryHeader>
              <DepartureAirport>EZE</DepartureAirport>      FIRST LEG: EZE-SCL
              <ArrivalAirport>SCL</ArrivalAirport>
              <EntryType>SEGMENT</EntryType>
       </EntryHeader>
</Entry>
<Entry>
       <EntryHeader>
              <DepartureAirport>EZE</DepartureAirport>      SECOND LEG: EZE-JFK
              <ArrivalAirport>JFK</ArrivalAirport>
              <EntryType>SEGMENT</EntryType>
       </EntryHeader>
</Entry>
<Entry>
       <EntryHeader>
              <DepartureAirport>SCL</DepartureAirport>      THIRD LEG: SCL-JFK
              <ArrivalAirport>JFK</ArrivalAirport>
              <EntryType>SEGMENT</EntryType>
       </EntryHeader>
       <GroupEntry sequenceId="1">
              <PnrIndicatorType/>
              <NumberInParty>1</NumberInParty>
              <Name>PEREZ/JOHN</Name>
              <Locator>ABCABC</Locator>
              <ClassOfService>O</ClassOfService>
              <StatusCode>HK</StatusCode>
              <NumberOfPassengers>2</NumberOfPassengers>
```

```
            <AgentId/>
            <UpdateDateTime>2017-11-16T19:19:21</UpdateDateTime>
      </GroupEntry>
      <GroupEntry sequenceId="2">
            <PnrIndicatorType/>
            <NumberInParty>1</NumberInParty>
            <Name>PEREZ/ANNA</Name>
            <Locator>ABCABC</Locator>
            <ClassOfService>O</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>2</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2017-11-16T19:19:21</UpdateDateTime>
      </GroupEntry>
      [...]
    </Entry>
</Details>
</ReportResult>
</Report>
```


3.3. PFX – List of Confirmed Passengers with their SSRs/OSIs

The PFX Report presents list of confirmed passengers including their SSRs or OSIs for all board points with the counts for each SSR/OSI type.

Key characteristic:

If Departure Airport and Arrival Airport are specified, report returns data for the leg or legs between the two locations.

1. If Departure Airport and Arrival Airport are not specified, report returns data for all flight legs ordered by departure point. For example, for a flight operating SCL-LIM-LAX, report returns passengers for each leg in the following order: SCL-LIM, SCL-LAX and LIM-LAX.
2. If Departure Airport but not Arrival Airport is specified, report returns data for all legs from the Departure Airport.
3. Report returns all PNRs containing SSRs or OSIs (all or matching specific codes entered) with counts for each.
4. It is possible to search for all SSR/OSI codes or a specific one.
5. If no specific SSR/OSI is included in the request, all SSR/OSI types will be presented.
6. If a specific SSR/OSI is included in the request, no other SSR/OSI types are presented.
7. If a specific SSR/OSI is included in the request, but there are no PNRs matching that criteria, empty list will be presented.
8. If user decides to include the SSR/OSI code in the request, one of the following SSR/OSI types needs to be defined: All, AFX or GFX.
9. It is possible to include up to sixteen specific SSR or OSI codes in a single entry.

10. The response will present each individual name and the SSRs/OSIs that apply to that name.

11. A summary of the SSR/OSI counts is presented in each response. Counts are calculated for each SSR/OSI code present in the response. These are counts of SSRs/OSI for the specific flight requested. Eg. from Trip_ReportsRS:

```
<Summary>
 <Counts Total="386">
     <Count Name="CHLD">9</Count>
     <Count Name="CKIN">2</Count>
     <Count Name="CTCE">18</Count>
     <Count Name="CTCM">16</Count>
     <Count Name="DOCV">2</Count>
     <Count Name="KSML">1</Count>
     <Count Name="MGEN">2</Count>
     <Count Name="NMEL">3</Count>
     <Count Name="NSST">2</Count>
     <Count Name="OTHS">4</Count>
     <Count Name="PCTC">83</Count>
     <Count Name="SEAT">102</Count>
     <Count Name="SSPR">3</Count>
     <Count Name="TKNE">136</Count>
     <Count Name="TKNM">1</Count>
     <Count Name="WCHR">2</Count>
 </Counts>
</Summary>
```

12. Counts are returned for total number of each type of SSR present for at least one passenger on the flight.

13. Counts are arranged alphabetically by SSR/OSI code.

14. Record locator is visible in output on Native and Trip_ResponseRS.

15. Report does not return passenger type Infant.

The PFX Report is available in Native Sabre and Trip_ReportsRQ.

Note: this report requires a dedicated activation.

3.3.1 Native Sabre

The Native Sabre format to generate PFX report:

Report Type	Format Example
PFX	**RK/PFX/(AirlineCode)(FlightNumber){ClassOfService}/(Date){BoardPoint}{OffPoint}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}{‡SSR}/{GFX or AFX}** RK/PFX/LA123Y/20JANLIMMIA‡WCHR **Note:** Required – Airline Code, Flight Number, Date Optional – Class Of Service, Board Point, Off Point, SSR Code

Input sample: `RK/PFX704/14JULSCL‡WCHR‡AVIH`

Output sample:

```
    123456789111111111122222222223333333333444444444455555555556666666
                        012345678901234567890123456789012345678901234567890123
A   SCLMAD
B   01ADAMS/JOHN Q..1.J        MDVLLW
C     WCHR NN1
D   01BROWN/JIM  10.Y        OAKYSW
E     WCHR LA 704Y14JUL/NN1
F   01CINCO/OCHO  10.Y       JBBABD
G     AVIH LA PN1 SCLMAD0704Y14JUL‡Q-FAX100016
H   01GRANT/JULIA  4.Y       KLUMIN
I     WCHR LA 704Y14JUL/NN1
J   01LINCOLN/MARY..4.Y           DUTQHI
…     WCHR LA 704Y14JUL/NN1
R   01TYLER/JOHN..1.B           SPJTTD
S     AVIH LA PN1 SCLMAD0704B14JUL‡Q-FAX100016
T   SCLFRA
U   01HOOVER/HERBE..1.B         TSRMPY
V     WCHR LA 704B14JUL/NN1
W   *********************
X   COUNTS
Y      AVIH       2
Z      WCHR     5
AA  TOTAL       7
AB
```

Col.#/ Range	Element	Definition
A1-6	SCLMAD	City Pair of the leg or segment as appropriate (6 characters)
B1-2	01	Number in Party
B3…	ADAMS/JOHN	Name Truncate if the name is longer than the length possible on the user interface
…B30	1	Number of passengers (Number in party is the number of passengers with this last name, or number of passengers in the group, e.g., 30 passengers in the CCM group, 1 passenger with last name of CEBRIANCANTOS)
B31	J	Booked class of service
C3-7	SSR/OSI code	SSR/OSI code (4 char)
C8…	SSR/OSI FREE TEXT	Free Text entry of SSR/OSI relevant data
D-S		Additional passengers
T1-6	SCLFRA	City Pair of the leg or segment as appropriate (6 char).
U1-2	01	Number in Party
U3…	HOOVER/HERBE	Name Truncate if the name is longer than the length possible on the user interface
…U31	1	Number of passengers (Number in party is the number of passengers with this last name, or number of passengers in the group, e.g., 30 passengers in the CCM group, 1 passenger with last name of CEBRIANCANTOS)
U32	B	Booked class of service
V3-7	SSR/OSI code	SSR/OSI code (4 char)

Col.#/ Range	Element	Definition
V8…	SSR/OSI FREE TEXT	Free Text entry of SSR/OSI relevant data Note: Display all SSR/OSI data as they appear in the PNR.
W	*********	Delimiter between passenger breakdown by city pair and counts
X1	COUNTS	Header
Y4-7	AVIH	SSR/OSI Code
Y13	2	Total SSR/OSI on the flight for the specific SSR/OSI (0-3 char)
Z4-7	WHCR	Additional SSR/OSI Codes
Z13	2	Total SSR/OSI on the flight for the specific SSR/OSI (0-3 char)
AA	TOTAL	Header
AA13	7	Total of all SSR/OSI for the flight

3.3.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria the user included in the request.

If you would like to search for passengers with all SSR/OSI types, there is no need to include any SSR Criteria in the request. If no SSR/OSI code is specified, the response contains all SSR/OSI types.

However, if you would like to present a list of passengers with specific SSR/OSI code only, you can include the searched SSR/OSI code in the request. It is possible to add up to sixteen SSR or OSI codes in the request. Please see the sample use cases below.

The SSR/OSI codes can be added with the use of the Type attribute of SSRCriteria element. The Type attribute accepts values: ALL (contains both AFX and GFX), AFX or GFX.

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
        <ReportName>PFX</ReportName>                                        MANDATORY
        <Criteria>
                <FlightCriteria>
                        <AirlineCode>LA</AirlineCode>                       MANDATORY
                        <FlightNumber>639</FlightNumber>                    MANDATORY
                        <DepartureAirport>LIM</DepartureAirport>            OPTIONAL
                        <ArrivalAirport>SCL</ArrivalAirport>                OPTIONAL
                        <DepartureDateTime>2018-01-20</DepartureDateTime>   MANDATORY
                        <ClassOfService>J</ClassOfService>                  OPTIONAL
                </FlightCriteria>
                <PosCriteria>LA</PosCriteria>                               MANDATORY
                <SSRCriteria Type=AFX>                              OPTIONAL (ALL, GFX or AFX)
                        <SpecialServiceRequest>
                                <Code>TKNM</Code>
                        </SpecialServiceRequest>
                        <SpecialServiceRequest>
```

```
                            <Code>TKNE</Code>
                        </SpecialServiceRequest>
                  </SSRCriteria>
          </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for PFX Report contains:

- Report Name and Format
- Header which presents indicated flight details
- Details including passenger list
- Summary including SSR Counts per each type and in total

3.3.3 Use Case – Native Sabre

Given Sabre PNRs assigned with the given carrier, generate a list of confirmed LA passengers with SSR code "WCHR" indicating a wheelchair passenger, and "AVIH" indicating Animal in Hold, for LA flight number 704, departing on 14-JUL-2018.

Input: `RK/PFX/LA704/14JULSCL‡WCHR‡AVIH`

Output:

```
SCLMAD
01ADAMS/JOHN      1.J MDVLLW
  WCHR NN1
01BROWN/JIM       1.Y OAKYSW
  WCHR LA 704Y14JUL/NN1
01CINCO/OCHO      1.Y JBBABD
  AVIH LA PN1 SCLMAD0704Y14JUL‡Q-FAX100016
01GRANT/JULIA     4.Y KLUMIN
  WCHR LA 704Y14JUL/NN1
01LINCOLN/MARY    4.Y DUTQHI
  WCHR LA 704Y14JUL/NN1
01TYLER/JOHN      1.B SPJTTD
  AVIH LA PN1 SCLMAD0704B14JUL‡Q-FAX100016
SCLFRA
01HOOVER/HERBE    1.B TSRMPY
  WCHR LA 704B14JUL/NN1
********************
COUNTS                                  COUNT OF SPECIFIC SSR/OSI CODE
   AVIH     2
   WCHR     5
TOTAL       7
```

3.3.4 Use Case – Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, generate a list of confirmed LA passengers SSR code "CHLD" indicating a child passenger, for LA flight number 639, departing on 20-JAN-2018, on Q class of service.

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>PFX</ReportName>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>639</FlightNumber>
              <DepartureDateTime>2018-01-20</DepartureDateTime>
              <ClassOfService>Q</ClassOfService>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
       <SSRCriteria Type="ALL">
              <SpecialServiceRequest>
                     <Code>CHLD</Code>
              </SpecialServiceRequest>
       </SSRCriteria>
  </Criteria>
</Report>
</Trip_ReportsRQ>
```

Sample response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Success>Success</Success>
<Report>
    <ReportName>PFX</ReportName>
    <ReportResult>
<Header>
    <AirlineCode>LA</AirlineCode>
    <FlightNumber>639</FlightNumber>
    <DepartureDateTime>2018-01-20T01:55:00</DepartureDateTime>
    <DepartureDayOfWeek>SAT</DepartureDayOfWeek>
    <DisplayType>PFX</DisplayType>
</Header>
<Details>
    <Entry>
        <EntryHeader>
            <DepartureAirport>LIM</DepartureAirport>
            <ArrivalAirport>MIA</ArrivalAirport>
            <EntryType>SEGMENT</EntryType>
        </EntryHeader>
        <PaxEntry>
            <NumberInParty>1</NumberInParty>
            <FirstName>JOHN</FirstName>
            <LastName>SMITH</LastName>
            <Locator>ABCDEF</Locator>
            <ClassOfService>Q</ClassOfService>
            <NumberOfPassengers>4</NumberOfPassengers>
            <SpecialServiceRequest type="AFX">
                <Code>CHLD</Code>
                <ActionCode>HK</ActionCode>
                <AirlineCode>LA</AirlineCode>
                <NumberInParty>1</NumberInParty>
                <FullText>CHLD LA HK1/12NOV09</FullText>
            </SpecialServiceRequest>
        </PaxEntry>
        <PaxEntry>
            <NumberInParty>1</NumberInParty>
            <FirstName>MARIA</FirstName>
```

```
            <LastName>SMITH</LastName>
            <Locator>ABCDEF</Locator>
            <ClassOfService>Q</ClassOfService>
            <NumberOfPassengers>4</NumberOfPassengers>
            <SpecialServiceRequest type="AFX">
                <Code>CHLD</Code>
                <ActionCode>HK</ActionCode>
                <AirlineCode>LA</AirlineCode>
                <NumberInParty>1</NumberInParty>
                <FullText>CHLD LA HK1/12JAN11</FullText>
            </SpecialServiceRequest>
        </PaxEntry>
    </Entry>
</Details>
<Summary>
    <Counts Total="2">                          COUNT OF SPECIFIC SSR/OSI CODE
        <Count Name="CHLD">2</Count>
    </Counts>
</Summary>
</ReportResult>
</Report>
</Trip_ReportsRS>
```


3.4. MLB – List of Confirmed Passengers

The MLB report presents list of confirmed passengers for the specified flight.

Key characteristic:

1. Report returns only confirmed passengers, taking into consideration following status code only: HK, KK, KL, BK, CG, DK, FG, GK, IG, NK, OB, OS, OX, PS, RR, SC, TK, CH, CR, LK, YG, ZB, ZH, ZK, ZR (Note: some of the codes may not be present for certain airlines))
2. Data returned in response is ordered by departure point. For example, for a flight operating en route SCL-LIM-LAX, report returns passenger list for SCL-LIM, SCL-LAX and LIM-LAX.
3. Report does not return passenger type Infant.

MLB Report is available in Native Sabre and Trip_ReportsRQ.

Note: this report requires a dedicated activation.

3.4.1 Native Sabre

The Native Sabre format to generate MLB Report:

Report Type	Format Example
MLB	**RK/MLB/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}{OffPoint}** RK/MLB/LA123Y/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Class Of Service, Board Point, Off Point

3.4.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter B as presented below:

<ReportFormat>B</ReportFormat>

Sample request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>MLB</ReportName>                                        MANDATORY
       <ReportFormat>B</ReportFormat>                                      OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                         MANDATORY
                     <FlightNumber>639</FlightNumber>                      MANDATORY
                     <DepartureAirport>LIM</DepartureAirport>              OPTIONAL
                     <ArrivalAirport>SCL</ArrivalAirport>                  OPTIONAL
                     <DepartureDateTime>2018-01-20</DepartureDateTime>     MANDATORY
                     <ClassOfService>J</ClassOfService>                    OPTIONAL
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLB Report contains:

- Report Name and Format
- Header which presents indicated flight details
- Details including passenger list

3.4.3 Use Case – Native Sabre

Given Sabre PNRs assigned with the given carrier, generate a list of confirmed LA passengers for LA flight number 639, departing on 20-JAN-2018.

Input: RK/MLB/LA639/20JAN/LIMSCL
Output:

```
MULTI
LA639  /20JAN       B
LIMSCL     20JAN
001   1LLATAS/LUCELI         YIFOBJ V HK1  PYDPW9199292 09JAN18
002   1GAJARDO/VERONICA      WDMWMN T HK1  CCHF97599028 09JAN18
003   1RONALDO/CRISTIANO     YWHAHD O HK1  PYDPW9199292 09JAN18
004   1SEGOVIA/PATRICIA      XPNJCV O HK1               02JAN18
005   1PERES/PEDRO           SEHWQN O HK1  PYDPW9199292 09JAN18
006   1CORTES/MARINA         RQQARI O HK1               02JAN18
007   1KUKU/JAIME            FOMIBR H HK2  EHUAH7599420 09JAN18
008   1LALA/LULU             FOMIBR H HK2  EHUAH7599420 09JAN18
009   1MONTOYA/JEAN          KOPFKY H HK1  PYDPW9199292 02JAN18
```

3.4.4 Use Case – Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, generate a list of confirmed LA passengers for LA flight number 639, departing on 10-JAN-2018, on B class of service.

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLB</ReportName>
<ReportFormat>B</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>639</FlightNumber>
              <DepartureDateTime>2018-01-10</DepartureDateTime>
              <ClassOfService>B</ClassOfService>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
  </Criteria>
</Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>MLB</ReportName>
<ReportFormat>B</ReportFormat>
<ReportResult>
<Header>
    <AirlineCode>LA</AirlineCode>
    <FlightNumber>639</FlightNumber>
    <DepartureDateTime>2018-01-20T01:55:00</DepartureDateTime>
    <DepartureDayOfWeek>SAT</DepartureDayOfWeek>
    <DisplayType>B</DisplayType>
</Header>
<Details>
    <Entry>
        <EntryHeader>
            <DepartureAirport>LIM</DepartureAirport>
            <ArrivalAirport>MIA</ArrivalAirport>
```

```
            <EntryType>SEGMENT</EntryType>
        </EntryHeader>
        <GroupEntry sequenceId="1">
            <PnrIndicatorType/>
            <NumberInParty>1</NumberInParty>
            <Name>NOVAK/AMY</Name>
            <Locator>XYZXYZ</Locator>
            <ClassOfService>B</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>2</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2017-11-03T22:16:15</UpdateDateTime>
        </GroupEntry>
        <GroupEntry sequenceId="2">
            <PnrIndicatorType/>
            <NumberInParty>1</NumberInParty>
            <Name>JOHNS/MIKE</Name>
            <Locator>XYZXYZ</Locator>
            <ClassOfService>B</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>2</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2017-11-03T22:16:15</UpdateDateTime>
        </GroupEntry>
        <GroupEntry sequenceId="3">
            <PnrIndicatorType/>
            <NumberInParty>1</NumberInParty>
            <Name>TYLER/RON</Name>
            <Locator>ABCABC</Locator>
            <ClassOfService>B</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>1</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2017-11-06T15:34:05</UpdateDateTime>
        </GroupEntry>
    </Entry>
</Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```


3.5. MLBT – List of Confirmed Passengers with an e-Ticket

The MLBT Report presents list of confirmed passengers per specific flight who are identified by the following SSRs/OSIs:

- SSR TKNA,
- SSR TKNM,
- SSR TKNE,
- OSI TKNO.

Key characteristic:

1. Report returns only confirmed passengers, taking into consideration following status codes only:

HK, KK, KL, BK, CG, DK, FG, GK, IG, NK, OB, OS, OX, PS, RR, SC, TK, CH, CR, LK, YG, ZB, ZH, ZK, ZR (Note: some of the codes may not be present for certain airlines).)

2. Data returned in response is ordered by departure point. For example, for a flight operating en route SCL-LIM-LAX, report returns passenger list for SCL-LIM, SCL-LAX and LIM-LAX.

3. Report does not return passenger type Infant.

MLBT Report is available in Native Sabre and Trip_ReportsRQ.

Note: this report requires a dedicated activation.

3.5.1 Native Sabre

The Native Sabre format to generate MLBT Report:

Report Type	Format Example
MLBT	**RK/MLBT/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}{OffPoint}** RK/MLBT/LA123Y/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Class Of Service, Board Point, Off Point

3.5.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter BT as presented below:

<ReportFormat>BT</ReportFormat>

Request sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
        <ReportName>MLBT</ReportName>                                   MANDATORY
        <ReportFormat>BT</ReportFormat>                                 OPTIONAL
        <Criteria>
                <FlightCriteria>
                        <AirlineCode>LA</AirlineCode>                   MANDATORY
                        <FlightNumber>639</FlightNumber>                MANDATORY
                        <DepartureAirport>LIM</DepartureAirport>        OPTIONAL
                        <ArrivalAirport>SCL</ArrivalAirport>            OPTIONAL
                        <DepartureDateTime>2018-01-20</DepartureDateTime>  MANDATORY
                        <ClassOfService>J</ClassOfService>              OPTIONAL
                </FlightCriteria>
                <PosCriteria>LA</PosCriteria>                           MANDATORY
```

```
      </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLBT Report contains:

- Report Name and Format
- Header which presents indicated flight details
- Details including passenger list

3.5.3 Use Case – Native Sabre

Given Sabre PNRs assigned with the given carrier. Generate a list of confirmed LA passengers holding tickets for LA flight number 8067, departing on 12-JAN-2018, on N class of service.

Below you will find the use case presented in Native Sabre.

Input: `RK/MLBT/LA8067N/12JAN`

Output:

```
MULTI
LA8067 /12JAN       BT
LIMGRU     12JAN
001   1BARROS/MANUEL       . ABDABD N HK2               02JAN18
002   1BRAUN/FELIPE        . OOOYYY N HK2               02JAN18
003   1CORREA/ANDREA       . NHNHNH N HK2               09JAN18
004   1MENDESFERREIRAVIEIRA. NHNHNH N HK2               09JAN18
```

3.5.4 Use Case – Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier. Generate a list of confirmed LA passengers holding tickets for LA flight number 2472, departing on 12-JAN-2018, on Y class of service.

Below you will find the use case presented with use of Trip_ReportsRQ.

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLBT</ReportName>
<ReportFormat>BT</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>2472</FlightNumber>
              <DepartureDateTime>2018-01-12</DepartureDateTime>
              <ClassOfService>Y</ClassOfService>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
  </Criteria>
</Report>
</Trip_ReportsRQ>
```

Response:


```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>MLBT</ReportName>
<ReportFormat>BT</ReportFormat>
<ReportResult>
<Header>
    <AirlineCode>LA</AirlineCode>
    <FlightNumber>639</FlightNumber>
    <DepartureDateTime>2018-01-20T01:55:00</DepartureDateTime>
    <DepartureDayOfWeek>SAT</DepartureDayOfWeek>
    <DisplayType>B</DisplayType>
</Header>
<Details>
    <Entry>
        <EntryHeader>
       <DepartureAirport>LIM</DepartureAirport>
       <ArrivalAirport>MEX</ArrivalAirport>
       <EntryType>SEGMENT</EntryType>
</EntryHeader>
<GroupEntry sequenceId="1">
       <PnrIndicatorType/>
       <NumberInParty>1</NumberInParty>
       <Name>PEREIRA/DOROTEA</Name>
       <Locator>ABGABG</Locator>
       <ClassOfService>Y</ClassOfService>
       <StatusCode>HK</StatusCode>
       <NumberOfPassengers>1</NumberOfPassengers>
       <AgentId/>
       <UpdateDateTime>2017-11-16T10:29:53</UpdateDateTime>
</GroupEntry>
</Entry>
</Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```


3.6. MLBS – Name List by Last Name

The MLBS Report presents list of confirmed passengers per specific flight with indicated last name.

Key characteristic:

1. Report generates two types of passenger lists:
   - with **exact last name search** – presents all confirmed passengers for specific flight, on a specific date, with indicated last name. The report will display only passengers with exact names as specified in the request.
   - with **wildcard last name search** – presents all confirmed passengers for specific flight, on a specific date, with last name starting with characters indicated in the request.
2. If there are no passengers with the specified last name the system will return an empty response.

Report returns only confirmed passengers, taking into consideration following status code only: HK, KK, KL, BK, CG, DK, FG, GK, IG, NK, OB, OS, OX, PS, RR, SC, TK, CH, CR, LK, YG, ZB, ZH, ZK, ZR (Note: some of the codes may not be present for certain airlines))

3. Data returned in response is ordered by departure point. For example, for a flight operating en route SCL-LIM-LAX, report returns passenger list for SCL-LIM, SCL-LAX and LIM-LAX.
4. Report does not return passenger type Infant.

It is available in Native Sabre and Trip_ReportsRQ.

Note: this report requires a dedicated activation.

3.6.1 Native Sabre

In Native Sabre it is possible to request two types of MLBS reports:

- MLBS with Exact Last
- MLBS with Wildcard Last

MLBS with Exact Last Name report contains only confirmed passengers for specific flight, on specific date, with last names as indicated in the Native format. Similar names are not presented. There is no limitation on the last name length.

Report Type	Format Example
MLBS with Exact Name Search	**RK/MLBS/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}{OffPoint}-(LastName)** RK/MLBS/LA123Y/20JAN/LIMMIA-SMITH **Note:** Required – Airline Code, Flight Number, Date, Last Name Optional – Class Of Service, Board Point, Off Point

MLBS with Wildcard Last Name report contains confirmed passengers for specific flight, on specific date, with last names starting with characters indicated in the Native format. It is required to enter at least two characters and end the entry with Cross of Lorraine (‡). Characters entered after the ‡ sign will not be taken into consideration.

Report Type	Format Example
MLBS with Wildcard Name Search	**RK/MLBS/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}{OffPoint}-(LastName)‡** RK/MLBS/LA123Y/20JAN/LIMMIA-JOHNS‡ **Note:** Required – Airline Code, Flight Number, Date, Last Name (at least two chars), Cross of Lorraine (‡) Optional – Class Of Service, Board Point, Off Point

3.6.2 Trip_ReportsRQ

In Trip_ReportsRQ it is possible to request two types of MLBS Reports.

ReportFormat is an optional element. If you decide to use it, enter BS as presented below:

<ReportFormat>BS</ReportFormat>

MLBS with Exact Last Name report contains only confirmed passengers for specific flight, on specific date, with last names as indicated in the request. Similar names are not presented. To generate the report it is required to enter LastName MatchMode=Exact in the request.

Request sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>MLBS</ReportName>                                    MANDATORY
       <ReportFormat>BS</ReportFormat>                                  OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                      MANDATORY
                     <FlightNumber>639</FlightNumber>                   MANDATORY
                     <DepartureAirport>LIM</DepartureAirport>           OPTIONAL
                     <ArrivalAirport>SCL</ArrivalAirport>               OPTIONAL
                     <DepartureDateTime>2018-01-20</DepartureDateTime>  MANDATORY
                     <ClassOfService>J</ClassOfService>                 OPTIONAL
              </FlightCriteria>
              <NameCriteria>                                            MANDATORY
                     <Name>
                     <LastName MatchMode="EXACT">SMITH</LastName>
                     </Name>
                     </NameCriteria>
              <PosCriteria>LA</PosCriteria>                             MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

MLBS with Wildcard Last Name report contains confirmed passengers for specific flight, on specific date, with last names starting with characters indicated in the request. To generate the report it is needed to enter LastName MatchMode=Start in the request.

Sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
```

```
<Report>
        <ReportName>MLBS</ReportName>                                          MANDATORY
        <ReportFormat>BS</ReportFormat>                                        OPTIONAL
        <Criteria>
                <FlightCriteria>
                        <AirlineCode>LA</AirlineCode>                          MANDATORY
                        <FlightNumber>639</FlightNumber>                       MANDATORY
                        <DepartureAirport>LIM</DepartureAirport>               OPTIONAL
                        <ArrivalAirport>SCL</ArrivalAirport>                   OPTIONAL
                        <DepartureDateTime>2018-01-20</DepartureDateTime>      MANDATORY
                        <ClassOfService>J</ClassOfService>                     OPTIONAL
                </FlightCriteria>
                <NameCriteria>                                                 MANDATORY
                        <Name>
                        <LastName MatchMode="START">JOHNS</LastName>
                        </Name>
                        </NameCriteria>
                <PosCriteria>LA</PosCriteria>                                  MANDATORY
        </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLBS Report contains:

- Report Name and Format
- Header which presents indicated flight details
- Details including passenger list

3.6.3 Use Case – Native Sabre

Given Sabre PNRs assigned with the given carrier, generate a list of confirmed LA passengers for LA flight number 8067, departing on 12-JAN-2018, with last name starting with characters “SAN”.

Input: `RK/MLBS/LA8067/12JAN-SAN‡`

Output:

```
MULTI
LA8067 /12JAN       BS
LIMGRU     12JAN
001   1SANTANA/PAULO MR      QFBACD O HK3               09JAN18
002   1SANTANA/CECILIA MRS   QFBACD O HK3               09JAN18
003   1SANTOS/ANNA           FGZPBS O HK2               09JAN18
004   1SANTOS/PAOLA          LSNRCX O HK2               02JAN18
```

3.6.4 Use Case – Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, generate a list of confirmed LA passengers for LA flight number 2472, departing on 12-JAN-2018, with last name starting with characters “ALB”.

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLBS</ReportName>
<ReportFormat>BS</ReportFormat>
```

```
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>2472</FlightNumber>
              <DepartureDateTime>2018-01-20</DepartureDateTime>
       </FlightCriteria>
       <NameCriteria>
       <Name>
              <LastName MatchMode="START">ALB</LastName>
       </Name>
</NameCriteria>
       <PosCriteria>LA</PosCriteria>
  </Criteria>
</Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>MLBS</ReportName>
<ReportFormat>BS</ReportFormat>
<ReportResult>
<Header>
       <AirlineCode>LA</AirlineCode>
       <FlightNumber>2472</FlightNumber>
       <DepartureDateTime>2018-01-12T08:40:00</DepartureDateTime>
       <DepartureDayOfWeek>FRI</DepartureDayOfWeek>
       <DisplayType>BS</DisplayType>
</Header>
<Details>
       <Entry>
              <EntryHeader>
                     <DepartureAirport>LIM</DepartureAirport>
                     <ArrivalAirport>MEX</ArrivalAirport>
                     <EntryType>SEGMENT</EntryType>
              </EntryHeader>
              <GroupEntry sequenceId="1">
                     <PnrIndicatorType/>
                     <NumberInParty>1</NumberInParty>
                     <Name>ALBERTSON/JOHN</Name>
                     <Locator>ABABAB</Locator>
                     <ClassOfService>T</ClassOfService>
                     <StatusCode>HK</StatusCode>
                     <NumberOfPassengers>4</NumberOfPassengers>
                     <AgentId>123456</AgentId>
                     <UpdateDateTime>2017-10-29T09:40:38</UpdateDateTime>
              </GroupEntry>
              <GroupEntry sequenceId="2">
                     <PnrIndicatorType/>
                     <NumberInParty>1</NumberInParty>
                     <Name>ALBERTSON/JAMES</Name>
                     <Locator>ABABAB</Locator>
                     <ClassOfService>T</ClassOfService>
                     <StatusCode>HK</StatusCode>
                     <NumberOfPassengers>4</NumberOfPassengers>
                     <AgentId>123456</AgentId>
                     <UpdateDateTime>2017-10-29T09:40:38</UpdateDateTime>
              </GroupEntry>
```

Sabre Inc. Confidential / All Rights Reserved

```
            <GroupEntry sequenceId="3">
                  <PnrIndicatorType/>
                  <NumberInParty>1</NumberInParty>
                  <Name>ALBERTSON/MARY</Name>
                  <Locator>ABABAB</Locator>
                  <ClassOfService>T</ClassOfService>
                  <StatusCode>HK</StatusCode>
                  <NumberOfPassengers>4</NumberOfPassengers>
                  <AgentId>123456</AgentId>
                  <UpdateDateTime>2017-10-29T09:40:38</UpdateDateTime>
            </GroupEntry>
            <GroupEntry sequenceId="4">
                  <PnrIndicatorType/>
                  <NumberInParty>1</NumberInParty>
                  <Name>ALBERT SMITH/MARTHA</Name>
                  <Locator>ABCBCA</Locator>
                  <ClassOfService>T</ClassOfService>
                  <StatusCode>HK</StatusCode>
                  <NumberOfPassengers>1</NumberOfPassengers>
                  <AgentId>1234567789</AgentId>
                  <UpdateDateTime>2017-10-29T06:54:07</UpdateDateTime>
            </GroupEntry>
      </Entry>
</Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```


3.7. MLBO – List of Confirmed Passengers with an Outbound Connection from Specified Flight

The MLBO Report presents list of confirmed passengers for specific flight, on specific date, which have an outbound connection for the specified flight. In other words, specified segment is not the last one in the itinerary.

Key characteristic:

1. Report returns only confirmed passengers, taking into consideration following status code only:

HK, KK, KL, BK, CG, DK, FG, GK, IG, NK, OB, OS, OX, PS, RR, SC, TK, CH, CR, LK, YG, ZB, ZH, ZK, ZR (Note: some of the codes may not be present for certain airlines)

2. Data returned in response is ordered by departure point. For example, for a flight operating en route SCL-LIM-LAX, report returns passenger list for SCL-LIM, SCL-LAX and LIM-LAX.

3. Report does not return passenger type Infant.

MLBO Report is available in Native Sabre and Trip_ReportsRQ.

Note: this report requires a dedicated activation.

3.7.1 Native Sabre

The Native Sabre format to generate MLBO Report:

Report Type	Format Example
MLBO	**RK/MLBO/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}{OffPoint}** RK/MLBO/LA123Y/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Class Of Service, Board Point, Off Point

3.7.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter O as presented below:

<ReportFormat>O</ReportFormat>

Request sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
        <ReportName>MLBO</ReportName>                                   MANDATORY
        <ReportFormat>O</ReportFormat>                                  OPTIONAL
        <Criteria>
                <FlightCriteria>
                        <AirlineCode>LA</AirlineCode>                   MANDATORY
                        <FlightNumber>639</FlightNumber>                MANDATORY
                        <DepartureAirport>LIM</DepartureAirport>        OPTIONAL
                        <ArrivalAirport>SCL</ArrivalAirport>            OPTIONAL
                        <DepartureDateTime>2018-01-20</DepartureDateTime>  MANDATORY
                        <ClassOfService>J</ClassOfService>              OPTIONAL
                </FlightCriteria>
                <PosCriteria>LA</PosCriteria>                           MANDATORY
        </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLBO Report contains:

- Report Name and Format
- Header which presents indicated flight details
- Details including passenger list

3.7.3 Use Case – Native Sabre

Given Sabre PNRs assigned with the given carrier, generate a list of confirmed LA passengers for LA flight number 2012, departing on 12-JAN-2018, with an outbound connection from the specified flight.

Sabre Inc. Confidential / All Rights Reserved

Example PNR that fulfills the requirements specified in the request:

```
*XYXYXY«
XYXYXY
 1.1COSTA/MARIA MS
 3 LA2012B 12JAN F CUZLIM HK1   945A 1115A /E
     /OPERATED BY LATAM AIRLINES PERU
 4 LA8067O 12JAN F LIMGRU HK1  1225P  825P HRS /E
```

Input: `RK/MLBO/LA2012/12JAN/CUZLIM`

Output:

```
MULTI
LA2012 /12JAN       O
CUZLIM     12JAN
001   1COSTA/MARIA    MS     XYXYXY B HK1             02JAN18
```

3.7.4 Use Case – Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, generate a list of confirmed LA passengers for LA flight number 532, departing on 26-NOV-2017 on class of service O, with an outbound connection from the specified flight.

Example of a PNR which fulfills the requirements specified in the request:

```
*XYXYXY«
XYXYXY
 1.1MOORE/JOHN  2.1MOORE/SUSANNE
 4 LA 532O 26NOV S EZEJFK HK2   620P  755A  27NOV M /E
     /CHG-EQ SCL MUST ADV CUSTOMER
 5 LA6922O 27NOV M JFKDCA HK2  1040A 1210P HRS /E
     /OPERATED BY AMERICAN AIRLINES FOR LATAM AIRLINES GROUP
     /AA 4332O/ABCABC
```

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLBO</ReportName>
<ReportFormat>O</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>532</FlightNumber>
              <DepartureDateTime>2017-11-26</DepartureDateTime>
              <ClassOfService>O</ClassOfService>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
  </Criteria>
</Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
```

```
<Report>
<ReportName>MLBO</ReportName>
<ReportFormat>O</ReportFormat>
<ReportResult>
<Header>
       <AirlineCode>LA</AirlineCode>
       <FlightNumber>532</FlightNumber>
       <DepartureDateTime>2017-11-26T18:20:00</DepartureDateTime>
       <DepartureDayOfWeek>SUN</DepartureDayOfWeek>
       <DisplayType>O</DisplayType>
</Header>
<Details>
       <Entry>
              <EntryHeader>
                     <DepartureAirport>EZE</DepartureAirport>
                     <ArrivalAirport>SCL</ArrivalAirport>
                     <EntryType>SEGMENT</EntryType>
              </EntryHeader>
       </Entry>
       <Entry>
              <EntryHeader>
                     <DepartureAirport>EZE</DepartureAirport>
                     <ArrivalAirport>JFK</ArrivalAirport>
                     <EntryType>SEGMENT</EntryType>
              </EntryHeader>
              <GroupEntry sequenceId="1">
                     <PnrIndicatorType/>
                     <NumberInParty>1</NumberInParty>
                     <Name>MOORE/JOHN</Name>
                     <Locator>XYXYXY</Locator>
                     <ClassOfService>O</ClassOfService>
                     <StatusCode>HK</StatusCode>
                     <NumberOfPassengers>2</NumberOfPassengers>
                     <AgentId/>
                     <UpdateDateTime>2017-11-16T17:09:37</UpdateDateTime>
              </GroupEntry>
              <GroupEntry sequenceId="2">
                     <PnrIndicatorType/>
                     <NumberInParty>1</NumberInParty>
                     <Name>MOORE/SUSANNE</Name>
                     <Locator>XYXYXY</Locator>
                     <ClassOfService>O</ClassOfService>
                     <StatusCode>HK</StatusCode>
                     <NumberOfPassengers>2</NumberOfPassengers>
                     <AgentId/>
                     <UpdateDateTime>2017-11-16T17:09:37</UpdateDateTime>
              </GroupEntry>
       </Entry>
       <Entry>
              <EntryHeader>
                     <DepartureAirport>SCL</DepartureAirport>
                     <ArrivalAirport>JFK</ArrivalAirport>
                     <EntryType>SEGMENT</EntryType>
              </EntryHeader>
              <GroupEntry sequenceId="3">
                     <PnrIndicatorType/>
                     <NumberInParty>1</NumberInParty>
                     <Name>SMITH/MAX</Name>
                     <Locator>ABDABD</Locator>
                     <ClassOfService>O</ClassOfService>
                     <StatusCode>HK</StatusCode>
                     <NumberOfPassengers>1</NumberOfPassengers>
```

```
                <AgentId/>
                <UpdateDateTime>2017-10-04T12:33:29</UpdateDateTime>
            </GroupEntry>
            <GroupEntry sequenceId="4">
                <PnrIndicatorType/>
                <NumberInParty>1</NumberInParty>
                <Name>DOE/JOSH</Name>
                <Locator>AXAXAX</Locator>
                <ClassOfService>O</ClassOfService>
                <StatusCode>HK</StatusCode>
                <NumberOfPassengers>1</NumberOfPassengers>
                <AgentId/>
                <UpdateDateTime>2017-11-17T16:55:10</UpdateDateTime>
            </GroupEntry>
            <GroupEntry sequenceId="5">
                <PnrIndicatorType/>
                <NumberInParty>1</NumberInParty>
                <Name>ROOS/SAM</Name>
                <Locator>AHGAHG</Locator>
                <ClassOfService>O</ClassOfService>
                <StatusCode>HK</StatusCode>
                <NumberOfPassengers>1</NumberOfPassengers>
                <AgentId/>
                <UpdateDateTime>2017-11-17T16:55:46</UpdateDateTime>
            </GroupEntry>
        </Entry>
</Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```


3.8. MLBI – List of Confirmed Passengers with an Inbound Connection to the Specified Flight

The MLBI Report presents list of confirmed passengers for specific flight, on specific date, which have an inbound connection for the specified flight. In other words, specified segment is not the first one in the itinerary.

Key characteristic:

Report returns only confirmed passengers, taking into consideration following status code only:

HK, KK, KL, BK, CG, DK, FG, GK, IG, NK, OB, OS, OX, PS, RR, SC, TK, CH, CR, LK, YG, ZB, ZH, ZK, ZR (Note: some of the codes may not be present for certain airlines)

Data returned in response is ordered by departure point. For example, for a flight operating en route SCL-LIM-LAX, report returns passenger list for SCL-LIM, SCL-LAX and LIM-LAX.

Report does not return passenger type Infant.

MLBI Report is available in Native Sabre and Trip_ReportsRQ.

Note: this report requires a dedicated activation.

3.8.1 Native Sabre

The Native Sabre format to generate MLBI report:

Report Type	Format Example
MLBI	**RK/MLBI/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}{OffPoint}** RK/MLBI/LA123Y/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Class Of Service, Board Point, Off Point

3.8.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter I as presented below:

<ReportFormat>I</ReportFormat>

Request sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>MLBI</ReportName>                                    MANDATORY
       <ReportFormat>I</ReportFormat>                                   OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                      MANDATORY
                     <FlightNumber>639</FlightNumber>                   MANDATORY
                     <DepartureAirport>LIM</DepartureAirport>           OPTIONAL
                     <ArrivalAirport>SCL</ArrivalAirport>               OPTIONAL
                     <DepartureDateTime>2018-01-20</DepartureDateTime>  MANDATORY
                     <ClassOfService>J</ClassOfService>                 OPTIONAL
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                             MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLBI Report contains:

- Report Name and Format
- Header which presents indicated flight details
- Details including passenger list

3.8.3 Use Case – Native Sabre

Given Sabre PNRs assigned with the given carrier, generate a list of confirmed LA passengers for LA flight number 532, departing on 26-NOV-2017 on class of service O, with an inbound connection to the specified flight.

Example PNR that fulfills the requirements specified in the request:

```
*ABCABC«
ABCABC
 1.1DA SILVA/ERNESTO MR
 4 4O2409V 23JAN T TIJMEX HK1   910A  235P /E
 5 LA 621O 23JAN T MEXSCL*HK1   655P  615A  24JAN W /E
 6 LA 750B 24JAN W SCLGRU*HK1   830A  120P /E
```

Input: `RK/MLBI/LA621/23JAN/MEXSCL`

Output:

```
MULTI
LA621  /23JAN       I
MEXSCL     23JAN
001   1DA SILVA/ERNESTO MR   ABCABC O HK1               02JAN18
002   1GONZALEZ/ANNA MARIA . BCABCA O HK1               09JAN18
```

3.8.4 Use Case – Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, generate a list of confirmed LA passengers for LA flight number 532, departing on 26-NOV-2017 on class of service O, with an inbound connection to the specified flight.

Example of a PNR which fulfills the requirements specified in the request:

```
*AKAKAK«
AKAKAK
 1.1BROOKS/JOHN  2.1BROOKS/MARIA
 1 LA 409S 26NOV S MVDSCL*HK2   650P  930P HRS /E
 2 LA 532O 26NOV S SCLJFK*HK2  1130P  755A  27NOV M HRS /E
 3 DL 429V 03DEC S JFKCUN HK2  1115A  320P /E
 4 LA2459X 09DEC J CUNLIM*HK2   335P  900P HRS /E
     /OPERATED BY LATAM AIRLINES PERU
 5 LA2420M 09DEC J LIMMVD*HK2  1159P  639A  10DEC S HRS /E
     /OPERATED BY LATAM AIRLINES PERU
```

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLBI</ReportName>
<ReportFormat>I</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>532</FlightNumber>
              <DepartureDateTime>2017-11-26</DepartureDateTime>
              <ClassOfService>O</ClassOfService>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
  </Criteria>
```

```
</Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>MLBI</ReportName>
<ReportFormat>I</ReportFormat>
<ReportResult>
<Header>
       <AirlineCode>LA</AirlineCode>
       <FlightNumber>532</FlightNumber>
       <DepartureDateTime>2017-11-26T18:20:00</DepartureDateTime>
       <DepartureDayOfWeek>SUN</DepartureDayOfWeek>
       <DisplayType>I</DisplayType>
</Header>
<Details>
       <Entry>
              <EntryHeader>
                     <DepartureAirport>EZE</DepartureAirport>
                     <ArrivalAirport>SCL</ArrivalAirport>
                     <EntryType>SEGMENT</EntryType>
              </EntryHeader>
              <GroupEntry sequenceId="1">
                     <PnrIndicatorType/>
                     <NumberInParty>1</NumberInParty>
                     <Name>DOE/SARAH MS</Name>
                     <Locator>ABCBCA</Locator>
                     <ClassOfService>O</ClassOfService>
                     <StatusCode>HK</StatusCode>
                     <NumberOfPassengers>2</NumberOfPassengers>
                     <AgentId/>
                     <UpdateDateTime>2017-11-01T03:20:33</UpdateDateTime>
              </GroupEntry>
              <GroupEntry sequenceId="2">
                     <PnrIndicatorType/>
                     <NumberInParty>1</NumberInParty>
                     <Name>SMITH/JAMES</Name>
                     <Locator>ABCBCA</Locator>
                     <ClassOfService>O</ClassOfService>
                     <StatusCode>HK</StatusCode>
                     <NumberOfPassengers>2</NumberOfPassengers>
                     <AgentId/>
                     <UpdateDateTime>2017-11-01T03:20:33</UpdateDateTime>
              </GroupEntry>
       </Entry>
       <Entry>
              <EntryHeader>
                     <DepartureAirport>EZE</DepartureAirport>
                     <ArrivalAirport>JFK</ArrivalAirport>
                     <EntryType>SEGMENT</EntryType>
              </EntryHeader>
       </Entry>
       <Entry>
              <EntryHeader>
                     <DepartureAirport>SCL</DepartureAirport>
                     <ArrivalAirport>JFK</ArrivalAirport>
                     <EntryType>SEGMENT</EntryType>
              </EntryHeader>
              <GroupEntry sequenceId="3">
```

```
                    <PnrIndicatorType/>
                    <NumberInParty>1</NumberInParty>
                    <Name>BROOKS/JOHN</Name>
                    <Locator>AKAKAK</Locator>
                    <ClassOfService>O</ClassOfService>
                    <StatusCode>HK</StatusCode>
                    <NumberOfPassengers>2</NumberOfPassengers>
                    <AgentId/>
                    <UpdateDateTime>2017-11-16T19:19:21</UpdateDateTime>
             </GroupEntry>
             <GroupEntry sequenceId="4">
                    <PnrIndicatorType/>
                    <NumberInParty>1</NumberInParty>
                    <Name>BROOKS/MARIA</Name>
                    <Locator>AKAKAK</Locator>
                    <ClassOfService>O</ClassOfService>
                    <StatusCode>HK</StatusCode>
                    <NumberOfPassengers>2</NumberOfPassengers>
                    <AgentId/>
                    <UpdateDateTime>2017-11-16T19:19:21</UpdateDateTime>
             </GroupEntry>
             [...]
       </Entry>
</Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```


3.9. MLC – List of Passengers Ever Booked on the Specified Flight

The MLC Report presents list of passengers for specific flight, on specific date, regardless of the status code. The list includes also passengers who have cancelled a booking on the considered flight.

Key characteristic:

1. Data returned in response is ordered by departure point. For example, for a flight operating en route SCL-LIM-LAX, report returns passenger list for SCL-LIM, SCL-LAX and LIM-LAX.

2. Report does not return passenger type Infant.

MLC Report is available in Native Sabre and Trip_ReportsRQ.

Note: this report requires a dedicated activation.

3.9.1 Native Sabre

The Native Sabre format to generate MLC report:

Report Type	Format Example
MLC	**RK/MLC/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}{OffPoint}** RK/MLC/LA123Y/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Class Of Service, Board Point, Off Point

3.9.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter C as presented below:

<ReportFormat>C</ReportFormat>

Sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>MLC</ReportName>                                        MANDATORY
       <ReportFormat>C</ReportFormat>                                      OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                         MANDATORY
                     <FlightNumber>639</FlightNumber>                      MANDATORY
                     <DepartureAirport>LIM</DepartureAirport>              OPTIONAL
                     <ArrivalAirport>SCL</ArrivalAirport>                  OPTIONAL
                     <DepartureDateTime>2018-01-20</DepartureDateTime>     MANDATORY
                     <ClassOfService>J</ClassOfService>                    OPTIONAL
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLC Report contains:

- Report Name and Format
- Header which presents indicated flight details
- Details including passenger list

3.9.3 Use Case – Native Sabre

Given Sabre PNRs assigned with the given carrier, generate a list of LA passengers regardless the status code, for LA flight number 532, departing on 26-NOV-2017.

Input: `RK/MLC/LA750Y/24JAN/SCLGRU`

Output:

```
MULTI
LA750  /24JAN       C
SCLGRU     24JAN
001   1VARGAS/MARIA          AAABBB Y HK3               02JAN18
002   1SMITH JONES/LAURA     AAABBB Y HK3               02JAN18
003   1RODRIGUES/VINCE       AAABBB Y HK3               02JAN18
004   1VARGAS/MARIA          AAABBB Y HK3               02JAN18
005   1SMITH JONES/LAURA     AAABBB Y HK3               02JAN18
006   1RODRIGUES/VINCE       AAABBB Y HK3               02JAN18
```

3.9.4 Use Case – Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, generate a list of LA passengers regardless the status code, for LA flight number 532, departing on 26-NOV-2017.

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLC</ReportName>
<ReportFormat>C</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>532</FlightNumber>
              <DepartureDateTime>2017-11-26</DepartureDateTime>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
  </Criteria>
</Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>MLC</ReportName>
<ReportFormat>C</ReportFormat>
<ReportResult>
<Header>
       <AirlineCode>LA</AirlineCode>
       <FlightNumber>532</FlightNumber>
       <DepartureDateTime>2017-11-26T18:20:00</DepartureDateTime>
       <DepartureDayOfWeek>SUN</DepartureDayOfWeek>
       <DisplayType>C</DisplayType>
</Header>
<Details>
```

```
        <Entry>
                <EntryHeader>
                        <DepartureAirport>EZE</DepartureAirport>
                        <ArrivalAirport>SCL</ArrivalAirport>
                        <EntryType>SEGMENT</EntryType>
                </EntryHeader>
                <GroupEntry sequenceId="1">
                        <PnrIndicatorType/>
                        <NumberInParty>1</NumberInParty>
                        <Name>AMBRICCA/DANIEL PABLO</Name>
                        <Locator>KKNQDF</Locator>
                        <ClassOfService>L</ClassOfService>
                        <StatusCode>HK</StatusCode>
                        <NumberOfPassengers>1</NumberOfPassengers>
                        <AgentId/>
                        <UpdateDateTime>2017-11-22T07:14:06</UpdateDateTime>
                </GroupEntry>
                [...]
                <GroupEntry sequenceId="212">
                        <PnrIndicatorType/>
                        <NumberInParty>1</NumberInParty>
                        <Name>FARTHING/MARIAANNEMRS</Name>
                        <Locator>FBHPVY</Locator>
                        <ClassOfService>Q</ClassOfService>
                        <StatusCode>HX</StatusCode>
                        <NumberOfPassengers>2</NumberOfPassengers>
                        <AgentId/>
                        <UpdateDateTime>2017-11-10T19:54:54</UpdateDateTime>
                </GroupEntry>
                [...]
        </Entry>
</Details>
</Trip_ReportsRS>
```


3.10. MLX – List of Cancelled Passengers on the Specified Flight

The MLX Report presents list of cancelled passengers for specific flight, on specific date. When report is ran to display cancelled passengers, it pulls from history and shows the segment and status it was associated with at time of cancellation.

Key characteristic:

1. Status codes for cancelled passengers are:
   HX, XX, XK, XL, IX, RM, WK, UN, CX, ZX (Note: some of the codes may not be present for certain airlines)
2. Data returned in response is ordered by departure point. For example, for a flight operating en route SCL-LIM-LAX, report returns passenger list for SCL-LIM, SCL-LAX and LIM-LAX.
3. Report does not return passenger type Infant.

MLX Report is available in Native Sabre and Trip_ReportsRQ.

Please note, this report requires a dedicated activation.

3.10.1 Native Sabre

The Native Sabre format to generate MLX Report is as follows:

Report Type	Format Example
MLX	**RK/MLX/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}{OffPoint}** RK/MLX/LA123Y/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Class Of Service, Board Point, Off Point

3.10.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter X as presented below:

```
<ReportFormat>X</ReportFormat>
```

Following is a sample request to generate the MLX Report:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
        <ReportName>MLX</ReportName>                                        MANDATORY
        <ReportFormat>X</ReportFormat>                                      OPTIONAL
        <Criteria>
                <FlightCriteria>
                        <AirlineCode>LA</AirlineCode>                       MANDATORY
                        <FlightNumber>639</FlightNumber>                    MANDATORY
                        <DepartureAirport>LIM</DepartureAirport>            OPTIONAL
                        <ArrivalAirport>SCL</ArrivalAirport>                OPTIONAL
                        <DepartureDateTime>2018-01-20</DepartureDateTime>   MANDATORY
                        <ClassOfService>J</ClassOfService>                  OPTIONAL
                </FlightCriteria>
                <PosCriteria>LA</PosCriteria>                               MANDATORY
        </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLX Report contains:

- Report Name and Format
- Header which presents indicated flight details
- Details including passenger list

3.10.3 Use Case – Native Sabre and Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier. Generate a list of LA cancelled passengers, for LA flight number 532, class of service N, departing on 24-JAN-2018.

Below you will find the use case presented in Native Sabre and with use of Trip_ReportsRQ.

The list includes all historical cancellations. If the passenger was cancelled and then confirmed, he will also appear on the list.

Native Sabre

Input: `RK/MLX/LA750N/24JAN/SCLGRU`

Output:

```
MULTI
LA750  /24JAN       X
SCLGRU     24JAN
001   1ALBERTSON/HENRY JAME. BDABDA N HK1               02JAN18
002   1ALBERTSON/MARIA LUCI. BDABDA N HK1               02JAN18
```

Trip_ReportsRQ

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLX</ReportName>
<ReportFormat>X</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>750</FlightNumber>
              <DepartureAirport>SCL</DepartureAirport>
              <ArrivalAirport>GRU</ArrivalAirport>
              <DepartureDateTime>2018-01-24</DepartureDateTime>
              <ClassOfService>N</ClassOfService>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
</Criteria></Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>MLX</ReportName>
<ReportFormat>X</ReportFormat>
<ReportResult>
       <Header>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>750</FlightNumber>
              <DepartureDateTime>2018-01-24T00:00:00</DepartureDateTime>
```

```
            <DepartureDayOfWeek>WED</DepartureDayOfWeek>
            <DisplayType>X</DisplayType>
            <DepartureAirport>SCL</DepartureAirport>
            <ArrivalAirport>GRU</ArrivalAirport>
      </Header>
      <Details>
            <Entry>
                  <EntryHeader>
                        <DepartureAirport>SCL</DepartureAirport>
                        <ArrivalAirport>GRU</ArrivalAirport>
                        <EntryType>SEGMENT</EntryType>
                        <DepartureLegTime>2018-01-24T00:00:00</DepartureLegTime>
                  </EntryHeader>
                  <GroupEntry sequenceId="1">
                        <PnrIndicatorType/>
                        <NumberInParty>1</NumberInParty>
                        <Name>ALBERTSON/HENRY JAMES MR</Name>
                        <Locator>BDABDA</Locator>
                        <ClassOfService>N</ClassOfService>
                        <StatusCode>HK</StatusCode>
                        <NumberOfPassengers>1</NumberOfPassengers>
                        <AgentId/>
                        <UpdateDateTime>2018-01-02T18:47:03</UpdateDateTime>
                  </GroupEntry>
                  <GroupEntry sequenceId="2">
                        <PnrIndicatorType/>
                        <NumberInParty>1</NumberInParty>
                        <Name>ALBERTSON/MARIA LUCIA MRS</Name>
                        <Locator>BDABDA</Locator>
                        <ClassOfService>N</ClassOfService>
                        <StatusCode>HK</StatusCode>
                        <NumberOfPassengers>1</NumberOfPassengers>
                        <AgentId/>
                        <UpdateDateTime>2018-01-02T18:47:03</UpdateDateTime>
                  </GroupEntry>
            </Entry>
      </Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```


3.11. TRI – Inbound Transfer Information List (Inbound Report)

The TRI Report presents list of passengers with a connection from the specified flight at the specified city, e.g. for flight LA123 from SCL to LIM, the report will list all passengers that are connecting in SCL from any flight.

TRI Report presents the following information:

1. The arrival times and number of passengers per class of service on the inbound flights with passengers transferring to specified flight.
2. The number of transit passengers by class of service that board the plane.
3. Report returns only confirmed passengers, taking into consideration following status code only:

HK, KK, KL, BK, CG, DK, FG, GK, IG, NK, OB, OS, OX, PS, RR, SC, TK, CH, CR, LK, YG, ZB, ZH, ZK, ZR (Note: some of the codes may not be present for certain airlines)

4. Report does not return passenger type Infant.
5. The list is sorted by class of service on the connecting flight, counts the number of passengers per connecting flight. If the connecting flight has multiple off points, each of them is calculated separately.

TRI Report is available in Native Sabre and Trip_ReportsRQ.

Note: this report requires a dedicated activation.

3.11.1 Native Sabre

The Native Sabre format to generate TRI report:

Report Type	Format Example
TRI	**RK/TRI/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}** RK/TRI/LA123Y/20JAN/LIM **Note:** Required – Airline Code, Flight Number, Date, Board Point Optional – Class Of Service

3.11.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

ReportFormat is an optional element. If you decide to use it, enter TRI as presented below:

<ReportFormat>TRI</ReportFormat>

Sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
        <ReportName>TRI</ReportName>                                        MANDATORY
        <ReportFormat>TRI</ReportFormat>                                    OPTIONAL
        <Criteria>
                <FlightCriteria>
                        <AirlineCode>LA</AirlineCode>                       MANDATORY
                        <FlightNumber>2474</FlightNumber>                   MANDATORY
                        <InboundAirport>LIM</InboundAirport>                MANDATORY
                        <DepartureDateTime>2018-01-20</DepartureDateTime>   MANDATORY
                        <ClassOfService>J</ClassOfService>                  OPTIONAL
                </FlightCriteria>
                <PosCriteria>LA</PosCriteria>                               MANDATORY
        </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for TRI Report contains:

- Report Name and Format
- Header which presents indicated flight details, including:
    - ClassList Type="TH" – shows a summary of how many passengers ‘in transit’ are scheduled for specific class of service. If we display a list for the first boarding point, the whole list will show “0” for all classes.
    - ClassList Type="TM" – shows a summary of how many passengers that disembark are scheduled for specific class of service. If we display a list for the first boarding point, the whole list will show “0” for all classes.

    Below you will find an extract from the Trip_ReportsRQ for TRI report presenting Class List Types:

```
<ClassList Type="TH">
      <Class Name="A">0</Class>
      <Class Name="B">0</Class>
      <Class Name="E">0</Class>
      <Class Name="G">0</Class>
      <Class Name="H">0</Class>
      <Class Name="K">0</Class>
      <Class Name="L">0</Class>
      <Class Name="M">0</Class>
      <Class Name="N">12</Class>
      <Class Name="O">3</Class>
      <Class Name="Q">2</Class>
      <Class Name="S">0</Class>
      <Class Name="T">5</Class>
      <Class Name="V">2</Class>
      <Class Name="X">0</Class>
      <Class Name="Y">0</Class>
</ClassList>
<ClassList Type="TM">
      <Class Name="A">12</Class>
      <Class Name="B">0</Class>
      <Class Name="E">2</Class>
      <Class Name="G">12</Class>
      <Class Name="H">0</Class>
      <Class Name="K">0</Class>
      <Class Name="L">0</Class>
      <Class Name="M">0</Class>
      <Class Name="N">4</Class>
      <Class Name="O">56</Class>
      <Class Name="Q">5</Class>
      <Class Name="S">9</Class>
      <Class Name="T">12</Class>
      <Class Name="V">0</Class>
      <Class Name="X">2</Class>
      <Class Name="Y">0</Class>
</ClassList>
```

- Details including list of passengers that connect from any flight to this flight (these numbers are independent of the TH and TM numbers).

Below you will find an extract from the Trip_ReportsRQ for TRI report presenting conneting flight details:

```
<ConnectingFlightEntry Type="INBOUND">
      <AirlineCode>LA</AirlineCode>
      <FlightNumber>638</FlightNumber>
      <ArrivalDateTime>2017-12-06T00:35:00</ArrivalDateTime>
      <TotalPassengers>3</TotalPassengers>
      <ClassList>
            <Class Name="S">1</Class>
            <Class Name="L">1</Class>
            <Class Name="O">1</Class>
      </ClassList>
      <ConnectingAirport Name="SCL">
            <ClassList>
            <Class Name="S">1</Class>
            <Class Name="L">1</Class>
            <Class Name="O">1</Class>
      </ClassList>
      </ConnectingAirport>
</ConnectingFlightEntry>
```

3.11.3 Use Case – Native Sabre

Given Sabre PNRs assigned with the given carrier. Generate the entire list of passengers that connect in LIM, for LA flight number 2462, departing on 23-JAN-2018.

The TRI report gives us the following information about the specified flight:

- There are 0 passengers 'in transit' as ClassList Type="TH" (presented in **green** below) shows 0 for all classes as LIM is the first boarding point.
- There are 0 passengers that disembark as ClassList Type="TM" (presented in **purple** below) shows 0 for all classes as LIM is the first boarding point.
- There are passengers that connect from a different flight to flight LA 2462 (presented in **orange** below):
  - 1 passenger from LA 536,
  - 1 passenger from LA 1314,
  - 1 passenger from LA 2428.

Input: `RK/TRI/LA2462/23JAN/LIM`

Output:

```
TR/LA2462/23JAN/LIM/FROM
TRANSFER
TO LA2462/23JAN AT LIM D1205
 TH  0A  0B  0C  0D  0E  0G  0H  0I  0J  0K  0L  0M  0N  0O  0Q
     0S  0T  0U  0V  0X  0Y  0Z
_TM  0A  0B  0C  0D  0E  0G  0H  0I  0J  0K  0L  0M  0N  0O  0Q
     0S  0T  0U  0V  0X  0Y  0Z
FROM LA536  A1050   1T
                    TOTAL PAX TRANSFER THIS FLIGHT      1
 SCL  1T
FROM LA1314 A1035   1B
                    TOTAL PAX TRANSFER THIS FLIGHT      1
 ASU  1B
FROM LA2428 A1040   1L
                    TOTAL PAX TRANSFER THIS FLIGHT      1
 EZE  1L
```

3.11.4 Use Case – Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, generate the entire list of passengers that connect in LIM, for LA flight number 4802, departing on 06-DEC-2017.

The TRI report gives us the following information about the specified flight:

- There are 0 passengers 'in transit' as ClassList Type="TH" shows 0 for all classes as LIM is the first boarding point (presented in **green** below).
- There are 0 passengers that disembark as ClassList Type="TM" shows 0 for all classes as LIM is the first boarding point (presented in **purple** below).
- There are passengers that connect from a different flight to flight LA 4802 (presented in **orange** below):
  - 2 passengers from LA 1425,
  - 2 passengers from LA 2054,
  - 1 passenger from LA 2303,
  - 1 passenger from LA 2407,
  - 3 passengers from LA 1449.

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>TRI</ReportName>
<ReportFormat>TRI</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>4802</FlightNumber>
              <InboundAirport>LIM</InboundAirport>
              <DepartureDateTime>2017-12-06</DepartureDateTime>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
  </Criteria>
</Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>TRI</ReportName>
<ReportFormat>TRI</ReportFormat>
<ReportResult>
<Header>
       <AirlineCode>LA</AirlineCode>
       <FlightNumber>4802</FlightNumber>
       <DepartureDateTime>2017-12-06T12:25:00</DepartureDateTime>
       <DisplayType>TRI</DisplayType>
       <InboundAirport>LIM</InboundAirport>
       <ClassList Type="TH">
              <Class Name="A">0</Class>
              <Class Name="B">0</Class>
              <Class Name="C">0</Class>
```

```
            <Class Name="D">0</Class>
            <Class Name="G">0</Class>
            <Class Name="H">0</Class>
            <Class Name="I">0</Class>
            <Class Name="J">0</Class>
            <Class Name="K">0</Class>
            <Class Name="L">0</Class>
            <Class Name="M">0</Class>
            <Class Name="N">0</Class>
            <Class Name="O">0</Class>
            <Class Name="Q">0</Class>
            <Class Name="S">0</Class>
            <Class Name="T">0</Class>
            <Class Name="U">0</Class>
            <Class Name="V">0</Class>
            <Class Name="X">0</Class>
            <Class Name="Y">0</Class>
            <Class Name="Z">0</Class>
      </ClassList>
      <ClassList Type="TM">
            <Class Name="A">0</Class>
            <Class Name="B">0</Class>
            <Class Name="C">0</Class>
            <Class Name="D">0</Class>
            <Class Name="G">0</Class>
            <Class Name="H">0</Class>
            <Class Name="I">0</Class>
            <Class Name="J">0</Class>
            <Class Name="K">0</Class>
            <Class Name="L">0</Class>
            <Class Name="M">0</Class>
            <Class Name="N">0</Class>
            <Class Name="O">0</Class>
            <Class Name="Q">0</Class>
            <Class Name="S">0</Class>
            <Class Name="T">0</Class>
            <Class Name="U">0</Class>
            <Class Name="V">0</Class>
            <Class Name="X">0</Class>
            <Class Name="Y">0</Class>
            <Class Name="Z">0</Class>
      </ClassList>
</Header>
<Details>
      <Entry>
            <ConnectingFlightEntry Type="INBOUND">
                  <AirlineCode>LA</AirlineCode>
                  <FlightNumber>1425</FlightNumber>
                  <ArrivalDateTime>2017-12-06T10:25:00</ArrivalDateTime>
                  <TotalPassengers>2</TotalPassengers>
                  <ClassList>
                        <Class Name="C">1</Class>
                        <Class Name="O">1</Class>
                  </ClassList>
                  <ConnectingAirport Name="GYE">
                        <ClassList>
                              <Class Name="C">1</Class>
                              <Class Name="O">1</Class>
                        </ClassList>
                  </ConnectingAirport>
            </ConnectingFlightEntry>
            <ConnectingFlightEntry Type="INBOUND">
                  <AirlineCode>LA</AirlineCode>
```

```
                <FlightNumber>2054</FlightNumber>
                <ArrivalDateTime>2017-12-06T10:10:00</ArrivalDateTime>
                <TotalPassengers>2</TotalPassengers>
                <ClassList>
                        <Class Name="B">1</Class>
                        <Class Name="Y">1</Class>
                </ClassList>
                <ConnectingAirport Name="CUZ">
                        <ClassList>
                                <Class Name="B">1</Class>
                                <Class Name="Y">1</Class>
                        </ClassList>
                </ConnectingAirport>
        </ConnectingFlightEntry>
        <ConnectingFlightEntry Type="INBOUND">
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>2303</FlightNumber>
                <ArrivalDateTime>2017-12-06T10:05:00</ArrivalDateTime>
                <TotalPassengers>1</TotalPassengers>
                <ClassList>
                        <Class Name="Y">1</Class>
                </ClassList>
                <ConnectingAirport Name="PIU">
                        <ClassList>
                                <Class Name="Y">1</Class>
                        </ClassList>
                </ConnectingAirport>
        </ConnectingFlightEntry>
        <ConnectingFlightEntry Type="INBOUND">
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>2407</FlightNumber>
                <ArrivalDateTime>2017-12-06T06:45:00</ArrivalDateTime>
                <TotalPassengers>1</TotalPassengers>
                <ClassList>
                        <Class Name="O">1</Class>
                </ClassList>
                <ConnectingAirport Name="VVI">
                        <ClassList>
                                <Class Name="O">1</Class>
                        </ClassList>
                </ConnectingAirport>
        </ConnectingFlightEntry>
        <ConnectingFlightEntry Type="INBOUND">
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>1449</FlightNumber>
                <ArrivalDateTime>2017-12-06T06:30:00</ArrivalDateTime>
                <TotalPassengers>3</TotalPassengers>
                <ClassList>
                        <Class Name="X">1</Class>
                        <Class Name="O">2</Class>
                </ClassList>
                <ConnectingAirport Name="UIO">
                        <ClassList>
                                <Class Name="X">1</Class>
                                <Class Name="O">2</Class>
                        </ClassList>
                </ConnectingAirport>
        </ConnectingFlightEntry>
    </Entry>
</Details>
</Trip_ReportsRS>
```

3.12. TRO – Outbound Transfer Information List (Outbound Report)

The TRO Report presents list of passengers with a connection to the specified flight at the specified city, e.g. for flight LA123 from SCL to LIM, the report will list all passengers that are connecting in LIM to any flight.

TRO Report presents the following information:

1. The departure times and number of passengers transferring from specified flight in specified city.
2. The number of transit passengers by class of service that board the plane.
3. Report returns only confirmed passengers, taking into consideration following status code only:

   HK, KK, KL, BK, CG, DK, FG, GK, IG, NK, OB, OS, OX, PS, RR, SC, TK, CH, CR, LK, YG, ZB, ZH, ZK, ZR (Note: some of the codes may not be present for certain airlines.
4. Report does not return passengers of Infant type.
5. The list is sorted by class of service on the connecting flight, counts the number of passengers per connecting flight.
6. If the connecting flight has multiple off points, each of them is calculated separately.

TRO Report is available in Native Sabre and Trip_ReportsRQ.

Note: this report requires a dedicated activation.

3.12.1 Native Sabre

The Native Sabre format to generate TRO Report:

Report Type	Format Example
TRO	**RK/TRO/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{OffPoint}** RK/TRO/LA123Y/20JAN/LIM **Note:** Required – Airline Code, Flight Number, Date, Off Point Optional – Class Of Service

3.12.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter TRO as presented below:

<ReportFormat>TRO</ReportFormat>

Ssample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>TRO</ReportName>                                          MANDATORY
       <ReportFormat>TRO</ReportFormat>                                      OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                           MANDATORY
                     <FlightNumber>2474</FlightNumber>                       MANDATORY
                     <OutboundAirport>LIM</OutboundAirport>                  MANDATORY
                     <DepartureDateTime>2017-12-06</DepartureDateTime>       MANDATORY
                     <ClassOfService>J</ClassOfService>                      OPTIONAL
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                  MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for TRO Report contains:

- Report Name and Format
- Header which presents indicated flight details, including:
    - ClassList Type="TH" – shows a summary of how many passengers ‘in transit’ are scheduled for specific class of service. E.g. for flight LA 123 which operates from SCL to LIM, the list will present all passengers that board in SCL and connect to any other flight in LIM.
    - ClassList Type="BD" – shows a summary of how many passengers board the plane in specified city. E.g. for flight LA 123 which operates from SCL to LIM, the list will present all passengers that board board in LIM and continue the travel.

      Below you will find an extract from the Trip_ReportsRQ for TRO report presenting Class List Types:

```
<ClassList Type="TH">
      <Class Name="A">0</Class>
      <Class Name="B">0</Class>
      <Class Name="E">0</Class>
      <Class Name="G">0</Class>
      <Class Name="H">0</Class>
      <Class Name="K">0</Class>
      <Class Name="L">0</Class>
      <Class Name="M">0</Class>
      <Class Name="N">12</Class>
      <Class Name="O">3</Class>
      <Class Name="Q">2</Class>
      <Class Name="S">0</Class>
      <Class Name="T">5</Class>
      <Class Name="V">2</Class>
      <Class Name="X">0</Class>
      <Class Name="Y">0</Class>
</ClassList>
<ClassList Type="BD">
      <Class Name="A">10</Class>
```

```
            <Class Name="B">0</Class>
            <Class Name="E">0</Class>
            <Class Name="G">0</Class>
            <Class Name="H">0</Class>
            <Class Name="K">1</Class>
            <Class Name="L">2</Class>
            <Class Name="M">0</Class>
            <Class Name="N">11</Class>
            <Class Name="O">32</Class>
            <Class Name="Q">17</Class>
            <Class Name="S">2</Class>
            <Class Name="T">13</Class>
            <Class Name="V">6</Class>
            <Class Name="X">0</Class>
            <Class Name="Y">0</Class>
      </ClassList>
```

- Details including list of passengers that are disembarking in the specified city and take a connection flight (these numbers are independent of the TH and BD numbers).

  Below you will find an extract from the Trip_ReportsRQ for TRO report presenting connecting flight details:

```
<ConnectingFlightEntry Type="OUTBOUND">
      <AirlineCode>LA</AirlineCode>
      <FlightNumber>2392</FlightNumber>
      <DepartureDateTime>2017-12-06T08:30:00</DepartureDateTime>
      <TotalPassengers>24</TotalPassengers>
      <ClassList>
            <Class Name="A">9</Class>
            <Class Name="T">2</Class>
            <Class Name="G">4</Class>
            <Class Name="O">9</Class>
      </ClassList>
      <ConnectingAirport Name="BOG">
            <ClassList>
                  <Class Name="A">9</Class>
                  <Class Name="T">2</Class>
                  <Class Name="G">4</Class>
                  <Class Name="O">9</Class>
            </ClassList>
      </ConnectingAirport>
</ConnectingFlightEntry>
```

3.12.3 Use Case – Native Sabre

Given Sabre PNRs assigned with the given carrier, generate the entire list of passengers that connect in LIM, for LA flight number 600, departing on 12-JAN-2018.

The TRO report gives us the following information about the specified flight:

- There are 6 passengers ‘in transit’ (ClassList Type="TH") (presented in green below).
- There are 53 passengers that board the plane in LIM to continue the travel on a connecting flight (ClassList Type="BD") (presented in purple below).
- There are passengers that connect to a different flight from flight LA 600 (presented in orange below):

- 1 passenger to LA 2462,
- 1 passenger to LA 1424,
- 2 passengers to AA 918,
- 4 passengers to LA 2721.

Input: `RK/TRO/LA600/12JAN/LIM`

Output:

```
TR/LA600/12JAN/LIM/TO
TRANSFER
FROM LA600/12JAN AT LIM A1050
 TH  0A  0B  0C  0D  0E  0G  0H  0I  0J  0K  0L  4M  0N  0O  0Q
     0S  0T  0U  0V  0X  2Y  0Z
 BD  0A  0B  0C  0D  0E  0G  0H  0I  0J  0K  2L  1M  6N  3O  0Q
     0S  0T  0U  0V  0X 41Y  0Z
TO   LA2462 D1205   1B
                    TOTAL PAX TRANSFER THIS FLIGHT      1
 MIA  1B
TO   LA1424 D1250   1Y
                    TOTAL PAX TRANSFER THIS FLIGHT      1
 GYE  1Y
TO   AA918  D2320   2Y
                    TOTAL PAX TRANSFER THIS FLIGHT      2
 MIA  2Y
TO   LA2721 D2100   4Y
                    TOTAL PAX TRANSFER THIS FLIGHT      4
 MIA  4Y
```

3.12.4 Use Case – Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, generate the entire list of passengers that connect in GRU, for LA flight number 2474, departing on 06-DEC-2017.

The TRO report gives us the following information about the specified flight:

- There are 24 passengers 'in transit' (ClassList Type="TH") (presented in green below).
- There are 94 passengers that board the plane in LIM to continue the travel on a connecting flight (ClassList Type="BD") (presented in purple below).
- There are passengers that connect to a different flight from flight LA 2474 (presented in orange below):
  - 24 passengers to LA 2392,
  - 1 passenger to LA 2396,
  - 15 passengers to LA 2458,
  - 11 passengers to LA 2452,
  - 2 passengers to LA 2125,
  - 7 passengers to LA2121,
  - 1 passenger to LA 2208,
  - 1 passenger to LA 2446,
  - 1 passenger to LA 2330,
  - 1 passenger to LA 2047,
  - 3 passengers to LA 2023,
  - 3 passengers to UX 176,
  - 1 passenger from to 1424.

Below you will find the use case presented with use of Trip_ReportsRQ.

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>TRO</ReportName>
<ReportFormat>TRO</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>2474</FlightNumber>
              <OutboundAirport>LIM</OutboundAirport>
              <DepartureDateTime>2017-12-06</DepartureDateTime>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
</Criteria></Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>TRO</ReportName>
<ReportFormat>TRO</ReportFormat>
<ReportResult>
<Header>
       <AirlineCode>LA</AirlineCode>
       <FlightNumber>2474</FlightNumber>
       <ArrivalDateTime>2017-12-06T06:40:00</ArrivalDateTime>
       <DisplayType>TRO</DisplayType>
       <OutboundAirport>LIM</OutboundAirport>
       <ClassList Type="TH">
              <Class Name="A">0</Class>
              <Class Name="B">0</Class>
              <Class Name="E">0</Class>
              <Class Name="G">0</Class>
              <Class Name="H">0</Class>
              <Class Name="K">0</Class>
              <Class Name="L">0</Class>
              <Class Name="M">0</Class>
              <Class Name="N">12</Class>
              <Class Name="O">3</Class>
              <Class Name="Q">2</Class>
              <Class Name="S">0</Class>
              <Class Name="T">5</Class>
              <Class Name="V">2</Class>
              <Class Name="X">0</Class>
              <Class Name="Y">0</Class>
       </ClassList>
       <ClassList Type="BD">
              <Class Name="A">10</Class>
              <Class Name="B">0</Class>
              <Class Name="E">0</Class>
              <Class Name="G">0</Class>
              <Class Name="H">0</Class>
              <Class Name="K">1</Class>
              <Class Name="L">2</Class>
              <Class Name="M">0</Class>
              <Class Name="N">11</Class>
```

```
                <Class Name="O">32</Class>
                <Class Name="Q">17</Class>
                <Class Name="S">2</Class>
                <Class Name="T">13</Class>
                <Class Name="V">6</Class>
                <Class Name="X">0</Class>
                <Class Name="Y">0</Class>
        </ClassList>
</Header>
<Details>
        <Entry>
                <ConnectingFlightEntry Type="OUTBOUND">
                        <AirlineCode>LA</AirlineCode>
                        <FlightNumber>2392</FlightNumber>
                        <DepartureDateTime>2017-12-06T08:30:00</DepartureDateTime>
                        <TotalPassengers>24</TotalPassengers>
                        <ClassList>
                                <Class Name="A">9</Class>
                                <Class Name="T">2</Class>
                                <Class Name="G">4</Class>
                                <Class Name="O">9</Class>
                        </ClassList>
                        <ConnectingAirport Name="BOG">
                                <ClassList>
                                        <Class Name="A">9</Class>
                                        <Class Name="T">2</Class>
                                        <Class Name="G">4</Class>
                                        <Class Name="O">9</Class>
                                </ClassList>
                        </ConnectingAirport>
                </ConnectingFlightEntry>
                <ConnectingFlightEntry Type="OUTBOUND">
                        <AirlineCode>LA</AirlineCode>
                        <FlightNumber>2396</FlightNumber>
                        <DepartureDateTime>2017-12-06T16:40:00</DepartureDateTime>
                        <TotalPassengers>1</TotalPassengers>
                        <ClassList>
                                <Class Name="S">1</Class>
                        </ClassList>
                        <ConnectingAirport Name="UIO">
                                <ClassList>
                                        <Class Name="S">1</Class>
                                </ClassList>
                        </ConnectingAirport>
                </ConnectingFlightEntry>
                <ConnectingFlightEntry Type="OUTBOUND">
                        <AirlineCode>LA</AirlineCode>
                        <FlightNumber>2458</FlightNumber>
                        <DepartureDateTime>2017-12-06T08:45:00</DepartureDateTime>
                        <TotalPassengers>15</TotalPassengers>
                        <ClassList>
                                <Class Name="Q">1</Class>
                                <Class Name="O">14</Class>
                        </ClassList>
                        <ConnectingAirport Name="CUN">
                                <ClassList>
                                        <Class Name="Q">1</Class>
                                        <Class Name="O">14</Class>
                                </ClassList>
                        </ConnectingAirport>
                </ConnectingFlightEntry>
                <ConnectingFlightEntry Type="OUTBOUND">
```

```
            <AirlineCode>LA</AirlineCode>
            <FlightNumber>2452</FlightNumber>
            <DepartureDateTime>2017-12-06T08:38:00</DepartureDateTime>
            <TotalPassengers>11</TotalPassengers>
            <ClassList>
                  <Class Name="Q">9</Class>
                  <Class Name="K">2</Class>
            </ClassList>
            <ConnectingAirport Name="PUJ">
                  <ClassList>
                        <Class Name="Q">9</Class>
                        <Class Name="K">2</Class>
                  </ClassList>
            </ConnectingAirport>
      </ConnectingFlightEntry>
      <ConnectingFlightEntry Type="OUTBOUND">
            <AirlineCode>LA</AirlineCode>
            <FlightNumber>2125</FlightNumber>
            <DepartureDateTime>2017-12-06T08:44:00</DepartureDateTime>
            <TotalPassengers>2</TotalPassengers>
            <ClassList>
                  <Class Name="B">2</Class>
            </ClassList>
            <ConnectingAirport Name="AQP">
                  <ClassList>
                        <Class Name="B">2</Class>
                  </ClassList>
            </ConnectingAirport>
      </ConnectingFlightEntry>
      <ConnectingFlightEntry Type="OUTBOUND">
            <AirlineCode>LA</AirlineCode>
            <FlightNumber>2121</FlightNumber>
            <DepartureDateTime>2017-12-06T09:00:00</DepartureDateTime>
            <TotalPassengers>7</TotalPassengers>
            <ClassList>
                  <Class Name="B">3</Class>
                  <Class Name="T">4</Class>
            </ClassList>
            <ConnectingAirport Name="CUZ">
                  <ClassList>
                        <Class Name="B">3</Class>
                        <Class Name="T">4</Class>
                  </ClassList>
            </ConnectingAirport>
      </ConnectingFlightEntry>
      <ConnectingFlightEntry Type="OUTBOUND">
            <AirlineCode>LA</AirlineCode>
            <FlightNumber>2208</FlightNumber>
            <DepartureDateTime>2017-12-06T15:55:00</DepartureDateTime>
            <TotalPassengers>1</TotalPassengers>
            <ClassList>
                  <Class Name="B">1</Class>
            </ClassList>
            <ConnectingAirport Name="TRU">
                  <ClassList>
                        <Class Name="B">1</Class>
                  </ClassList>
            </ConnectingAirport>
      </ConnectingFlightEntry>
      <ConnectingFlightEntry Type="OUTBOUND">
            <AirlineCode>LA</AirlineCode>
            <FlightNumber>2446</FlightNumber>
            <DepartureDateTime>2017-12-06T12:44:00</DepartureDateTime>
```

```
                <TotalPassengers>1</TotalPassengers>
                <ClassList>
                        <Class Name="O">1</Class>
                </ClassList>
                <ConnectingAirport Name="BOG">
                        <ClassList>
                                <Class Name="O">1</Class>
                        </ClassList>
                </ConnectingAirport>
        </ConnectingFlightEntry>
        <ConnectingFlightEntry Type="OUTBOUND">
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>2330</FlightNumber>
                <DepartureDateTime>2017-12-06T10:45:00</DepartureDateTime>
                <TotalPassengers>1</TotalPassengers>
                <ClassList>
                        <Class Name="B">1</Class>
                </ClassList>
                <ConnectingAirport Name="TBP">
                        <ClassList>
                                <Class Name="B">1</Class>
                        </ClassList>
                </ConnectingAirport>
        </ConnectingFlightEntry>
        <ConnectingFlightEntry Type="OUTBOUND">
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>2047</FlightNumber>
                <DepartureDateTime>2017-12-06T09:15:00</DepartureDateTime>
                <TotalPassengers>1</TotalPassengers>
                <ClassList>
                        <Class Name="B">1</Class>
                </ClassList>
                <ConnectingAirport Name="CUZ">
                        <ClassList>
                                <Class Name="B">1</Class>
                        </ClassList>
                </ConnectingAirport>
        </ConnectingFlightEntry>
        <ConnectingFlightEntry Type="OUTBOUND">
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>2023</FlightNumber>
                <DepartureDateTime>2017-12-06T08:10:00</DepartureDateTime>
                <TotalPassengers>3</TotalPassengers>
                <ClassList>
                        <Class Name="B">3</Class>
                </ClassList>
                <ConnectingAirport Name="CUZ">
                        <ClassList>
                                <Class Name="B">3</Class>
                        </ClassList>
                </ConnectingAirport>
        </ConnectingFlightEntry>
        <ConnectingFlightEntry Type="OUTBOUND">
                <AirlineCode>UX</AirlineCode>
                <FlightNumber>176</FlightNumber>
                <DepartureDateTime>2017-12-07T12:00:00</DepartureDateTime>
                <TotalPassengers>3</TotalPassengers>
                <ClassList>
                        <Class Name="N">3</Class>
                </ClassList>
                <ConnectingAirport Name="MAD">
                        <ClassList>
                                <Class Name="N">3</Class>
```

```
                        </ClassList>
                    </ConnectingAirport>
                </ConnectingFlightEntry>
                <ConnectingFlightEntry Type="OUTBOUND">
                    <AirlineCode>LA</AirlineCode>
                    <FlightNumber>1424</FlightNumber>
                    <DepartureDateTime>2017-12-06T12:50:00</DepartureDateTime>
                    <TotalPassengers>1</TotalPassengers>
                    <ClassList>
                        <Class Name="S">1</Class>
                    </ClassList>
                    <ConnectingAirport Name="GYE">
                        <ClassList>
                            <Class Name="S">1</Class>
                        </ClassList>
                    </ConnectingAirport>
                </ConnectingFlightEntry>
        </Entry>
</Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```


3.13. TRIN – Inbound Transfer Information List with Names

The TRIN Report presents list of passengers with a connection from the specified flight at the specified city. The list is sorted by class of service on the connecting flight, counts the number of passengers per connecting flight. Report presents passenger names, record locator, class of service and number in party for each transfer passenger additionally to TRI Report.

If the connecting flight has multiple off points, each of them is calculated separately.

Key characteristic:

1. Report returns only confirmed passengers, taking into consideration following status code only:

   HK, KK, KL, BK, CG, DK, FG, GK, IG, NK, OB, OS, OX, PS, RR, SC, TK, CH, CR, LK, YG, ZB, ZH, ZK, ZR (Note: some of the codes may not be present for certain airlines)

2. Report does not return passenger type Infant.

TRIN Report is available in Native Sabre and Trip_ReportsRQ.

Note: this report requires a dedicated activation.

3.13.1 Native Sabre

The Native Sabre format to generate TRIN Report:

Report Type	Format Example
TRIN	**RK/TRIN/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{BoardPoint}** RK/TRIN/LA123Y/20JAN/LIM **Note:** Required – Airline Code, Flight Number, Date, Board Point Optional – Class Of Service

3.13.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter TRIN as presented below:

<ReportFormat>TRIN</ReportFormat>

Sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>TRIN</ReportName>                                        MANDATORY
       <ReportFormat>TRIN</ReportFormat>                                    OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                          MANDATORY
                     <FlightNumber>2474</FlightNumber>                      MANDATORY
                     <InboundAirport>LIM</InboundAirport>                   MANDATORY
                     <DepartureDateTime>2018-01-20</DepartureDateTime>      MANDATORY
                     <ClassOfService>J</ClassOfService>                     OPTIONAL
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                 MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for TRIN Report contains:

- Report Name and Format
- Header which presents indicated flight details, including:
    - ClassList Type="TH" – shows a summary of how many passengers 'in transit' are scheduled for specific class of service. If we display a list for the first boarding point, the whole list will show "0" for all classes.
    - ClassList Type="TM" – shows a summary of how many passengers that disembark are scheduled for specific class of service. If we display a list for the first boarding point, the whole list will show "0" for all classes.

Below you will find an extract from the Trip_ReportsRQ for TRI report presenting Class List Types:

```
<ClassList Type="TH">
      <Class Name="A">0</Class>
      <Class Name="B">0</Class>
      <Class Name="E">0</Class>
      <Class Name="G">0</Class>
      <Class Name="H">0</Class>
      <Class Name="K">0</Class>
      <Class Name="L">0</Class>
      <Class Name="M">0</Class>
      <Class Name="N">12</Class>
      <Class Name="O">3</Class>
      <Class Name="Q">2</Class>
      <Class Name="S">0</Class>
      <Class Name="T">5</Class>
      <Class Name="V">2</Class>
      <Class Name="X">0</Class>
      <Class Name="Y">0</Class>
</ClassList>
<ClassList Type="TM">
      <Class Name="A">12</Class>
      <Class Name="B">0</Class>
      <Class Name="E">2</Class>
      <Class Name="G">12</Class>
      <Class Name="H">0</Class>
      <Class Name="K">0</Class>
      <Class Name="L">0</Class>
      <Class Name="M">0</Class>
      <Class Name="N">4</Class>
      <Class Name="O">56</Class>
      <Class Name="Q">5</Class>
      <Class Name="S">9</Class>
      <Class Name="T">12</Class>
      <Class Name="V">0</Class>
      <Class Name="X">2</Class>
      <Class Name="Y">0</Class>
</ClassList>
```

- Details including list of passengers with names that connect from any flight to this flight (these numbers are independent of the TH and TM numbers).

  Below you will find an extract from the Trip_ReportsRQ for TRIN report presenting connecting flight details with passenger names:

```
<ConnectingFlightEntry Type="INBOUND">
      <AirlineCode>LA</AirlineCode>
      <FlightNumber>536</FlightNumber>
      <ArrivalDateTime>2018-01-23T10:50:00</ArrivalDateTime>
      <TotalPassengers>1</TotalPassengers>
      <ClassList>
            <Class Name="T">1</Class>
      </ClassList>
      <ConnectingAirport Name="SCL">
            <ClassList>
                  <Class Name="T">1</Class>
            </ClassList>
            <Transferees>
```

```
                                <Transferee>
                                   <Name>ROSSI/MARIA</Name>
                                   <Locator>ABCBAC</Locator>
                                   <ClassOfService>T</ClassOfService>
                                   <NumberInParty>1</NumberInParty>
                                   <NumberOfPassengers>1</NumberOfPassengers>
                                </Transferee>
                             </Transferees>
                          </ConnectingAirport>
                       </ConnectingFlightEntry>
```


3.13.3 Use Case – Native Sabre and Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier. Generate the entire list of passengers with their names that connect in LIM, for LA flight number 2462, departing on 23-JAN-2018.

The TRIN report gives us the following information about the specified flight:

- There are 0 passengers 'in transit' as ClassList Type="TH" (presented in **green** below) shows 0 for all classes as LIM is the first boarding point.
- There are 0 passengers that disembark as ClassList Type="TM" (presented in **purple** below) shows 0 for all classes as LIM is the first boarding point.
- There are passengers that connect from a different flight to flight LA 2462 (presented in **orange** below):
    - 1 passenger from LA 536,
    - 1 passenger from LA 1314,
    - 1 passenger from LA 2428.

Below you will find the use case presented in Native Sabre and with use of Trip_ReportsRQ.

Native Sabre

Input: `RK/TRIN/LA2462/23JAN/LIM`

Output:

```
TR/LA2462/23JAN/LIM/FROM
TRANSFER
TO LA2462/23JAN AT LIM D1205
 TH  0A  0B  0C  0D  0E  0G  0H  0I  0J  0K  0L  0M  0N  0O  0Q
     0S  0T  0U  0V  0X  0Y  0Z
 TM  0A  0B  0C  0D  0E  0G  0H  0I  0J  0K  0L  0M  0N  0O  0Q
     0S  0T  0U  0V  0X  0Y  0Z
FROM LA536  A1050   1T
                    TOTAL PAX TRANSFER THIS FLIGHT      1
 SCL  1T
 1ROSSI/DANIELA                         ABCBCA T  1
FROM LA1314 A1035   1B
                    TOTAL PAX TRANSFER THIS FLIGHT      1
 ASU  1B
 1GOMEZ/SILVA                           AZAZAZ B  1
FROM LA2428 A1040   1L
                    TOTAL PAX TRANSFER THIS FLIGHT      1
 EZE  1L
 1FERNANDEZ/JUAN                        XYXYXY L  1
```

Trip_ReportsRQ

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>TRIN</ReportName>
<ReportFormat>TRIN</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>2462</FlightNumber>
              <InboundAirport>LIM</InboundAirport>
              <DepartureDateTime>2018-01-23</DepartureDateTime>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
</Criteria></Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>TRIN</ReportName>
<ReportFormat>TRIN</ReportFormat>
<ReportResult>
<Header>
  <AirlineCode>LA</AirlineCode>
  <FlightNumber>2462</FlightNumber>
  <DepartureDateTime>2018-01-23T12:05:00</DepartureDateTime>
  <DisplayType>TRIN</DisplayType>
  <InboundAirport>LIM</InboundAirport>
  <ClassList Type="TH">
      <Class Name="A">0</Class>
      <Class Name="B">0</Class>
      <Class Name="C">0</Class>
      <Class Name="D">0</Class>
      <Class Name="E">0</Class>
      <Class Name="G">0</Class>
      <Class Name="H">0</Class>
      <Class Name="I">0</Class>
      <Class Name="J">0</Class>
      <Class Name="K">0</Class>
      <Class Name="L">0</Class>
      <Class Name="M">0</Class>
      <Class Name="N">0</Class>
      <Class Name="O">0</Class>
      <Class Name="Q">0</Class>
      <Class Name="S">0</Class>
      <Class Name="T">0</Class>
      <Class Name="U">0</Class>
      <Class Name="V">0</Class>
      <Class Name="X">0</Class>
      <Class Name="Y">0</Class>
      <Class Name="Z">0</Class>
  </ClassList>
  <ClassList Type="TM">
      <Class Name="A">0</Class>
      <Class Name="B">0</Class>
      <Class Name="C">0</Class>
```

```
      <Class Name="D">0</Class>
      <Class Name="E">0</Class>
      <Class Name="G">0</Class>
      <Class Name="H">0</Class>
      <Class Name="I">0</Class>
      <Class Name="J">0</Class>
      <Class Name="K">0</Class>
      <Class Name="L">0</Class>
      <Class Name="M">0</Class>
      <Class Name="N">0</Class>
      <Class Name="O">0</Class>
      <Class Name="Q">0</Class>
      <Class Name="S">0</Class>
      <Class Name="T">0</Class>
      <Class Name="U">0</Class>
      <Class Name="V">0</Class>
      <Class Name="X">0</Class>
      <Class Name="Y">0</Class>
      <Class Name="Z">0</Class>
  </ClassList>
</Header>
<Details>
  <Entry>
      <ConnectingFlightEntry Type="INBOUND">
        <AirlineCode>LA</AirlineCode>
        <FlightNumber>536</FlightNumber>
        <ArrivalDateTime>2018-01-23T10:50:00</ArrivalDateTime>
        <TotalPassengers>1</TotalPassengers>
        <ClassList>
            <Class Name="T">1</Class>
        </ClassList>
        <ConnectingAirport Name="SCL">
            <ClassList>
                <Class Name="T">1</Class>
            </ClassList>
            <Transferees>
                <Transferee>
                    <Name>ROSSI/DANIELA</Name>
                    <Locator>ABCBCA</Locator>
                    <ClassOfService>T</ClassOfService>
                    <NumberInParty>1</NumberInParty>
                    <NumberOfPassengers>1</NumberOfPassengers>
                </Transferee>
            </Transferees>
        </ConnectingAirport>
      </ConnectingFlightEntry>
      <ConnectingFlightEntry Type="INBOUND">
        <AirlineCode>LA</AirlineCode>
        <FlightNumber>1314</FlightNumber>
        <ArrivalDateTime>2018-01-23T10:35:00</ArrivalDateTime>
        <TotalPassengers>1</TotalPassengers>
        <ClassList>
            <Class Name="B">1</Class>
        </ClassList>
        <ConnectingAirport Name="ASU">
            <ClassList>
                <Class Name="B">1</Class>
            </ClassList>
            <Transferees>
                <Transferee>
                    <Name>GOMEZ/SILVA</Name>
                    <Locator>AZAZAZ</Locator>
```

```
                    <ClassOfService>B</ClassOfService>
                    <NumberInParty>1</NumberInParty>
                    <NumberOfPassengers>1</NumberOfPassengers>
                </Transferee>
            </Transferees>
        </ConnectingAirport>
      </ConnectingFlightEntry>
      <ConnectingFlightEntry Type="INBOUND">
        <AirlineCode>LA</AirlineCode>
        <FlightNumber>2428</FlightNumber>
        <ArrivalDateTime>2018-01-23T10:40:00</ArrivalDateTime>
        <TotalPassengers>1</TotalPassengers>
        <ClassList>
            <Class Name="L">1</Class>
        </ClassList>
        <ConnectingAirport Name="EZE">
            <ClassList>
                <Class Name="L">1</Class>
            </ClassList>
            <Transferees>
                <Transferee>
                    <Name>FERNANDEZ/JUAN</Name>
                    <Locator>XYXYXY</Locator>
                    <ClassOfService>L</ClassOfService>
                    <NumberInParty>1</NumberInParty>
                    <NumberOfPassengers>1</NumberOfPassengers>
                </Transferee>
            </Transferees>
        </ConnectingAirport>
      </ConnectingFlightEntry>
  </Entry>
</Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```


3.14. TRON – Outbound Transfer Information List with Names

The TRON Report presents list of passengers with a connection from the specified flight at the specified city. The list is sorted by class of service on the connecting flight, counts the number of passengers per connecting flight. Report presents passenger names, record locator, class of service and number in party for each transfer passenger additionally to TRO Report.

If the connecting flight has multiple off points, each of them is calculated separately.

Key characteristic:

1. Report returns only confirmed passengers, taking into consideration following status code only:

HK, KK, KL, BK, CG, DK, FG, GK, IG, NK, OB, OS, OX, PS, RR, SC, TK, CH, CR, LK, YG, ZB, ZH, ZK, ZR (Note that all of these codes may not be used in all airlines partitions.)

2. Report does not return passenger type Infant.

TRON Report is available in Native Sabre and Trip_ReportsRQ.

Note: report requires a dedicated activation.

3.14.1 Native Sabre

The Native Sabre format to generate TRON Report is as follows:

Report Type	Format Example
TRON	**RK/TRON/(AirlineCode)(FlightNumber){ClassOfService}/(Date)/{OffPoint}** RK/TRON/LA123Y/20JAN/LIM **Note:** Required – Airline Code, Flight Number, Date, Off Point Optional – Class Of Service

3.14.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter TRON as presented below.

<ReportFormat>TRON</ReportFormat>

Following is a sample request to generate the TRON Report:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>TRON</ReportName>                                        MANDATORY
       <ReportFormat>TRON</ReportFormat>                                    OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                          MANDATORY
                     <FlightNumber>123</FlightNumber>                       MANDATORY
                     <OutboundAirport>LIM</OutboundAirport>                 MANDATORY
                     <DepartureDateTime>2017-12-06</DepartureDateTime>      MANDATORY
                     <ClassOfService>Y</ClassOfService>                     OPTIONAL
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                 MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for TRON Report contains:

- Report Name and Format
- Header which presents indicated flight details, including:

- ClassList Type="TH" – shows a summary of how many passengers ‘in transit’ are scheduled for specific class of service. E.g. for flight LA 123 which operates from SCL to LIM, the list will present all passengers that board in SCL and connect to any other flight in LIM.
- ClassList Type="BD" – shows a summary of how many passengers board the plane in specified city. E.g. for flight LA 123 which operates from SCL to LIM, the list will present all passengers that board board in LIM and continue the travel.

  Below you will find an extract from the Trip_ReportsRQ for TRO report presenting Class List Types:

```
<ClassList Type="TH">
      <Class Name="A">0</Class>
      <Class Name="B">0</Class>
      <Class Name="E">0</Class>
      <Class Name="G">0</Class>
      <Class Name="H">0</Class>
      <Class Name="K">0</Class>
      <Class Name="L">0</Class>
      <Class Name="M">0</Class>
      <Class Name="N">12</Class>
      <Class Name="O">3</Class>
      <Class Name="Q">2</Class>
      <Class Name="S">0</Class>
      <Class Name="T">5</Class>
      <Class Name="V">2</Class>
      <Class Name="X">0</Class>
      <Class Name="Y">0</Class>
</ClassList>
<ClassList Type="BD">
      <Class Name="A">10</Class>
      <Class Name="B">0</Class>
      <Class Name="E">0</Class>
      <Class Name="G">0</Class>
      <Class Name="H">0</Class>
      <Class Name="K">1</Class>
      <Class Name="L">2</Class>
      <Class Name="M">0</Class>
      <Class Name="N">11</Class>
      <Class Name="O">32</Class>
      <Class Name="Q">17</Class>
      <Class Name="S">2</Class>
      <Class Name="T">13</Class>
      <Class Name="V">6</Class>
      <Class Name="X">0</Class>
      <Class Name="Y">0</Class>
</ClassList>
```

- Details including list of passengers with their names that are disembarking in the specified city and take a connection flight (these numbers are independent of the TH and BD numbers).

  Below you will find an extract from the Trip_ReportsRQ for TRON report presenting connecting flight details with passengers’ names:

```
<ConnectingFlightEntry Type="OUTBOUND">
<AirlineCode>LA</AirlineCode>
<FlightNumber>2462</FlightNumber>
<DepartureDateTime>2018-01-12T12:05:00</DepartureDateTime>
<TotalPassengers>1</TotalPassengers>
<ClassList>
```

```
            <Class Name="B">1</Class>
        </ClassList>
        <ConnectingAirport Name="MIA">
            <ClassList>
                <Class Name="B">1</Class>
            </ClassList>
            <Transferees>
                <Transferee>
                    <Name>NOWAK/ADAM</Name>
                    <Locator>AAAAAA</Locator>
                    <ClassOfService>B</ClassOfService>
                    <NumberInParty>1</NumberInParty>
                    <NumberOfPassengers>1</NumberOfPassengers>
                </Transferee>
            </Transferees>
        </ConnectingAirport>
        </ConnectingFlightEntry>
```


3.14.3 Use Case – Native Sabre and Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier. Generate the entire list of passengers with their names that connect in LIM, for LA flight number 600, departing on 12-JAN-2018.

The TRON report gives us the following information about the specified flight:

- There are 6 passengers 'in transit' (ClassList Type="TH") (presented in **green** below).
- There are 53 passengers that board the plane in LIM to continue the travel on a connecting flight (ClassList Type="BD") (presented in **purple** below).
- There are passengers that connect to a different flight from flight LA 600 (presented in **orange** below):
    - 1 passenger to LA 2462,
    - 1 passenger to LA 1424,
    - 2 passengers to AA 918,
    - 4 passengers to LA 2721.

Below you will find the use case presented in Native Sabre and with use of Trip_ReportsRQ.

Native Sabre

Input: `RK/TRON/LA600/12JAN/LIM`

Output:

```
TR/LA600/12JAN/LIM/TO
TRANSFER
FROM LA600/12JAN AT LIM A1050
 TH  0A  0B  0C  0D  0E  0G  0H  0I  0J  0K  0L  4M  0N  0O  0Q
     0S  0T  0U  0V  0X  2Y  0Z
```

```
 BD   0A   0B   0C   0D   0E   0G   0H   0I   0J   0K   2L   1M   6N   3O   0Q
      0S   0T   0U   0V   0X 41Y   0Z
TO    LA2462 D1205    1B
                      TOTAL PAX TRANSFER THIS FLIGHT      1
 MIA  1B
 1NOWAK/ADAM                            AAAAAA B  1
TO    LA1424 D1250    1Y
                      TOTAL PAX TRANSFER THIS FLIGHT      1
 GYE  1Y
 1BRAD/PITT                             BBBBBB Y  1
TO    AA918  D2320    2Y
                      TOTAL PAX TRANSFER THIS FLIGHT      2
 MIA  2Y
 1KOWALSKI/JAN                          CCCCCC Y  1
1JONES/FRANK                           DDDDDD Y  1            ‡
TO    LA2721 D2100    4Y
                      TOTAL PAX TRANSFER THIS FLIGHT      4
 MIA  4Y
 2SMITH/JOHN/JULIE                      EEEEEE Y  2
 2LIS/JAKUB/KAROL                       FFFFFF Y  2
```

Trip_ReportsRQ

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>TRON</ReportName>
<ReportFormat>TRON</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>600</FlightNumber>
              <OutboundAirport>LIM</OutboundAirport>
              <DepartureDateTime>2018-01-12</DepartureDateTime>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
</Criteria></Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>TRON</ReportName>
<ReportFormat>TRON</ReportFormat>
<ReportResult>
<Header>
       <AirlineCode>LA</AirlineCode>
       <FlightNumber>600</FlightNumber>
       <ArrivalDateTime>2018-01-12T10:50:00</ArrivalDateTime>
       <DisplayType>TRON</DisplayType>
       <OutboundAirport>LIM</OutboundAirport>
       <ClassList Type="TH">
              <Class Name="A">0</Class>
              <Class Name="B">0</Class>
              <Class Name="C">0</Class>
              <Class Name="D">0</Class>
              <Class Name="E">0</Class>
```

```
            <Class Name="G">0</Class>
            <Class Name="H">0</Class>
            <Class Name="I">0</Class>
            <Class Name="J">0</Class>
            <Class Name="K">0</Class>
            <Class Name="L">0</Class>
            <Class Name="M">4</Class>
            <Class Name="N">0</Class>
            <Class Name="O">0</Class>
            <Class Name="Q">0</Class>
            <Class Name="S">0</Class>
            <Class Name="T">0</Class>
            <Class Name="U">0</Class>
            <Class Name="V">0</Class>
            <Class Name="X">0</Class>
            <Class Name="Y">2</Class>
            <Class Name="Z">0</Class>
      </ClassList>
      <ClassList Type="BD">
            <Class Name="A">0</Class>
            <Class Name="B">0</Class>
            <Class Name="C">0</Class>
            <Class Name="D">0</Class>
            <Class Name="E">0</Class>
            <Class Name="G">0</Class>
            <Class Name="H">0</Class>
            <Class Name="I">0</Class>
            <Class Name="J">0</Class>
            <Class Name="K">0</Class>
            <Class Name="L">2</Class>
            <Class Name="M">1</Class>
            <Class Name="N">6</Class>
            <Class Name="O">3</Class>
            <Class Name="Q">0</Class>
            <Class Name="S">0</Class>
            <Class Name="T">0</Class>
            <Class Name="U">0</Class>
            <Class Name="V">0</Class>
            <Class Name="X">0</Class>
            <Class Name="Y">41</Class>
            <Class Name="Z">0</Class>
      </ClassList>
</Header>
<Details>
      <Entry>
            <ConnectingFlightEntry Type="OUTBOUND">
                  <AirlineCode>LA</AirlineCode>
                  <FlightNumber>2462</FlightNumber>
                  <DepartureDateTime>2018-01-12T12:05:00</DepartureDateTime>
                  <TotalPassengers>1</TotalPassengers>
                  <ClassList>
                        <Class Name="B">1</Class>
                  </ClassList>
                  <ConnectingAirport Name="MIA">
                        <ClassList>
                              <Class Name="B">1</Class>
                        </ClassList>
                        <Transferees>
                              <Transferee>
                                    <Name>NOWAK/ADAM</Name>
                                    <Locator>AAAAAA</Locator>
                                    <ClassOfService>B</ClassOfService>
                                    <NumberInParty>1</NumberInParty>
```

```
                                <NumberOfPassengers>1</NumberOfPassengers>
                        </Transferee>
                </Transferees>
        </ConnectingAirport>
</ConnectingFlightEntry>
<ConnectingFlightEntry Type="OUTBOUND">
        <AirlineCode>LA</AirlineCode>
        <FlightNumber>1424</FlightNumber>
        <DepartureDateTime>2018-01-12T12:50:00</DepartureDateTime>
        <TotalPassengers>1</TotalPassengers>
        <ClassList>
                <Class Name="Y">1</Class>
        </ClassList>
        <ConnectingAirport Name="GYE">
                <ClassList>
                        <Class Name="Y">1</Class>
                </ClassList>
                <Transferees>
                        <Transferee>
                                <Name>BRAD/PITT</Name>
                                <Locator>BBBBBB</Locator>
                                <ClassOfService>Y</ClassOfService>
                                <NumberInParty>1</NumberInParty>
                                <NumberOfPassengers>1</NumberOfPassengers>
                        </Transferee>
                </Transferees>
        </ConnectingAirport>
</ConnectingFlightEntry>
<ConnectingFlightEntry Type="OUTBOUND">
        <AirlineCode>AA</AirlineCode>
        <FlightNumber>918</FlightNumber>
        <DepartureDateTime>2018-01-12T23:20:00</DepartureDateTime>
        <TotalPassengers>2</TotalPassengers>
        <ClassList>
                <Class Name="Y">2</Class>
        </ClassList>
        <ConnectingAirport Name="MIA">
                <ClassList>
                        <Class Name="Y">2</Class>
                </ClassList>
                <Transferees>
                        <Transferee>
                                <Name>KOWALSKI/JAN</Name>
                                <Locator>CCCCCC</Locator>
                                <ClassOfService>Y</ClassOfService>
                                <NumberInParty>1</NumberInParty>
                                <NumberOfPassengers>1</NumberOfPassengers>
                        </Transferee>
                        <Transferee>
                                <Name>JONES/FRANK</Name>
                                <Locator>DDDDDD</Locator>
                                <ClassOfService>Y</ClassOfService>
                                <NumberInParty>1</NumberInParty>
                                <NumberOfPassengers>1</NumberOfPassengers>
                        </Transferee>
                </Transferees>
        </ConnectingAirport>
</ConnectingFlightEntry>
<ConnectingFlightEntry Type="OUTBOUND">
        <AirlineCode>LA</AirlineCode>
        <FlightNumber>2721</FlightNumber>
        <DepartureDateTime>2018-01-12T21:00:00</DepartureDateTime>
        <TotalPassengers>4</TotalPassengers>
```

```
                    <ClassList>
                          <Class Name="Y">4</Class>
                    </ClassList>
                    <ConnectingAirport Name="MIA">
                          <ClassList>
                                <Class Name="Y">4</Class>
                          </ClassList>
                          <Transferees>
                                <Transferee>
                                      <Name>SMITH/JOHN/JULIE</Name>
                                      <Locator>EEEEEE</Locator>
                                      <ClassOfService>Y</ClassOfService>
                                      <NumberInParty>2</NumberInParty>
                                      <NumberOfPassengers>2</NumberOfPassengers>
                                </Transferee>
                                <Transferee>
                                      <Name>LIS/JAKUB/KAROL</Name>
                                      <Locator>FFFFFF</Locator>
                                      <ClassOfService>Y</ClassOfService>
                                      <NumberInParty>2</NumberInParty>
                                      <NumberOfPassengers>2</NumberOfPassengers>
                                </Transferee>
                          </Transferees>
                    </ConnectingAirport>
              </ConnectingFlightEntry>
       </Entry>
</Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```

Inventory Reports

4

4.1. General Information

Inventory reports gather and present flight information by segment, legs, cabin, fare class, segment status, and board point. Reports include booked, ticketed, authorization levels, actual capacity and available to sell counts.

BSF, BSR and BST are available in Native Sabre and via direct Trip_ReportsRQ API calls. BGR Report is accessible through the web service channel only.

All Inventory Reports are available up to 48 hours after the flight departure.

The next sections of this chapter describe the functionality of each Inventory Report in details.

4.2. BSF – Full Flight Booking Report

The BSF Report presents detailed inventory data by class of service for departure cities and flight segments.

BSF Report follows the below rules:

1. If origin and destination is included in the input, the system will determine the flight routing and return the report for the leg(s) and segment(s) included in the request.

2. If no origin and destination is included in the input, the system will determine the flight routing and return the report for all legs and segments in the routing.

Example for routing: SCL-MAD-FRA

Option 1 - Input: BSF/LA507/10DEC/SCLFRA
Report on Legs: SCL, MAD
Report on Segments: SCL-MAD, SCL-FRA, MAD-FRA

Option 2 - Input: BSF/LA507/10DEC/MADFRA
Report on Leg: MAD
Report on Segment: MAD-FRA

Option 3 - Input: BSF/LA507/10DEC/SCLMAD
Report on Leg: SCL
Report on Segment: SCL-MAD

Option 4 - Input: BSF/LA507/10DEC
Report on Legs: SCL, MAD
Report on Segments: SCL-MAD, SCL-FRA, MAD-FRA

BSF Report is available in Native Sabre and Trip_ReportsRQ up to 48 hours after the departure.

Please note, this report requires a dedicated activation.

Sabre Inc. Confidential / All Rights Reserved

4.2.1 Native Sabre

The Native Sabre format to generate BSF Report:

Report Type	Format Example
BSF	**RK/LL/BSF/(AirlineCode)(FlightNumber)/(Date)/{BoardPoint}{OffPoint}** RK/LL/BSF/LA123/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Board Point, Off Point

Input sample: `RK/LL/BSF/LA704/20DEC`

Output sample:

```
         1234567891111111111222222222233333333334444444444555555555566666666667777777777
                  0123456789012345678901234567890123456789012345678901234567890123456789
A        LA704  MO20DEC SCLFRA 26  RAF*330 JDI(UR)/YBHKMLVSNQOX(GTE) 340/CT2324 SMT 12
B        TIME C LEG AV OPN MAX CAP T/B  GRS BLK   B1  LIM  NL IND
C             J/DIUR
D        2030 J SCL AS  11  44       1             0    0  1
E            /D     AS  11  44       3             0   44  2
             /I     CC -29   0      29             0    0  3
             /U     CC -29   0       0             0    0  4
             /R     CC -29   0       0             0    0  5
F              CT       11  44  42  33    0   0   0
G        1515 J1MAD AS  32  40       0             0    3  1
             /D     AS  29  37       1             0    1  2
             /I     AS  29  36       7             0   20  3
             /U     AS  16  16       0             0    0  4
             /R     AS  16  16       0             0   16  5
H              CT       32  40  42   8    0   0   0
I             Y/BHKMLVSNQOGTXE
         2030 Y SCL AS  11 227       0             0    0  1
             /B     AS  11 227       0             0    0  2
             /H     AS  11 227       3             0    1  3
             /K     AS  11 226       0             0    1  4
             /M     AS  11 225       5             0    5  5
             /L     AS  11 220       1             0    2  6
             /V     AS  11 218      49             0  218  7
             /S     CC-158   0      16             0    0  8
             /N     CC-158   0      40             0    0  9
             /Q     CC-158   0      71             0    0 10
             /O     CC-158   0      30             0    0 11
             /G     CC-158   0       0             0    0 12
             /T     CC-158   0       1             0    0 13
             /X     CC-158   0       0             0    0 14
             /E     CC-158   0       0             0    0 15
               CT       11 227 218 216    0  35    0        4
         1515 Y1MAD AS  75 250       0             0    1  1
             /B     AS  74 249       0             0    4  2
             /H     AS  70 245       1             0   11  3
             /K     AS  60 234       0             0    0  4
             /M     AS  60 234       7             0    7  5
             /L     AS  60 227       0             0   30  6
             /V     AS  30 197      13             0   11  7
```

```
J
K
L
     /S      AS  30 186      17              0   45  8
     /N      AS   4 141      15              0   14  9
     /Q      AS   4 127      47              0   50 10
     /O      CR   2  77      60              0   60 11
     /G      CR   2  17       0              0    0 12
     /T      CR   2  17       2              0    3 13
     /X      CR   1  14      13              0   14 14
     /E      CR   0   0       0              0    0 15
       CT        75 250 218 175    0  16    4
SEG SCLMAD
SEG    CLS  BKD  GRS  BLK  WL  LSV  LSS  NL  SMT  GNM  IND
SCLMAD J      1    0    0   0    -    -   -   12    -    -
       D      2    0    0   0    -    -   -   12    -    -
       I     22    0    0   0    -    -   -   12    -    -
       U      0    0    0   0    -    -   -   12    -    -
       R      0    0    0   0    -    -   -   12    -    -
       Y      0    0    0   0    -    -   -   12    -    -
       B      0    0    0   0    -    -   -   12    -    -
       K      0    0    0   0    -    -   -   12    -    -
       M      5    0    0   0    -    -   -   12    -    -
       L      1    0    0   0    -    -   -   12    -    -
       V     36    1    0   0    -    -   -   12    -    -
       S     15    0    0   0    -    -   -   12    -    -
       N     40    2    0   0    -    -   -   12    -    -
       Q     51    1    0   0    -    -   -   12    -    -
M      O     26   15    0   0    -    -   -   12    -    -
N      G      0    0    0   0    -    -   -   12    -    -
       T      1    0    0   0    -    -   -   12    -    -
       X      0    0    0   0    -    -   -   12    -    -
       E      0    0    0   0    -    -   -   12    -    -
SCLMAD *TTL 202   19    0   0
       J456   0    -    -   0
       D456   1    -    -   0    -    -   -         -    -
       I456   4    -    -   0    -    -   -         -    -
       Y456   0    -    -   0    -    -   -         -    -
       B456   0    -    -   0    -    -   -         -    -
       H456   0    -    -   0    -    -   -         -    -
       K456   0    -    -   0    -    -   -         -    -
       M456   0    -    -   0    -    -   -         -    -
       L456   1    -    -   0    -    -   -         -    -
       V456  11    -    -   0    -    -   -         -    -
       S456   4    -    -   0    -    -   -         -    -
       N456  22    -    -   0    -    -   -         -    -
       Q456  35    -    -   0    -    -   -         -    -
       O456   5    -    -   0    -    -   -         -    -
       G456   0    -    -   0    -    -   -         -    -
       X456   0    -    -   0    -    -   -         -    -
SEG SCLFRA
SCLFRA J      0    0    0   0    -    -   -  12     -    -
       D      1    0    0   0    -    -   -  12     -    -
       I      7    0    0   0    -    -   -  12     -    -
       U      0    0    0   0    -    -   -  12     -    -
       R      0    0    0   0    -    -   -  12     -    -
       Y      0    0    0   0    -    -   -  12     -    -
       B      0    0    0   0    -    -   -  12     -    -
       H      1    0    0   0    -    -   -  12     -    -
       K      0    0    0   0    -    -   -  12     -    -
       M      0    0    0   0    -    -   -  12     -    -
       L      0    0    0   0    -    -   -  12     -    -
       V     13    0    0   0    -    -   -  12     -    -
       S      1    0    0   0    -    -   -  12     -    -
       N      0    0    0   0    -    -   -  12     -    -
       Q     20   16    0   0    -    -   -  12     -    -
```

```
        O      4    0    0    0    -    -    -   12    -    -
        G      0    0    0    0    -    -    -   12    -    -
        T      0    0    0    0    -    -    -   12    -    -
        X      0    0    0    0    -    -    -   12    -    -
        E      0    0    0    0    -    -    -   12    -    -
SCLFRA *TTL  47   16    0    0
SEG MADFRA TIV =
MADFRA J       0    0    0    0    -    -    -   12    -    -
        D      0    0    0    0    -    -    -   12    -    -
        I      0    0    0    0    -    -    -   12    -    -
        U      0    0    0    0    -    -    -   12    -    -
        R      0    0    0    0    -    -    -   12    -    -
        Y      0    0    0    0    -    -    -   12    -    -
        B      0    0    0    0    -    -    -   12    -    -
        H      0    0    0    0    -    -    -   12    -    -
        K      0    0    0    0    -    -    -   12    -    -
        M      7    0    0    0    -    -    -   12    -    -
        L      0    0    0    0    -    -    -   12    -    -
        V      0    0    0    0    -    -    -   12    -    -
        S     16    0    0    0    -    -    -   12    -    -
        N     15    0    0    0    -    -    -   12    -    -
        Q     27    0    0    0    -    -    -   12    -    -
        O     56    0    0    0    -    -    -   12    -    -
        G      0    0    0    0    -    -    -   12    -    -
        T      2    0    0    0    -    -    -   12    -    -
        X     13    0    0    0    -    -    -   12    -    -
        E      0    0    0    0    -    -    -   12    -    -
MADFRA *TTL 136    0    0    0
```

Fields explanation:

Col.#/ Range	Element	Definition
A1-2	LA	Carrier
A3-6	704	Flight number
A8-9	MO	Day of Week MO = Monday TU = Tuesday WE = Wednesday TH = Thursday FR = Friday SA = Saturday SU = Sunday
A10-14	20DEC	Date of flight
A15-21	SCLFRA	City Pair
A23-25	26	Days prior to departure (from date of request)
A27-33	RAF*330	RAF*330: the pre reservation seat is activated and 330 are the days before departure day - Asterisk indicates PRS activated, no asterisk PRS not activated.

Sabre Inc. Confidential / All Rights Reserved

Col.#/ Range	Element	Definition
A34-59	JDI(UR)/YBH KMLVSNQO X(GTE)	JDI: Are the RBD if there are between () are the Hidden RBD like (UR) – Not sent by SSM, only OneWorld and LAN or special agreements with other carriers such as AM (AM have frequent flyer program) and possibly TAM can see hidden RBD – See connectivity and alliance data collector. / indicator used to divide cabins. The length of this field is flexible based on the number of classes listed.
A61-70	340/CT2324	type of aircraft and table of configuration
A72-77	SMT 12	AVS table – no longer required as of 4/13/11.
B1-4	TIME	Column header Time of departure of the leg
B6	C	Class each leg is repeated for each base clas
B8-10	LEG	Origin of the leg
B12-13	AV	Availability Status AS = Flight opened or reopened CR = flight segment closed, request space CL = flight closed but waitlist open CC = flight closed, waitlist closed CN = flight cancelled (NOOP)
B15-17	OPN	Number of seats available for sale including overbook amount OPN = AU-bookings also taking into accound LIM
B19-21	MAX	aircraft capacity plus overbook amount, ie, 300 seats capacity would show 310 (Physical capacity + overbooking allowed = AU)
B23-25	CAP	aircraft capacity for the cabin
B27-29	T/B	booking passenger (local and transit booking) Total seats already booked by class by leg (local and transit bookings). This total includes individual psgrs, Codeshare psgrs, corporate psgrs, BSG psgrs – all confirmed passengers
B32-34	GRS	Corporate PNRs
B36-38	BLK	BSG PNRs by leg
B42-43	B1	Capacity restriction by leg On the 1845 SCL Y leg, there is a capacity restriction of 4 seats

Sabre Inc. Confidential / All Rights Reserved

<table>
<tr><th>Col.#/ Range</th><th>Element</th><th>Definition</th></tr>
<tr><td>B46-48</td><td>LIM</td><td>limit of seat Resiber calculates to know how many seats to protect by class
LIM = AU of the class – AU of the next lower class

LIM is calculated following the nesting order from the highest to the lowest class
Example:
<table>
<tr><td></td><td>AU</td><td>LIM</td><td>LIM</td></tr>
<tr><td>J</td><td>30</td><td>(30-26)</td><td>4</td></tr>
<tr><td>D</td><td>26</td><td>(26-22)</td><td>4</td></tr>
<tr><td>I</td><td>22</td><td>(22-13)</td><td>9</td></tr>
<tr><td>U</td><td>13</td><td>(13-3)</td><td>10</td></tr>
<tr><td>R</td><td>3</td><td>(3-0)</td><td>3</td></tr>
</table></td></tr>
<tr><td>B51-52</td><td>NL</td><td>order of nesting by leg</td></tr>
<tr><td>B54-56</td><td>IND</td><td>A = flight affected by an ad hoc schedule change
E = PFS was generated. Flight in route. The flight is closed for sale and check-in
L = Emergency locked or FIT
N = This leg accepts night fares
R = PNL was generated
X = cancelled leg or flight</td></tr>
<tr><td>C6-11</td><td>J/DIUR</td><td>Base class/booking classes</td></tr>
<tr><td>D1-4</td><td>2030</td><td>Departure time of the SCL leg</td></tr>
<tr><td>D6</td><td>J</td><td>Base Class (if J is inhibited, NL = 0)</td></tr>
<tr><td>D8-10</td><td>SCL</td><td>Origin of the leg</td></tr>
<tr><td>E5-6</td><td>/D</td><td>Booking class in J</td></tr>
<tr><td>F7-8</td><td>CT</td><td>Total by compartment/base class, by leg</td></tr>
<tr><td>F16-17</td><td>11</td><td>Open seats in J</td></tr>
<tr><td>F20-21</td><td>44</td><td>Maximum/AU in J</td></tr>
<tr><td>F24-25</td><td>42</td><td>J cabin capacity (actual cabin capacity will be shown for business and business economy even if AU is 0.</td></tr>
<tr><td>F28-29</td><td>33</td><td>Total booked in J</td></tr>
<tr><td>Row G</td><td></td><td>Beginning of data for MAD leg</td></tr>
<tr><td>H6-21</td><td>Y/BHKMLVS NQOGTXE</td><td>Y base class and booking classes in Y</td></tr>
<tr><td>Row I</td><td></td><td>Beginning of Y base class for SCL leg</td></tr>
<tr><td>J43</td><td>4</td><td>Capacity restriction number</td></tr>
<tr><td>K1-3</td><td>SEG</td><td>Header for Segment information</td></tr>
</table>

Sabre Inc. Confidential / All Rights Reserved

Col.#/ Range	Element	Definition
K5-10	SCLMAD	City Pair of the segment
L1-3	SEG	Segment header
L8-10	CLS	Header – Booking class
L13-15	BKD	Total seats booked by class by segment – all confirmed psgrs
L18-20	GRS	Corporate PNR psgr count, even if the C/ PNR is less than 10 passengers
L22-25	BLK	BSG psgrs
L28-29	WL	Waitlist
L32-34	LSV	Limit sales amount Segment limit amount "-" (dash) is shown if no LSV is set, if an LSV is set, the numerical value will be shown
K37-39	LSS	Limit sale sold If the classes are nesting by segmernt, LSS will display the authorization level by segment considering the LSV amount and the nesting order "-" (dash) is shown if no LSS is set, if an LSS is set, the numerical value will be shown
K42-43	NL	Indicator of the nesting order by segment as above for dash
K46-48	SMT	AVS table
K51-53	GNM	Number of names already given for the BSG PNRs by segment as above for dash
K56-58	IND	A – flight affected by ad hoc schedule change D – inhibit PRS by class by segment K – inhibit automatic waitlist confirmation P – permanent request (e.g., for charter) S – traffic restriction this segment. No local traffic. N – Not available for this segment as above for dash
Row L		Totals for this segment. The total is required for BKD, GRS, BLK, WL and GNM
M7	J	Class
M8-10	456	Codeshare Table Agreement
	0	BKD (Total bookings by class by segment)
	0	WL (Wailist by class by segment)

4.2.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS. Departure and Arrival Airport are optional.

The response will vary depending on the criteria you include in the request.

Sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>BSF</ReportName>                                        MANDATORY
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                         MANDATORY
                     <FlightNumber>125</FlightNumber>                      MANDATORY
                     <DepatureAirport>SCL</DepartureAirport>               OPTIONAL
                     <ArrivalAirport>LIM</ArrivalAirport>                  OPTIONAL
                     <DepartureDateTime>2017-12-14</DepartureDateTime>     MANDATORY
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for BSF Report contains:

- Report Name
- Header which presents indicated flight details, including:
  - Legs / Classes, e.g.:
    `<LegsClasses>JCDIZU/YBHKMLVXSNQOGTAE</LegsClasses>`
  - Aircraft Type, e.g.:
    `<AircraftType>B88</AircraftType>`
- Flight details

4.2.3 Use Case – Native Sabre and Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier. Generate the BSF inventory report for LA flight number 750, departing on 24-JAN-2018.

Native Sabre

Input: `RK/LL/BSF/LA750/24JAN/SCLGRU`
Output:

```
LA750  WE24JAN SCLGRU 9   RAF     JCDIZU/YBHKMLVXSNQOG-
CD2/
TIME C LEG AV OPN MAX CAP T/B GRS BLK   B1  LIM  NL IND
     C SCL  -  55  59       0   0   0         0   2   -
     D SCL  -  55  59       0   0   0         0   3   -
     I SCL  -  55  59       3   0   0         3   4   -
     Z SCL  -  55  56       0   0   0      -244   5   -
     U SCL  -  55 300       1   0   0       300   6   -
      CT       55  60  30   5   0   0    0
TIME C LEG AV OPN MAX CAP T/B GRS BLK   B1  LIM  NL IND
     B SCL  - 179 300       6   0   0         6   2   -
     H SCL  - 179 294       0   0   0         0   3   -
     K SCL  - 179 294       0   0   0         0   4   -
     M SCL  - 179 294       0   0   0         0   5   -
     L SCL  - 179 294       0   0   0         0   6   -
     V SCL  - 179 294       2   0   0         7   7   -
     X SCL  - 174 287       9   0   0        73   8   -
```

```
     S SCL  - 110 214      10   0   0         0   9   -
     N SCL  - 110 214       0   0   0        15  10   -‡
MD«
     Q SCL  - 105 199      15   0   0        46  11   -        ‡
     O SCL  -  74 153      46   0   0         0  12   -
     G SCL  -  74 153       0   0   0       -147  13   -
     T SCL  -  74 300      17   0   0       180  14   -
     A SCL  -  74 120      16   0   0         0  15   -
     E SCL  -  74 120       0   0   0       120  16   -
      CT      179 300 274 121   0   0    0
SEG    CLS  BKD  GRS  BLK   WL  LSV  LSS  NL  SMT  GNM  IND
SCLGRU   J    1    0    0    0    -    -   -         0    -
         C    0    0    0    0    -    -   -         0    -
         D    0    0    0    0    -    -   -         0    -
         I    3    0    0    0    -    -   -         0    -
         Z    0    0    0    0    -    -   -         0    -
         U    1    0    0    0    -    -   -         0    -
         Y    0    0    0    0    -    -   -         0    -
         B    6    0    0    0    -    -   -         0    -
         H    0    0    0    0    -    -   -         0    -
         K    0    0    0    0    -    -   -         0    -
         M    0    0    0    0    -    -   -         0    -    ‡
MD«
         L    0    0    0    0    -    -   -         0    -    ‡
         V    2    0    0    0    -    -   -         0    -
         X    9    0    0    0    -    -   -         0    -
         S   10    0    0    0    -    -   -         0    -
         N    0    0    0    0    -    -   -         0    -
         Q   15    0    0    0    -    -   -         0    -
         O   46    0    0    0    -    -   -         0    -
         G    0    0    0    0    -    -   -         0    -
         T   17    0    0    0    -    -   -         0    -
         A   16    0    0    0    -    -   -         0    -
         E    0    0    0    0    -    -   -         0    -
         *  126    0    0    0                        0
```

Trip_ReportsRQ

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>BSF</ReportName>
<Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>750</FlightNumber>
              <DepartureAirport>SCL</DepartureAirport>
              <ArrivalAirport>GRU</ArrivalAirport>
              <DepartureDateTime>2018-01-24</DepartureDateTime>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
</Criteria></Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
```

```
<ReportName>BSF</ReportName>
<ReportResult>
       <Header>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>750</FlightNumber>
              <DepartureDateTime>2018-01-24T00:00:00</DepartureDateTime>
              <DepartureDayOfWeek>WED</DepartureDayOfWeek>
              <DepartureAirport>SCL</DepartureAirport>
              <ArrivalAirport>GRU</ArrivalAirport>
              <DaysPriorToDeparture>9</DaysPriorToDeparture>
              <LegsClasses>JCDIZU/YBHKMLVXSNQOGTAE</LegsClasses>
              <AircraftType>CD2</AircraftType>
       </Header>
       <Details>
              <Entry>
                     <EntryHeader>
                            <ClassOfService>J</ClassOfService>
                            <EntryType>LEG</EntryType>
                            <DepartureLegTime>2018-01-24T08:30:00</DepartureLegTime>
                     </EntryHeader>
                     <FlightEntry>
                            <DepartureLegTime>0830</DepartureLegTime>
                            <ClassOfLeg>J</ClassOfLeg>
                            <LegOrigin>SCL</LegOrigin>
                            <AvailabilityStatus>-</AvailabilityStatus>
                            <AvailableSeats>55</AvailableSeats>
                            <AircraftCapacityAU>60</AircraftCapacityAU>
                            <TotalSeatsBooked>1</TotalSeatsBooked>
                            <CorporatePnrs>0</CorporatePnrs>
                            <BsgPnrs>0</BsgPnrs>
                            <CapacityRestriction>0</CapacityRestriction>
                            <LimitOfSeats>1</LimitOfSeats>
                            <OrderOfLegs>1</OrderOfLegs>
                            <FlightIndicator>-</FlightIndicator>
                            <EntryType>BASE</EntryType>
                     </FlightEntry>
                     <FlightEntry>
                            <DepartureLegTime>0830</DepartureLegTime>
                            <ClassOfLeg>C</ClassOfLeg>
                            <LegOrigin>SCL</LegOrigin>
                            <AvailabilityStatus>-</AvailabilityStatus>
                            <AvailableSeats>55</AvailableSeats>
                            <AircraftCapacityAU>59</AircraftCapacityAU>
                            <TotalSeatsBooked>0</TotalSeatsBooked>
                            <CorporatePnrs>0</CorporatePnrs>
                            <BsgPnrs>0</BsgPnrs>
                            <CapacityRestriction>0</CapacityRestriction>
                            <LimitOfSeats>0</LimitOfSeats>
                            <OrderOfLegs>2</OrderOfLegs>
                            <FlightIndicator>-</FlightIndicator>
                            <EntryType>NORMAL</EntryType>
                     </FlightEntry>
                     […]
       </Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```

4.3. BGR – Full Flight Booking Report in XML

The BGR Report presents detailed inventory data by class for departure cities and flight segments in structured XML format. It presents the same information as BSF Report.

BGR Report is available in Trip_ReportsRQ only up to 48 hours after the departure. BGR Report is not available in Native Sabre.

Note: this report requires a dedicated activation.

4.3.1 Trip_ReportsRQ

Following is a sample request to generate the BGR Report:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>BGR</ReportName>                                        MANDATORY
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                          MANDATORY
                     <FlightNumber>125</FlightNumber>                       MANDATORY
                     <DepatureAirport>SCL</DepartureAirport>                OPTIONAL
                     <ArrivalAirport>LIM</ArrivalAirport>                   OPTIONAL
                     <DepartureDateTime>2017-12-14</DepartureDateTime>      MANDATORY
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                 MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

4.4. BSR – Flight Booking and Ticketing Report

The BSR Report presents limited inventory data and ticketing information by class of service for departure cities and flight segments.

BSR Report follows the below rules:

1. If origin and destination is included in the input, the system will determine the flight routing and return the report for the leg(s) and segment(s) included in the request.

2. If no origin and destination is included in the input, the system will determine the flight routing and return the report for all legs and segments in the routing.

Example for routing: SCL-MAD-FRA

Option 1 - Input: BSR/LA507/10DEC/SCLFRA
Report on Legs: SCL, MAD
Report on Segments: SCL-MAD, SCL-FRA, MAD-FRA

Option 2 - Input: BSR/LA507/10DEC/MADFRA
Report on Leg: MAD
Report on Segment: MAD-FRA

Option 3 - Input: BSR/LA507/10DEC/SCLMAD
Report on Leg: SCL
Report on Segment: SCL-MAD

Option 4 - Input: BSR/LA507/10DEC
Report on Legs: SCL, MAD
Report on Segments: SCL-MAD, SCL-FRA, MAD-FRA

BSR Report is available in Native Sabre and Trip_ReportsRQ up to 48 hours after the departure.

Note: this report requires a dedicated activation.

4.4.1 Native Sabre

The Native Sabre format to generate BSR Report:

Report Type	Format Example
BSR	**RK/LL/BSR/(AirlineCode)(FlightNumber)/(Date)/{BoardPoint}{OffPoint}** RK/LL/BSR/LA123/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Board Point, Off Point

Input sample: `RK/LL/BSR/LA704/20DEC/SCLFRA`

Output sample:

```
         123456789111111111122222222223333333333444444444455555555556666666666677777777
                  012345678901234567890123456789012345678901234567890123456789012345678901234567
A        LA704 MO20DEC SCLFRA 26 RAF*330 JDI(UR)/YBHKMLVSNQOX(GTE)
B        340/CT2324
C        TIME C LEG AV OPN MAX CAP T/B GRS IBK TTK ITK  B1  LIM NL IND
              J/DIUR
         2030 J SCL AS  11  44       1       1       0        2  1
             /D     AS  10  42       3       3       2       42  2
             /I     CC -29   0      29      29      19        0  3
             /U     CC -29   0       0       0       0        0  4
             /R     CC -29   0       0       0       0        0  5
               CT       11  44  42  33   0  33  21  21
         1515 J1MAD AS  32  40       0       0       0        3  1
             /D     AS  29  37       1       1       0        1  2
             /I     AS  29  36       7       7       3       20  3
             /U     AS  16  16       0       0       0        0  4
             /R     AS  16  16       0       0       0       16  5
               CT       32  40  42   8   0   8   3   3
              Y/BHKMLVSNQOGTXE
         2030 Y SCL AS  12 227       0       0       0        5  1
             /B     AS   7 222       0       0       0        5  2
             /H     CR   2 217       3       3       2        5  3
             /K     CR   0 212       0       0       0       15  4
         SEG SCLMAD
         SEG    CLS  BKD  GRS  IBK  TTK  ITK  LSV  LSS  NL  SMT  GNM  IND
         SCLMAD J      1    0    1    0    0    -    -   -   12    -    -
                D      2    0    2    2    2    -    -   -   12    -    -
                I     22    0   22   16   16    -    -   -   12    -    -
                U      0    0    0    0    0    -    -   -   12    -    -
```

```
        R      0    0    0    0    0    -    -    -   12    -    -
        Y      0    0    0    0    0    -    -    -   12    -    -
        B      0    0    0    0    0    -    -    -   12    -    -
        H      2    0    2    1    1    -    -    -   12    -    -
        K      0    0    0    0    0    -    -    -   12    -    -
        M      5    0    5    3    3    -    -    -   12    -    -
        L      1    0    1    1    1    -    -    -   12    -    -
        V     35    1   34   28   28    -    -    -   12    -    -
        S     15    0   15   13   13    -    -    -   12    -    -
        N     40    2   38   40   38    -    -    -   12    -    -
        Q     51    1   50   50   49    -    -    -   12    -    -
        O     26   15   11   25   10    -    -    -   12    -    -
        G      0    0    0    0    0    -    -    -   12    -    -
        T      1    0    1    1    1    -    -    -   12    -    -
        X      0    0    0    0    0    -    -    -   12    -    -
        E      0    0    0    0    0    -    -    -   12    -    -
SCLMAD *TTL 201   19  182  180  162
SEG SCLFRA TIV =
SCLFRA J      0    0    0    0    0    -    -    -   12    -    -
        D      1    0    1    0    0    -    -    -   12    -    -
        I      7    0    7    3    3    -    -    -   12    -    -
        U      0    0    0    0    0    -    -    -   12    -    -
```

Col.#/ Range	Element	Definition
A1-2	LA	Carrier
A3-5	704	Flight number
A7-8	MO	Day of Week MO = Monday TU = Tuesday WE = Wednesday TH = Thursday FR = Friday SA = Saturday SU = Sunday
A9-13	20DEC	Date of flight
A15-20	SCLFRA	City Pair
A22-23	16	Days prior to departure (from date of request)
A25-31	RAF*330	RAF*330: the pre reservation seat is activated and 330 are the days before departure day - Asterisk indicates PRS activated, no asterisk PRS not activated.
A33-52	JDI(UR)/YBH KMLVSNQO X(GTE)	JDI: Are the RBD if there are between () are the Hidden RBD like (UR) – Not sent by SSM, only OneWorld and LAN or special agreements with other carriers such as AM (AM have frequent flyer program) and possibly TAM can see hidden RBD – See connectivity and alliance data collector. / indicator used to divide cabins.
B1-10	340/CT2324	763/CT2585 type of aircraft and table of configuration
C1-4	TIME	Column header Time of departure of the leg
C6	C	Class each leg is repeated for each base clas

Col.#/ Range	Element	Definition
C8-10	LEG	Origin of the leg
C12-13	AV	Availability Status AS = Flight opened or reopened CR = flight segment closed, request space CL = flight closed but waitlist open CC = flight closed, waitlist closed CN = flight cancelled (NOOP)
C15-17	OPN	Number of seats available for sale including overbook amount OPN = AU-bookings
C19-21	MAX	aircraft capacity plus overbook amount, ie, 300 seats capacity would show 310 (Physical capacity + overbooking = AU)
C23-25	CAP	aircraft capacity for the cabin
C27-29	T/B	booking passenger (local and transit booking) Total seats already booked by class by leg (local and transit bookings). This total includes individual psgrs, Codeshare psgrs, corporate psgrs, BSG psgrs – all confirmed passengers
C31-33	GRS	Corporate PNR psgr count, even if the C/ PNR is less than 10 passengers
C35-37	IBK	Total seats already booked by class of this leg for individual passengers. (BSG PNRs are included, /C PNRs are not) IBK = T/B – GRS
C39-41	TTK	Total nbr of psgrs with tickets, including BSG, /C, and codeshare
C43-45	ITK	Total nbr of Individual passenger with ticket, (BSG is included, /C is not)
C48-49	B1	Capacity restriction by leg On the 1845 SCL Y leg, there is a capacity restriction of 4 seats
C52-54	LIM	limit of seat Resiber calculates to know how many seats to protect by class LIM = AU of the class – AU of the next lower class LIM is calculated following the nesting order from the highest to the lowest class Example: <table><tr><td></td><td>AU</td><td>LIM</td><td>LIM</td></tr><tr><td>J</td><td>30</td><td>(30-26)</td><td>4</td></tr><tr><td>D</td><td>26</td><td>(26-22)</td><td>4</td></tr><tr><td>I</td><td>22</td><td>(22-13)</td><td>9</td></tr><tr><td>U</td><td>13</td><td>(13-3)</td><td>10</td></tr><tr><td>R</td><td>IND</td><td>(3-0)</td><td>3</td></tr></table>
C56-57	NL	order of nesting by leg
C59-61	IND	A = flight affected by an ad hoc schedule change E = PFS was generated. Flight in route. The flight is closed for sale and check-in L = Emergency locked or FIT N = This leg accepts night fares R = PNL was generated X = cancelled leg or flight

Sabre Inc. Confidential / All Rights Reserved

4.4.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS. Departure and Arrival Airport are optional.

Sample:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>BSR</ReportName>                                        MANDATORY
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                         MANDATORY
                     <FlightNumber>125</FlightNumber>                      MANDATORY
                     <DepatureAirport>SCL</DepartureAirport>               OPTIONAL
                     <ArrivalAirport>LIM</ArrivalAirport>                  OPTIONAL
                     <DepartureDateTime>2017-12-14</DepartureDateTime>     MANDATORY
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for BSR Report contains:

- Report Name
- Header which presents indicated flight details, including:
  - Legs / Classes, e.g.:
    `<LegsClasses>JCDIZU/YBHKMLVXSNQOGTAE</LegsClasses>`
  - Aircraft Type, e.g.:
    `<AircraftType>B88</AircraftType>`
- Flight details including ticketing information.

4.4.3 Use Case – Native Sabre and Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, generate the BSR inventory report for LA flight number 750, departing on 24-JAN-2018.

Native Sabre

Input: `RK/LL/BSR/LA750/24JAN/SCLGRU`
Output:

```
LA750  WE24JAN SCLGRU 9   RAF     JCDIZU/YBHKMLVXSNQOG-
CD2/
TIME C LEG AV OPN MAX CAP T/B GRS IBK TTK ITK  B1  LIM NL IND
     C SCL  -  55  59       0   0    0  0   0       0  2   -
     D SCL  -  55  59       0   0    0  0   0       0  3   -
     I SCL  -  55  59       3   0    3  3   3       3  4   -
     Z SCL  -  55  56       0   0    0  0   0     -244  5   -
     U SCL  -  55 300       1   0    1  1   1     300  6   -
      CT       55  60  30   5   0
TIME C LEG AV OPN MAX CAP T/B GRS IBK TTK ITK  B1  LIM NL IND
     B SCL  - 179 300       6   0    6  9   9       6  2   -
```

```
     H SCL  - 179 294       0   0    0  0   0       0  3   -
     K SCL  - 179 294       0   0    0  0   0       0  4   -
     M SCL  - 179 294       0   0    0  0   0       0  5   -
     L SCL  - 179 294       0   0    0  0   0       0  6   -
     V SCL  - 179 294       2   0    2  2   2       7  7   -
     X SCL  - 174 287       9   0    9  7   7      73  8   -
     S SCL  - 110 214      10   0   10 10  10       0  9   -
     N SCL  - 110 214       0   0    0  0   0      15 10   -‡
MD«
     Q SCL  - 105 199      15   0   15 13  13      46 11   -   ‡
     O SCL  -  74 153      46   0   46 42  42       0 12   -
     G SCL  -  74 153       0   0    0  0   0     -147 13   -
     T SCL  -  74 300      17   0   17 15  15     180 14   -
     A SCL  -  74 120      16   0   16 16  16       0 15   -
     E SCL  -  74 120       0   0    0  0   0     120 16   -
      CT      179 300 274 121   0
SEG    CLS  BKD  GRS  IBK  TTK  ITK  LSV  LSS  NL  SMT GNM IND
SCLGRU   J    1    0    1    1    1    -    -   -    -   0   -
         C    0    0    0    0    0    -    -   -    -   0   -
         D    0    0    0    0    0    -    -   -    -   0   -
         I    3    0    3    3    3    -    -   -    -   0   -
         Z    0    0    0    0    0    -    -   -    -   0   -
         U    1    0    1    1    1    -    -   -    -   0   -
         Y    0    0    0    0    0    -    -   -    -   0   -
         B    6    0    6    9    9    -    -   -    -   0   -
         H    0    0    0    0    0    -    -   -    -   0   -
         K    0    0    0    0    0    -    -   -    -   0   -
         M    0    0    0    0    0    -    -   -    -   0   - ‡
MD«
         L    0    0    0    0    0    -    -   -    -   0   - ‡
         V    2    0    2    2    2    -    -   -    -   0   -
         X    9    0    9    7    7    -    -   -    -   0   -
         S   10    0   10   10   10    -    -   -    -   0   -
         N    0    0    0    0    0    -    -   -    -   0   -
         Q   15    0   15   13   13    -    -   -    -   0   -
         O   46    0   46   42   42    -    -   -    -   0   -
         G    0    0    0    0    0    -    -   -    -   0   -
         T   17    0   17   15   15    -    -   -    -   0   -
         A   16    0   16   16   16    -    -   -    -   0   -
         E    0    0    0    0    0    -    -   -    -   0   -
         *  126    0  126  119  119                        0
```

Trip_ReportsRQ

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>BSR</ReportName>
<Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>750</FlightNumber>
              <DepartureAirport>SCL</DepartureAirport>
              <ArrivalAirport>GRU</ArrivalAirport>
              <DepartureDateTime>2018-01-24</DepartureDateTime>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
</Criteria></Report>
</Trip_ReportsRQ>
```

Response:


```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>BSR</ReportName>
<ReportResult>
       <Header>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>750</FlightNumber>
              <DepartureDateTime>2018-01-24T00:00:00</DepartureDateTime>
              <DepartureDayOfWeek>WED</DepartureDayOfWeek>
              <DepartureAirport>SCL</DepartureAirport>
              <ArrivalAirport>GRU</ArrivalAirport>
              <DaysPriorToDeparture>9</DaysPriorToDeparture>
              <LegsClasses>JCDIZU/YBHKMLVXSNQOGTAE</LegsClasses>
              <AircraftType>CD2</AircraftType>
       </Header>
       <Details>
              <Entry>
                     <EntryHeader>
                            <ClassOfService>J</ClassOfService>
                            <EntryType>LEG</EntryType>
                            <DepartureLegTime>2018-01-24T08:30:00</DepartureLegTime>
                     </EntryHeader>
                     <FlightEntry>
                            <DepartureLegTime>0830</DepartureLegTime>
                            <ClassOfLeg>J</ClassOfLeg>
                            <LegOrigin>SCL</LegOrigin>
                            <AvailabilityStatus>-</AvailabilityStatus>
                            <AvailableSeats>55</AvailableSeats>
                            <AircraftCapacityAU>60</AircraftCapacityAU>
                            <TotalSeatsBooked>1</TotalSeatsBooked>
                            <CorporatePnrs>0</CorporatePnrs>
                            <LimitOfSeats>1</LimitOfSeats>
                            <OrderOfLegs>1</OrderOfLegs>
                            <FlightIndicator>-</FlightIndicator>
       <TotalSeatsForIndividualWithBSGIncl>1</TotalSeatsForIndividualWithBSGIncl>
                            <TotalTicketsBsgCIncl>1</TotalTicketsBsgCIncl>
                            <TotalTicketsBsgIncl>1</TotalTicketsBsgIncl>
                            <EntryType>BASE</EntryType>
                     </FlightEntry>
                     [...]
              </Entry>
              <Entry>
                     <EntryHeader>
                            <DepartureAirport>SCL</DepartureAirport>
                            <ArrivalAirport>GRU</ArrivalAirport>
                     </EntryHeader>
                     <ShareEntry>
                            <ClassOfService>J</ClassOfService>
                            <CorporatePnrCount>0</CorporatePnrCount>
                            <BsgPnrs>0</BsgPnrs>
                            <WaitList>0</WaitList>
                            <TotalBookedSeats>1</TotalBookedSeats>
                            <LimitSalesAmount>-</LimitSalesAmount>
                            <LimitSaleSold>-</LimitSaleSold>
                            <OrderOfLegs>-</OrderOfLegs>
                            <AvsTable>-</AvsTable>
                            <NumberOfGivenNames>0</NumberOfGivenNames>
                            <CodeShareIndicator>-</CodeShareIndicator>
       <TotalSeatsForIndividualWithBSGIncl>1</TotalSeatsForIndividualWithBSGIncl>
                            <TotalTicketsBsgCIncl>1</TotalTicketsBsgCIncl>
```

```
                            <TotalTicketsBsgIncl>1</TotalTicketsBsgIncl>
                        </ShareEntry>
                        [...]
                    </Entry>
            </Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```

4.5. BST – Flight Summary Report

The BST Report presents limited inventory data and ticketing information by city. It displays data for all segments, all legs.

BST Report is available in Native Sabre and Trip_ReportsRQ up to 48 hours after the departure.

Note: this report requires a dedicated activation.

4.5.1 Native Sabre

The Native Sabre format to generate BST Report:

Report Type	Format Example
BST	**RK/LL/BST/(AirlineCode)(FlightNumber)/(Date)** RK/LL/BST/LA123/20JAN/ **Note:** Required – Airline Code, Flight Number, Date There are no Optional parameters for BST Report.

Input sample: `RK/LL/BST/LA704/02OCT`

Output sample:

```
    1234567891111111111222222222233333333334444444444555555555566666666667777777777
            0123456789012345678901234567890123456789012345678901234567890123456789012345678901234567
A   LA704 SA02OCT SCLFRA 16 RAF*330 JDI(UR)/YBHKMLVSNQOX(GTE)
B   340/CT2324
C   LEG OPN MAX CAP T/B W/L GRS BLK IBK TTK ITK IND
D   SCL 15  264 260 249 0   0   21  228 224 224
E   MAD 105 287 260 182 0   10  34  138 157 157
```

Col.#/ Range	Element	Definition
A1-2	LA	Carrier
A3-5	704	Flight number

A7-8	SA	Day of Week MO = Monday TU = Tuesday WE = Wednesday TH = Thursday FR = Friday SA = Saturday SU = Sunday
A9-13	02OCT	Date of flight
A15-20	SCLFRA	City Pair
A22-23	16	Days prior to departure (from date of request)
A25-31	RAF*330	RAF*330: the pre-reservation seat is activated and 330 are the days before departure day - Asterisk indicates PRS activated, no asterisk PRS not activated.
A33-57	JDI(UR)/YBHKMLVSNQOX(GTE)	JDI: Are the RBD if there are between () are the Hidden RBD like (UR) – Not sent by SSM, only OneWorld and LAN or special agreements with other carriers such as AM (AM have frequent flyer program) and possibly TAM can see hidden RBD – See connectivity and alliance data collector. / indicator used to divide cabins. (GTE) hidden Y compartment classes
B1-10	340/CT2324	763/CT2585 type of aircraft and table of configuration
C1-3	LEG	Specific leg being reported
C5-7	OPN	Number of seats available for sale including overbook amount OPN = AU-bookings
C9-11	MAX	Aircraft capacity plus overbook amount, ie, 300 seats capacity would show 310 Physical capacity + overbooking = AU)
C13-15	CAP	aircraft capacity for the cabin
C17-19	T/B	booking passenger (local and transit booking) Total seats already booked by class by leg (local and transit bookings). This total includes individual psgrs, Codeshare psgrs, corporate psgrs, BSG psgrs – all confirmed passengers
C21-23	W/L	Number of waitlisted passengers
C25-27	GRS	Corporate PNR psgr count, even if the C/ PNR is less than 10 passengers
C29-31	BLK	BSG psgrs
C33-35	IBK	Total seats already booked by class of this leg for individual passengers. (BSG PNRs are included, /C PNRs are not) IBK = T/B – GRS
C37-39	TTK	Total nbr of psgrs with tickets, including BSG, /C, and codeshare
C41-43	ITK	Total nbr of Individual passenger with ticket, (BSG is included, /C is not)
C45-47	IND	A = flight affected by an ad hoc schedule change E = PFS was generated. Flight in route. The flight is closed for sale and check-in L = Emergency locked or FIT N = This leg accepts night fares R = PNL was generated X = cancelled leg or flight

Sabre Inc. Confidential / All Rights Reserved

4.5.2 Trip_ReportsRQ

Trip_ReportsRQ for this report requires provisioning of some qualifiers and all of them are mandatory.

Sample request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>BST</ReportName>                                        MANDATORY
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                         MANDATORY
                     <FlightNumber>125</FlightNumber>                      MANDATORY
                     <DepartureDateTime>2017-12-14</DepartureDateTime>     MANDATORY
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for BST Report contains:

- Report Name
- Header which presents indicated flight details, including:
  - Legs / Classes, e.g.:
    `<LegsClasses>JCDIZU/YBHKMLVXSNQOGTAE</LegsClasses>`
  - Aircraft Type, e.g.:
    `<AircraftType>B88</AircraftType>`
- Flight details

4.5.3 Use Case – Native Sabre and Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier, generate the BST inventory report for LA flight number 750, departing on 24-JAN-2018.

Native Sabre

Input: `RK/LL/BST/LA750/24JAN`
Output:

```
LA750  WE24JAN SCLGRU 9   RAF     JCDIZU/YBHKMLVXSNQOG-
CD2/
LEG OPN MAX CAP T/B W/L GRS BLK IBK TTK ITK IND
SCL 234 360 304 126   0   0   0 126 119 119   -
```

Trip_ReportsRQ

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>BST</ReportName>
<Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>750</FlightNumber>
              <DepartureDateTime>2018-01-24</DepartureDateTime>
```

```
        </FlightCriteria>
        <PosCriteria>LA</PosCriteria>
</Criteria>
</Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>BST</ReportName>
<ReportResult>
        <Header>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>750</FlightNumber>
                <DepartureDateTime>2018-01-24T00:00:00</DepartureDateTime>
                <DepartureDayOfWeek>WED</DepartureDayOfWeek>
                <DepartureAirport>SCL</DepartureAirport>
                <ArrivalAirport>GRU</ArrivalAirport>
                <DaysPriorToDeparture>9</DaysPriorToDeparture>
                <LegsClasses>JCDIZU/YBHKMLVXSNQOGTAE</LegsClasses>
                <AircraftType>CD2</AircraftType>
        </Header>
        <Details>
                <Entry>
                        <FlightEntry>
                                <LegOrigin>SCL</LegOrigin>
                                <AvailableSeats>234</AvailableSeats>
                                <AircraftCapacityAU>360</AircraftCapacityAU>
                                <CabinCapacity>304</CabinCapacity>
                                <TotalSeatsBooked>126</TotalSeatsBooked>
                                <WaitListed>0</WaitListed>
                                <CorporatePnrs>0</CorporatePnrs>
                                <BsgPnrs>0</BsgPnrs>
                                <FlightIndicator>-</FlightIndicator>
        <TotalSeatsForIndividualWithBSGIncl>126</TotalSeatsForIndividualWithBSGIncl>
                                <TotalTicketsBsgCIncl>119</TotalTicketsBsgCIncl>
                                <TotalTicketsBsgIncl>119</TotalTicketsBsgIncl>
                                <EntryType>NORMAL</EntryType>
                        </FlightEntry>
                </Entry>
        </Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```

Group/Corporate Name PNR Lists

5

5.1. General Information

Group/Corporate Name PNR Lists gather and provide lists of PNRs for large parties, groups, corporate names and BSG PNRs. Reports present not only passenger name and PNR record locator but also flight information.

All Group/Corporate Name Reports are available in Native Sabre and with use of Trip_ReportsRQ.

The next sections of this chapter describe the functionality of each Inventory Report in details.

5.2. MLE – Block Space Group (BSG)

The MLE Report presents list of block space passengers on the requested flight and date.

5.2.1 Native Sabre

The Native Sabre format to generate MLE Report is as follows:

Report Type	Format Example
MLE	**RK/MLE/(AirlineCode)(FlightNumber)/(Date)/{BoardPoint}{OffPoint}** RK/MLE/LA123/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Board Point, Off Point

Input Sample: `RK/MLE/LA704/13AUG`
Output Sample:

```
   123456789111111111122222222223333333333444444444455555555556666 6
            0123456789012345678901234567890123456789012345678901234
A  MULTI
B  LA704 /13AUG          B
C  SCLMAD    13AUG
D  NIL
E  SCLFRA    13AUG
F  NIL
G  MADFRA    14AUG
H  001B 30CCM                    HF2EQI V HK30 SCL12        05APR10
I  002H  1CEBRIANCANTOS/FRANCIS+ JPE6XI V HK6  MADI1        29JUL10
J  003H  1DELPOZOSERRANO/JOSE L+ HP54BI V HK6  MADI1        29JUL10
K  004H  1GARCIAGARCIA/RICARDOJ+ C9VCLK V HK4  MADI1        04AUG10
```

Col.#/ Range	Element	Definition
A1-5	MULTI	
B1-2	LA	Carrier code
B3-6	704	Flight number
B7	/	Delimiter
B8-12	13AUG	Date of flight
B23	B	Display type – B for BSG
C1-6	SCLMAD	SCLMAD Segment data follows
C11-15	13AUG	Date of flight departure for this leg
D1-3	NIL	No data
E1-6	SCLFRA	SCLFRA Segment data follows
E11-15	13AUG	Date of flight departure for this leg
F1-3	NIL	No data
G1-6	MADFRA	MADFRA Segment data follows
G11-15	14AUG	Date of flight departure for this leg
H1-3	001	Line number
H4	B	PNR type indicator B = BSG Master PNR H = BSG Child PNR
H6-7	30	Number in party - the number of passengers with this last name, or number of passengers in the group, e.g., 30 passengers in the CCM group, 1 passenger with last name of CEBRIANCANTOS
H8-29	CCM	BSG Group name + indicates that there are more than 21 characters in the name
H31-36	HF2EQI	PNR record locator
H38	V	Booking class
H40-41	HK	Status code
H42-43	30	Number of passengers in PNR
H45-56	SCLLA0986	ID of office that created the PNR - Maximum of 12 characters.
H58-64	05APR10	Date of last modification to the PNR
Rows I, J, K		Data for child PNRs

5.2.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS. Departure and Arrival Airport are optional.

ReportFormat is an optional element. If you decide to use it, enter E as presented below:

<ReportFormat>E</ReportFormat>

Sample request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>MLE</ReportName>                                          MANDATORY
       <ReportFormat>E</ReportFormat>                                        OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                           MANDATORY
                     <FlightNumber>125</FlightNumber>                        MANDATORY
                     <DepatureAirport>SCL</DepartureAirport>                 OPTIONAL
                     <ArrivalAirport>LIM</ArrivalAirport>                    OPTIONAL
                     <DepartureDateTime>2017-12-14</DepartureDateTime>       MANDATORY
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                  MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLE Report contains:

- Report Name
- Header which presents indicated flight details
- Group PNR details

5.2.3 Use Case – Native Sabre and Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier. Generate the MLE report for LA flight number 530, departing on 30-MAY-2018.

Below you will find the use case presented in Native Sabre and with use of Trip_ReportsRQ.

Native Sabre

Input: `RK/MLE/LA530/30MAY/LIMJFK`

Output:

```
MULTI
LA530  /30MAY       B
LIMJFK
001B  0HOLIDAYS              KDYCFX Y HK11 HDQAP7599369 27DEC17
002H  4BOND/JAMES/LILY/HARR. ZSMWFL Y HK4  HDQAP7599369 27DEC17
003H  7TTER/A/B/C/D/E/F/G    ZSMGHO Y HK7  HDQAP7599369 27DEC17
```

Trip_ReportsRQ

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLE</ReportName>
<ReportFormat>E</ReportFormat>
<Criteria>
```

```
        <FlightCriteria>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>530</FlightNumber>
                <DepartureAirport>LIM</DepartureAirport>
                <ArrivalAirport>JFK</ArrivalAirport>
                <DepartureDateTime>2018-05-30</DepartureDateTime>
        </FlightCriteria>
        <PosCriteria>LA</PosCriteria>
</Criteria>
</Report>
</Trip_ReportsRQ>
```


Response:


```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>MLE</ReportName>
<ReportFormat>E</ReportFormat>
<ReportResult>
        <Header>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>530</FlightNumber>
                <DepartureDateTime>2018-05-30T00:16:00</DepartureDateTime>
                <DepartureDayOfWeek>WED</DepartureDayOfWeek>
                <DisplayType>B</DisplayType>
                <DepartureAirport>LIM</DepartureAirport>
                <ArrivalAirport>JFK</ArrivalAirport>
        </Header>
        <Details>
                <Entry>
                        <EntryHeader>
                                <DepartureAirport>LIM</DepartureAirport>
                                <ArrivalAirport>JFK</ArrivalAirport>
                                <EntryType>SEGMENT</EntryType>
                                <DepartureLegTime>2018-05-30T00:00:00</DepartureLegTime>
                        </EntryHeader>
                        <GroupEntry sequenceId="1">
                                <PnrIndicatorType>B</PnrIndicatorType>
                                <NumberInParty>0</NumberInParty>
                                <Name>HOLIDAYS</Name>
                                <Locator>KDYCFX</Locator>
                                <ClassOfService>Y</ClassOfService>
                                <StatusCode>HK</StatusCode>
                                <NumberOfPassengers>11</NumberOfPassengers>
                                <AgentId>HDQAP7599369</AgentId>
                                <UpdateDateTime>2017-12-27T06:16:57</UpdateDateTime>
                        </GroupEntry>
                        <GroupEntry>
                                <PnrIndicatorType>H</PnrIndicatorType>
                                <NumberInParty>4</NumberInParty>
                                <Name>BOND/JAMES/LILY/HARRY/KATE</Name>
                                <Locator>ZSMWFL</Locator>
                                <ClassOfService>Y</ClassOfService>
                                <StatusCode>HK</StatusCode>
                                <NumberOfPassengers>4</NumberOfPassengers>
                                <AgentId>HDQAP7599369</AgentId>
                                <UpdateDateTime>2017-12-27T08:08:44</UpdateDateTime>
                        </GroupEntry>
                        <GroupEntry>
                                <PnrIndicatorType>H</PnrIndicatorType>
```

```
                            <NumberInParty>7</NumberInParty>
                            <Name>TTER/A/B/C/D/E/F/G</Name>
                            <Locator>ZSMGHO</Locator>
                            <ClassOfService>Y</ClassOfService>
                            <StatusCode>HK</StatusCode>
                            <NumberOfPassengers>7</NumberOfPassengers>
                            <AgentId>HDQAP7599369</AgentId>
                            <UpdateDateTime>2017-12-27T08:21:06</UpdateDateTime>
                        </GroupEntry>
                    </Entry>
            </Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```


5.3. MLD – /C (corporate name) Group PNRs and the individuals in these PNRs

The MLD Report presents list of /C (corporate name) PNRs and the individuals in these PNRs for the requested flight and date.

5.3.1 Native Sabre

The Native Sabre format to generate MLD Report is as follows:

Report Type	Format Example
MLD	**RK/MLD/(AirlineCode)(FlightNumber)/(Date)/{BoardPoint}{OffPoint}** RK/MLD/LA123/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Board Point, Off Point

Input Sample: `RK/MLD/LA704/25DEC`

Output Sample:

```
   123456789111111111122222222223333333333444444444455555555556666666
            012345678901234567890123456789012345678901234567890123456789012345
A  MULTI
B  LA704 /25DEC          C
C  SCLMAD    13AUG
D  001C  0GRUPOSKY               KBVG31 V HK1  SCLLA        22NOV10
E  002N  1GUTIERREZ/JOSE         KBVG31 V HK1  SCLLA        23NOV10
F  003N  1DUBOULOZBEL/PATRICIA   KLM9M1 N HK1  PARLA        15NOV10
G  004N  1GENILLARD/CHRISTOPHER+ KLMM01 N HK1  PARLA        15NOV10
H  005C  0HVS/GRP/INTLCL/ANTART+ KLM9M1 N HK1  PARLA        15NOV10
I
```

```
J  006C  0HVS/GRP/INTLCL/ANTART+ KLMM01 N HK1  PARLA        15NOV10
K  007N  1HILLE/LUCAS            HKSS31 Q HK1  FRALA        10NOV10
L  008C  0SKYLINKTRAVEL/CHRISTM+ HKSS31 Q HK1  FRALA        10NOV10
M  009N  2GUIN/RAPHAELLEMARCELL+ JY9G71 O HK10 SCLLA        14OCT10
N  010N  1HIRSCH/PATRICIA        JY9G71 O HK10 SCLLA        14OCT10
O  011N  1HITCE/BRIGITTEM        JY9G71 O HK10 SCLLA        14OCT10
   012C  0HVS/GRP/INTLCL/ANTART+ KLMJW1 O HK1  SCLLA        13NOV10
```

Col.#/ Range	Element	Definition
A1-5	MULTI	
B1-2	LA	Carrier code
B3-6	704	Flight number
B7	/	Delimiter
B8-12	13AUG	Date of flight
B23	C	Display type – C for Corporate
C1-6	SCLMAD	SCLMAD Segment data follows
C11-15	13AUG	Date of flight departure for this leg
D1-3	001	Line number
D4	C	PNR type indicator C = Corporate Name PNR N = Individual passenger in the Corporate Name PNR
D6-7	0	Number in party - the number of passengers with this last name, or number of names missing in the Corporate name (0 indicates that all names have been provided
D8-29	GRUPOSKY	BSG Group name - maximum of 21 characters
D31-36	KBVG31	PNR record locator
D38	V	Booking class
D40-41	HK	Status code
D42-43	1	Number of passengers in PNR
D45-56	SCLLA	ID of office that created the PNR - Maximum of 12 characters
D58-64	22NOV10	Date of last modification to the PNR

5.3.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS. Departure and Arrival Airport are optional.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter D as presented below:

<ReportFormat>D</ReportFormat>

Sample request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>MLD</ReportName>                                          MANDATORY
       <ReportFormat>D</ReportFormat>                                        OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                           MANDATORY
                     <FlightNumber>125</FlightNumber>                        MANDATORY
                     <DepatureAirport>SCL</DepartureAirport>                 OPTIONAL
                     <ArrivalAirport>LIM</ArrivalAirport>                    OPTIONAL
                     <DepartureDateTime>2017-12-14</DepartureDateTime>       MANDATORY
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                  MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLD Report contains:

- Report Name
- Header which presents indicated flight details
- Group PNR details including passenger names

5.3.3 Use Case – Native Sabre and Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier. Generate the MLD report for JJ flight number 9625, departing on 01-FEB-2018.

Below you will find the use case presented in Native Sabre and with use of Trip_ReportsRQ.

Native Sabre

Input: `RK/MLD/JJ9625/01FEB/MCOGIG`

Output:

```
MULTI
JJ9625 /01FEB       C
MCOGIG
001C  0FIVE STAR             ABCABC Y HK11              15JAN18
002N  1BASTOS/ADAM           ABCABC Y HK11              15JAN18
003N  1SICONHA/MARY          ABCABC Y HK11              15JAN18
004N  1CARVALHO/ALOISIA      ABCABC Y HK11              15JAN18
005N  1SAVA/CLARA            ABCABC Y HK11              15JAN18
006N  1SAVA/EDUARDA          ABCABC Y HK11              15JAN18
007N  1AZELINO/NANCY         ABCABC Y HK11              15JAN18
008N  1MARRIO/FERNANDA       ABCABC Y HK11              15JAN18
009N  1GONZALEZ/MARI         ABCABC Y HK11              15JAN18
010N  1SMITH/JOAO            ABCABC Y HK11              15JAN18
011N  1SAM/GIOVANNA          ABCABC Y HK11              15JAN18
012N  1GAZZINI/MANUELA       ABCABC Y HK11              15JAN18
```

Trip_ReportsRQ

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLD</ReportName>
<ReportFormat>D</ReportFormat>
<Criteria>
       <FlightCriteria>
              <AirlineCode>JJ</AirlineCode>
              <FlightNumber>9625</FlightNumber>
              <DepartureAirport>MCO</DepartureAirport>
              <ArrivalAirport>GIG</ArrivalAirport>
              <DepartureDateTime>2018-02-01</DepartureDateTime>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
</Criteria></Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>MLD</ReportName>
<ReportFormat>D</ReportFormat>
<ReportResult>
       <Header>
              <AirlineCode>JJ</AirlineCode>
              <FlightNumber>9625</FlightNumber>
              <DepartureDateTime>2018-02-01T21:10:00</DepartureDateTime>
              <DepartureDayOfWeek>THU</DepartureDayOfWeek>
              <DisplayType>C</DisplayType>
              <DepartureAirport>MCO</DepartureAirport>
              <ArrivalAirport>GIG</ArrivalAirport>
       </Header>
       <Details>
              <Entry>
                     <EntryHeader>
                            <DepartureAirport>MCO</DepartureAirport>
                            <ArrivalAirport>GIG</ArrivalAirport>
                            <EntryType>SEGMENT</EntryType>
                            <DepartureLegTime>2018-02-01T00:00:00</DepartureLegTime>
                     </EntryHeader>
                     <GroupEntry sequenceId="1">
                            <PnrIndicatorType>C</PnrIndicatorType>
                            <NumberInParty>0</NumberInParty>
                            <Name>FIVE STAR</Name>
                            <Locator>ABCABC</Locator>
                            <ClassOfService>Y</ClassOfService>
                            <StatusCode>HK</StatusCode>
                            <NumberOfPassengers>11</NumberOfPassengers>
                            <AgentId/>
                            <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
                     </GroupEntry>
                     <GroupEntry sequenceId="2">
                            <PnrIndicatorType>N</PnrIndicatorType>
                            <NumberInParty>1</NumberInParty>
                            <Name>BASTOS/ADAM</Name>
                            <Locator>ABCABC</Locator>
```

```
            <ClassOfService>Y</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>11</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
        </GroupEntry>
        <GroupEntry sequenceId="3">
            <PnrIndicatorType>N</PnrIndicatorType>
            <NumberInParty>1</NumberInParty>
            <Name>SICONHA/MARY</Name>
            <Locator>ABCABC</Locator>
            <ClassOfService>Y</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>11</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
        </GroupEntry>
        <GroupEntry sequenceId="4">
            <PnrIndicatorType>N</PnrIndicatorType>
            <NumberInParty>1</NumberInParty>
            <Name>CARVALHO/ALOISIA</Name>
            <Locator>ABCABC</Locator>
            <ClassOfService>Y</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>11</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
        </GroupEntry>
        <GroupEntry sequenceId="5">
            <PnrIndicatorType>N</PnrIndicatorType>
            <NumberInParty>1</NumberInParty>
            <Name>SAVA/CLARA</Name>
            <Locator>ABCABC</Locator>
            <ClassOfService>Y</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>11</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
        </GroupEntry>
        <GroupEntry sequenceId="6">
            <PnrIndicatorType>N</PnrIndicatorType>
            <NumberInParty>1</NumberInParty>
            <Name>SAVA/EDUARDA</Name>
            <Locator>ABCABC</Locator>
            <ClassOfService>Y</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>11</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
        </GroupEntry>
        <GroupEntry sequenceId="7">
            <PnrIndicatorType>N</PnrIndicatorType>
            <NumberInParty>1</NumberInParty>
            <Name>AZELINO/NANCY</Name>
            <Locator>ABCABC</Locator>
            <ClassOfService>Y</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>11</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
        </GroupEntry>
        <GroupEntry sequenceId="8">
            <PnrIndicatorType>N</PnrIndicatorType>
```

```
                        <NumberInPartyy>1</NumberInParty>
                        <Name>MARRIO/FERNANDA</Name>
                        <Locator>ABCABC</Locator>
                        <ClassOfService>Y</ClassOfService>
                        <StatusCode>HK</StatusCode>
                        <NumberOfPassengers>11</NumberOfPassengers>
                        <AgentId/>
                        <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
                    </GroupEntry>
                    <GroupEntry sequenceId="9">
                        <PnrIndicatorType>N</PnrIndicatorType>
                        <NumberInParty>1</NumberInParty>
                        <Name>GONZALEZ/MARI</Name>
                        <Locator>ABCABC</Locator>
                        <ClassOfService>Y</ClassOfService>
                        <StatusCode>HK</StatusCode>
                        <NumberOfPassengers>11</NumberOfPassengers>
                        <AgentId/>
                        <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
                    </GroupEntry>
                    <GroupEntry sequenceId="10">
                        <PnrIndicatorType>N</PnrIndicatorType>
                        <NumberInParty>1</NumberInParty>
                        <Name>SMITH/JOAO</Name>
                        <Locator>ABCABC</Locator>
                        <ClassOfService>Y</ClassOfService>
                        <StatusCode>HK</StatusCode>
                        <NumberOfPassengers>11</NumberOfPassengers>
                        <AgentId/>
                        <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
                    </GroupEntry>
                    <GroupEntry sequenceId="11">
                        <PnrIndicatorType>N</PnrIndicatorType>
                        <NumberInParty>1</NumberInParty>
                        <Name>SAM/GIOVANNA</Name>
                        <Locator>ABCABC</Locator>
                        <ClassOfService>Y</ClassOfService>
                        <StatusCode>HK</StatusCode>
                        <NumberOfPassengers>11</NumberOfPassengers>
                        <AgentId/>
                        <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
                    </GroupEntry>
                    <GroupEntry sequenceId="12">
                        <PnrIndicatorType>N</PnrIndicatorType>
                        <NumberInParty>1</NumberInParty>
                        <Name>GAZZINI/MANUELA</Name>
                        <Locator>ABCABC</Locator>
                        <ClassOfService>Y</ClassOfService>
                        <StatusCode>HK</StatusCode>
                        <NumberOfPassengers>11</NumberOfPassengers>
                        <AgentId/>
                        <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
                    </GroupEntry>
                </Entry>
        </Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```

5.4. MLG – /C (corporate name) Group PNRs

The MLG Report presents list of /C (corporate name) PNRs for the requested flight and date.

5.4.1 Native Sabre

The Native Sabre format to generate MLG Report is as follows:

Report Type	Format Example
MLG	**RK/MLG/(AirlineCode)(FlightNumber)/(Date)/{BoardPoint}{OffPoint}** RK/MLG/LA123/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Board Point, Off Point

5.4.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS. Departure and Arrival Airport are optional.

ReportFormat is an optional element. If you decide to use it, enter G as presented below:

<ReportFormat>G</ReportFormat>

Sampel request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>MLG</ReportName>                                        MANDATORY
       <ReportFormat>G</ReportFormat>                                      OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                         MANDATORY
                     <FlightNumber>125</FlightNumber>                      MANDATORY
                     <DepatureAirport>SCL</DepartureAirport>               OPTIONAL
                     <ArrivalAirport>LIM</ArrivalAirport>                  OPTIONAL
                     <DepartureDateTime>2017-12-14</DepartureDateTime>     MANDATORY
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                                MANDATORY
       </Criteria>
</Report>
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLG Report contains:

- Report Name

- Header which presents indicated flight details
- Group PNR details

5.4.3 Use Case – Native Sabre and Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier. Generate the MLG report for JJ flight number 9625, departing on 01-FEB-2018.

Below you will find the use case presented in Native Sabre and with use of Trip_ReportsRQ.

Native Sabre

Input: `RK/MLG/JJ9625/01FEB/MCOGIG`

Output:

```
MULTI
JJ9625 /01FEB       C
MCOGIG
001C 11FIVE STAR             MRZZCC Y HK11              15JAN18
```

Trip_ReportsRQ

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLG</ReportName>
<ReportFormat>G</ReportFormat>
<Criteria>
       <FlightCriteria>
              <AirlineCode>JJ</AirlineCode>
              <FlightNumber>9625</FlightNumber>
              <DepartureAirport>MCO</DepartureAirport>
              <ArrivalAirport>GIG</ArrivalAirport>
              <DepartureDateTime>2018-02-01</DepartureDateTime>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
</Criteria></Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes)>
<Success>Success</Success>
<Report>
<ReportName>MLG</ReportName>
<ReportFormat>G</ReportFormat>
<ReportResult>
   <Header>
      <AirlineCode>JJ</AirlineCode>
      <FlightNumber>9625</FlightNumber>
      <DepartureDateTime>2018-02-01T21:10:00</DepartureDateTime>
      <DepartureDayOfWeek>THU</DepartureDayOfWeek>
      <DisplayType>C</DisplayType>
      <DepartureAirport>MCO</DepartureAirport>
```

```
      <ArrivalAirport>GIG</ArrivalAirport>
   </Header>
   <Details>
      <Entry>
         <EntryHeader>
            <DepartureAirport>MCO</DepartureAirport>
            <ArrivalAirport>GIG</ArrivalAirport>
            <EntryType>SEGMENT</EntryType>
         </EntryHeader>
         <GroupEntry sequenceId="1">
            <PnrIndicatorType>C</PnrIndicatorType>
            <NumberInParty>11</NumberInParty>
            <Name>FIVE STAR</Name>
            <Locator>MRZZCC</Locator>
            <ClassOfService>Y</ClassOfService>
            <StatusCode>HK</StatusCode>
            <NumberOfPassengers>11</NumberOfPassengers>
            <AgentId/>
            <UpdateDateTime>2018-01-15T01:02:26</UpdateDateTime>
         </GroupEntry>
      </Entry>
   </Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```

Reaccommodated Passengers

6

6.1. MLR – Passenger Reaccommodation List

The MLR Report presents passenger list of all PNRs that were on a disrupted flight, even if the flight has been cancelled. The MLR report shows also the flight on which the passengers were protected after the reaccommodation process has been completed. The list will also include flights which have undergone a schedule change that did not result in a change of flight, i.e., a time change.

The date used in the input may range between 30 days prior and 330 days after the date the request is made.

You can retrieve the Passenger Reaccommodation List for:

- Any given flight, canceled or active, which displays historical reaccommodation information for all passengers on the flight.
- All passengers that were originally on the requested flight along with the flight to which they were reaccommodated including the carrier code, flight number, date, class of service, departure and arrival cities and status code.
- All passengers that were originally on another flight and reaccommodated to the requested flight, e.g., a request for flight 600/21MAR will include passengers reaccommodated *from* 600/21MAR to another and passengers reaccommodated *to* 600/21MAR from another flight.
- If reaccommodation is from a single flight to a connection, the connection will be included in the display.
- If there is no reaccommodation to a different flight, e.g., equipment change or departure/ arrival time changes only, the list include the flight as both the 'to' and 'from' flight.
- The list for each passenger includes all reaccommodations/flight changes made since the passenger originally booked their flight. This can be referred to as historical reaccomodations.
- If the PNR has been through multiple schedule changes all "FROM" (disrupted flight) and "TO" (protection flight), flights are shown as well. The report will include information from past date PNRs up to 30 days after the last flight in the PNR was flown. E.g.:

  > On 1 June 2017 John Smith booked space on LA600 SCLLIM for travel on 1 January 2018. Flight 600 was subject to schedule changes on 5 June, 10 July, 1 August, 9 September, 19 October, 22 November and 19 December.
  > A request made on 10 June 2017 for flight LA602/1JAN will show Mr. Smith as having been impacted on the 5 June schedule change.
  > A request made on 20 December 2017 for flight 602/1JAN will show Mr. Smith as having been impacted by the 5 June, 10 July, 1 August, 9 September, 19 October, 22 November and 19 December schedule changes.

Sabre Inc. Confidential / All Rights Reserved

6.1.1 Native Sabre

Report Type	Format Example
MLR	**RK/MLR/(AirlineCode)(FlightNumber)/(Date)/{BoardPoint}{OffPoint}** RK/MLR/LA123/20JAN/LIMMIA **Note:** Required – Airline Code, Flight Number, Date Optional – Board Point, Off Point

MLR Report Sample

```
RK/MLR/LA502/21DEC«
MULTI
LA502  /21DEC       B
SCLMIA
001   YKGZOZ/KGEG                                  KRHJTA Y SC1
      LA 502  Y 21DEC   SCLMIA HK -WK/ LA2370  Y 22DEC   SCLLIM
SC 20DEC17/0324
                                       LA2462  Y 22DEC   LIMMIA
SC 20DEC17/0324
```

6.1.2 Trip_ReportsRQ

Trip_ReportsRQ for this report allows defining the search criteria as per user's needs. However, there are four search criteria that must be always included: Airline Code, Flight Number, Departure Date and POS.

The response will vary depending on how many criteria you include in the request.

ReportFormat is an optional element. If you decide to use it, enter R as presented below:

<ReportFormat>R</ReportFormat>

Sample request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
       <ReportName>MLR</ReportName>                                    MANDATORY
       <ReportFormat>R</ReportFormat>                                  OPTIONAL
       <Criteria>
              <FlightCriteria>
                     <AirlineCode>LA</AirlineCode>                     MANDATORY
                     <FlightNumber>639</FlightNumber>                  MANDATORY
                     <DepartureAirport>LIM</DepartureAirport>          OPTIONAL
                     <ArrivalAirport>SCL</ArrivalAirport>              OPTIONAL
                     <DepartureDateTime>2018-01-20</DepartureDateTime> MANDATORY
                     <ClassOfService>J</ClassOfService>                OPTIONAL
              </FlightCriteria>
              <PosCriteria>LA</PosCriteria>                            MANDATORY
       </Criteria>
</Report>
```

```
</Trip_ReportsRQ>
```

The Trip_ReportsRS for MLR Report contains:

- Report Name and Format
- Header which presents indicated flight details
- Details including passenger list, old flight and new flight details.

6.1.3 Use Case Analysis

Please note there are 6 PNRS (AAAAAA, BBBBBB, CCCCCC, DDDDDD, EEEEEE) in each scenario. Each scenario assumes the same PNRs.

Following are original PNRs and segments:

```
PNR         Segments

AAAAAA      LA260  21APR PMC 16:40 - SCL 18:25 HK
            LA600  21APR SCL 20:05 - LIM 22:25 HK
            LA2514 22APR LIM 00:20 - MIA 07:05 HK

BBBBBB      LA260  21APR PMC 16:40 - SCL 18:25 HK
            LA600  21APR SCL 20:05 - LIM 22:25 HK

CCCCCC      LA600  21APR SCL 20:05 - LIM 22:25 HK
            LA2514 22APR LIM 00:20 - MIA 07:05 HK

DDDDDD      LA600  21APR SCL 20:05 - LIM 22:25 HK

EEEEEE      LA500  21APR SCL 20:55 - MIA 05:40 HK
```

Scenario #0: The Passenger Reaccommodation List is compiled on 11APR for flight LA600 21APR. The list shows no PNRs in the list.

===

Reaccommodation 1 – Schedule Change happens on 10APR: Flight LA260 on 21APR is cancelled, PNR AAAAAA and BBBBBB are reaccommodated to the same flight numbers next day.

Following are PNRs and segments after the Reaccommodation 1:

```
PNR         Segments

AAAAAA      LA260  21APR PMC 16:40 - SCL 18:25 WK
            LA600  21APR SCL 20:05 - LIM 22:25 WK
            LA2514 22APR LIM 00:20 - MIA 07:05 WK
            LA260  22APR PMC 16:40 - SCL 18:25 SC
            LA600  22APR SCL 20:05 - LIM 22:25 SC
            LA2514 23APR LIM 00:20 - MIA 07:05 SC

BBBBBB      LA260  21APR PMC 16:40 - SCL 18:25 WK
            LA600  21APR SCL 20:05 - LIM 22:25 WK
            LA260  22APR PMC 16:40 - SCL 18:25 SC
            LA600  22APR SCL 20:05 - LIM 22:25 SC
```

```
CCCCCC      LA600  21APR SCL 20:05 - LIM 22:25 HK
            LA2514 22APR LIM 00:20 - MIA 07:05 HK

DDDDDD      LA600  21APR SCL 20:05 - LIM 22:25 HK

EEEEEE      LA500  21APR SCL 20:55 - MIA 05:40 HK
```

Scenario #1: The Passenger Reaccommodation List is compiled on 11APR for flight LA600 21APR. The list shows the following PNRs: AAAAAA and BBBBBB.

===

Reaccommodation 2 – Schedule Change happens on 12APR (following on previous Schedule Changes as described in preceding scenario): Flight LA2514 on 22APR is cancelled, PNR CCCCCC is reaccommodated to the direct flight on the same day: LA500 21APR SCL 20:55 – MIA 05:40 (i.e. changing original itinerary from 2 segments to 1 segment)

Following are PNRs and segments after the Reaccommodation 2:

```
PNR         Segments

AAAAAA      LA260  21APR PMC 16:40 - SCL 18:25 WK
            LA600  21APR SCL 20:05 - LIM 22:25 WK
            LA2514 22APR LIM 00:20 - MIA 07:05 WK
            LA260  22APR PMC 16:40 - SCL 18:25 SC
            LA600  22APR SCL 20:05 - LIM 22:25 SC
            LA2514 23APR LIM 00:20 - MIA 07:05 SC

BBBBBB      LA260  21APR PMC 16:40 - SCL 18:25 WK
            LA600  21APR SCL 20:05 - LIM 22:25 WK
            LA260  22APR PMC 16:40 - SCL 18:25 SC
            LA600  22APR SCL 20:05 - LIM 22:25 SC

CCCCCC      LA600  21APR SCL 20:05 - LIM 22:25 WK
            LA2514 22APR LIM 00:20 - MIA 07:05 WK
            LA500  21APR SCL 20:55 - MIA 05:40 SC

DDDDDD      LA600  21APR SCL 20:05 - LIM 22:25 HK

EEEEEE      LA500  21APR SCL 20:55 - MIA 05:40 HK
```

Scenario #2: The Passenger Reaccommodation List is compiled on 13APR for flight LA600 21APR. The list shows the following PNRs: AAAAAA, BBBBBB and CCCCCC.

===

Reaccommodation 3 – Schedule Change happens on 16APR (following on previous Schedule Changes as described in preceding scenario): Flight LA500 on 21 APR is cancelled, PNRs CCCCCC and EEEEEE are reaccommodated to flight number LA 600 21APR SCL 20:05 – LIM and LA2510 22APR LIM 12:40 – MIA 19:25

Following are PNRs and segments after the Reaccommodation 3:

```
PNR         Segments

AAAAAA      LA260  21APR PMC 16:40 - SCL 18:25 WK
            LA600  21APR SCL 20:05 - LIM 22:25 WK
```

```
            LA2514 22APR LIM 00:20 - MIA 07:05 WK
            LA260  22APR PMC 16:40 - SCL 18:25 SC
            LA600  22APR SCL 20:05 - LIM 22:25 SC
            LA2514 23APR LIM 00:20 - MIA 07:05 SC

BBBBBB      LA260  21APR PMC 16:40 - SCL 18:25 WK
            LA600  21APR SCL 20:05 - LIM 22:25 WK
            LA260  22APR PMC 16:40 - SCL 18:25 SC
            LA600  22APR SCL 20:05 - LIM 22:25 SC

CCCCCC      LA600  21APR SCL 20:05 - LIM 22:25 WK
            LA2514 22APR LIM 00:20 - MIA 07:05 WK
            LA500  21APR SCL 20:55 - MIA 05:40 WK
            LA600  21APR SCL 20:05 - LIM 22:25 SC
            LA2510 22APR LIM 12:40 - MIA 19:25 SC

DDDDDD      LA600  21APR SCL 20:05 - LIM 22:25 WK
            LA600  22APR SCL 20:05 - LIM 22:25 SC

EEEEEE      LA500  21APR SCL 20:55 - MIA 05:40 WK
            LA600  21APR SCL 20:05 - LIM 22:25 SC
            LA2510 22APR LIM 12:40 - MIA 19:25 SC
```

Scenario #3: The Passenger Reaccommodation List is compiled on 17APR for flight LA600 21APR (please note that PNR CCCCCC is back on its original LA600 21APR flight). The list shows the following PNRs: AAAAAA, BBBBBB, CCCCCC, DDDDDD, EEEEEE.

6.1.4 Use Case – Native Sabre and Trip_ReportsRQ

Given Sabre PNRs assigned with the given carrier and flight. Generate a list of LA reaccommodated passengers, for LA flight number 703, departing on 21-DEC-2017.

There are five reaccommodated passengers on the list. The reaccomodation which took place on flight LA703 is a change of flight: from LA703 MAD-SCL, to LA703 MAD-GRU-SCL.

Native Sabre

Input:

```
RK/MLR/LA703/21DEC
```

Output:

```
MULTI
LA703  /21DEC       B
MADGRU
NIL
MADSCL
NIL
GRUSCL
001   GTEAGB/AAFNFXGB                              MIDDPO L HK1
      LA 703  L 20DEC   MADSCL HK -WK/ LA 703  L 20DEC   MADGRU
SC 20DEC17/0324
                                        LA 703  L 22DEC   GRUSCL
SC 20DEC17/0324
```

```
002   FERNANDEZ/JUAN                                MIDFRR Y HK1
      LA 703  Y 20DEC   MADSCL HK -WK/ LA 703  Y 20DEC   MADGRU
SC 20DEC17/0324
                                        LA 703  Y 22DEC   GRUSCL
SC 20DEC17/0324
003   GTEEN/AAFNIXN DR                              YGYHAW C HK1
      LA 703  C 20DEC   MADSCL HK -WK/ LA 703  C 20DEC   MADGRU‡
MD«
SC 20DEC17/0324                                                 ‡
                                        LA 703  C 22DEC   GRUSCL
SC 20DEC17/0324
004   GOMEZ/VICTOR SR                               KQFNQX L HK1
      LA 703  L 20DEC   MADSCL HK -WK/ LA 703  L 20DEC   MADGRU
SC 20DEC17/0324
                                        LA 703  L 22DEC   GRUSCL
SC 20DEC17/0324
005   SANCHA/MARIO                                  MIDEYP H HK1
      LA 703  H 20DEC   MADSCL HK -WK/ LA 703  H 20DEC   MADGRU
SC 20DEC17/0324
                                        LA 703  H 22DEC   GRUSCL
SC 20DEC17/0324
```

Trip_ReportsRQ

Request:

```
<Trip_ReportsRQ Version="x.x" xmlns="http://webservices.sabre.com/triprecord">
<Report>
<ReportName>MLR</ReportName>
<ReportFormat>R</ReportFormat>
  <Criteria>
       <FlightCriteria>
              <AirlineCode>LA</AirlineCode>
              <FlightNumber>703</FlightNumber>
              <DepartureDateTime>2017-12-20</DepartureDateTime>
       </FlightCriteria>
       <PosCriteria>LA</PosCriteria>
  </Criteria>
</Report>
</Trip_ReportsRQ>
```

Response:

```
<Trip_ReportsRS (RS shortened for documentation purposes))>
<Success>Success</Success>
<Report>
<ReportName>MLC</ReportName>
<ReportFormat>C</ReportFormat>
<ReportResult>
<Header>
       <AirlineCode>LA</AirlineCode>
       <FlightNumber>703</FlightNumber>
       <DepartureDateTime>2017-12-20T00:00:00</DepartureDateTime>
       <DepartureDayOfWeek>WED</DepartureDayOfWeek>
       <DisplayType>B</DisplayType>
</Header>
<Details>
<Entry>
<EntryHeader>
       <DepartureAirport>MAD</DepartureAirport>
```

```
        <ArrivalAirport>GRU</ArrivalAirport>
        <DepartureLegTime>2017-12-20T21:15:00</DepartureLegTime>
</EntryHeader>
<ScheduleChangeEntry>
        <PnrIndicatorType> </PnrIndicatorType>
        <NumberInParty>1</NumberInParty>
        <Name>GTEAGB/AAFNFXGB</Name>
        <Locator>MIDDPO</Locator>
        <ClassOfService>L</ClassOfService>
        <StatusCode>SC</StatusCode>
        <HistoryActionCode>WK</HistoryActionCode>
        <NumberOfPassengers>1</NumberOfPassengers>
        <UpdateDateTime>2017-12-20T03:24:00</UpdateDateTime>
        <OldFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>HK</StatusCode>
        </OldFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>GRU</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-22T07:20:00</DepartureDateTime>
                <DepartureAirport>GRU</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
</ScheduleChangeEntry>
<ScheduleChangeEntry>
        <PnrIndicatorType> </PnrIndicatorType>
        <NumberInParty>1</NumberInParty>
        <Name>FERNANDEZ/JUAN</Name>
        <Locator>MIDFRR</Locator>
        <ClassOfService>Y</ClassOfService>
        <StatusCode>SC</StatusCode>
        <HistoryActionCode>WK</HistoryActionCode>
        <NumberOfPassengers>1</NumberOfPassengers>
        <UpdateDateTime>2017-12-20T03:24:00</UpdateDateTime>
        <OldFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>Y</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>HK</StatusCode>
        </OldFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
```

```
            <FlightNumber>703</FlightNumber>
            <ClassOfService>Y</ClassOfService>
            <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
            <DepartureAirport>MAD</DepartureAirport>
            <ArrivalAirport>GRU</ArrivalAirport>
            <StatusCode>SC</StatusCode>
      </NewFlight>
      <NewFlight>
            <AirlineCode>LA</AirlineCode>
            <FlightNumber>703</FlightNumber>
            <ClassOfService>Y</ClassOfService>
            <DepartureDateTime>2017-12-22T07:20:00</DepartureDateTime>
            <DepartureAirport>GRU</DepartureAirport>
            <ArrivalAirport>SCL</ArrivalAirport>
            <StatusCode>SC</StatusCode>
      </NewFlight>
</ScheduleChangeEntry>
<ScheduleChangeEntry>
      <PnrIndicatorType> </PnrIndicatorType>
      <NumberInParty>1</NumberInParty>
      <Name>GTEEN/AAFNIXN DR</Name>
      <Locator>YGYHAW</Locator>
      <ClassOfService>C</ClassOfService>
      <StatusCode>SC</StatusCode>
      <HistoryActionCode>WK</HistoryActionCode>
      <NumberOfPassengers>1</NumberOfPassengers>
      <UpdateDateTime>2017-12-20T03:24:00</UpdateDateTime>
      <OldFlight>
            <AirlineCode>LA</AirlineCode>
            <FlightNumber>703</FlightNumber>
            <ClassOfService>C</ClassOfService>
            <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
            <DepartureAirport>MAD</DepartureAirport>
            <ArrivalAirport>SCL</ArrivalAirport>
            <StatusCode>HK</StatusCode>
      </OldFlight>
      <NewFlight>
            <AirlineCode>LA</AirlineCode>
            <FlightNumber>703</FlightNumber>
            <ClassOfService>C</ClassOfService>
            <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
            <DepartureAirport>MAD</DepartureAirport>
            <ArrivalAirport>GRU</ArrivalAirport>
            <StatusCode>SC</StatusCode>
      </NewFlight>
      <NewFlight>
            <AirlineCode>LA</AirlineCode>
            <FlightNumber>703</FlightNumber>
            <ClassOfService>C</ClassOfService>
            <DepartureDateTime>2017-12-22T07:20:00</DepartureDateTime>
            <DepartureAirport>GRU</DepartureAirport>
            <ArrivalAirport>SCL</ArrivalAirport>
            <StatusCode>SC</StatusCode>
      </NewFlight>
</ScheduleChangeEntry>
<ScheduleChangeEntry>
      <PnrIndicatorType> </PnrIndicatorType>
      <NumberInParty>1</NumberInParty>
      <Name>GOMEZ/VICTOR SR</Name>
      <Locator>KQFNQX</Locator>
      <ClassOfService>L</ClassOfService>
      <StatusCode>SC</StatusCode>
      <HistoryActionCode>WK</HistoryActionCode>
```

```
        <NumberOfPassengers>1</NumberOfPassengers>
        <UpdateDateTime>2017-12-20T03:24:00</UpdateDateTime>
        <OldFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>HK</StatusCode>
        </OldFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>GRU</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-22T07:20:00</DepartureDateTime>
                <DepartureAirport>GRU</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
</ScheduleChangeEntry>
<ScheduleChangeEntry>
        <PnrIndicatorType> </PnrIndicatorType>
        <NumberInParty>1</NumberInParty>
        <Name>SANCHA/MARIO</Name>
        <Locator>MIDEYP</Locator>
        <ClassOfService>H</ClassOfService>
        <StatusCode>SC</StatusCode>
        <HistoryActionCode>WK</HistoryActionCode>
        <NumberOfPassengers>1</NumberOfPassengers>
        <UpdateDateTime>2017-12-20T03:24:00</UpdateDateTime>
        <OldFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>H</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>HK</StatusCode>
        </OldFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>H</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>GRU</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>H</ClassOfService>
                <DepartureDateTime>2017-12-22T07:20:00</DepartureDateTime>
```

```
                <DepartureAirport>GRU</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
</ScheduleChangeEntry>
<ScheduleChangeEntry>
        <PnrIndicatorType> </PnrIndicatorType>
        <NumberInParty>1</NumberInParty>
        <Name>GTEAGB/AAFNFXGB</Name>
        <Locator>MIDDPO</Locator>
        <ClassOfService>L</ClassOfService>
        <StatusCode>SC</StatusCode>
        <HistoryActionCode>WK</HistoryActionCode>
        <NumberOfPassengers>1</NumberOfPassengers>
        <UpdateDateTime>2017-12-20T03:24:00</UpdateDateTime>
        <OldFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>HK</StatusCode>
        </OldFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>GRU</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-22T07:20:00</DepartureDateTime>
                <DepartureAirport>GRU</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
</ScheduleChangeEntry>
<ScheduleChangeEntry>
        <PnrIndicatorType> </PnrIndicatorType>
        <NumberInParty>1</NumberInParty>
        <Name>FERNANDEZ/JUAN</Name>
        <Locator>MIDFRR</Locator>
        <ClassOfService>Y</ClassOfService>
        <StatusCode>SC</StatusCode>
        <HistoryActionCode>WK</HistoryActionCode>
        <NumberOfPassengers>1</NumberOfPassengers>
        <UpdateDateTime>2017-12-20T03:24:00</UpdateDateTime>
        <OldFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>Y</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>HK</StatusCode>
        </OldFlight>
        <NewFlight>
```

```
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>Y</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>GRU</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>Y</ClassOfService>
                <DepartureDateTime>2017-12-22T07:20:00</DepartureDateTime>
                <DepartureAirport>GRU</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
</ScheduleChangeEntry>
<ScheduleChangeEntry>
        <PnrIndicatorType> </PnrIndicatorType>
        <NumberInParty>1</NumberInParty>
        <Name>GTEEN/AAFNIXN DR</Name>
        <Locator>YGYHAW</Locator>
        <ClassOfService>C</ClassOfService>
        <StatusCode>SC</StatusCode>
        <HistoryActionCode>WK</HistoryActionCode>
        <NumberOfPassengers>1</NumberOfPassengers>
        <UpdateDateTime>2017-12-20T03:24:00</UpdateDateTime>
        <OldFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>C</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>HK</StatusCode>
        </OldFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>C</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>GRU</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>C</ClassOfService>
                <DepartureDateTime>2017-12-22T07:20:00</DepartureDateTime>
                <DepartureAirport>GRU</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
</ScheduleChangeEntry>
<ScheduleChangeEntry>
        <PnrIndicatorType> </PnrIndicatorType>
        <NumberInParty>1</NumberInParty>
        <Name>GOMEZ/VICTOR SR</Name>
        <Locator>KQFNQX</Locator>
        <ClassOfService>L</ClassOfService>
        <StatusCode>SC</StatusCode>
```

```
        <HistoryActionCode>WK</HistoryActionCode>
        <NumberOfPassengers>1</NumberOfPassengers>
        <UpdateDateTime>2017-12-20T03:24:00</UpdateDateTime>
        <OldFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>HK</StatusCode>
        </OldFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>GRU</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>L</ClassOfService>
                <DepartureDateTime>2017-12-22T07:20:00</DepartureDateTime>
                <DepartureAirport>GRU</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
</ScheduleChangeEntry>
<ScheduleChangeEntry>
        <PnrIndicatorType> </PnrIndicatorType>
        <NumberInParty>1</NumberInParty>
        <Name>SANCHA/MARIO</Name>
        <Locator>MIDEYP</Locator>
        <ClassOfService>H</ClassOfService>
        <StatusCode>SC</StatusCode>
        <HistoryActionCode>WK</HistoryActionCode>
        <NumberOfPassengers>1</NumberOfPassengers>
        <UpdateDateTime>2017-12-20T03:24:00</UpdateDateTime>
        <OldFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>H</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>SCL</ArrivalAirport>
                <StatusCode>HK</StatusCode>
        </OldFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>H</ClassOfService>
                <DepartureDateTime>2017-12-20T21:15:00</DepartureDateTime>
                <DepartureAirport>MAD</DepartureAirport>
                <ArrivalAirport>GRU</ArrivalAirport>
                <StatusCode>SC</StatusCode>
        </NewFlight>
        <NewFlight>
                <AirlineCode>LA</AirlineCode>
                <FlightNumber>703</FlightNumber>
                <ClassOfService>H</ClassOfService>
```

```
              <DepartureDateTime>2017-12-22T07:20:00</DepartureDateTime>
              <DepartureAirport>GRU</DepartureAirport>
              <ArrivalAirport>SCL</ArrivalAirport>
              <StatusCode>SC</StatusCode>
       </NewFlight>
</ScheduleChangeEntry>
</Entry>
</Details>
</ReportResult>
</Report>
</Trip_ReportsRS>
```

Error and warning messages

7

7.1. List of Codes – Native Sabre and Trip_ReportsRQ

The table below presents a list of error and warning messages that Trip_ReportsRQ can return. Some of the messages indicated the request needs some adjustments to be executed correctly. In such a case please update the request and retry the web service call. In case of issues with service unavailability, please contact Technical Support.

Code	Message / description
301401	UNKNOWN REPORTS ERROR - Such message appears in case of processing error in the TRIP application. User should repeat the request.
301402	INVALID POS – Indicated POS is incorrect. User should provide a correct POS.
301403	INVALID AIRLINE CODE – Indicated airline code is incorrect. User should provide a correct airline code.
301404	INVALID FLIGHT NUMBER – Indicated flight number is incorrect. User should provide a correct flight number.
301405	AUTHENTICATION ERROR – User is not authorized to invoke Trip Reports. Only authorized users are able to generate Trip Reports.
301406	INVALID DEPARTURE DATE – Indicated departure date is incorrect. User should provide a correct departure date for specified flight.
301407	INVALID REPORT TYPE – Indicated report type is incorrect. User should provide a correct report type.
301408	INVALID CITY PAIR – Such error appears if the origin/destination segment does not match any origin and destination for the flight. User should provide a correct city pair.
301409	INVALID CITY – The error appears if the city does not match any origin city for the flight. User should provide a correct city code for specified flight.
301410	INVALID REQUEST – Such error appears in the Trip_ReporstRQ response if any other part of the input is incorrect. User should verify the request and update the incorrect parts of request.
301411	FLIGHT NOT FOUND – The error appears if specified flight does not operate on requested date. User should provide a correct flight number or date.

Sabre Inc. Confidential / All Rights Reserved

301412	DAYS LIMIT EXCEEDED - The error appears only in BST report if provided date range is too wide.
301413	INVALID DATE RANGE OR FREQUENCY – The error appears only in BST report if provided date range is incorrect.
301414	INVALID OR MISSING NAME CRITERIA – Name criteria is missing. User should add name criteria in the request.
301415	TRIP EXECUTION FAILED – The error appears in case of any issues in the TRIP application. All such issues should be escalated.
301416	SSI EXECUTION FAILED – The error appears in case of issues in the SSI application. All such issues should be escalated.
301417	INCOMPLETE SSI RESPONSE – The error appears in case of issues in the SSI application. All such issues should be escalated.
301418	TRIP REPORTS GENERATION TIMEOUT – The error appears in case of timeout in the TRIP application. User should repeat the request or modify the criteria.
-	RESPONSE TRUNCATED - USE SPECIFIC CRITERIA – Such message appears on any of the reports when the response is too large to return all the data. Instead response contains a partial list with mentioned message as the last line in the display.
-	FORMAT – the error appears in Native Sabre if any other part of the input is incorrect.

7.2. Samples

In this section you can find some examples of the most popular error responses given. For the sample of API calls, version x.x.x represents the current web version of service.

USE CASE

The service was invoked with an invalid security token. This is a generic error message, not specific for the Trip_ReportsRQ service. The following content is included in the response. Please establish the web service session again, include the proper token in the request, verify the endpoint used and retry the call.

```
<soap-env:Body>
<soap-env:Fault>
   <faultcode>soap-env:Client.InvalidSecurityToken</faultcode>
   <faultstring>Invalid or Expired binary security token: ... </faultstring>
   <detail>
      <StackTrace>com.sabre.universalservices.base.session.SessionException:
errors.session.USG_INVALID_SECURITY_TOKEN</StackTrace>
   </detail>
</soap-env:Fault>
</soap-env:Body>
```

USE CASE

The service was invoked by a user who is not authorized to generate Trip Reports. The following is the response. The request should be done by an authorized user.

```
<Trip_ReportsRS xmlns="http://webservices.sabre.com/triprecord" Version="x.x.x">
<Errors>
   <Error ErrorCode="301405" Severity="MODERATE" ErrorMessage="AUTHENTICATION ERROR"/>
</Errors>
</Trip_ReportsRS>
```

USE CASE

User tries to generate a report in Native Sabre, although the user does not know she/he is not authorized to do so or the report is not activated for the considered carrier. The entry should be done by an authorized user and it should be confirmed the solution is activated for the airline.

```
RK/MLX/LA600/23JAN/SCLLIM«
‡AUTHENTICATION ERROR‡
```

USE CASE

User tries to generate a report in Native Sabre with an invalid entry. The format should be corrected by adding more last name characters before Cross of Lorraine sign ‡.

```
RK/MLBS/LA600/23JAN/SCLLIM-S‡«
‡FORMAT‡
```

USE CASE

User tries d to generate in Native Sabre but there were zero results for the flight number and date. User should check the date and generate the report for the correct date again, or contact the support team.

```
RK/TRI/LA4802/12JAN/LIM«
NO RESULTS FOUND
```

USE CASE

User tries to generate a report in Native Sabre provisioning a flight number which does not operate on provided date. The format should be corrected by changing flight number or date.

```
RK/TRI/LA4802/06DEC/LIM«
‡FLIGHT NOT FOUND‡
```

USE CASE

User tries to generate a report in Native Sabre provisioning an incorrect departure city (can also appear for the arrival city) for the flight. The format should be corrected by changing city code.

Sabre Inc. Confidential / All Rights Reserved

```
RK/TRI/LA2456/23JAN/CUN«
‡INVALID CITY‡
```

Glossary 8

Term	Description
AAA	Agent Assembly Area – refers to the buffer in the Sabre system where content is retained while a Sabre Host session is active.
AE	Air Extra - Additional products and services offered by airlines in addition to the airfare are sold separately. Makes products and services available throughout within the normal workflow. Examples of Air Extras are pre-purchased seat assignments and checked bag fees.
AS	Sabre Airline Solutions
Locator	PNR record locator
OAC	Office Accounting Code
OSI	Other Supplementary Information can be used when action or reply from carrier is not required
OTA	Open Travel Alliance XML format
PCC	Pseudo City Code uniquely identifies travel agency in the same way that a city code identifies a city
PNR	Passenger Name Record
POS	Point of Sale
PSS	Passenger Service System also known as Sabre Host
SSR	Special Service Request is used when action or response from carrier is required
SRW	Sabre Red Workspace application, called also Native Sabre System
STL	SABRE XML format
Segment	Field of a Passenger Name Record holding actual booking (Air, Car, Hotel etc.)

Sabre Inc. Confidential / All Rights Reserved

TN	Sabre Travel Network
TVL	Travel Itinerary Read XML format

Sabre Inc. Confidential / All Rights Reserved

Technical Support 9

If you have any questions or need assistance, please contact our Global Customer Support Center.

9.1. Telephone

When reporting **production or other critical/time sensitive issues**, please contact us via the telephone.

Sabre Airline Solutions (selected countries listed below):

Country	Toll free number
Australia	1-800-081-993
Brazil	0800-891-9210
Canada	1-866-598-1706
Chile	800-412555
China	4001-202-315
France	0800-909-657
Germany	0800-181-7245
India	000-800-100-6116
Italy	800-787-417
Mexico	01-800-123-8537
Russia	810-800-240-31012
Spain	900-995-926
UAE	800-035-702-569
UK	0800-0288446
USA	1-888-421-8889 or 1-800-677-0856

Sabre Inc. Confidential / All Rights Reserved

Countries with no-toll free service	+1 770 261 0080 (toll call).

9.2. Email

E-mail is monitored 24 x 7 with a response within 24 hours or less:

- SabreSonic.helpdesk@sabre.com (for Sabre Airline Solutions)

Providing the support desk with the necessary files at the time of initial contact improves our ability to troubleshoot and provide a timely resolution:

- Please include the Sabre Pseudo City Code (PCC) or related Office Acocunting Codes (OAC) or Domain where the issue is occurring.
- When reporting an issue with SOAP based Sabre APIs the input and output payloads are required. Please attach the payloads as separate files, and name them clearly.
- To help ensure that our environment is free of viruses, our policy mandates that all messages received by Sabre from external sources follow special file name guidelines. File names must end in ".sabre.zip" or the zipped attachment will be removed by the e-mail server (for example, “docs.zip” would need to be renamed to “docs.sabre.zip”).
- If your correspondence is regarding a previously reported issue, please include the service incident (“SI”) number in the subject line of your message.
- The subject line should contain a brief description of the problem or question. Please avoid a subject line containing only the words ‘Question’, ‘Issue’, ‘Problem’, etc.
- In the body of the e-mail include as much information as possible to explain the problem and the steps necessary to recreate it.

9.3. Links

Find more details on the following pages:

- https://myhelp.sabre.com/
- http://community.sabre.com/ (Sabre Community Portal for Sabre Airline Solutions)
- https://developer.sabre.com/resources/support
- https://developer.sabre.com/contact