


jQuery introduction

- jQuery is a lightweight, "**write less, do more**", **JavaScript library**.
- The purpose of jQuery is to make it **much easier to use JavaScript** on your website.
- jQuery takes **a lot of common tasks** that require many lines of JavaScript code to accomplish, and **wraps them into methods** that you can call with **a single line of code**.
- jQuery also **simplifies a lot of the complicated things** from JavaScript, like AJAX calls and DOM manipulation.



The jQuery library contains the following features:

- HTML/DOM manipulation
- CSS manipulation
- HTML event methods
- Effects and animations
- AJAX
- Utilities

jQuery introduction

Adding jQuery to Your Web Pages

There are several ways to start using **jQuery** on your web site.

1) Download the jQuery library from jquery.com:

- The jQuery library is **a single JavaScript file**, and you reference it with the HTML `<script>` tag (notice that the `<script>` tag should be inside the `<head>` section):

```
<head>  
  <script src="jquery-3.6.4.min.js"></script>  
</head>
```

(or)

2) Include jQuery from a CDN, like Google:

- If you don't want to download and host jQuery yourself, you can include it from a **CDN (Content Delivery Network)**.


```
<head>  
  <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.6.4/jquery.min.js"></script>  
</head>
```

jQuery introduction - `$(document).ready()`

`$(document).ready()` and `$(())`

- A page can't be manipulated safely until the document is "**ready**."
- The code inserted between `$(document).ready()` is **executed only once** when page is ready for JavaScript code to execute.
- In place of `$(document).ready()`, we can use shorthand notation `$(())` only.

Ex. Changes the background-color of all `<p>` tag or paragraph to cyan.



The first paragraph is selected.


The second paragraph is selected.

The third paragraph is selected.

```
<html>
<head>
  <title>First jQuery Example</title>
  <script type="text/javascript" src="https://code.jquery.com/jquery-3.6.0.min.js">
  </script>
  <script>
    $(document).ready(function() {
      $("p").css("background-color", "cyan");
    });
  </script>
</head>
<body>
  <p>The first paragraph is selected.</p>
  <p>The second paragraph is selected.</p>
  <p>The third paragraph is selected.</p>
</body>
</html>
```

jQuery introduction - \$(document).ready()

- we use jQuery to add a **click event listener** to the button that **displays an alert message when clicked**.
- The **\$(document).ready()** function ensures that the code inside it will only run once the document has finished loading, so that the button element exists and can be selected by its ID.



```
<html>
<head>
  <title>My First jQuery Program</title>
  <script src="https://code.jquery.com/jquery-
3.6.0.min.js"></script>
</head>
<body>
  <button id="myButton">Click me!</button>
  <script>
    $(document).ready(function() {
      $("#myButton").click(function() {
        alert("Hello, world!");
      });
    });
  </script>
</body>
</html>
```

jQuery Selectors

jQuery Selectors

- Used to **select and manipulate HTML elements**.
- jQuery selectors are used to **"find" (or select)** HTML elements based on their **name, id, classes, types, attributes, values** of attributes and much more.
- All selectors in jQuery start with the **dollar sign** and **parentheses**: **\$()**.

jQuery Selectors:

- **Element selector:** selects all elements with the **specified tag name**.
For example, `$("p")` selects all `<p>` elements.
- **Class selector:** selects all elements with the **specified class**.
For example, `$(".my-class")` selects all elements with the class `my-class`.
- **ID selector:** selects the element with the specified ID.
For ex, `$("#my-id")` selects the element with the ID `my-id`.
- **Attribute selector:** selects all elements that have the specified attribute.
 - For example, `$("input[type='text']")` selects all `<input>` elements with a **type attribute of text**.

jQuery Selectors

1) The element Selector:

- The jQuery element selector **selects elements based on the element name.**
- We can select all `<p>` elements on a page like this:
`$("p")`.

Ex.

When a user clicks on a button, all `<p>` elements will be hidden




```
<html>
<head>
<script src="https://code.jquery.com/jquery-
3.6.0.min.js"></script>
<script>
$(document).ready(function(){
    $("button").click(function(){
        $("p").hide(); //element selector
    });
});
</script>
</head>
<body>
<h2>This is a heading</h2>
<p>This is a paragraph.</p>
<p>This is another paragraph.</p>
<button>Click me to hide paragraphs</button>
</body> </html>
```

jQuery Selectors

2) The #id Selector:

- The jQuery **#id selector** uses the **id attribute** of an HTML tag to find the specific element.
- To find an element with a specific id, write a **hash character**, followed by the id of the HTML element:

`$("#test")` .



Ex.

When a user clicks on a button, all **<p>** elements will be hidden:

```
<html>
<head>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.6.4/jquery.min.js">
</script>
<script>
$(document).ready(function(){
    $("button").click(function(){
        $("#test").hide(); //id selector
    });
});
</script>
</head>
<body>
<h2>This is a heading</h2>
<p>This is a paragraph.</p>
<p id="test">This is another paragraph.</p>
<button>Click me to hide paragraphs</button>
</body> </html>
```

jQuery Selectors

3) The .class Selector


- The jQuery .class selector **finds elements with a specific class.**
- To find elements with a specific class, write a period character, followed by the name of the class:

`$(".test")`

Example

When a user clicks on a button, all <p> elements will be hidden:

```
<html>
<head>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.6.4/jquery.min.js">
</script>
<script>
$(document).ready(function(){
    $("button").click(function(){
        $(".test").hide();
    });
});
</script>
</head>
<body>
<h2 class="test">This is a heading</h2>
<p class="test">This is a paragraph.</p>
<p>This is another paragraph.</p>
<button>Click me to hide paragraphs</button>
</body> </html>
```




jQuery Selectors

3) Attribute selector

- It selects all elements that have the specified attribute.
- For example, `$("input[type='text']")` selects all `<input>` elements with a type attribute of text.

`$("input[type='text']")`



- select all `<input>` elements with a **type** attribute of **"text"**, and apply a CSS style

```
<!DOCTYPE html>
<html>
<head>
  <title>Attribute Selector Example</title>
  <script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>
</head>
<body>
  <input type="text" value="Hello">
  <input type="text" value="World">
  <input type="number" value="123">
  <script>
    $(document).ready(function() {
      $("input[type='text']").css("background-color", "yellow");
    });
  </script>
</body>
</html>
```

jQuery Events

- **Events are the **actions**** that can be detected by your web application.
- They are used to create dynamic web pages.
- An event shows the exact moment when something happens.

These are some examples of events.

- **A mouse click**
- **An HTML form submission**
- **A web page loading**
- **A keystroke on the keyboard**
- **Scrolling of the web page etc.**

Syntax for event methods:

- Most of the DOM events have an equivalent jQuery method.
- To assign a click events to all paragraph on a page, do this:

```
$("p").click ();
```

- The next step defines what should happen when the event fires. You must pass a function to the event.

```
$("p").click(function(){  
    // action goes here!!  
});
```

Mouse Events	Keyboard Events	Form Events	Document/Window Events
click	keypress	submit	load
dblclick	keydown	change	resize
mouseenter	keyup	focus	scroll
mouseleave		blur	unload

jQuery Events- jQuery click()

1) jQuery click Event:

- When we click on an element, the **click event** occurs and once the click event occurs **it execute the click () method** or attaches a function to run.


Syntax:

\$(selector).click()

- It is used to trigger the click event for the selected elements.

\$(selector).click(function)

```
<html>
<head>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/jquery.min.js"></script>
<script>
$(document).ready(function(){
    $("p").click(function(){
        alert("This paragraph was clicked.");
    });
});
</script>
</head>
<body>
<p>Click on the statement.</p>
</body>
</html>
```



Click on the stateme

This page says


This paragraph was clicked.

OK

jQuery Events- dblclick()

2) dblclick() event

- The `dblclick()` method attaches an event handler function to an HTML element.
- The **function is executed when the user double-clicks on the HTML element**




```
<!DOCTYPE html>
<html>
<head>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.6.4/jquery.min.js"></script>
<script>
$(document).ready(function(){
    $("p").dblclick(function(){
        $(this).hide();
    });
});
</script>
</head>
<body>
<p>If you double-click on me, I will
disappear.</p>
<p>Click me away!</p>
<p>Click me too!</p>
</body>
</html>
```


jQuery Events - mouseenter() event

3) mouseenter() event:

- The **mouseenter()** method attaches an event handler function to an HTML element.
- The function is executed when the mouse pointer enters the HTML element.



Enter this paragraph.



```
<!DOCTYPE html>
<html>
<head>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.6.4/jquery.min.js"></script>
<script>
$(document).ready(function(){
  $("#p1").mouseenter(function(){
    alert("You entered p1!");
  });
});
</script>
</head>
<body>

<p id="p1">Enter this paragraph.</p>

</body>
</html>
```

jQuery Events - Keydown event

4) `keydown()` event:

- This event is triggered when a key on the keyboard is pressed down.
- To handle a keydown event using jQuery, you can use the `.keydown()` method.
- The keydown event to detect when the Enter key is pressed and display an alert:

```
<!DOCTYPE html>
<html>
<head>
  <title>Keydown Event Example</title>
  <script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>
</head>
<body>
  <input type="text" id="myInput">
  <script>
    $(document).ready(function() {
      $("#myInput").keydown(function(){
        alert("Enter key pressed!");
      });
    });
  </script>
</body>
</html>
```

jQuery Objects

- The jQuery object is a **collection of DOM elements** and **behaves like a special array**.
- Everything in jQuery is an object.
- When we create a new element or select an existing element the jQuery returns those elements in a collection.

The syntax of creating jQuery empty object:

```
var obj = { };
```

or

The syntax of creating an object using properties

```
var obj = { property1:value1, property2:value2... propertyN:valueN };
```

or

The syntax of creating an object using selector

```
var obj = $( "selector" );
```

Parameters:

- **property** – It specifies the property for the object to assign.
- **value** – It specifies the value to set for the specific property of the object. The property and value are separated by the colon(:) and each property-value pair is separated by the comma(,).
- **selector** – It specifies the element to select to return the object. it can be a single element or multiple elements.

Return value:

The return value of the object is **the object** if **selector element found**, else return **an empty object** if **selector element not found**.

jQuery Objects

The JQuery object can be created as..


```
var $obj = $(selector);
```

```
<!DOCTYPE html>
<html>
<head>
  <title>jQuery Objects Example</title>
  <script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>
  <style>
    div {
      width: 100px;
      height: 100px;
      border: 1px solid black;
    }
  </style>
</head>
<body>
  <div id="box"></div>
```

```
<script>
  $(document).ready(function() {
    var $box = $("#box"); // create a jQuery
    object for the div
    $box.css("background-color", "red"); //
    set its background color to red

    $box.click(function() {
      alert("Box is clicked!");
    }); // attach a click event handler to
    the div

  });
</script>
</body>
</html>
```



jQuery Objects

var headings = \$("h3");
creates a jQuery object that contains all
<h3> elements in the HTML document

```
<html lang = "en">
<head>
<script src = "https://code.jquery.com/jquery-
3.5.0.js"></script>
<title > This is an example for jQuery object
</title>
<style>
#h3
{
width : 150px;
height : 100px;
border : 2px solid red;
font-size : 20px;
}
```

```
</style>
</head>
<body>
<h3> This is an Example for jQuery object: </h3>
<h3 id = "h3" > This is a example heading. </h3>
<p > This is a paragraph example. </p>
<button onclick="obj()"> click here to create
and display jQuery object </button>
<div id = "div1"> </div>
<div id = "div2"> </div>
<script>
function obj()
{
var headings = $("h3");
// displly the number of h3 tags on the page.
$("#div1").text("The no.of h3 are:"+headings.length);
// Selecting only the first h1 element on the page
$("#div2").text("The first h3 heading is:" +$("h3")[0]);
}
</script>
</body></html>
```

jQuery Objects

Example of object with some properties

```
<!doctype html>
<html lang = "en">
<head>
<meta charset = "utf-8">
<script src = "https://code.jquery.com/jquery-
3.5.0.js"></script>
<title > This is an example for jQuery object
</title>
<style>
#p1 {
color : blue;
}
#p2 {
color : red;
background-color : yellow;
}
</style>
</head>
```

```
<body>
<h3> This is an Example for jQuery object:
</h3>
<p id = "p1"> </p>
<button onclick = "checkRes()" > Click here to create
and display the object and its properties. </button>
<p id = "p2"> </p>
<script>
var obj = { Sub1: "JavaScript", Sub2: "CSS",
Sub3: "jQuery", Sub4: "Java" };
function checkRes()
{
$("#p2" ).text( "The object properties are : "
+obj.Sub1+ " " +obj.Sub2+ " " +obj.Sub3+ " "
+obj.Sub4);
}
</script>
</body>
</html>
```

jQuery Objects

Example of object with some properties

```
<!DOCTYPE html>
<html>
<head>
  <meta charset="UTF-8">
  <title>jQuery Object with Properties
Example</title>
  <script src="https://code.jquery.com/jquery-
3.6.0.min.js"></script>
  <style>
    #myDiv {
      width: 100px;
      height: 100px;
      border: 1px solid black;
    }
  </style>
</head>
<body>
```

```
<div id="myDiv"></div>
<script>
  var options = {
    backgroundColor: "green",
    position: "absolute",
    top: "150px",
    left: "150px"
  };

  $("#myDiv").css(options);

  options.backgroundColor = "red";
  options.top = "200px";

  $("#myDiv").css(options);
</script>

</body>
</html>
```