



SAFETY DATA SHEET

1. Identification

Product identifier BEHR DYNASTY® Interior Matte Paint– Medium Base

Other means of identification

Product code 1654

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process LLC
1801 E. St. Andrew Place
Santa Ana, CA 92705

Telephone 714-545-7101

Emergency telephone +1 760 476 3962
+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction.

Precautionary statement

Prevention Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves.

Response If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.

Storage Not assigned.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Silica gel, precipitated, crystalline-free	112926-00-8	10 - 30
Titanium dioxide	13463-67-7	10 - 30
2-Butoxyethyl benzoate	5451-76-3	0.5 - 1.5
3-(2-aminoethylamino)propylmethyl dimethoxysilane	3069-29-2	0.1 - 1
Cristobalite	14464-46-1	0.1 - 1



Chemical name	CAS number	%
Diatomaceous Earth (Flux calcined)	68855-54-9	0.1 - 1
2-Methyl-2H-isothiazol-3-one	2682-20-4	0 - 0.1
Biocide	55965-84-9	0 - 0.1
Composition comments	All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.	
4. First-aid measures		
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.	
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.	
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.	
Ingestion	Rinse mouth. Get medical attention if symptoms occur.	
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash. Mild skin irritation.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.	
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.	
5. Fire-fighting measures		
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.	
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.	
General fire hazards	No unusual fire or explosion hazards noted.	
6. Accidental release measures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.	
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.	
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Avoid release to the environment.	
7. Handling and storage		
Precautions for safe handling	Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.	
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).	

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Silica gel, precipitated, crystalline-free (CAS 112926-00-8)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		0.8 mg/m3	
		20 mppcf	

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale particles
		0.2 mg/m3	Respirable nanoscale particles

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Cristobalite (CAS 14464-46-1)	IDLH	25 mg/m3
Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)	IDLH	3000 mg/m3
Silica gel, precipitated, crystalline-free (CAS 112926-00-8)	IDLH	3000 mg/m3
Titanium dioxide (CAS 13463-67-7)	IDLH	5000 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
Silica gel, precipitated, crystalline-free (CAS 112926-00-8)	TWA	6 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Skin protection	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	White.
Odor	Slight.
Odor threshold	Not available.
pH	7 - 10
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 99 °F (> 37.22 °C)
Flash point	Not applicable.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	50 - 140 KU
Other information	
Density	10.69 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	47 g/l (excluding water) (Coating) 20 g/l (including water) (Material)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction. Causes mild skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash. Mild skin irritation.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
------------	---------	--------------

Silica gel, precipitated, crystalline-free (CAS 112926-00-8)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 2200 mg/m³, 4 hours

Oral

LD50 Rat > 5000 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Causes mild skin irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.
Due to the form of the product, exposure to the potentially carcinogenic components is not expected.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1)	1 Carcinogenic to humans.
Silica gel, precipitated, crystalline-free (CAS 112926-00-8)	3 Not classifiable as to carcinogenicity to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Cristobalite (CAS 14464-46-1) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Cristobalite (CAS 14464-46-1) Cancer

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No data available.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.				
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)					
2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4)		1.0 % One-Time Export Notification only.			
CERCLA Hazardous Substance List (40 CFR 302.4)					
2-Butoxyethyl benzoate (CAS 5451-76-3)		Listed			
Ammonium hydroxide (CAS 1336-21-6)		Listed			
Carbendazim (CAS 10605-21-7)		Listed			
SARA 304 Emergency release notification					
Ammonium hydroxide (CAS 1336-21-6)		100 LBS			
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)					
Cristobalite (CAS 14464-46-1)		Cancer lung effects immune system effects kidney effects			
Toxic Substances Control Act (TSCA)		All components are listed on or exempt from the U.S. EPA TSCA Inventory List.			
Superfund Amendments and Reauthorization Act of 1986 (SARA)					
SARA 302 Extremely hazardous substance					
Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
Ammonium hydroxide	1336-21-6	100	500		

SARA 311/312 Hazardous chemical Yes
Classified hazard categories Respiratory or skin sensitization
SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-Butoxyethyl benzoate (CAS 5451-76-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Ammonium hydroxide (CAS 1336-21-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Ammonium hydroxide (CAS 1336-21-6)

Cristobalite (CAS 14464-46-1)

Silica gel, precipitated, crystalline-free (CAS 112926-00-8)

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethyl benzoate (CAS 5451-76-3)

3-Iodo-2-propynyl butylcarbamate (CAS 55406-53-6)

Ammonium hydroxide (CAS 1336-21-6)

Carbendazim (CAS 10605-21-7)

Cristobalite (CAS 14464-46-1)

Silica gel, precipitated, crystalline-free (CAS 112926-00-8)

Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethyl benzoate (CAS 5451-76-3)

Ammonium hydroxide (CAS 1336-21-6)

Cristobalite (CAS 14464-46-1)

Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Ammonium hydroxide (CAS 1336-21-6)

Cristobalite (CAS 14464-46-1)

Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)

Silica gel, precipitated, crystalline-free (CAS 112926-00-8)

Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

Issue date 15-April-2025

Revision date -

Version # 01

HMIS® ratings Health: 2
Flammability: 0
Physical hazard: 0

List of abbreviations CAS: Chemical Abstract Service.
DOT: Department of Transportation.
IARC: International Agency for Research on Cancer.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IDLH: Immediately Dangerous To Life or Health.
IMDG: International Maritime Dangerous Goods.
LC50: Lethal Concentration 50%.
LD50: Lethal Dose 50%.
MARPOL: International Convention for the Prevention of Pollution from Ships.
PEL: Permissible Exposure Limit.
TWA: Time Weighted Average.

References

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
HSDB® - Hazardous Substances Data Bank
NLM: Hazardous Substances Data Base

Disclaimer

Behr Process LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.