

PocketBase with Dart (Part 2)

Student DB Example

Student Data Model

- In this example, we model a student with the following information.

```
Name  
Age  
Major  
createdAt
```

- To store the information in the DB, we need additional information.

```
id // automatically generated from pocketbase  
createdAt
```

JSON

```
{  
  "name": "Alice Johnson",  
  "age": 21,  
  "major": "Computer Science",  
  "createdAt": "2025-08-25 11:15:14.123Z"  
}
```

Pocketbase RecordModel

- RecordModel is the representation of information in Pocketbase.

```
RecordModel {  
  // Automatically generated Unique identifier  
  id: "abc123def456",  
  // Your actual data  
  data: {  
    "name": "Alice Johnson",  
    "age": 21,  
    "major": "Computer Science",  
    "createdAt": "2025-08-25 11:15:14.123Z"  
  },  
}
```

models/student.dart

```
/// Student model for PocketBase
class Student {
  final String id;          // PocketBase document ID
  final String name;        // Student name
  final int age;            // Student age
  final String major;       // Student's major
  final DateTime createdAt; // Timestamp
  // constructor
  const Student({
    required this.id,
    required this.name,
    required this.age,
    required this.major,
    required this.createdAt,
  });
}
```

JSON service functions

```
Map<String, dynamic> toJson() {  
    return {  
        'name': name,  
        'age': age,  
        'major': major,  
        'createdAt': createdAt.toIso8601String(),  
    };  
}  
  
factory Student.fromJson(Map<String, dynamic> map) {  
    return Student(  
        id: map['id'] as String? ?? '',  
        name: map['name'] as String? ?? '',  
        age: map['age'] as int? ?? 0,  
        major: map['major'] as String? ?? '',  
        createdAt: _parseDateTime(map['createdAt']),  
    );  
}
```

Collection Setup

- We already created Student collection.
 - Check `scripts/create_collection.sh`

```
curl -X POST http://localhost:8090/api/collections \
-H "Content-Type: application/json" \
-H "Authorization: Bearer YOUR_ADMIN_TOKEN" \
-d '{ ... }'
```

- We can use the `collections.create()` function.

```
await pb.collections.create(body: {  
  'name': 'students',  
  'type': 'base',  
  'schema': [  
    {'name': 'name', 'type': 'text', 'required': true},  
    {'name': 'age', 'type': 'number', 'required': true},  
    {'name': 'major', 'type': 'text', 'required': true},  
    {'name': 'createdAt', 'type': 'date', 'required': true},  
  ],  
  'createRule': '@request.auth.id != ""',  
  'updateRule': '@request.auth.id != ""',  
  'deleteRule': '@request.auth.id != ""',  
  'listRule': '',  
  'viewRule': '',  
});
```

CRUD

- The next step is to create CRUD functions.
- PocketBaseCrudService class contains the CRUD service functions for the Student collection.

PocketBaseCrudService

```
class PocketBaseCrudService {  
  // Instance variables instead of static  
  final PocketBase _pb;  
  final String _collection = 'students';  
  
  // Constructor – this makes it an instance-based class  
  PocketBaseCrudService({  
    String baseUrl = 'http://127.0.0.1:8090',  
  }) : _pb = PocketBase(baseUrl);  
  
  /// Get reference to students collection  
  RecordService get _studentsRef =>  
    _pb.collection(_collection);  
}
```

```
/// Initialize service and authenticate
Future<void> initialize() async {
  try {
    await pb.health.check();
    // Authenticate if needed
    await pb.collection('users').authWithPassword(
      'admin@example.com', 'password123'
    );
    print('✅ PocketBase service initialized');
  } catch (e) {
    print('❌ PocketBase initialization failed: $e');
    rethrow;
  }
}
```

CREATE Operations

```
/// CREATE: Add new student to PocketBase
Future<String> createStudent(Student student) async {
  try {
    final record = await pb.collection(_collection).create(
      body: student.toMap()
    );

    print('✅ CREATE: Student added with ID: ${record.id}');
    return record.id;

  } catch (e) {
    print('❌ CREATE Error: $e');
    throw Exception('Failed to create student: $e');
  }
}
```

Bulk Student Creation

```
Future<List<String>> createMultipleStudents(List<Student> tudents) async {  
    List<String> createdIds = [];  
    try {  
        for (Student student in students) {  
            final id = await createStudent(student);  
            createdIds.add(id);  
        }  
        print('✅ CREATE: ${students.length} students created');  
        return createdIds;  
    } catch (e) {  
        print('❌ BULK CREATE Error: $e');  
        throw Exception('Failed to create students: $e');  
    }  
}
```

Create: Usage Example

```
// Create single student
Student alice = Student(
    id: '', // Will be auto-generated
    name: 'Alice Johnson',
    age: 20,
    major: 'Computer Science',
    createdAt: DateTime.now(),
);

String studentId =
    await PocketBaseStudentService.createStudent(alice);
```

Generated PocketBase Record:

```
{  
  "id": "abc123def456",  
  "name": "Alice Johnson",  
  "age": 20,  
  "major": "Computer Science",  
  "createdAt": "2024-01-15T10:30:00.000Z"  
}
```

READ Operations

Get All Students with Pagination

```
static Future<List<Student>> getAllStudents({  
  int page = 1, int perPage = 20 }) async {  
  try {  
    final result = await pb.collection(_collection).getList(  
      page: page, perPage: perPage,  
      sort: '+createdAt',  
    );  
    List<Student> students = result.items  
      .map((record) => Student.fromRecord(record))  
      .toList();  
    return students;  
  } catch (e) {  
    throw Exception('Failed to get students: $e');  
  }  
}
```

Get Single Student

```
/// READ: Get specific student by ID
static Future<Student?> getStudentById(String id) async {
  try {
    final record = await pb.collection(_collection).getOne(id);

    Student student = Student.fromRecord(record);
    print('✅ READ: Found student with ID $id');
    return student;
  } catch (e) {
    if (e.toString().contains('404')) {
      print('❌ READ: No student found with ID $id');
      return null;
    }
    print('❌ READ Error: $e');
    throw Exception('Failed to get student: $e');
  }
}
```

Get Students by Major

```
/// READ: Search students by major
static Future<List<Student>> getStudentsByMajor(String major) async {
  try {
    final result = await pb.collection(_collection).getList(
      filter: 'major = "$major"',
      sort: '+name',
    );

    List<Student> students = result.items
      .map((record) => Student.fromRecord(record))
      .toList();

    print('✅ READ: Found ${students.length} $major students');
    return students;
  } catch (e) {
    print('❌ SEARCH Error: $e');
    throw Exception('Failed to search students: $e');
  }
}
```

Get Students by Age

```
Future<List<Student>> getStudentsByAgeRange(int minAge, int maxAge) async {
  try {
    final result = await _studentsRef.getList(
      page: 1,
      perPage: 500,
      filter: 'age >= $minAge && age <= $maxAge',
      sort: '+age',
    );

    List<Student> students =
      result.items.map((record) => Student.fromJson(record.data)).toList();

    print(
      '✅ READ: Retrieved ${students.length} students aged $minAge-$maxAge');
    return students;
  } catch (e) {
    print('❌ READ Error: $e');
    throw Exception('Failed to get students by age range: $e');
  }
}
```

Read: Usage Example

```
// 2-1. READ - Get all students
print('\n2 Reading all students...');
List<Student> allStudents = await pbgetAllStudents();
for (Student student in allStudents) {
    print('  📖 $student');
}

// 2-2. READ - Get specific student
print('\n3 Reading specific student..');
Student? foundAlice = await pbgetStudentById(aliceId);
if (foundAlice != null) {
    print('  📖 Found: $foundAlice');
}
```

```
// 3-1. Search by Major
List<Student> students =
    await pb.getStudentsByMajor("Computer Science");
for (Student student in students) {
    print('CS $student');
}

// 3-2. Search by Age Range
List<Student> youngStudents =

    await pb.etStudentsByAgeRange(18, 21);
for (Student student in youngStudents) {
    print('Age 18 - 21 🎓 $student');
}
```

UPDATE Operations

- Update Specific Fields

```
/// UPDATE: Update specific student fields
Future<void> updateStudent(String id,
                           Map<String, dynamic> updates) async {
  try {
    await pb.collection(_collection).update(id, body: updates);
    print('✅ UPDATE: Student $id updated successfully');
  } catch (e) {
    print('❌ UPDATE Error: $e');
    throw Exception('Failed to update student: $e');
  }
}
```

- **Update Entire Student**
- From the Student object, get the id to update the whole data.

```
/// UPDATE: Replace entire student record
Future<void> updateEntireStudent(Student student) async {
  try {
    await pb.collection(_collection).update(
      student.id,
      body: student.toMap()
    );
    print('✅ UPDATE: Student ${student.id} replaced successfully');
  } catch (e) {
    print('❌ UPDATE Error: $e');
    throw Exception('Failed to update student: $e');
  }
}
```

Update Examples

```
// Update specific fields
await PocketBaseStudentService.updateStudent(storedId, {
  'age': 21,
  'major': 'Data Science'
});

// Update entire record
Student updatedAlice = Student(
  id: 'abc123',
  name: 'Alice Johnson-Smith',
  age: 21,
  major: 'Data Science',
  createdAt: DateTime.now(),
);
await PocketBaseStudentService.updateEntireStudent(updatedAlice);
```

DELETE Operations

Delete Single Student

```
/// DELETE: Remove student by ID
Future<void> deleteStudent(String id) async {
  try {
    await pb.collection(_collection).delete(id);
    print('✅ DELETE: Student $id deleted successfully');
  } catch (e) {
    print('❌ DELETE Error: $e');
    throw Exception('Failed to delete student: $e');
  }
}
```

Delete All Students

```
/// DELETE: Remove all students (batch operation)
Future<void> deleteAllStudents() async {
  try {
    int page = 1;
    int totalDeleted = 0;

    while (true) {
      final result = await pb.collection(_collection).getList(
        page: page, perPage: 100
      );
      if (result.items.isEmpty) break;
      for (final record in result.items) {
        await pb.collection(_collection).delete(record.id);
        totalDeleted++;
      }
    }

    print('✅ DELETE: $totalDeleted students deleted successfully');
  } catch (e) {
    print('❌ DELETE ALL Error: $e');
    throw Exception('Failed to delete all students: $e');
  }
}
```

Databases

Feature	PocketBase	Firebase	SQLite	IndexedDB
Type	Server + SQLite	Cloud NoSQL	File-based SQL	Browser NoSQL
Location	Self-hosted	Google Cloud	Local file	Browser storage
Real-time	✓ Built-in	✓ Built-in	✗ None	✗ None
Authentication	✓ Built-in	✓ Complete	✗ Manual	✗ Manual
Scalability	⚠ Manual	✓ Automatic	✗ Single user	✗ Single user
Queries	✓ REST API	✓ Rich NoSQL	✓ Full SQL	✗ Key-value
Offline	✗ Network only	✓ Smart sync	✓ Always	✓ Always
Cost	 Free hosting	 Pay-per-use	 Free	 Free

Decision Framework

Choose PocketBase for: Self-hosted real-time apps, educational projects, MVPs, data control`

- **Choose IndexedDB** for: Browser-only applications, offline-first web apps, client-side caching

- **Choose SQLite** for: Single-user apps, offline-first, embedded applications
- **Choose Firebase** for: Global scale, automatic scaling, rapid development without hosting

PocketBase Limitations

Scalability Limitations:

- Single server architecture
- Manual scaling required
- SQLite performance limits
- No automatic load balancing

Feature Limitations:

- No complex JOINS in filters
- Limited aggregation functions
- No server-side transactions
- Basic search capabilities

Operational Considerations:

- Requires server management
- Manual backup strategies
- Security configuration needed
- Monitoring and maintenance overhead