

ASE 230 Tools Installation - MySQL

Windows Users

Install MySQL **inside WSL2**, not on Windows directly.

See "02.install_ase230_tools_with_wsl2.md" first.

Run This Automatically Instead

A `run.sh` is just a script — a text file listing the same commands

you'd otherwise type by hand — that runs them all for you in one step. This one captures everything below (install, start the server, verify), with Mac/Linux(WSL2) handled automatically. See `code/04. mysql installation/readme.txt` for more on what it does and why.

```
cd "code/04. mysql installation"  
bash run.sh
```

```
( code/04. mysql installation/run.sh )
```

This should work in most cases, but depending on your

macOS

```
brew install mysql  
brew services start mysql
```

Linux / WSL2 (Ubuntu)

```
sudo apt update  
sudo apt install mysql-server  
sudo service mysql start
```

On a fresh install the server may not be running yet, so start it first. Use `sudo service mysql start`, not `sudo systemctl start mysql` — most WSL2 distros don't run systemd by default, and `systemctl` will fail there ("System has not been booted with systemd"). `service` works whether or not systemd is running, so it's the safer command for this course.

Verify

```
mysql --version  
sudo service mysql status
```

Note for This Course

Some project weeks use MySQL via Docker Compose instead of a local install — follow the project's `docker-compose.yml` when one is provided, and skip the manual install above in that case.

