

ASE 230 Tools Installation - MySQL

Windows Users

Install MySQL inside WSL2, not on Windows directly.

See `02. install_ase230_tools_with_wsl2.pdf` first.

Run This Automatically Instead

A `run.sh` is just a script - a text file listing the same commands you'd otherwise type by hand - that runs them all for you in one step. This one captures everything below (install, start the server, verify), with macOS and Ubuntu/WSL2 handled automatically. See `code/04. mysql installation/readme.txt` for more on what it does and why.

```
cd "code/04. mysql installation"  
bash run.sh
```

```
( code/04. mysql installation/run.sh )
```

This should work in most cases, but depending on your system you may need to follow the manual steps below.

macOS

```
brew install mysql  
brew services start mysql
```

Ubuntu / WSL2

```
sudo apt update  
sudo apt install -y mysql-server  
sudo service mysql start
```

On a fresh install the server may not be running yet, so start it first. Use `sudo service mysql start`, not `sudo systemctl start mysql` - most WSL2 distros don't run systemd by default, and `systemctl` will fail there ("System has not been booted with systemd"). `service` works whether or not systemd is running, so it's the safer command for this course.

Verify on Ubuntu / WSL2

```
mysql --version  
sudo service mysql start  
sudo mysql -e "SELECT VERSION();"
```

On many Ubuntu installations, MySQL uses `auth_socket` authentication for `root`. Use `sudo mysql` rather than `mysql -u root -p`.

Verify on macOS

```
brew services start mysql  
mysql --version  
mysql -u root -e "SELECT VERSION();"
```

Homebrew normally configures MySQL without a root password. If you set one, use `mysql -u root -p` instead.