

(Optional) run1-6-3.sh

Build and run the Blade pages.

Learning Goals

- Explain which files `run1-6-3.sh` reuses from Lesson 4 and which files are new.
- Run the Blade application and test it in the browser and with `curl`.
- Explain why a POST without a CSRF token returns `419`.

`run1-6-3.sh` works like `run1-4.sh`. The steps are the same, and only the copied files differ.

1. Prepare: Create the Laravel project (only once) and install the API routes
2. Check: Is MySQL running?
3. Database: Create studentdb and the ase230 user if missing
4. Configure: Point Laravel's .env at studentdb
5. Copy: Copy the finished files into the project
6. Migrate: Create the `students` table if missing
7. Seed: Insert sample students
8. Verify: Print the routes

- Steps 1 to 4, 6, and 7 are explained in `4-2. run1-4.sh.md`, including the WSL2 `sudo mysql` login.

Step 5: Two Sources of Files

```
LESSON4_DIR="$SCRIPT_DIR/../../4. Models and Database/student-api1-4"

# From Lesson 4: the same finished files
for f in app/Http/Controllers/Api/StudentController.php \
        app/Models/Student.php routes/api.php \
        database/migrations/..._create_students_table.php \
        database/seeder/StudentSeeder.php
do cp "$LESSON4_DIR/$f" "$f"; done

# New in Lesson 6: the web controller, web routes, and Blade views
for f in app/Http/Controllers/StudentController.php routes/web.php
do cp "$SOURCE_DIR/$f" "$f"; done
cp -R "$SOURCE_DIR/resources/views/." resources/views/
```

- The model, table, seeder, and API are **not** copied again: Lesson 6 reuses the Lesson 4 files.
- So the `4. Models and Database` folder must exist. The script stops with a message if it does not.

The New Files

File	Role
<code>StudentController.php</code>	Web controller: <code>return view(...)</code> and <code>redirect()</code>
<code>routes/web.php</code>	<code>Route::resource('students', ...)</code>
<code>layouts/app.blade.php</code>	Page frame: navigation, flash message, <code>@yield</code>

File	Role
<code>students/index.blade.php</code>	Student table
<code>students/show.blade.php</code>	One student
<code>students/create.blade.php</code> , <code>edit.blade.php</code>	Forms
<code>students/_form.blade.php</code>	Fields shared by both forms

- `cp -R views/. resources/views/` copies the whole folder in one command. The dot after `views/` means "the contents".

Run and Test

```
cd "6. View and Controllers/6-3"  
bash ./run1-6-3.sh  
cd student-api  
php artisan serve --port=8080  
# WSL2: php artisan serve --host=0.0.0.0 --port=8080
```

Open `http://localhost:8080/` . It redirects to `/students` .

- The page loads Bootstrap from the Internet (CDN). Without a connection, the page works but looks plain.

Try It in the Browser

1. Click **Add Student** and press **Create** with empty fields.
 - The page shows the validation messages. The fields keep what you typed.
2. Fill in all fields and press **Create**.
 - You return to the list, and a green message says the student was created.
3. Open a student, click **Edit**, change the major, and save.
4. Click **Delete** in the list.
5. Open `/api/students` . The same data appears as JSON.

Test with curl

```
curl -s -o /dev/null -w "%{http_code}\n" http://localhost:8080/students
curl -s -o /dev/null -w "%{http_code}\n" http://localhost:8080/students/999999
curl -s -o /dev/null -w "%{http_code}\n" -X POST http://localhost:8080/students \
  -d 'name=Test&email=test@university.edu&age=20&major=Art&year=1'
```

Request	Status	Why
GET /students	200	The page loads
GET /students/999999	404	Route model binding finds no student
POST /students with no token	419	No CSRF token in the form data

- All commands are in `test1-6-3.sh`. `-w "%{http_code}"` prints only the status number.