

Getting Started with Hugo

Build the example, then write your own project documentation.

Learning Goals

- Run and check the supplied Hugo example.
- Replace sample content with your own API documentation.

Before You Start

Install Hugo with
[Hugo Installation](#), then check it:

```
hugo version
```

Run these commands in macOS Terminal or your WSL2 terminal.

Preview the Example

Copy `module3/code/2_Hugo/` to a practice directory. From that directory:

```
chmod +x run.sh
./run.sh serve
```

`./run.sh serve` runs `hugo server -D`. `./run.sh` runs `hugo --minify` and checks the result.

Open `http://localhost:1313`, then stop with **Ctrl+C**.

What Is Inside

- `hugo.toml` : site title, `baseURL` , and links
- `content/` : your pages, written in Markdown
- `layouts/_default/` : three page templates
- `static/` : stylesheet and images

There is no theme to download. The templates are plain HTML.

Configure Your Site

Edit `my-portfolio/hugo.toml`:

```
baseURL = 'https://yourusername.github.io/'  
title = 'John Doe'  
  
[params]  
  github = 'https://github.com/yourusername'  
  email = 'john@example.com'
```

Replace these sample values. Also replace `John Doe` and `john@example.com` in `content/_index.md` and `content/about.md`.

Use Your GitHub Pages Repository

Set `baseUrl` to the URL of your GitHub Pages repository. For the course workflow, the repository is

`yourusername.github.io` .

- `yourusername` is *YOUR* GitHub username (not the repository name itself).

GitHub Actions will publish this Hugo site in the next lesson.

Edit the Markdown

Sample content is in:

```
module3/code/2_Hugo/my-portfolio/content/ .
```

```
---  
title: "My Laravel API"  
draft: false  
---
```

Write your own endpoints, authentication instructions, run commands, and screenshots below this front matter.

Add a Page and Screenshot

From `my-portfolio/` :

This creates `content/projects/my-api.md` .

```
hugo new projects/my-api.md
```

```
Content "projects/my-api.md" created
```

Edit the New Page

Edit the generated page and set `draft: false`.

New pages start as drafts, so they do not appear in the `./run.sh` build until you do.

Put a screenshot in `static/images/my-api.png`, then reference it in the page.

Use `student-api.md` as an example.

```
! [My API response] (/images/my-api.png)
```

Convert Marp Content

Marp and Hugo both use Markdown, but their formatting is different.

- Remove `marp`, `theme`, `paginate`, and slide-layout comments.
- Replace slide separators with ordinary headings.
- Preserve useful code examples and explain how to run them.
- Update image paths to match `static/images/`.

Build What You Will Publish

```
./run.sh
```

This runs `hugo --minify` and checks the important generated pages.

A page visible only in the preview may still be a draft.

Command Summary

```
./run.sh serve           # preview at localhost:1313  
hugo new projects/my-api.md # add a page  
./run.sh                 # build and check publishable files
```

Before submission, check About, API documentation, screenshots, navigation, and repository links. Then follow the GitHub Actions lesson.