

ASE 230 Tools Installation - PHP

Download code from ASE 230 GitHub Repository

Find the GitHub Repository:

<https://github.com/nkuase/ase230>

- All the pdf slides, questions, and code can be found in the repository.

- Each module has the set of files.

- For course tools, find the information in

https://github.com/nkuase/ase230/tree/main/course_tools

Use `run.sh` if necessary

A `run.sh` (in the `code` directories) is just a script

- It is a text file listing the same commands you'd otherwise type by hand - that runs them all for you in one step.
- This one captures everything below (install, extensions, Composer, verify), with macOS and Ubuntu/WSL2 handled automatically.

Beware the danger of `run.sh`

If you don't understand what `run.sh` does, you may not be able to solve problems it may cause.

- Be sure to understand all the commands in the script.
- If necessary, run each command one by one to troubleshoot or understand the command.

Windows Users

Install PHP inside WSL2, not on Windows directly.

- See `02.`
`install_ase230_tools_with_wsl2.pdf` first,
then run the commands below in your Ubuntu
terminal.

Ubuntu / WSL2

Install PHP related packages.

```
sudo apt update  
sudo apt install -y curl php php-cli php-mysql \  
php-curl php-mbstring php-xml php-zip
```

macOS Users

Visit <https://brew.sh> for brew installation if you don't have **brew** installed yet.

```
# Install Homebrew if you don't have it:  
/bin/bash -c \  
"$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/HEAD/install.sh)"
```

Beware!

After a fresh Homebrew installation, `brew` may not be available in the current shell until its environment is added to `PATH`.

- On Apple Silicon Macs, Homebrew is typically installed in `/opt/homebrew`. On Intel Macs, it is typically installed in `/usr/local`.

```
if [[ -x /opt/homebrew/bin/brew ]]; then
    eval "$(/opt/homebrew/bin/brew shellenv)"
elif [[ -x /usr/local/bin/brew ]]; then
    eval "$(/usr/local/bin/brew shellenv)"
fi
```


Install PHP

```
brew install php  
brew install composer
```

```
php --version  
php -r 'echo "PHP works\n";'  
composer --version
```

Verify the Install

```
php --version  
php -r 'echo "PHP works\n";'
```

Composer (PHP Package Manager)

macOS: Composer was installed with Homebrew on the macOS slide.

Ubuntu / WSL2: the official Composer installer needs a signature check plus a few follow-up steps before it's usable.

Composer install details (Ubuntu / WSL2)

The Ubuntu/WSL2 section of `code/03. php`
`installation/run.sh` runs this verified installation,
and skips it when Composer is already installed.

As covered earlier ("Beware the danger of `run.sh`"), read it first.

- Then, either run the whole script, or copy its commands out and run them one by one:

```
cd "code/03. php installation"  
bash run.sh
```

Editor: VS Code

Open your project folder directly in VS Code.

Recommended extensions:

- PHP Intelephense (autocomplete, error checking)
- PHP Debug

Troubleshooting

php: command not found

Add PHP to `PATH`, restart terminal.

Extension not loading

```
php -m          # list loaded extensions
php --ini       # show config file used
```

Uninstall PHP on Ubuntu/WSL2 (Optional)

Ubuntu / WSL2: Remove PHP and the extensions installed for this course.

```
sudo apt remove --purge -y php php-cli php-mysql \  
php-curl php-mbstring php-xml php-zip  
sudo apt autoremove -y
```


Uninstall PHP on macOS (Optional)

macOS: Remove the Homebrew-installed PHP and Composer packages.

```
brew uninstall php composer
```

Reference

- PHP Manual: <https://www.php.net/docs.php>
- PHP: The Right Way:
<https://phptherightway.com/>