Wisio cc
Calibration & Inspection Laboratories

sanas Calibration Laboratory
CAL 174-00-00

Calibration Certificate

Certificate No: D25-274 04 **Calibration Date: 31 July 2025**

Customer: Selago Industries
1 Dombeya Street
Braelyn, East London

Recommended Expiring Date: 31 July 2028
(Customer Instructions 36 Months)

Calibration of: SCREW PLUG GAUGE (TFW) **Type:** Go/Not Go **Size:** M12x1.0-6H
Graduation: N/A **Units:** mm
Serial: 08-0121-07 **Manufacturer:** TA
Basis of Calibration E.T.R.T.O. 1990/BS 3643-2:1981 **Calibration Procedure No:** QI 21
Traceable Standards/Equipment used:

Steel Gauge Block Set (Grade "0")	Serial No: 140094	Cert.No: 084/DM/2020
Measuring Cylinders (Thread Setting Drums)	Serial No: Various	Cert.No: 384/DM/2021
Measuring Cylinders (Best Size Wires)	Serial No: Various	Cert.No: 383/DM/2021
Floating Carriadge Micrometer	Serial No: 638	Cert.No: D25-001 29

Notes: Calibration of this instrument was performed at the Premises of Wisio, 9 Falcon Crescent.
Environment: Temperature: 20º C Humidity: 40 To 60%
Receiving Date: 2025/07/31
Issue Date: 2025/07/31
Pre-Calibration Condition: Satisfactory

Statement of Calibration

Feature	Specified (mm)	Calibration Results (mm)		
Effective Diameter Go	0.0055 **11.362** -0.0055 **Wear Tolerance** 11.3445		**0 Deg.**	**90 Deg.**
		L	11.367	11.367
		C	11.368	11.368
		T	11.368	11.368
Effective Diameter No Go	0.0055 **11.5155** -0.0055 **Wear Tolerance** N/A		**0 Deg.**	**90 Deg.**
		L	11.520	11.520
		T	11.520	11.520

Uncertainty of Measurement: ± 5.1 µm

Digitally signed by Izak Francios Jacobus Roos

31 July 2025
Calibration Date:

Calibrated By: I.F.J. Roos

Authorised by: I.F.J. Roos
(Technical Signatory)

----------END OF CERTIFICATE----------

Terms and Conditions

This certificate is issued in accordance with the conditions of the approval granted by SANAS (South African National Accreditation System)

Traceability

Instruments and Standards used as per Calibration Procedure are TRACEABLE to NATIONAL and /or INTERNATIONAL STANDARDS.

Validity of Calibration

The values in this certificate are correct at the time of calibration and related to the DUT identified on this certificate. Subsequent accuracy will depend on factors such as transport, handling methods and frequency of use of this equipment. The Re-calibration period of this equipment should be determined to ensure that the accuracy remains within the required limits. Each instrument or gauge member must have the customers own unique serial number.

Uncertainty of Measurement

The reported uncertainty of measurement is based on a standard uncertainty multiplied by a coverage factor of k = 2, which, unless specifically stated otherwise, provides a level of confidence of approximately 95%, the uncertainty of measurement has been estimated in accordance with the principals defined in the GUM Guide of Uncertainty of Measurement, ISO Geneva, 1993

Disclaimer

WISIO cc will maintain a professional standard in its performance of calibration activities. We will not be liable for claims whatsoever arising out of the use, implementation or inability to use any of the results generated on our certificates. The subsequent accuracy will depend on factors such as transport, care, handling and frequency of use.

Copyright

Copyright of this certificate is owned by WISIO cc This certificate may only be reproduced as a complete, exact facsimile of the original, after prior written approval is obtained from WISIO cc.

Certificate signatures

Electronically signed certificates are only valid as an electronic document in *.pdf format where signatures can be verified. All elctronically signed certificates are null and void if printed as a hard copy certificate. Hard copy certificates will be stamped and manually signed

Note: The Metrological confirmation process is the responsibility of the customer.

Statements of conformity to specifications are not made or implied in this report. Review the results, expanded uncertainty, and specifications to ensure they meet your requirements.

Manufacturers Specifications are used for Permissible Error (Tolerances) where applicable.