

Welcome

In this lecture, we explore real volumetric test data obtained from a vent pipe.

We will:

- Input parameters of a vent pipe used by a major truck **manufacturer**
- Illustrate how a good reference **volume** can be used to filter good parts from bad
- Illustrate how reference **volume** effects the **integrity** of leak rates
- Discuss how this can be scaled upwards for bigger **spatial industries**

Ventilation Pipe

Ventilation pipes can be complex objects in terms of volumetric data sets. They incorporate numerous cylinders and multiple surpluses.

In pressure testing industries, good **reference volumes** allow products to be tested accordingly to an agreed quality standard. The procedure will have its own specification of what is acceptable and what is not. Its not uncommon for distinct companies to have their own set standards and manufacturers will follow these.



Ventilation Pipe via
Automotive Industries

In reality, there exists no perfect seal and the terminology **tightness** is used to refer to how well **fitted** a particular part is. Leak testing equipment exists as a step in the **firewall chain** to prevent poor quality parts reaching global ecosystems. Natural crystallisation processes can and do work to seal minute microscopic leaks which often always go unnoticed in industries which utilise fluid powers.

Leak testing hardware in industry commonly requires a **barometer** unit (**NA** often use psi), reference test **volume** and a max **leak rate**. Aside from this three main properties include time parameters. Adequate amounts of time need be given for parts to be adequately tested. The **leak rate** is emitted by a sensor which measures the vibration (a wobble) upon test part pressurisation.



Ventilation Pipe Measurement

| | | | | | | |
|-------------------|------|------|--------|---------|------|---------|
| Ventilation ... X | | | | | | |
| File | Edit | View | Volume | Surplus | Help | 74039.4 |

| Cylinder | Diameter | Length | Unit | Volume | |
|----------|----------|--------|-----------------|--------------|---------|
| X1_1 | 6 mm | 75 mm | mm ³ | 2120.575041 | 🔗 ⚙️ 🗑️ |
| X1_2 | 6 mm | 75 mm | mm ³ | 2120.575041 | 🔗 ⚙️ 🗑️ |
| X2_1 | 6 mm | 60 mm | mm ³ | 1696.460033 | 🔗 ⚙️ 🗑️ |
| X2_2 | 6 mm | 60 mm | mm ³ | 1696.460033 | 🔗 ⚙️ 🗑️ |
| X2_3 | 6 mm | 60 mm | mm ³ | 1696.460033 | 🔗 ⚙️ 🗑️ |
| X2_4 | 6 mm | 60 mm | mm ³ | 1696.460033 | 🔗 ⚙️ 🗑️ |
| X3 | 6 mm | 209 mm | mm ³ | 5909.335781 | 🔗 ⚙️ 🗑️ |
| X4 | 6 mm | 212 mm | mm ³ | 5994.158783 | 🔗 ⚙️ 🗑️ |
| X5_1 | 6 mm | 163 mm | mm ³ | 4608.716423 | 🔗 ⚙️ 🗑️ |
| X5_2 | 6 mm | 163 mm | mm ³ | 4608.716423 | 🔗 ⚙️ 🗑️ |
| X6 | 6 mm | 806 mm | mm ³ | 22789.113109 | 🔗 ⚙️ 🗑️ |

| Object | Unit | Volume | |
|-------------------|-----------------|--------------------|----|
| 5x FITTING_1 | mm ³ | 2513.2741228718346 | 🗑️ |
| 1x FITTING_2 | mm ³ | 589.0486225480862 | 🗑️ |
| 1x Intake Coil | mm ³ | 6000 | 🗑️ |
| 1x Test Circuitry | mm ³ | 10000 | 🗑️ |

The dataset (seen left) is a real measurement standard for a real life vent pipe used by a major truck manufacturer.

Our platform simplifies the entire process of making complex **volume** datasets. Without volume.cc, a complicated spreadsheet needs to be utilised, maintained and only serves the need of one technician. These spreadsheets become outdated, corrupt and cannot easily be **shared**.

Now this part in particular has eleven cylinders with multiple surpluses. Most reasonable people would agree the volume requirements become extensive as the complexity of a part increases.

Our service is of great benefit because it can act as a transparent layer between public and private industries. As the complexities within supply chains increase, so does the need for a quality protocol which can manage, store and distribute volumetric datasets.

Sound Reference Volumes

| Unit | cc/m | cc/s | mm3/s |
|------|-------|--------|--------|
| 1 | 11.02 | 0.1837 | 183.67 |
| 2 | 10.99 | 0.1832 | 183.17 |
| 3 | 10.80 | 0.1800 | 180.00 |
| 4 | 10.67 | 0.1778 | 177.83 |
| 5 | 10.73 | 0.1788 | 178.83 |
| 6 | 10.62 | 0.1770 | 177.00 |
| 7 | 10.67 | 0.1778 | 177.83 |
| 8 | 10.69 | 0.1782 | 178.17 |
| 9 | 10.80 | 0.1800 | 180.00 |
| 10 | 10.77 | 0.1795 | 179.50 |
| 11 | 10.69 | 0.1782 | 178.17 |
| 12 | 10.72 | 0.1787 | 178.67 |
| 13 | 10.62 | 0.1770 | 177.00 |
| 14 | 10.51 | 0.1752 | 175.17 |
| 15 | 11.13 | 0.1855 | 185.50 |
| 16 | 10.81 | 0.1802 | 180.17 |
| 17 | 10.80 | 0.1800 | 180.00 |
| 18 | 10.80 | 0.1800 | 180.00 |
| 19 | 10.69 | 0.1782 | 178.17 |
| 20 | 10.67 | 0.1778 | 177.83 |

Pressure tested @ 59.1cc

| Unit | cc/m | cc/s | mm3/s |
|------|-------|--------|--------|
| 1 | 13.56 | 0.2260 | 226.00 |
| 2 | 13.36 | 0.2227 | 222.67 |
| 3 | 13.32 | 0.2220 | 222.00 |
| 4 | 13.36 | 0.2227 | 222.67 |
| 5 | 13.36 | 0.2227 | 222.67 |
| 6 | 13.30 | 0.2217 | 221.67 |
| 7 | 13.40 | 0.2233 | 223.33 |
| 8 | 13.52 | 0.2253 | 225.33 |
| 9 | 13.50 | 0.2250 | 225.00 |
| 10 | 13.44 | 0.2240 | 224.00 |
| 11 | 13.40 | 0.2233 | 223.33 |
| 12 | 13.42 | 0.2237 | 223.67 |
| 13 | 13.36 | 0.2227 | 222.67 |
| 14 | 13.36 | 0.2227 | 222.67 |
| 15 | 13.30 | 0.2217 | 221.67 |
| 16 | 13.40 | 0.2233 | 223.33 |
| 17 | 13.44 | 0.2240 | 224.00 |
| 18 | 13.42 | 0.2237 | 223.67 |
| 19 | 13.48 | 0.2247 | 224.67 |
| 20 | 13.44 | 0.2240 | 224.00 |

Pressure tested @ 74.1cc

The test data available when a bad vent pipe undergoes a repeated pressure test shows really how important a satisfactory reference **volume** is. In fact, the evidence is clear that if the reference volume is not satisfactory, the manufacturer is simply not testing them to any reasonable standard.

The mean (average) **leak rates** of a part will differ in respect to its reference **volume**. Higher reference **volume** means more **volume loss** per second. This is a technique to identify problematic gradual leaks and also ensures a more stringent test.

Gradual leaks are defined as a test sensor which vibrates (the wobble) upon its first feed pressurisation phrase and then stops wobbling. The part has been pressurised to the correct **barometer** and no wobble thereafter exists because the part is now stable and thereby verified to be **leak free**.

Good parts will inherit a **volume** loss very close but not equal to zero upon its pressurisation interval.

Sound Reference Volumes

The test data also shows us that when **good quality** parts are tested, the sensor will vibrate a tiny 2.n cubic millimetres. Its not noticeable but given an extensive amount of data, it indicates that the sensor is one which is indeed actually very well calibrated. **Leak detection technologies** from leak testing hardware are an excellent piece of engineering.

And because the data trend is repeatable, we get that consistency which we can recall from lecture 2. Consistency makes everyone comfortable with everything because it works and continues to work.

The manufacturer will communicate what **volume** loss is unacceptable accordingly to their own set of standards. The **volume loss** will only be accurate if the reference volume is satisfactory.

| | cc/m | cc/s | mm3/s |
|-------|---------|-----------|------------|
| Max: | 0.47 | 0.0078333 | 7.83333333 |
| Min: | 0.01 | 0.0001667 | 0.16666667 |
| Mean: | 0.12625 | 0.0021042 | 2.10416667 |

To the observer, the leak rate is equal to zero but given a further resolution it really isn't

Leak caught after given a satisfactory reference volume – this part had been dispatched and had passed a prior test standard. It was found that the pressure was correct but the reference volume was not satisfactory



4.50 4.17 1.17 1.33 1.67 2.67 1.33 1.50 4.00 2.00 1.00 5.00 1.83 0.67 1.83 4.33 2.83 2.50 2.00 4.83 0.67 1.50 0.50 2.67 2.67 1.17

Discussion

Pressurisation and **leak technologies** are very interesting. They are fundamentally important for the successful execution of **spatial industries**. The only difference between the technologies we're using currently and the challenges out there awaiting us within space is the **scale**.

Star ships and **multi planetary bases** will all inherit distinct geometric shapes, they will all use **pressurisation** technologies and the **pressurisation** technology will rely upon sound **leak free** verification techniques.

In the next lecture, we explore **verification**.