

# There and Back Again a DateTime Journey

DATA TYPES FOR DATA SCIENCE IN PYTHON



Jason Myers  
Instructor

# From string to datetime

- The `datetime` module is part of the Python standard library
- Use the `datetime` type from inside the `datetime` module
- `.strptime()` method converts from a string to a `datetime` object

```
from datetime import datetime  
print(parking_violations_date)
```

```
06/11/2016
```

# Parsing strings into datetimes

```
date_dt = datetime.strptime(parking_violations_date,  
                             '%m/%d/%Y')  
  
print(date_dt)
```

```
2016-06-11 00:00:00
```

# Time Format Strings

Directive	Meaning	Example
%d	Day of the month as a zero-padded decimal number.	01, 02, ..., 31
%m	Month as a zero-padded decimal number.	01, 02, ..., 12
%Y	Year with century as a decimal number.	0001, 0002, ..., 2013, 2014, ..., 9998, 9999

Full list available in the Python documentation

# Datetime to String

- `.strftime()` method uses a format string to convert a datetime object to a string

```
date_dt.strftime('%m/%d/%Y')
```

```
'06/11/2016'
```

- `isoformat()` method outputs a datetime as an ISO standard string

```
date_dt.isoformat()
```

```
'2016-06-11T00:00:00'
```


# Let's practice!

DATA TYPES FOR DATA SCIENCE IN PYTHON

# Working with Datetime Components and current time

DATA TYPES FOR DATA SCIENCE IN PYTHON

Jason Myers  
Instructor



# Datetime Components

- `day` , `month` , `year` , `hour` , `minute` , `second` , and more are available from a datetime instance
- Great for grouping data

```
daily_violations = defaultdict(int)
for violation in parking_violations:
    violation_date = datetime.strptime(violation[4],
                                       '%m/%d/%Y')
    daily_violations[violation_date.day] += 1
```



# Datetime Components - Results

```
print(sorted(daily_violations.items()))
```

```
[(1, 80986), (2, 79831), (3, 74610), (4, 69555),  
(5, 68729), (6, 76232), (7, 82477), (8, 72472),  
(9, 80415), (10, 75387), (11, 73287), (12, 74614),  
(13, 75278), (14, 81803), (15, 79122), (16, 80692),  
(17, 73677), (18, 75927), (19, 80813), (20, 80992),  
(21, 78138), (22, 81872), (23, 78104), (24, 63490),  
(25, 78898), (26, 78830), (27, 80164), (28, 81954),  
(29, 80585), (30, 65864), (31, 44125)]
```

# What is the deal with now

- `.now()` method returns the current local datetime
- `.utcnow()` method returns the current UTC datetime

```
from datetime import datetime  
  
local_dt = datetime.now()  
  
print(local_dt)
```

```
2017-05-05 12:30:00.740415
```

# What is the deal with utcnow

```
utc_dt = datetime.utcnow()  
print(utc_dt)
```

```
2017-05-05 17:30:05.467221
```

# Timezones

- Naive datetime objects have no timezone data
- Aware datetime objects have a timezone
- Timezone data is available via the `pytz` module via the `timezone` object
- Aware objects have `.astimezone()` so you can get the time in another timezone

# Timezones in action

```
from pytz import timezone

record_dt = datetime.strptime('07/12/2016 04:39PM',
    ....: '%m/%d/%Y %H:%M%p')

ny_tz = timezone('US/Eastern')

a_tz = timezone('US/Pacific')

ny_dt = record_dt.replace(tzinfo=ny_tz)

la_dt = ny_dt.astimezone(la_tz)
```

# Timezones in action - results

```
print(ny_dt)
```

```
2016-07-12 04:39:00-04:00
```

```
print(la_dt)
```


```
2016-07-12 01:39:00-07:00
```

# Let's practice!

DATA TYPES FOR DATA SCIENCE IN PYTHON

# Time Travel (Adding and Subtracting Time)

DATA TYPES FOR DATA SCIENCE IN PYTHON



Jason Myers  
Instructor



# Incrementing through time

- `timedelta` is used to represent an amount of change in time
- Used to add or subtract a set amount of time from a datetime object

```
from datetime import timedelta  
flashback = timedelta(days=90)  
print(record_dt)
```

```
2016-07-12 04:39:00
```

# Adding and subtracting timedeltas

```
print(record_dt - flashback)
```

```
2016-04-13 04:39:00
```

```
print(record_dt + flashback)
```

```
2016-10-10 04:39:00
```

# Datetime differences

- Use the `-` operator to calculate the difference
- Returns a timedelta with the difference

```
time_diff = record_dt - record2_dt  
type(time_diff)
```

```
datetime.timedelta
```

```
print(time_diff)
```

```
0:00:04
```

# Let's practice!

DATA TYPES FOR DATA SCIENCE IN PYTHON

# HELP! Libraries to make it easier

DATA TYPES FOR DATA SCIENCE IN PYTHON



Jason Myers  
Instructor

# Parsing time with pendulum

- `.parse()` will attempt to convert a string to a pendulum datetime object without the need of the format string

```
import pendulum

occurred = violation[4] + ' ' + violation[5] + 'M'

occurred_dt = pendulum.parse(occurred, tz='US/Eastern')

print(occured_dt)
```

```
'2016-06-11T14:38:00-04:00'
```

# Timezone hopping with pendulum

- `.in_timezone()` method converts a pendulum time object to a desired timezone.
- `.now()` method accepts a timezone you want to get the current time in

```
print(violation_dts)
```

```
[<Pendulum [2016-06-11T14:38:00-04:00]>,
 <Pendulum [2016-04-25T14:09:00-04:00]>,
 <Pendulum [2016-04-23T07:49:00-04:00]>,
 <Pendulum [2016-04-26T07:09:00-04:00]>,
 <Pendulum [2016-01-04T09:52:00-05:00]>]
```

# More timezone hopping

```
for violation_dt in violation_dts:  
    print(violation_dt.in_timezone('Asia/Tokyo'))
```

```
2016-06-12T03:38:00+09:00  
2016-04-26T03:09:00+09:00  
2016-04-23T20:49:00+09:00  
2016-04-26T20:09:00+09:00  
2016-01-04T23:52:00+09:00
```

```
print(pendulum.now('Asia/Tokyo'))
```

```
<Pendulum [2017-05-06T08:20:40.104160+09:00]>
```



# Humanizing differences

- `.in_XXX()` methods provide the difference in a chosen metric
- `.in_words()` provides the difference in a nice expressive form

```
diff = violation_dts[3] - violation_dts[2]  
diff
```

```
<Period [2016-04-26T07:09:00-04:00 ->  
        2016-04-23T07:49:00-04:00]>
```

```
print(diff.in_words())
```

```
'2 days 23 hours 20 minutes'
```

# More human than human

```
print(diff.in_days())
```

```
2
```

```
print(diff.in_hours())
```

```
71
```

# Let's practice!

DATA TYPES FOR DATA SCIENCE IN PYTHON