



Why

We discuss inferring (or learning) functions from examples.

Definitions

A *predictor* $f : \mathcal{U} \rightarrow \mathcal{V}$ is a function from \mathcal{U} to \mathcal{V} . An *inducer* is a function from finite datasets in $\mathcal{U} \times \mathcal{V}$ to predictors from \mathcal{U} to \mathcal{V} . A *learner* is a function family of inducers, indexed by n , each defined for datasets of size n . We call \mathcal{U} the *inputs*, \mathcal{V} the *outputs*, and $f(u)$ the *prediction* of f on $u \in \mathcal{U}$.

Predicting relations

A *relation inducer* is a function from finite datasets in $\mathcal{U} \times \mathcal{V}$ to *relations* on $\mathcal{U} \times \mathcal{V}$. Since we can associate any relation R between \mathcal{U} and \mathcal{V} with a function $f : \mathcal{U} \times \mathcal{V} \rightarrow \{0, 1\}$, $f(u, v) = 1$ if and only if $(u, v) \in R$, the predictor case can accomodate learning general relations, beyond functions.

Notation

Let D be a dataset of size n in $\mathcal{U} \times \mathcal{V}$. Let $g : \mathcal{U} \rightarrow \mathcal{V}$, a predictor, which makes prediction $g(u)$ on input $u \in \mathcal{U}$. Let $G_n : (\mathcal{U} \times \mathcal{V})^n \rightarrow (\mathcal{U} \times \mathcal{V})$ be an inducer, so that $G_n(D)$ is the predictor which the inductor associates with dataset D . Then $\{G_n : (\mathcal{U} \times \mathcal{V})^n \rightarrow \mathcal{P}((\mathcal{U} \times \mathcal{V}))\}_{n \in \mathbf{N}}$ is a learner.

Consistent and complete datasets

Let $D = ((u_i, v_i))_{i=1}^n$ be a dataset and $R \subset X \times Y$ a relation. D is *consistent with* R if each $(u_i, v_i) \in R$. D is *consistent* if there exists a relation with which it is consistent. A dataset is always consistent (take $R = \mathcal{U} \times \mathcal{V}$). D is *functionally consistent* if it is consistent with a function; in this case, $x_i = x_j \Rightarrow y_i = y_j$. D is *functionally complete* if $\cup_i \{x_i\} = X$. In this case, the dataset includes every element of the relation.

Other terminology

Other terms for the inputs include *independent variables*, *explanatory variables*, *precepts*, *covariates*, *patterns*, *instances*, or *observations*. Other terms for the outputs include *dependent variables*, *explained variables*, *postcepts*, *targets*, *outcomes*, *labels* or *observational outcomes*. An input, output pair is sometimes called a *record pair*.

Other terms for a learner include *learning algorithm*, or *supervised learning algorithm*. Other terms for a predictor include *input-output mapping*, *prediction rule*, *hypothesis*, *concept*, or *classifier*.

