Marginalia

Write into the margins!

1 Setup

Put something akin to the following at the start of your .typ file:

```
#import "@preview/marginalia:0.1.3" as marginalia: note, wideblock
#let config = (
    // inner: ( far: 5mm, width: 15mm, sep: 5mm ),
    // outer: ( far: 5mm, width: 15mm, sep: 5mm ),
    // top: 2.5cm,
    // bottom: 2.5cm,
    // book: false,
    // clearance: 12pt,
    // flush-numbers: false,
    // numbering: /* numbering-function */,
)
#marginalia.configure(..config)
#set page(
    // setup margins:
    ..marginalia.page-setup(..config),
    /* other page setup */
```

Where you can then customize config to your preferences. Shown here (as comments) are the default values taken if the corresponding keys are unset.

See the appendix for a more detailed explanation of the configure()
and page-setup() functions.

2 Margin-Notes

By default, the #note[...] command places a note to the right/outer margin, like so:
. By giving the argument reverse: true, we obtain a note on the left/inner margin.o If config.book = true, the side will of course be adjusted automatically.

If • we ⋄ place ■ multiple □ notes ▲ in △ one ▼ line, ⋄ they automatically adjust their positions. Additionally, a dy argument can be passed to shift their initial position by that amount vertically. They may still get shifted around, unless configured otherwise via the shift parameter of #note().

Notes will shift vertically to avoid other notes, wideblocks, and the top page margin. It will attempt to move one note below a wide-block if there is not enough space above, but if there are multiple notes that would need to be rearranged you must assist by manually setting dy such that their initial position is below the wideblock.

Contents

1	Setup 1
2	Margin-Notes 1
	2.1 Markers
	2.2 Styling 2
3	Wide Blocks 2
4	Figures
	4.1 Notefigures
	4.2 Large Figures 3
5	Other Tidbits 3
	5.1 Absolute Placement 3
	5.2 Headers
	and Background 3
6	Troubleshooting / Known
	Bugs 5
7	Thanks
A	Detailed Documentation of
	all Exported Symbols 6

• This is a note.

They can contain any content, and will wrap within the note column.

- Note 1
- Note 2
- Note 3
- □ Note 4
- ▲ Note 5
- △ This note was given 15pt dy, but it was shifted more than that to avoid Notes 1–5.
- This note was given 10cm dy and was shifted less than that to stay on the page.

o Reversed.

This note was given 15pt dy. 13. March 2025 Marginalia Page 2 of 11

- Note from second column.
- Lorem ipsum dolor sit.
- Like so. The lorem-ipsum note was also placed with keeporder.
- Unnumbered notes "avoid" being shifted if possible, preferring to shift other notes up.

Like this.

Unless they are given a dy argument moving them above the

Margin notes also work from within most containers such as blocks or #column()s.•

Blah blah. To force the notes to appear in the margin in the same order as they appear in the text, use #note(keep-order: true)[] for all notes whose relative order is important.

2.1 Markers

The margin notes are decorated with little symbols, which by default hang into the gap. If this is not desired, set the configuration option flush-numbers: true. Setting the argument numbered: false, we obtain notes without icon/number:

To change the markers, you can override config.numbering-function which is used to generate the markers.

2.2 Styling

Both <u>note()</u> and <u>notefigure()</u> accept a text-style and par-style parameter:

- text-style: (size: 5pt, font: ("Iosevka Extended")) gives
- par-style: (spacing: 20pt, leading: -2pt) gives -

The default options here are meant to be as close as possible to the stock footnote style.

Lorem ipsum dolor sit amet.

Lorem ipsum

Lorem dolor sit. ipsum

3 Wide Blocks

The command <code>#wideblock[...]</code> can be used to wrap content in a wide block which spans into the margin-note-column.

Note: when using an asyymetric page layout with book: true, wideblocks which span across pagebreaks are messy, because there is no way for the wideblock to detect the pagebreak and adjust ist position after it.

It is possible to use notes in a wide block: A.A. They will automatically shift downwards to avoid colliding with the wideblock.

▲ Voila.

#wideblock(reverse: true)[...]: The reverse option makes the block extend to the inside margin instead. This is analogous to the reverse option on notes and allows placing notes in their usual column.

Notes above a wideblock will shift upwards if necessary. In this manual, a reverse wideblock is used to set the appendix to make it take up fewer pages. This is also why the appendix is no longer using book: true.

#wideblock(double: true) [...]: The double option makes it extend both ways. Note that setting both reverse: true and double: true is disallowed and will panic.

Figure 1: A notefigure.

Figure 2: A marked notefigure.

4 Figures

4.1 Notefigures

For small figures, you can place them in the margin with marginalia.notefigure. It accepts all arguments figure takes (except placement and scope), plus all arguments note takes (except alignbaseline). However, by default it has no marker, and to get a marker like other notes, you must pass numbered: true, it will get a marker like other notes: •

Page 3 of 11	Marginalia	13. March 2025
Ор	Additionally, the dy argument now takes a relative length, where 100% is the distance between the top of the figure content and the first baseline of the caption. By default, figures have a dy of Opt - 100%, which results in the caption being aligned horizontally to the text. • A label can be attached to the figure using the label argument.	Top (no shift) Top (no shift, no baseline align
	4.2 Large Figures For larger figures, use the following set and show rules:	Figure 3: Aligned to top of figure with dy: Opt.
	<pre>cap: Opt) aption(position: top) caption.where(position: top): note.with(numbered:false, dy:1em)</pre>	
		Figure 4: A figure.
	For wide figures, simply place a figure in a wideblock. The caption gets placed beneath the figure automatically, courtesy of regular wide-block-avoidance.	
wideblock(fi	<pre>gure(image(), caption: [A figure in a wide block.]))</pre>	
		Figure 6: A figure in a reversed
		Figure 6: A figure in a reversed
	5 Other Tidbits	Figure 7: A figure in a double-
	5 Other Tidbits 5.1 Absolute Placement You can place notes in absolute positions relative to the page using place:	Figure 6: A figure in a reversed wide block. Figure 7: A figure in a double-
	5.1 Absolute Placement You can place notes in absolute positions relative to the page using	Figure 6: A figure in a reversed wide block. Figure 7: A figure in a double-
	5.1 Absolute Placement You can place notes in absolute positions relative to the page using place: ote(numbered: false, reverse: true)[Top])	Figure 6: A figure in a reversed wide block. Figure 7: A figure in a double-
place(bottom	5.1 Absolute Placement You can place notes in absolute positions relative to the page using place: ote(numbered: false, reverse: true)[Top]) , note(numbered: false, reverse: true)[Bottom]) To avoid these notes moving about, use shift: false (or shift:	Figure 6: A figure in a reversed wide block. Figure 7: A figure in a double-
<pre>#place(bottom #place(top, n</pre>	5.1 Absolute Placement You can place notes in absolute positions relative to the page using place: ote(numbered: false, reverse: true)[Top]) I, note(numbered: false, reverse: true)[Bottom]) To avoid these notes moving about, use shift: false (or shift: "ignore" if you don't mind overlaps.) ote(numbered: false, shift: false)[Top (no shift)])	Figure 6: A figure in a reversed wide block. Figure 7: A figure in a double-
*place(bottom	5.1 Absolute Placement You can place notes in absolute positions relative to the page using place: ote(numbered: false, reverse: true)[Top]) In note(numbered: false, reverse: true)[Bottom]) To avoid these notes moving about, use shift: false (or shift: "ignore" if you don't mind overlaps.) ote(numbered: false, shift: false)[Top (no shift)]) In note(numbered: false, shift: false)[Bottom (no shift)]) By default, notes are aligned to their first baseline. To align the top of	Figure 6: A figure in a reversed wide block. Figure 7: A figure in a double-

13. March 2025 Marginalia Page 4 of 11

 Also, please don't .update() the marginalia._config directly, this can easily break the notes. In your documents, consider removing this check and simplifying the if a bit.

Here's how the headers in this document were made:

```
#set page(header: context {
 marginalia.notecounter.update(0)
 let book = marginalia._config.get().book
 let leftm = marginalia.get-left()
  let rightm = marginalia.get-right()
  if here().page() > 1 {
    wideblock(double: true, {
      box(width: leftm.width, {
        if not (book) or calc.odd(here().page()) [
          Page
          #counter(page).display("1 of 1", both: true)
        ] else [
          #datetime.today().display(/**/)
      })
      h(leftm.sep)
      box(width: 1fr, smallcaps[Marginalia])
      h(rightm.sep)
      box(width: rightm.width, {
        if not (book) or calc.odd(here().page()) [
          #datetime.today().display(/**/)
        ] else [
          Page
          #counter(page).display("1 of 1", both: true)
     })
   })
 }
```

Not that you should copy them, they're mostly here to showcase the columns and help me verify that everything gets placed in the right spot. And here's the code for the lines in the background:

```
#set page(background: context {
  let leftm = marginalia.get-left()
  let rightm = marginalia.get-right()
  place(top, dy: marginalia._config.get().top,
        line(length: 100%, stroke: luma(90%)))
  place(top, dy: marginalia._config.get().top - page.header-ascent,
        line(length: 100%, stroke: luma(90%)))
  place(bottom, dy: -marginalia._config.get().bottom,
        line(length: 100%, stroke: luma(90%)))
  place(dx: leftm.far,
        rect(width: leftm.width, height: 100%, stroke: (x: luma(90%))))
  place(dx: leftm.far + leftm.width + leftm.sep,
        rect(width: 10pt, height: 100%, stroke: (left: luma(90%))))
  place(right, dx: -rightm.far,
        rect(width: rightm.width, height: 100%, stroke: (x: luma(90%))))
  place(right, dx: -rightm.far - rightm.width - rightm.sep,
        rect(width: 10pt, height: 100%, stroke: (right: luma(90%))))
})
```

Page 5 of 11	Marginalia	13. March 2025	
	6 Troubleshooting / Known Bugs		
	 If the document needs multiple passes to figure out page-breaks, it can break the note positioning. This can usually be resolved by placing a #pagebreak() or #pagebreak(weak: true) in an appropriate location. 	This can happen for example with outlines which barely fit/ don't fit onto the page.	
Notes on the other side are usually fine though.	nuchably, bact to arraid them it negatible	In this manual, for example, it works fine (with warnings) here, ▲ but not on the first page. △ Probably because there aren't many other notes around.	
	 If book is true, wideblocks that break across pages are broken. Sadly there doesn't seem to be a way to detect and react to page-breaks from within a block, so I don't know how to fix this. 		
	• If you encounter anything else which looks like a bug to you, please create an "issue" on GitHub if no-one else has done so already.		
	7 Thanks		
	Many thanks go to Nathan Jessurun for their <u>drafting</u> package, which has served as a starting point and was very helpful in figuring out how to position margin-notes.		
	The wideblock functionality was inspired by the one provided in the <u>tufte-memo</u> template.		
	Also shout-out to <u>tidy</u> , which was used to produce the appendix.		

Page 6 of 11 Marginalia 13. March 2025

A Detailed Documentation of all Exported Symbols

A.1 configure

This will update the marginalia config with the provided config options.

The default values for the margins have been chosen such that they match the default typst margins for a4. It is strongly recommended to change at least one of either inner or outer to be wide enough to actually contain text.

The shown default values are for the first usage of this function. On later calls, unspecified options are kept from the previous configuration state:

```
configure(clearance: 5pt)
configure(book: true)
is equivalent to configure(clearance: 5pt, book: true).
Parameters
  configure(
    inner: dictionary,
    outer: dictionary,
    top: length,
    bottom: length,
    book: boolean,
    clearance: length,
    flush-numbers: boolean,
    numbering: function string
inner: (far: 5mm, width: 15mm, sep: 5mm)
                                               dictionary
Inside/left margins.
• far: Distance between edge of page and margin (note) column.
• width: Width of the margin column.
• sep: Distance between margin column and main text column.
The page inside/left margin should equal far + width + sep.
If partial dictionary is given, it will be filled up with defaults.
outer: (far: 5mm, width: 15mm, sep: 5mm)
                                              dictionary
Outside/right margins. Analogous to inner.
top: 2.5cm
                         Top margin.
             length
bottom: 2.5cm
                length
                            Bottom margin.
book: false
              boolean
• If true, will use inside/outside margins, alternating on each page.
• If false, will use left/right margins with all pages the same.
clearance: 12pt
                   length
Minimal vertical distance between notes and to wide blocks.
flush-numbers: false
                       boolean
```

Disallow note markers hanging into the whitespace.

Functions:

- configure()
- get-left()
- get-right()
- note()
- note-numbering()
- notefigure()
- page-setup()
- wideblock()

Variables:

- notecounter
- <u>note-markers</u>
- note-markers-alternating

Page 7 of 11 Marginalia 13. March 2025

```
numbering: note-numbering function or string
```

Function or numbering-string to generate the note markers from the notecounter.

Examples:

- (..i) => super(numbering("1", ..i)) for superscript numbers
- (..i) => super(numbering("a", ..i)) for superscript letters
- marginalia.note-numbering.with(repeat: false, markers: ()) for small blue numbers

A.2 get-left

Returns a dictionary with the keys far, width, sep containing the respective widths of the left margin on the current page. (On both even and odd pages.)

Mostly internal.

Requires context.

Parameters

```
get-left() → dictionary
```

A.3 get-right

Returns a dictionary with the keys far, width, sep containing the respective widths of the right margin on the current page. (On both even and odd pages.)

Mostly internal.

Requires context.

Parameters

```
get-right() → dictionary
```

A.4 note

Create a marginnote. Will adjust it's position downwards to avoid previously placed notes, and upwards to avoid extending past the bottom margin.

Parameters

```
note(
  numbered: boolean,
  reverse: boolean,
  dy: length,
  align-baseline: boolean,
  keep-order: boolean,
  shift: boolean auto "avoid" "ignore",
  text-style: dictionary,
  par-style: dictionary,
  (body): content
)
```

numbered: true **boolean** Whether to put a mark.

reverse: false boolean Whether to put it in the opposite (inner/left) margin.

Page 8 of 11 Marginalia 13. March 2025

```
dy: Opt length
```

Inital vertical offset of the note. Note may get shifted still to avoid other notes.

```
align-baseline: true boolean
```

Whether to align the baselines or not.

• If false, the top of the note is aligned with the main-text baseline.

```
keep-order: false boolean
```

Notes with keep-order: true are not re-ordered relative to one another.

```
shift: auto boolean or auto or "avoid" or "ignore"
```

Whether the note may get shifted around to avoid other notes.

- true: The note may shift to avoid other notes, wide-blocks and the top/bottom margins.
- false: The note is placed exactly where it appears, and other notes may shift to avoid it.
- "avoid": The note is only shifted if shifting other notes is not sufficent to avoid a collision.
- "ignore": Like false, but other notes do not try to avoid it.
- auto: true if numbered, "avoid" otherwise.

```
text-style: (size: 0.85em, style: "normal", weight: "regular")
dictionary
```

Will be used to set the text style.

```
par-style:
dictionary
(spacing: 1.2em, leading: 0.5em, hanging-indent: 0pt)
```

Will be used to set the par style.

A.5 note-numbering

Format note marker

Parameters

```
note-numbering(
  markers: array(string),
  repeat: boolean,
  (..),
  (number): int
) → content
```

markers: note-markers-alternating array(string)

```
#for i in array.range(1,15) [
    #note-numbering(markers: note-
markers, i)
]\
#for i in array.range(1,15) [
    #note-numbering(markers: note-
markers-alternating, i)
]
```

Page 9 of 11 Marginalia 13. March 2025

```
repeat: true boolean
```

Whether to (true) loop over the icons, or (false) continue with numbers after icons run out.

```
#for i in array.range(1,15) [
    #note-numbering(repeat: true, i)
]\
#for i in array.range(1,15) [
    #note-numbering(repeat: false, i)
]
```

A.6 notefigure

Creates a figure in the margin.

Parameters numbered, reverse, keep-order, shift, text-style and par-style work the same as for note().

Parameters

```
notefigure(
    numbered: boolean,
    reverse: boolean,
    dy: relative length,
    keep-order: boolean,
    shift: boolean auto "avoid" "ignore",
    text-style: dictionary,
    par-style: dictionary,
    gap: length,
    label: none label,
    ⟨content⟩: content,
    ⟨..figureargs⟩: arguments
) → content
```

dy: Opt - 100% relative length

How much to shift the note. 100% corresponds to the height of content + gap + the first baseline.

Thus dy: Opt - 100% aligns the text and caption baselines.

```
gap: 0.55em length
```

Pass-through to #figure(), but used to adjust the vertical position.

label: none or label A label to attach to the figure.

```
(content) content Positional
```

The figure content, e.g. an image. Pass-through to #figure(), but used to adjust the vertical position.

```
(..figureargs) arguments Positional Pass-through to #figure().
```

(E.g. caption)

Page 10 of 11 Marginalia 13. March 2025

A.7 page-setup

Page setup helper

This will generate a dictionary (margin: ...) compatible with the passed config. This can then be spread into the page setup like so:

```
#set page( ..page-setup(..config) )
```

Takes the same options as configure().

Parameters

```
page-setup((..config): dictionary) → dictionary
(..config) dictionary Positional
```

Missing entries are filled with package defaults. Note: missing entries are *not* taken from the current marginalia config, as this would require context.

A.8 wideblock

Creates a block that extends into the outside/right margin.

Note: This does not handle page-breaks sensibly. If config.book = false, this is not a problem, as then the margins on all pages are the same. However, when using alternating page margins, a multi-page wideblock will not work properly. To be able to set this appendix in a many-page wideblock, this code was used:

```
#configure(..config, book: false)

#set page(..page-setup(..config, book: false))

#wideblock(reverse: true)[...]

Parameters

wideblock(reverse: boolean, double: boolean, (body): content) → content

reverse: false boolean Whether to extend into the inside/left margin instead.

double: false boolean
```

Whether to extend into both margins. Cannot be combined with reverse.

A.9 notecounter counter

The counter used for the note icons.

If you use <u>note-numbering()</u> without <u>note-numbering.repeat</u>, it is reccommended you reset this occasionally, e.g. per heading or per page.

```
notecounter.update(1)
```

A.10 note-markers

Icons to use for note markers.

```
("◆", "●", "■", "▲", "♥", "◇", "○", "□", "△", "♡")
```

Mostly internal.

Page 11 of 11		Marginalia	13. March 2025	
rage II of II		MARGINALIA	15. March 2025	
A.11 note-	mar	kers-alternating		
Icons to use fo	or not	e markers, alternating filled/outlined.		
("•", "0", "	• ", '	◇", "■", "□", "▲", "△", "♥", "♡")		