

Theoretic

Contents

1 Summary	1	Proposition A.1 Funky!	A2
Theorem 1.2 Foo	1	A.7 show-entry-as	A2
1.1 Setup	1	A.8 show-ref	A3
2 Features	1	Theorem A.3 Pythagoras	A3
3 Styling	3	Theorem Only Named	A3
4 Preset Styles	4	A.9 solutions	A4
4.1 basic	4	A.10 theorem	A4
4.2 fancy	4	Theorem 2 Pythagoras	A4
4.3 bar	5	Theorem A.12 AAAAA / ZZZZZZ	A6
A Detailed Documentation of all Exported Symbols	A1	Theorem A.14 Positional	A6
A.1 fmt-body	A1	Theorem A.15 Named	A6
A.2 fmt-prefix	A1	Theorem A.16 Mixed	A6
A.3 proof	A1	A.11 toc	A6
A.4 proof-fmt-prefix	A1	Theorem A.17 Z	A8
A.5 qed	A2	Theorem A.18 A	A8
A.6 restate	A2	A.12 toc-entry	A8
		A.13 thm-counter	A10
		B Solutions	A10

1 Summary

This package provides opinionated functions to create theorems and similar environments.

```
#theorem[This is a theorem.]
#proof[
  Ends with Equation? No Problem:
  $ norm(x) = sqrt( sum_(k = 1)^d x_k ) . $
]
#theorem(<thm:foo>)[Foo][This is a named theorem.]
#proof[@thm:foo-][
  - Ends with a list or enum? Easy.
]
```

Theorem 1.1 This is a theorem.

Proof. Ends with Equation? No Problem:

$$\|x\| = \sqrt{\sum_{k=1}^d x_k}.$$

Theorem 1.2 (Foo) This is a named theorem.

Proof of Theorem 1.2.

- Ends with a list or enum? Easy.

1.1 Setup

Put the following at the top of your document:

```
#import "@preview/theoretic:0.2.0" as theoretic: theorem, proof, qed
#show ref: theoretic.show-ref // Otherwise, references won't work.

// set up your needed presets
#let corollary = theorem.with(kind: "corollary", supplement: "Corollary")
#let example = theorem.with(kind: "example", supplement: "Example", number: none)
// ..etc
```

See `#theoretic.theorem()` (Section A.10) for a detailed description of customization options.

2 Features

- Except for `#show ref: theoretic.show-ref`, no “setup” is necessary. All configuration is achieved via parameters on the `#theoretic.theorem()` function. Use `theorem.with(..)` for your preset needs. → `#theoretic.theorem()`

- Automatic numbering. If your headings are numbered, it will use top-level heading numbers as the first component, otherwise it will simply number your theorems starting with Theorem 1.

```
#theorem(number: "!!")[
  Number can be overridden per-theorem.
]
#theorem(number: 400)[
  If a `number` is passed (as opposed to a string or
  content),
]
#theorem[
  ...subsequent theorems will pick it up.
]
```

Theorem !! Number can be overridden per-theorem.

Theorem 2.400 If a number is passed (as opposed to a string or content),

Theorem 2.401 ...subsequent theorems will pick it up.

- Flexible References via specific supplements.

→ [#theoretic.show-ref\(\)](#)

```
@thm:foo vs @thm:foo[-] vs @thm:foo[--] vs @thm:foo[!]
vs @thm:foo[!!] vs @thm:foo[!!!] vs @thm:foo[?] vs
@thm:foo[Statement]
```

Theorem 1.2 (Foo) vs Theorem 1.2 vs 1.2 vs Foo
(Theorem 1.2) vs Foo (1.2) vs Foo vs Theorem vs
Statement 1.2 (Foo)

- Custom outlines: Outline for headings *and/or* theorems.

→ [#theoretic.toc\(\)](#)

- Filter for specific kinds of theorem to create e.g. a list of definitions.
- Optionally sorted alphabetically!
- Theorems can have a different title for outlines (`theorem(toctitle: ...)`) and can even have multiple entries in a sorted outline.
- Highly customizable!
 - (And this customization can be reused for regular outlines)

→ [#theoretic.toc-entry\(\)](#)

→ [#theoretic.show-entry-as\(\)](#)

- Exercise solutions:

→ [#theoretic.solutions\(\)](#)

- Every theorem environment can have a solution, which is shown in a separate section.
- Solutions section automatically hides itself if there are no solutions to show.

```
#theorem(kind: "exercise", supplement: "Exercise",
  solution: [
    // no cheating! //
  ])[
  Go look for the solution of this exercise at the end of
  this document.
]
```

Exercise 2.402 Go look for the solution of this exercise at the end of this document.¹

- Automatic QED placement!

→ [#theoretic.proof\(\)](#) & [#theoretic.qed\(\)](#)

In most cases, it should place the QED symbol appropriately automatically:

```
#proof[This is a proof. $x=y$]
#proof[
  This is a proof.
  $ x = y $
]
#proof[
  #set math.equation(numbering: "(1)")
  This is a proof.
  $ x = y $
]
```

Proof. This is a proof. $x = y$ ■

Proof. This is a proof.

$$x = y$$

Proof. This is a proof.

$$x = y \quad (1)$$

■

```
#proof[
  This is a proof.
  - #lorem(3)
]
```

¹Solution in Appendix

```

]
#proof[
  This is a proof.
  - #lorem(3) $ x = y $
]
#proof[
  This is a proof.
  + #lorem(3)
  + #lorem(3)
  + #lorem(3)
  + #lorem(3)
]

```

Proof. This is a proof.
 ▶ Lorem ipsum dolor. ■

Proof. This is a proof.
 ▶ Lorem ipsum dolor.

$$x = y$$
 ■

Proof. This is a proof.
 1. Lorem ipsum dolor.
 1. Lorem ipsum dolor.
 1. Lorem ipsum dolor. ■

Specifically, it works for lists, enums, and unnumbered block equations, which may be nested. If your proof ends with some other block, you should might want to place a `#qed()` manually. For proper alignment with a block equation, use

```
#set math.equation(numbering: (..) => {qed()}, number-align: bottom)
```

placed directly in front of the equation.

- Any theorem can be restated. → `#theoretic.restate()`

```
theoretic.restate(<thm:foo>)
// the prefix links to the original
```

Theorem 1.2 (Foo) This is a named theorem.

3 Styling

In case you are not happy with one of the styled presets, or if you want to add more kinds of theorem – e.g. for other languages, you can customize the formatting by overriding the `fmt-prefix`, `fmt-body`, `fmt-suffix` and `block-args` parameters.

For how this can look, I recommend looking at how the predefined styles are made: See the code on [GitHub](#).

4 Preset Styles

Use with

```
#import "lib.typ" as theoretic
#import theoretic.styles.<name>: *
```

4.1 basic

Theorem 4.1. This is an example theorem created using `#theorem[...]`.

Proposition 4.2. Using `#proposition[...]`.

Lemma 4.3. Using `#lemma[...]`.

Corollary 4.4. Using `#corollary[...]`.

Definition 4.5. Using `#definicion[...]`.

Exercise 4.6. Using `#exercise[...]`.

Algorithm 4.7. Using `#algorithm[...]`.

Axiom 4.8. Using `#axiom[...]`.

Example. Using `#example[...]`.

Counter-Example. Using `#counter-example[...]`.

Remark. Using `#remark[...]`.

Note. Using `#note[...]`.

Claim. Using `#claim[...]`.

Proof. Using `#proof[...]`.

Theorem 4.9 (Title). This is an example theorem created using `#theorem(toctitle: none)[Title][...]`.

Proposition 4.10 (Title). Lorem ipsum dolor.

Lemma 4.11 (Title). Lorem ipsum dolor.

Corollary 4.12 (Title). Lorem ipsum dolor.

Definition 4.13 (Title). Lorem ipsum dolor.

Exercise 4.14 (Title). Lorem ipsum dolor.

Algorithm 4.15 (Title). Lorem ipsum dolor.

Axiom 4.16 (Title). Lorem ipsum dolor.

Example (Title). Lorem ipsum dolor.

Counter-Example (Title). Lorem ipsum dolor.

Remark (Title). Lorem ipsum dolor.

Note (Title). Lorem ipsum dolor.

Claim (Title). Lorem ipsum dolor.

■ *Proof of Title.* Lorem ipsum dolor. ■

4.2 fancy

This style is intended² for use with a font that supports stretch: 85% and weight: "semibold". It is here shown using the font "Besley*", which you can download on GitHub.

Theorem 4.18 This is an example theorem created using `#theorem[...]`.

Proposition 4.19 Using `#proposition[...]`.

Lemma 4.20 Using `#lemma[...]`.

Corollary 4.21 Using `#corollary[...]`.

Definition 4.22 Using `#definicion[...]`.

Exercise 4.23 Using `#exercise[...]`.

Algorithm 4.24 Using `#algorithm[...]`.

Axiom 4.25 Using `#axiom[...]`.

Example 4.26 Using `#example[...]`.

Counter-Example 4.27 Using `#counter-example[...]`.

Remark 4.28 Using `#remark[...]`.

Note 4.29 Using `#note[...]`.

Claim 4.30 Using `#claim[...]`.

Proof. Using `#proof[...]`.

Theorem 4.31 Title This is an example theorem created using `#theorem(toctitle: none)[Title][...]`.

Proposition 4.32 Title Lorem ipsum dolor.

Lemma 4.33 Title Lorem ipsum dolor.

Corollary 4.34 Title Lorem ipsum dolor.

Definition 4.35 Title Lorem ipsum dolor.

Exercise 4.36 Title Lorem ipsum dolor.

Algorithm 4.37 Title Lorem ipsum dolor.

Axiom 4.38 Title Lorem ipsum dolor.

Example 4.39 Title Lorem ipsum dolor.

Counter-Example 4.40 Title Lorem ipsum dolor.

Remark 4.41 Title Lorem ipsum dolor.

Note 4.42 Title Lorem ipsum dolor.

Claim 4.43 Title Lorem ipsum dolor.

□ *Proof of Title.* Lorem ipsum dolor. □

²It still looks okay in other fonts, but it does not reach full potential. Compare: **Lemma 4.17 Lorem** ipsum.

4.3 bar

Theorem 4.44

This is an example theorem created using `#theorem[...]`.

Proposition 4.45

Using `#proposition[...]`.

Lemma 4.46

Using `#lemma[...]`.

Corollary 4.47

Using `#corollary[...]`.

Definition 4.48

Using `#definitor[...]`.

Exercise 4.49

Using `#exercise[...]`.

Algorithm 4.50

Using `#algorithm[...]`.

Axiom 4.51

Using `#axiom[...]`.

Example

Using `#example[...]`.

Counter-Example

Using `#counter-example[...]`.

Remark

Using `#remark[...]`.

Note

Using `#note[...]`.

Claim

Using `#claim[...]`.

Proof: Using `#proof[...]`.

Theorem 4.52

This is an example theorem created using `#theorem(toctitle: none)[Title][...]`.

Proposition 4.53

Lorem ipsum dolor.

Lemma 4.54

Lorem ipsum dolor.

Corollary 4.55

Lorem ipsum dolor.

Definition 4.56

Lorem ipsum dolor.

Exercise 4.57

Lorem ipsum dolor.

Algorithm 4.58

Lorem ipsum dolor.

Axiom 4.59

Lorem ipsum dolor.

Example

Lorem ipsum dolor.

Counter-Example

Lorem ipsum dolor.

Remark

Lorem ipsum dolor.

Note

Lorem ipsum dolor.

Claim

Lorem ipsum dolor.

Proof of Title: Lorem ipsum dolor.

Title

Title

Title

Title

Title

Title

Title

Title

Title

Title

Title

Title

Title

A Detailed Documentation of all Exported Symbols

A.1 fmt-body

Function to format the body

Default value of theorem.fmt-body.

Parameters

`fmt-body(<body>: content, <solution>: content) → content`

`<body>` `content` Positional Theorem content.

A.2 fmt-prefix

Function to run at beginning of theorem.

Default value of theorem.fmt-prefix.

```
#fmt-prefix([Theorem], [1.34], none)...  
#fmt-prefix([Theorem], [1.34], [Pythagoras])...
```

Theorem 1.34 ...
Theorem 1.34 (Pythagoras) ...

Parameters

`fmt-prefix(<supplement>: content, <number>: content none, <title>: content none) → content`

A.3 proof

This is just theorem() with different defaults.

```
#proof[#lorem(5)]  
#proof[@pythagoras[!]][#lorem(6)]
```

Proof. Lorem ipsum dolor sit amet. ■
Proof of Pythagoras (Theorem A.3). Lorem ipsum
dolor sit amet, consectetur. ■

Parameters

```
proof(  
  fmt-prefix: function,  
  fmt-suffix: function none,  
  kind: "proof" string,  
  supplement: "Proof" content,  
  number: none auto none integer content,  
  <..args>: arguments  
) → content
```

`fmt-prefix`: proof-fmt-prefix `function`

`fmt-suffix`: qed.with(force: false) `function` or `none`

A.4 proof-fmt-prefix

Function to run at beginning of proof.

Default value of `proof.fmt-prefix`.

```
#proof-fmt-prefix([Proof], none, none)...  
#proof-fmt-prefix([Proof], none, [@pythagoras])...
```

Proof. ...
Proof of Theorem A.3 (Pythagoras). ...

Parameters

`proof-fmt-prefix`(`<supplement>`: `content`, `<number>`: `content` `none`, `<title>`: `content` `none`) → `content`

A.5 qed

Place a QED mark and clear the `_thm_needs_qed` flag, so that the theorem environment itself won't place one.

See `proof.fmt-suffix`.

Parameters

`qed`(`suffix`: `sym.qed` `content`, `force`: `boolean`) → `content`

`force`: `true` `boolean` Whether to place suffix no matter the `_thm_needs_qed` flag.

A.6 restate

Re-state a theorem.

It will reuse the original kind, supplement, number, title, body, and styling. It will *not* re-emit the solution or label, and it will use `toctitle`: `none` to avoid duplicate toc entries.

```
#let proposition = theorem.with(  
  kind: "proposition",  
  supplement: "Proposition",  
  fmt-prefix: (s,n,t) => smallcaps({ s ; if n ≠ none  
[ #n]; if t ≠ none [ (#t)]; h(1em) })  
)  
#proposition(<funky>)[Funky!][Blah _blah_ blah.]  
Restated:  
#restate("funky")  
Restated with customizations:  
#restate(<funky>, fmt-body: (b, s) => text(red, {b; s}))
```

PROPOSITION A.1 (FUNKY!) Blah *blah* blah.
Restated:
PROPOSITION A.1 (FUNKY!) Blah *blah* blah.
Restated with customizations:
PROPOSITION A.1 (FUNKY!) **Blah *blah* blah.**

Parameters

`restate`(`<label>`: `label` `string`, `<..args>`) → `content`

`<label>` `label` or `string` Positional Label of the theorem to restate.

`<..args>` Positional

Override arguments for the theorem function.

(Setting body, solution, kind, supplement, number, title or toctitle here is not recommended.)

A.7 show-entry-as

Helper function to adapt actual outlines to look the same as those made with `toc()`. This is useful if you want to have e.g. a list of figures and a list of definitions and want them to share their style.

Note: For typst versions ≤ 0.12 , this function is a bit “hacky” and might not always work. (It deconstructs the `outline.entry` based on heuristics.)

```
#import theoretic: show-entry-as, toc-entry

#outline(target: figure, title: [Typst Default])

#show outline.entry: show-entry-as(toc-entry.with(hanging-indent: 60pt, /*...*/))
#outline(target: figure, title: [Using `theoretic.toc-entry`])

#figure(
  caption: [Example Figure],
  block(height: 2em, width: 100%, fill: gradient.linear(..color.map.viridis))
)
```

Typst Default

Figure 1 Example Figure A3

Using theoretic.toc-entry

Figure 1 Example Figure A3



Figure 1: Example Figure

Parameters

`show-entry-as(<toc-entry>: function)`

`<toc-entry>` `function` Positional

Customize `toc-entry()` used.

Expects a function taking five positional arguments (level, target, prefix, body, page).

A.8 show-ref

Show-rule-function to be able to @ labelled theorems.

Use via `#show ref: show-ref` at the beginning of your document.

```
#show ref: theoretic.show-ref
#theorem(label: <fact>, supplement: "Fact")[#lorem(2)]
#theorem(label: <pythagoras>,"Pythagoras")[#lorem(2)]
#theorem(label: <z1>, title: "Only Named", number: none)
[#lorem(2)]
#theorem(label: <y>, number: "Y")[#lorem(2)]
#theorem(label: "5", number: none)[#lorem(2)]
```

As a consequence of @fact and @pythagoras[!].

Fact A.2 Lorem ipsum.

Theorem A.3 (Pythagoras) Lorem ipsum.

Theorem (Only Named) Lorem ipsum.

Theorem Y Lorem ipsum.

Theorem Lorem ipsum.

As a consequence of Fact A.2 and Pythagoras (A.3)...

The reference can be controlled via the supplement passed:

	BOTH	WITHOUT TITLE	WITHOUT NUMBER	NEITHER
@ref (Full)	Theorem A.3 (Pythagoras)	Fact A.2 / Theorem Y	Theorem (Only Named)	Theorem
@ref[-] (Compact)	Theorem A.3	Fact A.2 / Theorem Y	Theorem (Only Named)	Theorem

@ref[--] (Number)	<u>A.3</u>	<u>A.2 / Y</u>	(Only Named)	<u>Theorem</u>
@ref[!] (Inverted)	Pythagoras (Theorem A.3)	Fact A.2 / <u>Theorem Y</u>	Only Named (Theorem)	<u>Theorem</u>
@ref[!!] (Compact Inverted)	Pythagoras (A.3)	Fact A.2 / <u>Theorem Y</u>	Only Named	<u>Theorem</u>
@ref[!!!] (Name)	Pythagoras	Fact A.2 / <u>Theorem Y</u>	Only Named	<u>Theorem</u>
@ref[?] (Kind)	<u>Theorem</u>	Fact / Theorem	Theorem	<u>Theorem</u>
@ref[Custom] (Custom Supplement)	Custom A.3 (Pythagoras)	Custom A.2 / <u>Custom Y</u>	Custom (Only Named)	<u>Custom</u>

Note: the fact that references and links in this document are underlined in gray is achieved with a separate `@show` link: it \Rightarrow `underline(..)` rule, and not because of this function.

Parameters

`show-ref(<it>: ref)`

A.9 solutions

List all solutions, if any.

See Section B for how it looks. Currently not customizable, working on it.

Parameters

`solutions(title: "Solutions" content) \rightarrow content`

A.10 theorem

Theorem Environment

```
#set heading(numbering: none)

#theorem[If the headings are not numbered, theorem
numbering starts at 1.]

= Heading
#theorem(title: "Pythagoras")[
  Given a right-angled triangle, the length
  of the hypotenuse squared is equal to the
  sum of the squares of the remainig sides'
  lengths.
]
```

Theorem 1 If the headings are not numbered, theorem numbering starts at 1.

Heading

Theorem 2 (Pythagoras) Given a right-angled triangle, the length of the hypotenuse squared is equal to the sum of the squares of the remainig sides' lengths.

Parameters

```
theorem(
  fmt-prefix: function,
  fmt-body: function,
  fmt-suffix: function none,
  block-args: dict,
  kind: string,
  supplement: content,
  number: auto none integer content,
  title: none content,
  toctitle: auto none content array,
  label: none label string,
  solution: none content,
```

```

    <..unnamed-and-body>: arguments
  ) → content

```

fmt-prefix: fmt-prefix function

fmt-body: fmt-body function

fmt-suffix: none function or none

Will be called at the end of the theorem if `_thm_needs_qed` hasn't been cleared. (E.g. by `qed()`)

block-args: (:) dict Arguments to pass to the `#block[]` containing the theorem.

kind: "theorem" string Used for filtering e.g. when creating table of theorems.

supplement: "Theorem" content

What to label the environment.

It is recommended to keep kind and supplement matching (except for “subtypes”, e.g. one might have the kind of “Example” and “Counter-Example” both as “example”)

number: auto auto or none or integer or content

- If `auto`, will continue numbering from last numbered theorem.
- If `integer`, it will continue the numbering of later theorems from the given number.
- If `content`, it is shown as-is, with no side-effects.

```

#let corollary = theorem.with(
  kind: "corollary",
  supplement: "Corollary")

#corollary[#lorem(2)]

#corollary(number: none)[Skip number]
#corollary[Resume numbering]

#corollary(number: "X")[Custom "number"]
#corollary[Resume numbering]

#corollary(number: 10)[Set number]
#corollary[Continue from set number]

```

```

Corollary A.3  Lorem ipsum.
Corollary     Skip number
Corollary A.4  Resume numbering
Corollary X    Custom "number"
Corollary A.5  Resume numbering
Corollary A.10 Set number
Corollary A.11 Continue from set number

```

title: none none or content Title of the Theorem. Usually shown in parentheses after the number.

This can also be passed as a positional argument.

toctitle: auto auto or none or content or array

Title of the Theorem to be used in outlines.

- `auto` to use the title.
- `none` to hide it from the outlines.

If you pass an array, in *sorted* outlines (`toc.sort`) it will be split into multiple entries. All but the first one are marked as secondary.

```

#theorem(
  title: [A to Z],
  toctitle: ([AAAAA], [ZZZZZ])

```

```
)[
  Compare how this appears in different outlines!
]
```

Theorem A.12 (A to Z) Compare how this appears in different outlines!

label: `none` or `label` or `string`

Label (for references)

This can also be passed as a positional argument. In that case it must be a label and not a string.

NB: Simply putting a `<label>` after the `#theorem[]` does not work for referencing.

solution: `none` or `content`

Optional Solution. See also `solutions()`.

```
#theorem(solution: [This will show up wherever
`#theoretic.solutions()` is placed.])[#lorem(5)]
```

Theorem A.13 Lorem ipsum dolor sit amet.³

<..unnamed-and-body> `arguments` Positional

The last positional argument given is used as the theorem body.

Other positional arguments are used for the title and label, depending on their type.

```
// Any of these work:
#theorem(<positional>)[Positional][#lorem(4)]
#theorem(label: <named>, title: [Named])[#lorem(4)]
#theorem([Mixed], label: <mixed>)[#lorem(4)]
```

Theorem A.14 (Positional) Lorem ipsum dolor sit.

Theorem A.15 (Named) Lorem ipsum dolor sit.

Theorem A.16 (Mixed) Lorem ipsum dolor sit.


A.11 toc

Create an outline that includes named theorems.

Can be styled with show rules for `outline.entry()`. See the source code of this manual for an example.

```
#heading(outlined: false, level: 3)[
  Contents
]
#toc(depth: 1)
```

³Solution in Appendix



Contents

1 Summary 1
 Theorem 1.2 Foo 1
2 Features 1
3 Styling 3
4 Preset Styles 4
A Detailed Documentation of all Exported
 Symbols A1
 Proposition A.1 Funky! A2
 Theorem A.3 Pythagoras A3
 Theorem Only Named A3
 Theorem 2 Pythagoras A4
 Theorem A.12 AAAAAA / ZZZZZZ A6
 Theorem A.14 Positional A6
 Theorem A.15 Named A6
 Theorem A.16 Mixed A6
 Theorem A.17 Z A8
 Theorem A.18 A A8
B Solutions A10

Parameters

```
toc(  
  depth: integer,  
  exclude: array (string),  
  level: integer auto,  
  toc-entry: function,  
  sort: bool  
) -> content
```

depth: 2 integer Maximum depth of headings to consider

exclude: ("proof", "solution") array (string) list of theorem.kinds to ignore.

```
#heading(outlined: false, level: 3)[  
  Table of Examples  
]  
#toc(  
  depth: 0,  
  exclude: ("proof", "solution", "theorem")  
)
```

Table of Examples
Proposition A.1 Funky! A2

level: auto integer or auto Fake level to use for theorems. If auto, it will use depth + 1.

toc-entry: toc-entry function

Customize toc-entry() used.

Expects a function taking five positional arguments (level, target, prefix, body, page).

sort: false bool Whether to sort the entries alphabetically.

Only respected if depth is 0.

If true, this will also split entries where toctitle is an array into separate entries.

```
#theorem("Z")[Blah blah.]
#theorem("A")[Blah blah.]
#heading(outlined: false, level: 3)[
  Sorted Table of Theorems
]
#set text(size: 9pt)
#toc(
  depth: 0,
  sort: true,
  toc-entry: toc-entry.with(hanging-indent: 60pt),
)
```

Theorem A.17 (Z) Blah blah.

Theorem A.18 (A) Blah blah.

Sorted Table of Theorems

Theorem A.18	A	A8
Theorem A.12	AAAAA	A6
Theorem 1.2	Foo	1
Proposition A.1	Funky!	A2
Theorem A.16	Mixed	A6
Theorem A.15	Named	A6
Theorem	Only Named	A3
Theorem A.14	Positional	A6
Theorem A.3	Pythagoras	A3
Theorem 2	Pythagoras	A4
Theorem A.17	Z	A8
Theorem A.12	(ZZZZZZ)	A6

A.12 toc-entry

Create a toc entry.

Pass this to `toc()` using `.with(..)` to customize the `fmt-` parameters used.

This is used because since Typst 0.13, it is no longer possible to call `outline.entry` outside of an actual outline element, and one “cannot outline metadata”.

This manual uses

```
set par(justify: false)
let indents = (0pt, 15pt, 37pt)
let hang-indents = (15pt, 22pt, 54pt)
let text-styles = ((weight: 700), (size: 10pt), (size: 9pt, weight: 500), (size: 9pt, fill: luma(20%)), )
theoretic.toc(toc-entry: theoretic.toc-entry.with(
  indent: (level) => { indents.at(level - 1) },
  hanging-indent: (level) => { hang-indents.at(level - 1) },
  fmt-prefix: (prefix, level, _s) => {
    set text(..text-styles.at(level - 1), number-width: "tabular")
    prefix
    h(4pt)
  },
  fmt-body: (body, level, _s) => {
    set text(..text-styles.at(level - 1))
    body
  },
  fmt-fill: (level, _s) => {
    if level == 2 {
      set text(..text-styles.at(2))
      box(width: 1fr, align(right, repeat(gap: 9pt, justify: false, [.])))
    }
  },
  fmt-page: (page, level, _s) => {
    set text(..text-styles.at(level - 1), number-width: "tabular")
    box(width: 18pt, align(right, [#page]))
  },
  above: (level) => {
    if level == 1 {
      auto // paragraph spacing
    } else {
      7pt
    }
  }
)
```

```

    },
    below: auto,
  ))

```

Parameters

```

toc-entry(
  <level>: int,
  <target>: location,
  <prefix>: content none,
  <body>: content,
  <page>: content,
  secondary: boolean,
  indent: relative length function,
  hanging-indent: relative length function auto,
  above: relative length function,
  below: relative length function,
  fmt-prefix: (prefix, level, secondary) => if prefix ≠ none {
    prefix
    h(0.5em, weak: false)
  } function,
  fmt-body: (body, level, secondary) => if secondary [(#body) ] else [#body ] function,
  fmt-fill: (level, secondary) => box(width: 1fr, repeat[.~]) function,
  fmt-page: (page, level, secondary) => page function
)

```

secondary: false boolean

This is true for entries where the toc-title is an array, the entry was split and this is *not* the first one (in order specified).

indent: 1em relative length or function How much to indent each entry.

- If **relative length**, it will be multiplied with level - 1.
- If **function**, will be called with the level as argument.

hanging-indent: auto relative length or function or auto

How much more to indent subsequent lines (in addition th `toc-entry.indent`).

If the prefix is shorter than this, this will lead to a gap between prefix and body; If the prefix is longer, the body will start immediately after the prefix.

- If **function**, will be called with the level as argument.
- If **auto**, will use the width of the prefix

```

#let example-entry = theoretic.toc-entry.with(1, here(),
[Section 1.], lorem(6), [0])
#let example-entry-2 = theoretic.toc-entry.with(2, here(),
[Section 1.1.], lorem(6), [0])

// aligned with end of prefix
#example-entry(hanging-indent: auto)
#example-entry-2(hanging-indent: auto)

#example-entry(hanging-indent: 1em)
#example-entry-2(hanging-indent: 1em)
#example-entry(hanging-indent: 80pt)
#example-entry-2(hanging-indent: 80pt)

```

Section 1. Lorem ipsum dolor sit amet, consecte-	
tur.	0
Section 1.1. Lorem ipsum dolor sit amet, con-	
sectetur.	0
Section 1. Lorem ipsum dolor sit amet, consecte-	
tur.	0
Section 1.1. Lorem ipsum dolor sit amet, con-	
sectetur.	0
Section 1. Lorem ipsum dolor sit amet,	
consectetur.	0
Section 1.1. Lorem ipsum dolor sit	
amet, consectetur.	0

above: 0.7em relative length or function If function, will be called with the level as argument.

below: 0.7em relative length or function If function, will be called with the level as argument.

A.13 thm-counter counter

Counts theorems.

In most cases, it is not necessary to reset this manually, it will get updated accordingly if you pass an integer to `theorem.number`.

B Solutions

Solution of Exercise 2.402. Yay! you found it!

Solution of Theorem A.13. This will show up wherever `#theoretic.solutions()` is placed.