Indexing and Query Optimization

mongoDB

Agenda

- What are indexes?
- Why do I need them?
- Working with indexes in MongoDB
- Optimize your queries
- Avoiding common mistakes

What Are Indexes?



What Are Indexes?

Imagine you're looking for a recipe in a cookbook ordered by recipe name. Looking up a recipe by name is quick and easy.

Consult the Index

http://files.backyardchickens.com/images/BYC-Cookbook-index-3.gif

mongoDB

Linked List

Finding 7 in a Linked List



Finding 7 In a Tree



Indexes in MongoDB are B-Trees



Queries, inserts and deletes: O(log(n)) time

B-Trees



Indexes are the single biggest tunable performance factor in MongoDB

Absent or suboptimal indexes are the most common avoidable MongoDB performance problem.

Why do I need indexes?

A brief story

Working with Indexes in MongoDB

mongoDB

How Do I Create Indexes?

```
// Create an index if one does not exist
db.recipes.ensureIndex ( { main_ingredient : 1 } )
```

```
// The client remembers the index and raises no errors
db.recipes.ensureIndex( { main_ingredient : 1 } )
```

* 1 means ascending, -1 descending

What Can Be Indexed?

```
// Multiple fields (compound key indexes)
db.recipes.ensureIndex({
    main_ingredient: 1,
    calories: -1
})

// Arrays of values (multikey indexes)
{
    name: 'Chicken Noodle Soup’,
    ingredients : [ 'chicken', 'noodles’ ]
}

db.recipes.ensureIndex( { ingredients : 1 } )
```

What Can Be Indexed?

```
// Embedded documents
{
    name : 'Apple Pie',
    contributor : {
        name : 'Joe American',
        id : 'joea123'
    }
}

db.recipes.ensureIndex ( { 'contributor.id' : 1 } )

db.recipes.ensureIndex ( { 'contributor' : 1 } )
```

How Do I Manage Indexes?

```
// List a collection's indexes
db.recipes.getIndexes()
db.recipes.getIndexKeys()

// Drop a specific index
db.recipes.dropIndex ( { ingredients : 1 } )

// Drop all indexes and recreate them
db.recipes.reIndex( )

// Default (unique) index on _id
```

Background Index Builds

```
// Index creation is a blocking operation that can take a long time
// Background creation yields to other operations
db.recipes.ensureIndex (
    { ingredients: 1 },
    { background: true }
)
```

Options

- Uniqueness constraints (unique, dropDups)
- Sparse Indexes

Uniqueness Constraints

```
// Only one recipe can have a given value for name
db.recipes.ensureIndex( { name: 1 }, { unique: true } )


// Force index on collection with duplicate recipe names – drop the duplicates
db.recipes.ensureIndex(
    { name: 1 },
    { unique: true, dropDups: true }
)
```

* dropDups should be used with caution

Sparse Indexes

```
// Only documents with field calories will be indexed
db.recipes.ensureIndex(
    { calories : -1 },
    { sparse : true }
)
// Allow multiple documents to not have calories field
db.recipes.ensureIndex (
    { name: 1 , calories : -1 },
    { unique : true, sparse : true }
)
```

* Missing fields are stored as null(s) in the index

Other Index Types

- Geospatial Indexes (2d Sphere)
- Text Indexes
- TTL Collections (expireAfterSeconds)
- Hashed Indexes for sharding

Geospatial Indexes

```
// Add GeoJSON
{
    name: 'MongoDB Palo Alto',
    loc: { type : "Point",
           coordinates: [ 37.449157 , -122.158574 ] }
}
// Index the coordinates
db.locations.ensureIndex( { loc : '2dsphere' } )
```

Geospatial Indexes

```
// Query for locations 'near' a particular coordinate
db.locations.find ( {
    loc: { $near:
            { $geometry:
                { type : “Point”,
                coordinates: [ 37.4, -122.3 ] },
            $maxDistance: 40 }
            }
} )
```

Text Indexes

```
db.recipes.insert( { _id : 4 , y : “add flour and mix" } );
db.recipes.ensureIndex( { y : "text" } );
```

Limitations

- Collections can not have > 64 indexes.
- Index keys can not be > 1024 bytes (1K).
- The name of an index, including the namespace, must be < 125 characters.
- Queries can only use 1 index*
- Indexes have storage requirements, and impact the performance of writes.
- In memory sort (no-index) limited to 32mb of return data.

Optimize Your Queries

mongoDB

The “Explain” Plan (Pre-Index)

```
db.recipes.find( { calories:
    { $lt : 40 } }
).explain( )
{
   "cursor" : "BasicCursor" ,
   "n" : 42,
   "nscannedObjects” : 12345,
   "nscanned" : 12345,
    ...
   "millis" : 356,
    ...
}
```

* Doesn’t use cached plans, re-evals and resets cache

The “Explain” Plan (Post-Index)

```
db.recipes.find( { calories:
    { $lt : 40 } }
).explain( )
{
   "cursor" : ”BtreeCursor calories_1" ,
   "n" : 42,
   "nscannedObjects” : 42,
   "nscanned" : 42,
    ...
   "millis" : 3,
    ...
}
```

* Doesn’t use cached plans, re-evals and resets cache

Profiling Slow Operations

db.setProfilingLevel(*n* , *slowms=100ms*)

n=0 profiler off

n=1 record operations longer than *slowms*

n=2 record all queries

db.system.profile.find()

* The profile collection is a capped collection, and fixed in size

The Query Optimizer

- For each "type" of query, MongoDB periodically tries *all* useful indexes
- Aborts the rest as soon as one plan wins
- The winning plan is temporarily cached for each “type” of query

Manually Select Index to Use

```
// Tell the database what index to use
db.recipes.find( {
    calories: { $lt : 1000 } }
).hint ( { _id : 1 } )

// Tell the database to NOT use an index
db.recipes.find(
    { calories: { $lt : 1000 } }
).hint( { $natural : 1 } )
```

Use Indexes to Sort Query Results

```
// Given the following index
db.collection.ensureIndex( { a : 1, b : 1 , c : 1, d : 1 } )

// The following query and sort operations can use the index
db.collection.find( ).sort( { a : 1 } )
db.collection.find( ).sort( { a : 1, b : 1 } )

db.collection.find( { a : 4 } ).sort( { a : 1, b : 1 } )

//This query will not use the index, but will use the index to sort
db.collection.find( { b : 5 } ).sort( { a : 1, b : 1 } )
```

Indexes that won't work for sorting query results

```
// Given the following index
db.collection.ensureIndex( { a : 1, b : 1, c : 1, d : 1 } )

// These can not sort using the index
db.collection.find( ).sort( { b : 1 } )
db.collection.find( { b : 5 } ).sort( { b : 1 } )
```

Indexes that won't work for sorting query results

```
// MongoDB can return data from just the index
db.recipes.ensureIndex({ main_ingredient : 1, name : 1 })

// Return only the ingredients field
db.recipes.find(
    { main_ingredient : 'chicken' },
    { _id: 0, name : 1 }
)

// indexOnly will be true in the explain plan
db.recipes.find(
    { main_ingredient : 'chicken' },
    { _id: 0, name: 1 }
).explain()
{
    "indexOnly" : true,
}
```

Absent or suboptimal indexes are the most common avoidable MongoDB performance problem.

Avoiding Common Mistakes

mongoDB

Trying to Use Multiple Indexes

```
// MongoDB can only use one index for a query
db.collection.ensureIndex( { a : 1 } )
db.collection.ensureIndex( { b : 1 } )

// Only one of the above indexes is used
db.collection.find( { a : 3, b : 4 } )
```

Compound Key Mistakes

```
// MongoDB can only use one index for a query
db.collection.ensureIndex({ a: 1 })
db.collection.ensureIndex({ b: 1 })

// Only one of the above indexes is used
db.collection.find({ a: 3, b: 4 })

// Use a compound index
db.collection.ensureIndex( { a : 1, b : 1 } )
```

Low Selectivity Indexes

```
db.collection.distinct('status')
[ 'new', 'processed' ]

db.collection.ensureIndex( { status : 1 } )

// Low selectivity indexes provide little benefit
db.collection.find( { status : 'new' } )

// Better
db.collection.ensureIndex ({ status : 1, created_at : -1 } )
db.collection.find(
    { status : 'new' }
).sort( { created_at : -1 } )
```

Regular Expressions

```
db.users.ensureIndex( { username : 1 } )

// Left anchored regex queries can use the index
db.users.find( { username : /^joe smith/ } )

// But not generic regexes
db.users.find( {username : /smith/ } )

// Or case insensitive queries
db.users.find( { username : /Joe/i } )
```

Negation

```
// Indexes aren't helpful with negations
db.things.ensureIndex( { x : 1 } )

// e.g. "not equal" queries
db.things.find( { x : { $ne : 3 } } )

// ...or "not in" queries
db.things.find( { x : { $nin : [2, 3, 4 ] } } )

// ...or the $not operator
db.people.find( { name: { $not : 'John Doe' } } )
```

Choosing the right indexes is one of the most important things you can do as a MongoDB developer.

Take indexes into consideration when designing your application.


Thank You
mongoDB