

Class08Lab

Nancy Leon-Rivera

Table of contents

Save your input data file into your Project directory	1
Complete the following code to input the data and store as wisc.df	1
Tidy to remove diagnosis	4

Save your input data file into your Project directory

```
fna.data <- "WisconsinCancer.csv"
```

Complete the following code to input the data and store as wisc.df

```
wisc.df <- read.csv("WisconsinCancer.csv", row.names=1)
head(wisc.df)
```

	diagnosis	radius_mean	texture_mean	perimeter_mean	area_mean
842302	M	17.99	10.38	122.80	1001.0
842517	M	20.57	17.77	132.90	1326.0
84300903	M	19.69	21.25	130.00	1203.0
84348301	M	11.42	20.38	77.58	386.1
84358402	M	20.29	14.34	135.10	1297.0
843786	M	12.45	15.70	82.57	477.1
	smoothness_mean	compactness_mean	concavity_mean	concave.points_mean	
842302	0.11840	0.27760	0.3001	0.14710	
842517	0.08474	0.07864	0.0869	0.07017	

84300903	0.10960	0.15990	0.1974	0.12790	
84348301	0.14250	0.28390	0.2414	0.10520	
84358402	0.10030	0.13280	0.1980	0.10430	
843786	0.12780	0.17000	0.1578	0.08089	
	symmetry_mean	fractal_dimension_mean	radius_se	texture_se	perimeter_se
842302	0.2419	0.07871	1.0950	0.9053	8.589
842517	0.1812	0.05667	0.5435	0.7339	3.398
84300903	0.2069	0.05999	0.7456	0.7869	4.585
84348301	0.2597	0.09744	0.4956	1.1560	3.445
84358402	0.1809	0.05883	0.7572	0.7813	5.438
843786	0.2087	0.07613	0.3345	0.8902	2.217
	area_se	smoothness_se	compactness_se	concavity_se	concave.points_se
842302	153.40	0.006399	0.04904	0.05373	0.01587
842517	74.08	0.005225	0.01308	0.01860	0.01340
84300903	94.03	0.006150	0.04006	0.03832	0.02058
84348301	27.23	0.009110	0.07458	0.05661	0.01867
84358402	94.44	0.011490	0.02461	0.05688	0.01885
843786	27.19	0.007510	0.03345	0.03672	0.01137
	symmetry_se	fractal_dimension_se	radius_worst	texture_worst	
842302	0.03003	0.006193	25.38	17.33	
842517	0.01389	0.003532	24.99	23.41	
84300903	0.02250	0.004571	23.57	25.53	
84348301	0.05963	0.009208	14.91	26.50	
84358402	0.01756	0.005115	22.54	16.67	
843786	0.02165	0.005082	15.47	23.75	
	perimeter_worst	area_worst	smoothness_worst	compactness_worst	
842302	184.60	2019.0	0.1622	0.6656	
842517	158.80	1956.0	0.1238	0.1866	
84300903	152.50	1709.0	0.1444	0.4245	
84348301	98.87	567.7	0.2098	0.8663	
84358402	152.20	1575.0	0.1374	0.2050	
843786	103.40	741.6	0.1791	0.5249	
	concavity_worst	concave.points_worst	symmetry_worst		
842302	0.7119	0.2654	0.4601		
842517	0.2416	0.1860	0.2750		
84300903	0.4504	0.2430	0.3613		
84348301	0.6869	0.2575	0.6638		
84358402	0.4000	0.1625	0.2364		
843786	0.5355	0.1741	0.3985		
	fractal_dimension_worst				
842302	0.11890				
842517	0.08902				
84300903	0.08758				

84348301	0.17300
84358402	0.07678
843786	0.12440

Q. How many samples/patients are in this dataset?

There are 569 samples in this dataset

Q. How many cancer/non-cancer diagnosis samples are in this dataset?

```
Diagnosis <- wisc.df$diagnosis=="M"
sum(Diagnosis)
```

```
[1] 212
```

The `table()` function is a super useful utility for counting up the number of observations for each type.

```
table(wisc.df$diagnosis)
```

```
  B    M
357 212
```

Q. How many columns/dimensions are there?

```
ncol(wisc.df)
```

```
[1] 31
```

Q. How many columns are suffixed with “_mean”?

```
colnames(wisc.df)
```

```
[1] "diagnosis"          "radius_mean"
[3] "texture_mean"       "perimeter_mean"
[5] "area_mean"          "smoothness_mean"
[7] "compactness_mean"   "concavity_mean"
[9] "concave.points_mean" "symmetry_mean"
[11] "fractal_dimension_mean" "radius_se"
```

```

[13] "texture_se"           "perimeter_se"
[15] "area_se"              "smoothness_se"
[17] "compactness_se"      "concavity_se"
[19] "concave.points_se"   "symmetry_se"
[21] "fractal_dimension_se" "radius_worst"
[23] "texture_worst"        "perimeter_worst"
[25] "area_worst"           "smoothness_worst"
[27] "compactness_worst"    "concavity_worst"
[29] "concave.points_worst" "symmetry_worst"
[31] "fractal_dimension_worst"

```

The `grep()` function can help us find pattern matches here:

```
length(grep("_mean", colnames(wisc.df)))
```

```
[1] 10
```

Tidy to remove diagnosis

```
#Save the vector of this expert diagnosis for later and remove it from the data to undergo c.
```

```
diagnosis <- wisc.df$diagnosis
```


```
#instead of remove the column you create a new data with the diagnosis data removed
wisc.data <- wisc.df[, -1]
```

```
##Cluster the dataset
```

Let's try `hclust`.

```
hc.raw <- hclust(dist(wisc.data))
plot(hc.raw)
```

Cluster Dendrogram



```
dist(wisc.data)
hclust (*, "complete")
```

TO get some clusters out of this I can “cut” the tree at given height:

```
grps <- cutree(hc.raw, h=4000)
table(grps)
```

```
grps
  1  2
549 20
```

To see the correspondence of our cluster groups `grps` with the expert diagnosis I can use `table()`:

```
table(grps, diagnosis)
```

```
      diagnosis
grps   B    M
  1  357 192
  2    0  20
```

That is not that useful a clustering result...

##PCA should now be the first step for data analysis ##Principal Component Analysis (PCA)

Scaling data before analysis is often critical.

Side-note: The default for `prcomp()` is `scale=FALSE`.

There's a data set in R called `mtcars` which has loads of numbers about old cars.

```
head(mtcars)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
Hornet 4 Drive	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
Hornet Sportabout	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
Valiant	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

```
colMeans(mtcars)
```

mpg	cyl	disp	hp	drat	wt	qsec
20.090625	6.187500	230.721875	146.687500	3.596563	3.217250	17.848750
vs	am	gear	carb			
0.437500	0.406250	3.687500	2.812500			

```
apply(mtcars, 2, sd)
```

mpg	cyl	disp	hp	drat	wt
6.0269481	1.7859216	123.9386938	68.5628685	0.5346787	0.9784574
qsec	vs	am	gear	carb	
1.7869432	0.5040161	0.4989909	0.7378041	1.6152000	

```
pc.noscale <- prcomp(mtcars, scale=F)
pc.scale <- prcomp(mtcars, scale=T)
```

Let's look at the loadings first:


```
pc.noscale$rotation
```

	PC1	PC2	PC3	PC4	PC5
mpg	-0.038118199	0.009184847	0.982070847	0.047634784	-0.08832843
cyl	0.012035150	-0.003372487	-0.063483942	-0.227991962	0.23872590
disp	0.899568146	0.435372320	0.031442656	-0.005086826	-0.01073597
hp	0.434784387	-0.899307303	0.025093049	0.035715638	0.01655194
drat	-0.002660077	-0.003900205	0.039724928	-0.057129357	-0.13332765
wt	0.006239405	0.004861023	-0.084910258	0.127962867	-0.24354296
qsec	-0.006671270	0.025011743	-0.071670457	0.886472188	-0.21416101
vs	-0.002729474	0.002198425	0.004203328	0.177123945	-0.01688851
am	-0.001962644	-0.005793760	0.054806391	-0.135658793	-0.06270200
gear	-0.002604768	-0.011272462	0.048524372	-0.129913811	-0.27616440
carb	0.005766010	-0.027779208	-0.102897231	-0.268931427	-0.85520810


	PC6	PC7	PC8	PC9	PC10
mpg	-0.143790084	-0.039239174	-2.271040e-02	-0.002790139	0.030630361
cyl	-0.793818050	0.425011021	1.890403e-01	0.042677206	0.131718534
disp	0.007424138	0.000582398	5.841464e-04	0.003532713	-0.005399132
hp	0.001653685	-0.002212538	-4.748087e-06	-0.003734085	0.001862554
drat	0.227229260	0.034847411	9.385817e-01	-0.014131110	0.184102094
wt	-0.127142296	-0.186558915	-1.561907e-01	-0.390600261	0.829886844
qsec	-0.189564973	0.254844548	1.028515e-01	-0.095914479	-0.204240658
vs	0.102619063	-0.080788938	2.132903e-03	0.684043835	0.303060724
am	0.205217266	0.200858874	2.273255e-02	-0.572372433	-0.162808201
gear	0.334971103	0.801625551	-2.174878e-01	0.156118559	0.203540645
carb	-0.283788381	-0.165474186	-3.972219e-03	0.127583043	-0.239954748

	PC11
mpg	0.0158569365
cyl	-0.1454453628
disp	-0.0009420262
hp	0.0021526102
drat	0.0973818815
wt	0.0198581635
qsec	-0.0110677880
vs	-0.6256900918
am	-0.7331658036
gear	0.1909325849
carb	-0.0557957968

```
library(ggplot2)
ggplot(pc.noscale$rotation) + aes(PC1, rownames(pc.noscale$rotation)) +
  geom_col()
```



```
ggplot(pc.scale$rotation) + aes(PC1, rownames(pc.noscale$rotation)) +  
  geom_col()
```



The main PC result figure is often called a “score plot” or “PC plot” etc...


```
pca <- prcomp(wisc.data, scale =T)
#if means and stdev are different scale data
```

See how well we are doing:


```
summary(pca)
```

Importance of components:

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	3.6444	2.3857	1.67867	1.40735	1.28403	1.09880	0.82172
Proportion of Variance	0.4427	0.1897	0.09393	0.06602	0.05496	0.04025	0.02251
Cumulative Proportion	0.4427	0.6324	0.72636	0.79239	0.84734	0.88759	0.91010
	PC8	PC9	PC10	PC11	PC12	PC13	PC14
Standard deviation	0.69037	0.6457	0.59219	0.5421	0.51104	0.49128	0.39624
Proportion of Variance	0.01589	0.0139	0.01169	0.0098	0.00871	0.00805	0.00523
Cumulative Proportion	0.92598	0.9399	0.95157	0.9614	0.97007	0.97812	0.98335
	PC15	PC16	PC17	PC18	PC19	PC20	PC21
Standard deviation	0.30681	0.28260	0.24372	0.22939	0.22244	0.17652	0.1731
Proportion of Variance	0.00314	0.00266	0.00198	0.00175	0.00165	0.00104	0.0010
Cumulative Proportion	0.98649	0.98915	0.99113	0.99288	0.99453	0.99557	0.9966
	PC22	PC23	PC24	PC25	PC26	PC27	PC28
Standard deviation	0.16565	0.15602	0.1344	0.12442	0.09043	0.08307	0.03987
Proportion of Variance	0.00091	0.00081	0.0006	0.00052	0.00027	0.00023	0.00005
Cumulative Proportion	0.99749	0.99830	0.9989	0.99942	0.99969	0.99992	0.99997
	PC29	PC30					
Standard deviation	0.02736	0.01153					
Proportion of Variance	0.00002	0.00000					
Cumulative Proportion	1.00000	1.00000					

Our PC plot

```
ggplot(pca$x) +aes(PC1,PC2, col=diagnosis) +
  geom_point() + xlab("PC1 (44.3%)") +
  ylab("PC2 (18.9%)")
```



Q. How many PCs capture 80% of the original variance in the dataset?

```
summary(pca)
```

Importance of components:

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	3.6444	2.3857	1.67867	1.40735	1.28403	1.09880	0.82172
Proportion of Variance	0.4427	0.1897	0.09393	0.06602	0.05496	0.04025	0.02251
Cumulative Proportion	0.4427	0.6324	0.72636	0.79239	0.84734	0.88759	0.91010
	PC8	PC9	PC10	PC11	PC12	PC13	PC14
Standard deviation	0.69037	0.6457	0.59219	0.5421	0.51104	0.49128	0.39624
Proportion of Variance	0.01589	0.0139	0.01169	0.0098	0.00871	0.00805	0.00523
Cumulative Proportion	0.92598	0.9399	0.95157	0.9614	0.97007	0.97812	0.98335
	PC15	PC16	PC17	PC18	PC19	PC20	PC21
Standard deviation	0.30681	0.28260	0.24372	0.22939	0.22244	0.17652	0.1731
Proportion of Variance	0.00314	0.00266	0.00198	0.00175	0.00165	0.00104	0.0010
Cumulative Proportion	0.98649	0.98915	0.99113	0.99288	0.99453	0.99557	0.9966
	PC22	PC23	PC24	PC25	PC26	PC27	PC28
Standard deviation	0.16565	0.15602	0.1344	0.12442	0.09043	0.08307	0.03987
Proportion of Variance	0.00091	0.00081	0.0006	0.00052	0.00027	0.00023	0.00005
Cumulative Proportion	0.99749	0.99830	0.9989	0.99942	0.99969	0.99992	0.99997
	PC29	PC30					

```
Standard deviation      0.02736 0.01153
Proportion of Variance 0.00002 0.00000
Cumulative Proportion  1.00000 1.00000
```

```
##PC5
```

Q. Use ggplot to plot a “screen-plot” of the variance per PC.

```
#can use stdev as vairance
attributes(pca)
```

```
$names
[1] "sdev"      "rotation" "center"    "scale"     "x"

$class
[1] "prcomp"
```

We can extract stdev and figure out the total variance

```
v <- pca$sdev^2
sum(v)
```

```
[1] 30
```

The proportion of variance captured in each PC

```
round(v/sum(v),2)
```

```
[1] 0.44 0.19 0.09 0.07 0.05 0.04 0.02 0.02 0.01 0.01 0.01 0.01 0.01 0.01 0.00
[16] 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00
```

Cummulative variance captured


```
which(cumsum(v/sum(v)) >0.8)[1]
```

```
[1] 5
```

```
library(factoextra)
```

Welcome! Want to learn more? See two factoextra-related books at <https://goo.gl/ve3WBa>

```
fviz_eig(pca, addlabels = TRUE)
```




Combine PCA and clustering We saw earlier that clustering the raw data alone did not provide useful results.

We can use our new PC variables (our PCs) as a basis for clustering. Use our `$x` PC scores and cluster in the PC1-2 subspace

```
hc.pca <- hclust(dist(pca$x[,1:2]), method="ward.D2")  
plot(hc.pca)  
abline(h=60, col="blue")
```

Cluster Dendrogram



```
dist(pca$x[, 1:2])
hclust (*, "ward.D2")
```

Q. Does your clustering help separate cancer from on-cancer samples (i.e. diagnosis “M vsB”)?

```
mb.grps <- cutree(hc.pca, h=60)
table(mb.grps)
```

```
mb.grps
  1    2
195 374
```

```
table(mb.grps, diagnosis)
```

```
      diagnosis
mb.grps  B    M
  1    18  177
  2   339   35
```

```
table(diagnosis)
```

```
diagnosis
  B    M
357 212
```

Positive cancer samples "M" Negative non-cancer samples "B"

True our cluster/grp 1 False our cluster/grp 2

Q. How many true positive do we have?

Q. How many false positive do we have?

Sensitivity How many of the positives did we get right. $TP/(TP+FN)$

$TN/(TN+FN)$

##Prediction with our PCA Model

We can take new data(in this case from UofM) and project it onto our new variables (PCs).

Readd the UofM data first

```
url <- "new_samples.csv"
url <- "https://tinyurl.com/new-samples-CSV"
new <- read.csv(url)
#Projection
npc <- predict(pca, newdata=new)
npc
```

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
[1,]	2.576616	-3.135913	1.3990492	-0.7631950	2.781648	-0.8150185	-0.3959098
[2,]	-4.754928	-3.009033	-0.1660946	-0.6052952	-1.140698	-1.2189945	0.8193031
	PC8	PC9	PC10	PC11	PC12	PC13	PC14
[1,]	-0.2307350	0.1029569	-0.9272861	0.3411457	0.375921	0.1610764	1.187882
[2,]	-0.3307423	0.5281896	-0.4855301	0.7173233	-1.185917	0.5893856	0.303029
	PC15	PC16	PC17	PC18	PC19	PC20	
[1,]	0.3216974	-0.1743616	-0.07875393	-0.11207028	-0.08802955	-0.2495216	
[2,]	0.1299153	0.1448061	-0.40509706	0.06565549	0.25591230	-0.4289500	
	PC21	PC22	PC23	PC24	PC25	PC26	
[1,]	0.1228233	0.09358453	0.08347651	0.1223396	0.02124121	0.078884581	
[2,]	-0.1224776	0.01732146	0.06316631	-0.2338618	-0.20755948	-0.009833238	
	PC27	PC28	PC29	PC30			
[1,]	0.220199544	-0.02946023	-0.015620933	0.005269029			
[2,]	-0.001134152	0.09638361	0.002795349	-0.019015820			

Base R plot

```
plot(pca$x[,1:2], col=mb.grps)
##Add the new points

points(npc[,1], npc[,2], col="blue", pch=16, cex=3)
text(npc[,1], npc[,2], c(1,2), col="red")
```

