

HW Class06 Q6

```
library(bio3d)
s1 <- read.pdb("4AKE") # kinase with drug
```

Note: Accessing on-line PDB file

```
s2 <- read.pdb("1AKE") # kinase no drug
```

Note: Accessing on-line PDB file

PDB has ALT records, taking A only, rm.alt=TRUE


```
s3 <- read.pdb("1E4Y") # kinase with drug
```

Note: Accessing on-line PDB file


```
s1.chainA <- trim.pdb(s1, chain="A", elety="CA")
s2.chainA <- trim.pdb(s2, chain="A", elety="CA")
s3.chainA <- trim.pdb(s3, chain="A", elety="CA")

s1.b <- s1.chainA$atom$b
s2.b <- s2.chainA$atom$b
s3.b <- s3.chainA$atom$b


plotb3(s1.b, sse=s1.chainA, typ="l", ylab="Bfactor")
```



```
plotb3(s2.b, sse=s2.chainA, typ="l", ylab="Bfactor")
```



```
plotb3(s3.b, sse=s3.chainA, typ="l", ylab="Bfactor")
```



Q1. What type of object is returned from the read.pdb() function?

It returns an object of class `pdb`, its a list containing different components that describe the structure of a protein or nucleic acids in PDB format.

Q2. What does the trim.pdb() function do?

It's used to filter or extract specific parts of the PDB structure.


```
s1.chainA <- trim.pdb(s1, chain="A", elety="CA")
s2.chainA <- trim.pdb(s2, chain="A", elety="CA")
s3.chainA <- trim.pdb(s3, chain="A", elety="CA")
```

Q3. What input parameter would turn off the marginal black and grey rectangles in the plots and what do they represent in this case?

To turn off the marginal black and grey rectangles I would use `sse=F`

```
plotb3(s1.b, sse=FALSE, typ="l", ylab="Bfactor")
```

Warning in plotb3(s1.b, sse = FALSE, typ = "l", ylab = "Bfactor"): Length of input 'sse' does not equal the length of input 'x'; Ignoring 'sse'




They represent the SSE of the protein. Black rectangles represent alpha helices and grey represents beta strands.

Q4. What would be a better plot to compare across the different proteins?

To compare across the different proteins I would overlap their plots in a single graph.

```
plot(s1.b, type="l", col="blue", ylab="B-factor", xlab="Residue", ylim=range(c(s1.b, s2.b, s3.b)))
lines(s2.b, col="red")
lines(s3.b, col="green")
legend("topright", legend=c("4AKE", "1AKE", "1E4Y"), col=c("blue", "red", "green"), lty=1)
```

B-factor Comparison



Q5. Which proteins are more similar to each other in their B-factor trends. How could you quantify this? HINT: try the `rbind()`, `dist()` and `hclust()` functions together with a resulting dendrogram plot. Look up the documentation to see what each of these functions does.

1AKE and 1E4Y

Q6. How would you generalize the original code above to work with any set of input protein structures?

```
library(bio3d)
#Need to define a function to analyze proteins
analyze_protein <- function(pdb_ID, chains)
{
  #loop through each PDB ID and chain
  for(i in seq_along(pdb_ID)){
    #read the PDB file for the current protein structure
    pdb <- read.pdb(pdb_ID[i])
    #need to trim PDB to include only the specified chain and CA atoms
    chain_data <- trim.pdb(pdb, chain=chains[i], eley="CA")
    #extract the B-factor values from the trimmed PDB data
    b_factors <- chain_data$atom$b
```

```


#plot the B-factors with SSE
  plotb3(b_factors, sse=chain_data, typ="l", ylab="Bfactor", main=paste("B-factor plot for
}
}

#list of PDB IDs
pdb_ID <- c("4AKE", "1AKE", "1E4Y")
#list corresponding chains for each PDB ID
chains <- c("A", "A", "A")
analyze_protein(pdb_ID, chains)

```

Note: Accessing on-line PDB file

Warning in get.pdb(file, path = tempdir(), verbose = FALSE):
C:\Users\leonn\AppData\Local\Temp\Rtmpi2PvPH\4AKE.pdb exists. Skipping download




Note: Accessing on-line PDB file

Warning in get.pdb(file, path = tempdir(), verbose = FALSE):
C:\Users\leonn\AppData\Local\Temp\Rtmpi2PvPH\1AKE.pdb exists. Skipping download

PDB has ALT records, taking A only, rm.alt=TRUE

B-factor plot for 1AKE chain A



Note: Accessing on-line PDB file

Warning in get.pdb(file, path = tempdir(), verbose = FALSE):
C:\Users\leonn\AppData\Local\Temp\Rtmpi2PvPH\1E4Y.pdb exists. Skipping download

B-factor plot for 1E4Y chain A

