Software Engineering

Chapter 6: User Experience (UX) Design & Human-Centered AI

Prof. Nien-Lin Hsueh
Department of Information Engineering and Computer Science
Feng Chia University

Chapter 6: Roadmap & Core Curriculum

Part 1: Foundations & Usability Heuristics

- **6.1 Foundations of User Experience (UX):** What is UX, Norman Doors, the 3 bad design archetypes, Taiwan NHI App case study, UI vs. UX distinction, 5-stage Design Thinking.
- **6.2 Nielsen's 10 Usability Heuristics:** System status visibility, real-world match, user control & freedom, consistency, error prevention, recognition over recall, efficiency accelerators, minimalist aesthetics, error recovery, documentation.

Part 2: AI-Powered UX & Interaction Design

- **6.3 AI for UX (AI4UX):** AI as a design amplifier, the RTCF prompt engineering framework (Role-Task-Constraint-Format), automated heuristic audits, multi-agent prototyping.
- **6.4 UX for AI (UX4AI):** Designing for non-deterministic AI, managing latency & thinking traces, human agency & steerability, hallucination guardrails, explainable AI (XAI).
- **6.5 Evaluation & Synthesis:** Heuristic severity ratings (0 to 4), heuristic evaluation vs. user testing, chapter recap quiz, and engineering takeaways.

6.1 Foundations of User Experience (UX)

> *"Good design is actually a lot harder to notice than poor design, in part because good designs fit our needs so well that the design is invisible."*
> *— Don Norman, The Design of Everyday Things*

Why Good Design Matters: The "Norman Door"

> ***What is a "Norman Door"?*** *A door whose design sends the* ***wrong visual signal****—such as installing a prominent* ***pull handle*** *on a door that must actually be* ***pushed****!*

- **The Emotional Impact (Embarrassment & Frustration):**
  - You see a handle, pull instinctively, and suddenly can't open the door—making you feel **embarrassed, foolish, or even angry** in front of others.
  - Yet **you are not to blame—the design failed** by fighting human instinct!
- **Why This Brings Us to User Experience (UX):**
  - *"When a simple door needs a '**PUSH**' sign, the design is faulty."* — Don Norman
  - Software is full of "digital Norman Doors": good **UX Design** aligns visual cues with human intuition so users feel **confident and effortless**, never frustrated.

The Frustration of Bad UI/UX

> *"Users rarely blame the software architect when an interface is confusing—they feel **frustrated**, blame themselves, and **abandon the product**."*

- **The Emotional Toll of Poor Software:**
  - Cognitive overload, confusion, anxiety, and ultimate user abandonment.
  - Users do not blame software architects; they blame themselves or leave 1-star reviews.
- **Why Bad UX Destroys Business Value:**
  - **Cart Abandonment:** 70% of e-commerce carts are dropped due to convoluted checkout flows.
  - **Support Costs:** Thousands of expensive customer tickets originate from confusing navigation.
  - **Employee Burnout:** Enterprise software with terrible UX causes daily operational errors and lost productivity.



Bad Design Archetype (1): "Night Market" Sensory Overload

> ***The "Night Market Chaos" (Arngren-Style Overload):*** *Stuffing hundreds of competing products and links into a single screen with zero visual hierarchy.*

- **Why This Design Fails:**
  - **Broken Pattern Recognition:** Every product block has a random aspect ratio, font size, and alignment, forcing the brain to painfully refocus on every single item.
  - **No Grid System or Visual Anchors:** Lacks horizontal/vertical alignment guides; the human eye has no natural scanning path.
  - **Acute Sensory Overload:** When everything screams for attention simultaneously, users suffer cognitive fatigue and immediately bounce.



https://www.mockplus.com/blog/post/bad-web-design

Bad Design Archetype (2): "Paint is Free" Color & Contrast

> ***The "Paint is Free" Nightmare:*** *Abusing clashing colors, busy textured backgrounds, and drop-shadows that destroy readability and brand trust.*

- **Why This Design Fails:**
  - **Color Contrast Collapse:** Dark red and neon yellow text over a wavy cyan gradient causes visual vibration and violates **WCAG accessibility standards**.
  - **Typography Nightmares:** Heavy 3D drop-shadows and jagged, unaligned link lists create severe eye strain.
  - **Zero Negative Space & Lost Trust:** Cramming text without breathing room—especially on a medical X-ray supplier site—instantly destroys professional credibility.

https://www.mockplus.com/blog/post/bad-web-design

Bad Design Archetype (3): "Where Do I Start?" Missing Hierarchy

> ***The "Where Do I Start?" Archetype:*** *Cluttering dozens of identical buttons and ultra-wide text lines without a clear primary Call-to-Action (CTA).*

- **Why This Design Fails:**
  - **Missing Visual Focal Point:** Dozens of identical red and black buttons on the left carry equal visual weight—users have no idea which button to click first.
  - **Information Flood:** Phone numbers, addresses, and slogans are crammed into a neon banner with no visual priority.
  - **Uncontrolled Line Length:** Paragraphs stretch across the entire screen width, far exceeding the ergonomic reading limit of **45–75 characters per line**.

https://www.mockplus.com/blog/post/bad-web-design

Case Study: Taiwan NHI Mask App — Where Do You Pre-Order?

> ***Classroom Challenge:*** *Guess which icon (**1–6**) you had to tap when you wanted to **pre-order masks**?*

v1 Emergency Launch: Guess Where (1–6)?

1. Mask Query | **2.** My Health Bank | **3.** Reform Diary
4. Hospital Search | **5.** E-Counter | **6.** More...

Answer: Buried in #2! → Refactored 3×3 Grid

Why #2 (My Health Bank)? It had the login module!
Redesign: Promoted **eMask Pre-Order** directly to top row.

Case Study Analysis: Backend-Driven vs. User-Centered UX

- **Why the v1 Emergency Design Failed (Implementation-Driven UI):**
  - **Conway's Law & Module Convenience:** Because mask pre-ordering required identity login, engineers stuffed it inside **#2 My Health Bank (`健康存摺`)** where authentication already existed.
  - **False Signifier Trap:** Icon **#1 (`口罩查詢`)** had a mask illustration and the word "Mask," luring millions of users into a dead-end map view while the red banner at the top looked like an unclickable advertisement.
  - **Inconsistent Visual Weight:** Icons had random sizes and shapes (circles, rectangles, 3D books) with zero grid alignment.
- **How the Refactored Version Fixed It (Goal-Directed 3×3 Grid):**
  - **Surface-Level Task Visibility:** Extracted `eMask 口罩預購`, `History 購買紀錄`, and `Mask Map 口罩地圖` as distinct, top-row first-class actions matching citizen goals.
  - **Standardized Visual System:** Unified all 9 entry points into consistent circular icons with clear bilingual (**English + Chinese**) labels.

Why is UX So Hard? The Empathy Gap

> ***The Cardinal Rule of UX:*** *"You are **not** your user—never assume that because you built the backend schema, the interface is obvious to a first-time visitor."*

- **1. "You Are Not the User":**
  - Software engineers possess deep technical mental models (relational schemas, API routes, thread lifecycles).
  - End users possess everyday domain mental models (ordering dinner, booking an appointment, paying a bill).
- **2. The Curse of Knowledge:**
  - Once an engineer builds a complex feature, it seems "obvious" and "intuitive" to them.
  - They forget the cognitive friction experienced by a first-time user encountering the screen cold.
- **3. Defensive vs. Empathetic Thinking:**
  - Engineers often design interfaces to match backend database tables rather than natural human mental steps.



UI (User Interface) vs. UX (User Experience)

- **User Interface (UI):**
  - The tangible, sensory touchpoints through which humans interact with software.
  - *Elements:* Buttons, typography, color palettes, spacing, CSS grids, icons, transitions, animations.
  - *Core Question:* "How does the screen look, render, and react visually?"
- **User Experience (UX):**
  - The overall, end-to-end emotional and psychological journey a human has with a brand, service, or system.
  - *Elements:* Task efficiency, friction, cognitive load, user satisfaction, error recovery, trust.
  - *Core Question:* "How effectively, intuitively, and pleasantly does the user achieve their goal?"
- **The Classical Analogy:**
  - UI is the saddle, stirrup, and reins; UX is the feeling of riding the horse!

Visualizing UI vs. UX: Anatomy of Interaction



The 5-Stage UX Design Thinking Process



The 5 Stages of Design Thinking: Process Breakdown

- **1. Empathize:**
  - Conduct qualitative user interviews, contextual field inquiries, and observational studies.
  - Identify unarticulated frustrations and true emotional pain points.
- **2. Define:**
  - Synthesize user research into concrete personas, empathy maps, and precise "How Might We" problem statements.
- **3. Ideate:**
  - Brainstorm diverse potential solutions without premature judgment; sketch rapid low-fidelity paper wireframes.
- **4. Prototype:**
  - Build interactive, testable artifacts (clickable Figma mockups, interactive HTML/CSS code components).
- **5. Test:**
  - Put prototypes in front of real users, observe stumbling blocks, measure task completion rates, and iterate.

Concept Check Question 1: UI vs. UX & The Empathy Gap

A mobile banking app has sleek animations (**polished UI**), yet **68% of new users abandon transfers** because the flow exposes raw database codes (`TXN_ROUTING_ID`). What is the root failure and proper **Design Thinking** remedy?

- **A.** A **UI visual defect**; replace CSS animations with higher-contrast Material Design buttons.
- **B.** A **backend latency bottleneck**; add Redis caching so transfer queries finish in under 50ms.
- **C.** A **UX Empathy Gap failure**; research user pain points and prototype flows around customer mental models.
- **D.** A **user training gap**; require new customers to watch a 15-minute tutorial before transferring funds.

6.2 Nielsen's 10 Usability Heuristics

> *"Jakob's Law: Users spend most of their time on other sites. This means that users prefer your site to work the same way as all the other sites they already know."*
> *— Jakob Nielsen, Nielsen Norman Group*

Overview: Nielsen's 10 Usability Heuristics

> *"Heuristics are broad rules of thumb, not rigid laws—distilled from decades of empirical HCI research."*

- 🚦 **NS01. Visibility of System Status:** Keep users informed through timely feedback.
- 🌍 **NS02. Match System & Real World:** Speak the user's language using natural concepts.
- 🚪 **NS03. User Control & Freedom:** Provide clear emergency exits (undo/redo).
- 📐 **NS04. Consistency & Standards:** Follow platform conventions (Jakob's Law).
- 🛡️ **NS05. Error Prevention:** Eliminate error-prone conditions beforehand.
- 👁️ **NS06. Recognition Rather Than Recall:** Make objects, actions, and options visible.
- ⚡ **NS07. Flexibility & Efficiency:** Provide accelerators for power users.
- 🎨 **NS08. Aesthetic & Minimalist Design:** Maximize signal-to-noise ratio.
- 🩹 **NS09. Help Users Recover from Errors:** Express error messages in plain language.
- 📖 **NS10. Help and Documentation:** Provide searchable, contextual guidance.

NS01: Visibility of System Status

- **Heuristic Principle:**

> *"The system should always **keep users informed** about what is going on, through **appropriate feedback** within a **reasonable time**."*

- **Core Interaction Patterns:**
  - **Immediate Touch Feedback:** Active button states, ripple effects, and micro-animations validating input registration.
  - **Progress Transparency:** Deterministic progress bars (% complete), multi-step checkout steppers (1. Cart → 2. Shipping → 3. Payment).
  - **Background Task Feedback:** Spinners with descriptive, dynamic status copy ("*Uploading image 3 of 5...*").
  - **Connection State Indicators:** Real-time online/offline banners and live synchronization indicators.

NS01 in Practice (1/2): Progress Bars, Steppers & Sync State



NS01 in Practice (2/2): Batch File Import Progress & ETA



NS02: Match Between System and the Real World

- **Heuristic Principle:**

> *"The system should **speak the users' language**, with **words, phrases, and concepts familiar to the user**, rather than system-oriented terms. Follow **real-world conventions**."*

- **Natural Spatial Mapping (Natural Mapping):**
  - Controls should mirror the physical arrangement of the objects they manipulate.
  - *Classic Counter-Example:* Gas stove burner knobs arranged in a straight line for a 2x2 grid force mental translation and errors.
  - *Good Design:* Arranging 4 knobs in the exact same 2x2 layout as the burners makes operation instantaneous and error-free.
- **Familiar Conceptual Metaphors:**
  - Trash can for deletions, desktop folder icons for directory trees, and shopping carts for e-commerce purchases.

NS02 in Practice (1/2): Natural Spatial Mapping of Controls

Unnatural Mapping (Arbitrary)



High Cognitive Friction — Which knob controls which burner? Requires labels and mental translation.

Natural Mapping (Spatial Correspondence)



Intuitive Operation — Subconscious, error-free physical mapping.

NS02 in Practice (2/2): Speaking Everyday User Language

> ***Why It Matters:*** *Exposing raw backend exceptions (`HTTP 502`, `ERR_SOCKET_TIMEOUT`) forces everyday shoppers to decipher engineering jargon and triggers panic over double-charging.*

- **System-Oriented Jargon (Bad):**
  - ❌ "*Transaction Exception 403: Acquirer socket connection timed out.*"
  - Leaves customers anxious: "*Was my credit card charged or not?*"
- **Human-Centered Language (Good):**
  - ✅ **Reassuring Status:** Clearly confirms **"we couldn't complete the charge"** (no money lost!).
  - ✅ **Everyday Vocabulary:** Explains that the "*payment channel is currently busy.*"
  - ✅ **Actionable Next Steps:** Offers clear choices (`Retry Payment` or `Use Different Card`).



NS03: User Control & Freedom (Emergency Exits)

- **Heuristic Principle:**

> *"Users often choose system functions **by mistake** and will need a clearly marked **'emergency exit'** to leave the unwanted state **without having to go through an extended dialogue**."*

- **Essential Implementation Patterns:**
  - **Universal Undo / Redo:** Support `Ctrl+Z` / `Cmd+Z` across all text editors, canvas tools, and destructive state changes.
  - **Cancelation Actions:** Provide clear, high-contrast "Cancel" buttons on modals, file uploads, and bulk operations.
  - **Non-Destructive Navigation:** Allow users to back out of a checkout or registration wizard without wiping previously entered form data.
  - **Soft Deletes:** Move deleted items to a "Trash Bin" with a 30-day restoration window before permanent deletion.

NS03 in Practice (1/2): Instant "Undo" Toast After Drag-and-Drop



NS03 in Practice (2/2): Email Trash "Undo" & Post "Discard" Exits



1. Post-Action "Undo" Banner (Gmail)

Instead of pestering users with "Are you sure?" popups on every email delete or send, Gmail executes immediately and surfaces a 1-click [Undo] banner so accidental clicks are effortlessly reversed.

2. Clear "Cancel / Discard" Exit (Mobile Composer)

When a user taps [Cancel] while drafting a post, an explicit action sheet lets them safely [Discard] the draft or [Keep] editing—never trapping the user inside an unwanted workflow.



NS04: Consistency & Standards (Jakob's Law)

- **Heuristic Principle:**

> *"Users **should not have to wonder** whether **different words, situations, or actions mean the same thing**. Follow **platform and industry conventions**."*

- **Jakob's Law of Internet User Experience:**
  - Users spend 99% of their digital lives on **other websites and apps**.
  - They expect your software to follow established conventions (e.g., logo at top-left returns home, shopping cart at top-right, magnifying glass indicates search).
- **Two Dimensions of Consistency:**
  - **Internal Consistency:** Uniform fonts, button styles, padding, and terminology across your own app (Design Systems).
  - **External Consistency:** Adhering to platform standards (Apple HIG for iOS, Material Design for Android).

NS04 in Practice (1/2): Consistent Form Controls & Button Hierarchy



NS04 in Practice (2/2): Platform-Standard Keyboard Conventions



NS05: Error Prevention

- **Heuristic Principle:**

> *"Even better than good error messages is a **careful design** which **prevents a problem from occurring in the first place**."*

- **Defensive Design Patterns:**
  - **Eliminate Error-Prone States:** Grey out or disable the "Submit" button until all mandatory fields pass real-time validation.
  - **Input Constraints:** Use visual Date Pickers instead of freeform text boxes to prevent date formatting syntax errors (`MM/DD/YYYY` vs. `DD/MM/YYYY`).
  - **Confirmation for Irreversible Actions:** Display high-friction confirmation dialogs before permanent actions (e.g., typing the repository name to delete a GitHub repo).
  - **Intelligent Defaults:** Pre-fill sensible default parameters to eliminate blank-form intimidation.

NS05 in Practice (1/2): Destructive Safeguards & Missing Attachment Check





NS05 in Practice (2/2): Disabled Action Until Explicit Name Match



NS06: Recognition Rather Than Recall

- **Heuristic Principle:**

> *"**Minimize the user's memory load** by making **objects, actions, and options visible**. The user **should not have to remember information** from one part of the dialogue to another."*

- **Cognitive Psychology Foundation:**
  - **Recognition (Easy):** Identifying something you have seen before when presented with visual cues (e.g., multiple-choice quiz).
  - **Recall (Hard):** Retrieving information entirely from memory without assistance (e.g., blank-slate command line terminal).
- **UI Implementations:**
  - Autocomplete search dropdowns displaying recent search keywords.
  - Visual thumbnails of recently edited documents instead of raw filenames.
  - Contextual action toolbars appearing when text is selected.

NS06 in Practice (1/2): Forced Recall vs. Search History Recognition

Pure Recall (High Cognitive Load)



Forced Recall — Requires mental effort to retrieve past searches from memory.

Effortless Recognition (Low Cognitive Load)



Recognition Over Recall — Past queries and suggestions are immediately visible for 1-tap selection.

NS06 in Practice (2/2): Contextual Menus Eliminate Recall

> ***Why Is This a Recall vs. Recognition Issue?*** *Without contextual menus, users must* ***memorize and recall*** *which top-level menu (`Edit`, `Tools`, or `Format`) or hotkey hides an action!*

- **The Recall Burden (Traditional Menu / CLI):**
  - After highlighting a paragraph, a user must search their memory: "*Where is the summarize tool? Is it buried under `Tools → AI` or `Edit → Transform`? What was the shortcut?*"
- **The Recognition Solution (Contextual Toolbar):**
  - The moment text is highlighted, valid actions (`Translate`, `Summarize`, `Improve Writing`) appear **visibly right beside the cursor**.
  - Users **see and recognize** available options on the spot—zero menu hunting or command memorization!



NS07: Flexibility & Efficiency of Use (Accelerators)

- **Heuristic Principle:**

> *"**Accelerators**—unseen by the novice user—may often **speed up the interaction for the expert user** such that the system can **cater to both inexperienced and experienced users**."*

- **Dual-Track Interaction Design:**
  - **Novice Path:** Guided visual menus, onboarding tours, wizard steppers, and descriptive labels.
  - **Expert Accelerators:** Keyboard shortcuts (`Cmd+K` command palette), multi-touch gestures, reusable templates, and batch actions.
- **Progressive Mastery:**
  - Display keyboard shortcut hints directly inside dropdown menus, enabling novices to gradually transition into power users.

NS07 in Practice (1/2): Keyboard Shortcuts & Code Snippet Accelerators



Keyboard Shortcuts & Menu Accelerators

Intelligent Code Snippet Expansion

NS07 in Practice (2/2): Multi-Select Batch Operations for Power Users



NS08: Aesthetic & Minimalist Design

- **Heuristic Principle:**

> *"Dialogues should **not contain information which is irrelevant** or rarely needed. Every **extra unit of information** in a dialogue **competes with the relevant units** and **diminishes their relative visibility**."*

- **The Signal-to-Noise Ratio (SNR):**
  - **Signal:** Information directly relevant to the user's immediate decision.
  - **Noise:** Visual clutter, redundant borders, unnecessary badges, decorative chrome.
- **Technique: Progressive Disclosure:**
  - Show only the primary, essential controls upfront.
  - Tuck advanced settings behind "Advanced Options" accordions or secondary tabs.

NS08 in Practice (1/2): Information Overload vs. Minimalist Clarity

Low Signal-to-Noise Ratio (Information Overload)



Visual Noise — Critical actions are buried; high cognitive strain.

High Signal-to-Noise Ratio (Minimalist Clarity)



Aesthetic Minimalism — Clear visual hierarchy spotlights the primary user goal.

NS08 in Practice (2/2): Focused KPI Dashboard with Progressive Disclosure



NS09: Help Users Recognize, Diagnose, & Recover from Errors

- **Heuristic Principle:**

> *"Error messages should be expressed in **plain language** (**no codes**), **precisely indicate the problem**, and **constructively suggest a solution**."*

- **The Anatomy of a Terrible Error Message:**
  - ❌ "*Error 0x80004005: Unexpected runtime exception in thread main.*" (Terrifies the user; completely unhelpful).
- **The Anatomy of a Great Error Message:**
  - ✅ **Plain Language:** "*We couldn't charge your credit card.*"
  - ✅ **Precise Cause:** "*The expiration date entered (05/23) is in the past.*"
  - ✅ **Constructive Recovery:** "*Please enter an updated expiration date or choose a different payment method [Update Card].*"

NS09 in Practice (1/2): Cryptic 404 Dead-End vs. Helpful 404 Recovery

Cryptic Error (Dead End)



Constructive Recovery (Helpful 404)



NS09 in Practice (2/2): Plain-Language Upload Diagnosis & Recovery



NS10: Help and Documentation

- **Heuristic Principle:**

> *"Even though it is better if the system can be used without documentation, it may be necessary to provide help and documentation. Any such information should be **easy to search**, **focused on the user's task**, **list concrete steps** to be carried out, and **not be too large**."*

- **Modern Documentation Paradigms:**
  - **Contextual Tooltips:** Inline `?` icons explaining complex form requirements on hover.
  - **Interactive Onboarding Tours:** Lightweight, multi-step interactive walkthroughs highlighting key UI areas for first-time signups.
  - **Searchable Task-Oriented Help Centers:** Documentation organized by customer goals rather than internal system architecture.

NS10 in Practice (1/2): Contextual Tooltips & Interactive Spotlight Tours

Passive
Contextual Help



Active
Interactive Onboarding



Unobtrusive — Accessible on demand without cluttering the screen.

NS10 in Practice (2/2): Task-Focused Step-by-Step Guided Walkthrough



Concept Check Question 2: Usability Heuristics

When designing an e-commerce checkout flow, a team replaces raw text date inputs with an interactive calendar picker and automatically disables the "Place Order" button until all required shipping addresses pass validation. Which Nielsen Heuristic is primarily demonstrated?

- **A.** NS01: Visibility of System Status.
- **B.** NS05: Error Prevention.
- **C.** NS07: Flexibility and Efficiency of Use.
- **D.** NS10: Help and Documentation.

6.3 AI for UX (AI4UX): Amplifying Design Workflows

> *"AI will not replace UX designers, but UX designers who use AI will replace those who do not."* „

What is AI for UX (AI4UX)?

- **The AI-Amplified Designer:**
  - Generative AI acts as a **cognitive partner and speed multiplier** across every stage of the design thinking process.
- **Core Application Areas:**
  - **Research & Empathy:** Generating diverse synthetic user personas, simulating edge-case user interviews.
  - **Ideation & Copywriting:** Rapidly generating microcopy variations, localization strings, and accessibility alt text.
  - **Automated Heuristic Audits:** Feeding UI screenshots to multimodal LLMs to identify Nielsen heuristic violations.
  - **Generative Prototyping:** Text-to-wireframe and text-to-code pipelines (v0, Figma AI, Galileo).

AI for UX: The Augmented Human-AI Design Workflow

The RTCF Prompt Engineering Framework for Designers

To get precise, professional UX output from AI models, avoid vague prompts (❌ "*Help me design a login page*"). Use the structured **RTCF Framework**:

- **R — Role:**
  - Define the AI's persona and expertise (e.g., "*Act as a Lead UX Researcher specializing in accessibility and WCAG 2.1 AA standards.*").
- **T — Task:**
  - Define the concrete objective (e.g., "*Conduct a heuristic evaluation of this mobile checkout wireframe.*").
- **C — Constraints:**
  - Enforce domain rules (e.g., "*Evaluate strictly against Nielsen's Heuristics NS01, NS03, and NS05; target a 375px mobile viewport.*").
- **F — Format:**
  - Specify the output structure (e.g., "*Provide results in a 4-column Markdown table: [Heuristic ID, Observed Issue, Severity (0-4), Concrete Fix Recommendation].*").

Multi-Agent Prototyping & Generative UI

- **Autonomous Multi-Agent Architecture:**
  - Modern IDEs and agent systems (e.g., Antigravity, Devin, Claude Code) orchestrate specialized agents working in tandem.
  - **UX Research Agent:** Analyzes customer tickets and synthesizes user pain points.
  - **Design System Agent:** Generates CSS tokens, typography scales, and accessible color palettes.
  - **Frontend Code Agent:** Translates specifications into responsive HTML/CSS/React components.
- **The Human-in-the-Loop Safeguard:**
  - AI generates rapid prototypes; human engineers evaluate ergonomics, brand voice, and real user empathy.

Multi-Agent Architecture: Collaborative Prototyping Pipelines

Google Antigravity Agent

Modern AI Pair-Programming & Autonomous Engineering Engine

Read Every Turn • Permanent Full Injection

📋 AGENTS.md (Project Directives & Rules)

- **Hierarchical Scope Traversal:** Automatically walks up directories from local folder to repository root and global configs.
- **Enforces Engineering Standards:** Standardizes naming conventions, tech stacks, and domain terminology across the team.
- **Core UX & Architecture Guardrails:** Hard rules for real-time status feedback, destructive action safeguards, and zero broken links.
- **Safeguards Design Consistency:** Enforces unified design tokens, typography, and interactive component behaviors (NS04).

Task Match Triggered • Progressive Disclosure

🧰 .agents/ (Modular Skills & Tools)

- **Lightweight YAML Headers:** Only skill descriptions are indexed initially, saving valuable context window tokens.
- **Dynamic Intent Activation:** Full SOPs, reference manuals, and execution steps are loaded on demand upon task match.
- **Encapsulated Executable Scripts:** Bundles local automation scripts (`scripts/`) for autonomous loop execution.
- **Deep Ecosystem Integration:** Native support for extensible Model Context Protocol (MCP) servers and lifecycle workflow hooks.

6.4 UX for AI (UX4AI): Designing Human-Centered AI

> *"The hardest part of building AI products is not training the model—it is designing the interface that makes probabilistic intelligence understandable, steerable, and trustworthy."*

Unique UX Challenges in AI-Native Products

- **1. Non-Determinism & Unpredictability:**
  - Traditional software: `2 + 2` always returns `4`.
  - AI systems: Submitting the identical prompt twice may yield completely different phrasing, tone, or formatting.
- **2. The "Hallucination" Dilemma:**
  - Generative models can generate completely fabricated facts, non-existent API methods, or fake citations with total syntactic confidence.
- **3. Latency & the "Thinking" Black Box:**
  - Complex reasoning models (e.g., o1, Gemini Thinking) require 5 to 30 seconds of inference time before returning a single token.
- **4. The Calibration of Trust:**
  - **Over-trust:** Users blindly accept false AI code without reviewing it, leading to production outages.
  - **Under-trust:** Users abandon the AI after a single minor mistake, losing all productivity benefits.

AI + NS01: Visibility of AI State & Thinking Traces

- **The Problem of AI Latency & Black Boxes:**
  - Long inference times (10-30s) leave users staring at blank screens, wondering if the server crashed.
- **Interaction Solutions:**
  - **Streaming Tokens:** Stream text responses token-by-token immediately, providing instant perceived performance.
  - **Collapsible Reasoning Traces:** Display interactive "Thinking Process" accordions showing internal reasoning steps and tool execution.
  - **RAG Grounding Citations:** Provide clickable source pills linking directly to retrieved reference documents.

AI + NS01 in Practice: Streaming Tokens & Collapsible Reasoning



AI + NS02 & NS03: Grounding, Control & Human Agency

- **AI + NS02 (Match with Real World):**
  - **Transparent Bot Identity:** Clearly disclose that the system is an AI assistant; avoid deceptive pseudo-human personas.
  - **Conversational Grounding:** Establish shared context using familiar conversational turns and natural language.
- **AI + NS03 (User Control & Freedom):**
  - **Stop Generation Button:** Provide an instant button to abort runaway or misdirected responses.
  - **Prompt Branching:** Allow users to edit previous prompts and fork alternative conversation threads.
  - **Steerability Sliders:** Provide controls for temperature, brevity, and response tone.

AI + NS03 in Practice: User Steerability & Cancelation Controls



AI + NS05: Error Prevention & Agentic Guardrails

- **The Extreme Stakes of Agentic AI:**
  - Autonomous agents can execute shell commands, edit production code, and interact with external APIs.
  - An unchecked hallucination can delete files, drop database tables, or leak API keys.
- **Human-in-the-Loop (HITL) Guardrails:**
  - **Pre-Execution Confirmation:** Require explicit developer approval before running terminal commands or modifying files.
  - **Diff Previews:** Display color-coded git-style diffs showing exactly what lines the AI proposes to modify.
  - **Sandboxed Execution:** Run unverified AI code in isolated containers before applying changes to host environments.

AI + NS05 in Practice: Human-in-the-Loop Confirmation & Diff Auditing



AI + NS07 & NS10: Accelerators & Explainability (XAI)

- **AI + NS07 (Flexibility & Accelerators):**
  - **Slash Commands:** Quick keyboard triggers (`/explain`, `/refactor`, `/fix-tests`) allowing power users to bypass conversational typing.
  - **Multi-Modal Drag-and-Drop:** Allowing users to drag screenshots, PDF diagrams, and log files directly into the prompt box.
- **AI + NS10 (Explainable AI - XAI):**
  - **"Why this answer?":** Contextual tooltips explaining which source documents or prompt instructions triggered the recommendation.
  - **Model Cards & Confidence Meters:** Explicitly disclosing active model versions and estimated prediction confidence.

AI + NS10 in Practice: Explainable AI & Contextual Citations



Concept Check Question 3: UX for AI Design

When designing an autonomous AI coding assistant that can inspect directories, edit source files, and execute shell commands, which design pattern best fulfills **Error Prevention (NS05)** and **User Agency (NS03)**?

- **A.** Allowing the agent to execute all file deletions and shell scripts silently in the background without user interruption.
- **B.** Requiring explicit human-in-the-loop review and confirmation before executing high-risk file modifications or system terminal commands.
- **C.** Removing the ability to stop or cancel running background tasks once the AI begins executing code.
- **D.** Hiding all command execution logs from developers to avoid visual clutter and information overload.

6.5 Evaluation & Engineering Synthesis

> *"Evaluating usability with 5 users uncovers roughly 85% of all usability problems."*
> *— Jakob Nielsen*

Conducting a Formal Heuristic Evaluation

- **What is a Heuristic Evaluation?**
  - A discount usability inspection method where independent evaluators examine an interface against established heuristics (e.g., Nielsen's 10).
- **Nielsen's 5-Point Severity Rating Scale:**
  - **0 = Not a usability problem:** Does not affect user progress.
  - **1 = Cosmetic problem only:** Minor visual blemish; fix only if extra time is available.
  - **2 = Minor usability problem:** Low priority; causes minor inconvenience but user can recover.
  - **3 = Major usability problem:** High priority; severely delays or confuses users; must be fixed before release.
  - **4 = Usability catastrophe:** Imperative to fix! Completely blocks task completion; software cannot ship!

Heuristic Evaluation vs. Empirical User Testing

Dimension	Heuristic Evaluation (Expert Inspection)	Empirical User Testing (Real End-Users)
Evaluators	3 to 5 UX Experts / Senior Engineers	5 Real Representative End-Users
When to Use	Early in design (wireframes, early prototypes)	Later in development (interactive prototypes, staging)
Cost & Speed	Extremely fast (1–2 days); low financial cost	Slower (1–2 weeks); requires recruitment and lab setup
Primary Strength	Quickly finds obvious heuristic violations & edge cases	Reveals authentic human behavioral friction & surprises
Limitation	Experts can miss domain-specific workflow quirks	Users reveal *what* broke, but not always *why* or *how to fix*

Chapter Recap: Fill-in-the-Blank Challenge

Test your mastery of the core concepts in Chapter 6:

- **1.** A door with a pull handle that must be pushed to open is famously known as a ___ Door.
- **2.** ___ Law states that users spend most of their time on other websites, expecting your site to follow common conventions.
- **3.** Nielsen Heuristic ___ states that preventing mistakes beforehand is vastly superior to displaying polite error messages.
- **4.** The prompt engineering framework for designers consisting of Role, Task, Constraint, and Format is abbreviated ___.
- **5.** In AI interfaces, displaying streaming tokens and collapsible reasoning steps exemplifies heuristic ___: Visibility of System Status.
- **6.** On Nielsen's severity rating scale, a usability defect that completely blocks task completion and prevents product release is rated as a ___.

Chapter Recap: Solution Key

Here are the completed principles and technical terms:

- **1.** A door with a pull handle that must be pushed to open is famously known as a **Norman** Door.
- **2. Jakob's** Law states that users spend most of their time on other websites, expecting your site to follow common conventions.
- **3.** Nielsen Heuristic **NS05: Error Prevention** states that preventing mistakes beforehand is vastly superior to displaying polite error messages.
- **4.** The prompt engineering framework for designers consisting of Role, Task, Constraint, and Format is abbreviated **RTCF**.
- **5.** In AI interfaces, displaying streaming tokens and collapsible reasoning steps exemplifies heuristic **NS01**: Visibility of System Status.
- **6.** On Nielsen's severity rating scale, a usability defect that completely blocks task completion and prevents product release is rated as a **4 (Catastrophe)**.

Chapter Summary & Engineering Takeaways

- **1. Human Psychology Precedes Code:**
  - Excellent software engineers design for human cognitive limits (working memory, emotional frustration, mental models).
  - When users stumble, fix the interface affordances rather than blaming user competence.
- **2. Internalize Nielsen's 10 Heuristics:**
  - Make status visible (NS01), match real-world metaphors (NS02), offer undo exits (NS03), adhere to standards (NS04), prevent errors proactively (NS05), and write constructive error messages (NS09).
- **3. Master AI-Augmented Design (AI4UX & UX4AI):**
  - Use structured RTCF prompting to accelerate research, prototyping, and automated heuristic audits.
  - Design AI products for calibrated trust: stream tokens, show reasoning traces, mandate human confirmations for agentic actions, and provide in-place error recovery.