Software Engineering

Chapter 5: Software Design, Architecture & OO Principles

From Universal Foundations & Architecture Modeling to SOLID Craftsmanship

Prof. Nien-Lin Hsueh
Department of Information Engineering and Computer Science
Feng Chia University

Chapter 5: Roadmap & Core Curriculum

Part 1: Process, Principles & Macro Design

- **5.1 Software Design Foundations & Process:** The 4-stage design process (Arch → Interface → OO → Data) and specifications (SDS & ADRs).
- **5.2 Universal Design Principles:** Abstraction, encapsulation, separation of concerns, modularity, and cohesion & coupling.
- **5.3 Stage 1 — Architectural Design:** 6 classic patterns, Food Delivery synthesis, ATAM, and **UML Package & Deployment Diagrams**.
- **5.4 Stage 2 — Interface & Contract Spec: Design by Contract (DbC)** and **UML Component Diagrams** (Lollipop & Socket).

Part 2: Micro OO Design, Data, AI & Synthesis

- **5.5 Stage 3 — Component & OO Design:** GoF 23 Design Patterns and the 5 SOLID principles via **UML Class Diagrams**.
- **5.6 Stage 4 — Data & Persistence Design:** 3-level data modeling, **UML ERD**, 3NF, Redis Geo-caching, and polyglot persistence.
- **5.7 AI-Augmented Software Design:** AI copilots across all 4 design stages and human-in-the-loop blind spot governance.
- **5.8 Conceptual Synthesis & References:** End-to-end curriculum review, self-assessment matrix, and classic literature.

5.1 Software Design Foundations, Process & Specifications

> *"There are two ways of constructing a software design: One way is to make it so simple that there are obviously no deficiencies, and the other way is to make it so complicated that there are no obvious deficiencies."*
> *— C. A. R. Hoare (Turing Award Laureate)*


What is Software Design?

- **From Requirements (What) to Implementation (How):**
  - **Requirements Engineering (SRS)**: Defines stakeholder problems, use cases, and quality expectations (*what to build*).
  - **Software Design (SDS)**: Conceptualizes structural decomposition, interface contracts, class hierarchies, and data schemas (*how to build*).
- **Core Activities of Software Design:**
  - **Blueprint & Specification Creation**: Establishes architectural models, formal interface contracts, and database schemas so teams can build in parallel.
  - **Trade-off Decision Making**: Balances competing non-functional forces (e.g., latency vs. consistency vs. cloud cost).
- **The Distinction Between Design and Coding:**
  - Coding expresses logic in a specific programming language syntax.
  - Design determines **how modules are partitioned, how interfaces are contracted, and how data is persisted** for long-term evolvability.

Why is Software Design Crucial?

- **1. Eliminating "Vibe Coding" and Structural Code Rot:**
  - Coding without design rapidly triggers the **4 Symptoms of Poor Design** (Robert C. Martin):
    - **Rigidity**: A single change forces cascading edits across dozens of unrelated files.
    - **Fragility**: Fixing a bug in Module A inexplicably breaks an unrelated Module B.
    - **Immobility**: Tangled components cannot be extracted for reuse in other systems.
    - **Viscosity**: Doing things right is harder than hacking, tempting devs to take shortcuts.
- **2. Quality Attributes are Designed In, Not Tested In:**
  - Scalability, fault isolation, `< 200ms` latency, and security must be architected from day one—they cannot be patched in via unit tests later.
- **3. Barry Boehm's Cost of Defect Removal Curve:**
  - Catching an architectural flaw in **Design** costs **$1**; in integration testing **$10**; in **production**, it escalates to **$50–$100x**!

The 4-Stage Software Design Process & Design Specifications



The 4 Design Stages & Deliverables (SDS & ADRs)

> ***Chapter 5 Master Plan:*** *After mastering* ***Universal Design Principles (5.2)****, we follow the exact* ***4-Stage Design Process (5.3 → 5.6)*** *and pair each stage with its canonical* ***UML Diagram****.*

The 4 Iterative Design Stages & UML Models

1. **Stage 1 — Architectural Design (Sec 5.3)**:
   - Synthesize patterns (Layered, Microservices), run ATAM, and model **UML Package & Deployment Diagrams**.
2. **Stage 2 — Interface & Contract Spec (Sec 5.4)**:
   - Specify **Design by Contract (DbC)** (`Pre`, `Post`, `Invariant`) and wire **UML Component Diagrams** (`—○` / `—(`).
3. **Stage 3 — Component & OO Design (Sec 5.5)**:
   - Apply GoF 23 Patterns & **5 SOLID Principles** modeled via **UML Class & Interface Diagrams**.
4. **Stage 4 — Data & Persistence Design (Sec 5.6)**:
   - Design 3-level **UML ERD Schemas**, 3NF tables, Redis spatial caches, and polyglot persistence.

Design Specification Deliverables (SDS & ADRs)

- **Software Design Specification (SDS — IEEE 1016)**:
  - **Enables Parallel Engineering**: Frontend, Backend, DBAs, and QA build and write tests simultaneously against locked specs.
  - **Contents**: Package/Deployment views, Component API contracts (OpenAPI/Protobuf), Class models & DDL schemas.
- **Architecture Decision Records (ADRs — Michael Nygard)**:
  - Lightweight, Git-versioned records (`Title`, `Status`, `Context`, `Decision`, `Consequences`) capturing **why** key trade-offs were chosen —preventing costly "*Architectural Archaeology*"!

5.2 Universal Software Design Principles

> *"Good design is easily changeable; poor design resists change at every step."*
> *— Dave Thomas (The Pragmatic Programmer)*

Universal Principles: Fractal Across Every Scale

- **Software Design is Fractal:**
  - The same fundamental principles govern software quality regardless of zoom level:
    - **System Scale (Macro)**: Microservices partition business domains into decoupled, cohesive services.
    - **Module Scale (Meso)**: Packages and libraries isolate responsibilities behind public API boundaries.
    - **Class Scale (Micro)**: Individual classes encapsulate state and maintain a single, cohesive reason to change.
- **Core Tenets Guard Against Complexity:**
  - Computer memory is vast, but human working memory is strictly limited (Miller's Law: 7 ± 2 chunks).
  - Software principles are cognitive tools designed to keep software understandable, testable, and modifiable by human engineering teams.

Core Design Tenets: Modularity, Abstraction & SoC


- **1. Abstraction — *[Cognitive View: "What It Does"]*:**
  - Distills complex reality into clean, high-level public contracts (`interface`) while ignoring irrelevant details, reducing developer mental load.
- **2. Encapsulation & Information Hiding — *[Protective Boundary: "How State Is Guarded"]*:**
  - *David Parnas's Principle:* Bundles state and behavior inside a capsule while locking away `private` secrets to prevent external state corruption.
- **3. Separation of Concerns (SoC) — *[Logical Dimension: "Orthogonal Aspects"]*:**
  - Separates distinct problem domains or roles (e.g., UI presentation vs. business rules vs. SQL persistence vs. logging) so concerns never tangle.
- **4. Modularity — *[Structural Packaging: "Swappable Building Blocks"]*:**
  - Physically organizes software into discrete, self-contained units (packages, libraries, microservices) that compile, test, and deploy independently.

The Golden Rule: High Cohesion & Low Coupling

- **Cohesion :**
  - Measures how tightly focused and related the internal responsibilities of a single class or module are.
  - **Engineering Goal: High Cohesion** (A module should do one thing, and do it exceptionally well).
- **Coupling :**
  - Measures the strength of direct interdependencies between separate modules.
  - **Engineering Goal: Low Coupling** (Modules communicate via abstract contracts, remaining ignorant of internal implementation details).
- **The Universal Golden Rule:**

> ***Maximize Cohesion, Minimize Coupling!***
> *High cohesion makes modules understandable and maintainable; low coupling prevents modifications from causing cascading system ripple effects.*


Cohesion & Coupling: Bad vs. Good Design (UML Comparison)



- **Bad Design (`OrderManager`)**: Cramming SQL, pricing math, HTML rendering, and SMTP sockets into one class yields **Coincidental Cohesion** and **Tight Concrete Coupling**.
- **Good Design (`OrderProcessor`)**: Delegating to focused collaborators via injected interfaces achieves **Functional Cohesion** and **Loose Abstract Coupling**.


Visual Spectrum: The 7 Levels of Cohesion (Strong to Weak)


Strong & Focused Cohesion (Levels 7 → 4)



7. Functional Cohesion
(1 Single Well-Defined Task)


IDEAL (BEST)






6. Sequential Cohesion
(Output of A Feeds Input of B)

STRONG





Direct Data Relay Pipeline



5. Communicational
(Operate on Same Data Record)

ACCEPTABLE






4. Procedural Cohesion
(Grouped by Order, Diff Data)

MODERATE

Step 1: checkPermission()
↓ (Control Order Only)
Step 2: writeDiskAudit()


Weak & Entangled Cohesion (Levels 3 → 1)



3. Temporal Cohesion
(Same Time Slot Only)

WEAK (REFACTOR)






2. Logical Cohesion
(Flag-Controlled Switch Box)

POOR (ANTI–OCP)





1. Coincidental Cohesion
(Zero Meaningful Relation)

WORST (ELIMINATE)



Cohesion Refactoring Rule (Single Responsibility Principle)

Split Coincidental / Logical / Temporal God Classes (Levels 1–3)
→ Into Focused Functional & Sequential Collaborators (Levels 6–7)


Levels and Types of Cohesion: From Weak to Strong

- **Cohesion Spectrum (Yourdon & Constantine):** How strongly focused a single module's internal elements are:

Level	Cohesion Type	Core Characteristics	Real-World Example	Quality
7	**Functional**	Performs one single, well-defined domain or math task	`computeSalesTax()`, `sin(x)`	**Ideal (Best)**
6	**Sequential**	Output of one step serves directly as input to the next	`read()` → `parse()` → `validate()`	**Strong**
5	**Communicational**	Operations share the same input or output data structure	`updateAddr()` & `printLabel()`	**Acceptable**
4	**Procedural**	Grouped by execution order, operating on different data	`checkAuth()` then `auditLog()`	**Moderate**
3	**Temporal**	Grouped purely because they execute at the same time	`initStartup()`, `closeAll()`	**Weak (Avoid)**
2	**Logical**	Similar tasks selected via an external control flag	`export(int mode)` (PDF/CSV)	**Weak (Avoid)**
1	**Coincidental**	Unrelated catch-all tasks with no meaningful relationship	`CommonUtils`, `MiscHelper`	**Worst**

Visual Spectrum: The 6 Levels of Coupling (Loose to Tight)


Loose & Modular Coupling (Levels 6 → 4)



6. Message / Event
(Async Events, Zero Direct Ref)

IDEAL (LOOSEST)


```
publish(OrderPlaced)
```
Sender & Receiver Have
0 Compile–Time Dependency



5. Data Coupling
(Passes Needed Primitives Only)

BEST (DIRECT)

```
calcFee(double km)
```
Passes Only Exact Values
Zero Knowledge of Order
or Customer Class Structure



4. Stamp Coupling
(Whole Object for 1 Field)

MODERATE


```
findZone(Customer c)
return map.get(c.zipCode);
```
Risk: Tied to Customer Class
Fix: Pass String zipCode

Loose Coupling Firewall (Levels 5–6 + Interface Contracts)

Module A → [Narrow Interface / Primitives / Event] → Module B

Result: Changing Module B Internals Causes Zero Ripple Effect on Module A


Tight & Pathological Coupling (Levels 3 → 1)



3. Control Coupling
(Flag Dictates Internal Branch)

HIGH RISK


```
pay(amt, int mode)
```
Caller Must Know Internal
if/else Flag Constants
Fix: Polymorphic Strategy



2. Common (Global)
(Shared Global Mutable State)

SEVERE RISK

```
GlobalApp.currentCart
```
Hidden Side Effects &
Thread Race Conditions
Any Reader Can Corrupt All



1. Content Coupling
(Mutates Private Internals)

WORST (PATHOLOGICAL)

```
Encapsulation Breach
order.payment.rawSql
= "UPDATE paid=1";
```
Any Change in B Breaks A!

Tight Coupling Ripple Effect (Levels 1–3 Domino Failure)

Change 1 Private Field in Mod B → Breaks Mod A → Breaks Mod C

→ Refactor to Data / Event Coupling (Levels 5–6) via Narrow Interfaces

Levels and Types of Coupling: From Tight to Loose

- **Coupling Spectrum:** Measures the degree of direct interconnections and dependencies between separate modules:

Level	Coupling Type	Coupling Mechanism & Risk	Real-World Example	Quality
1	**Content (Pathological)**	Reaches directly into private fields/branches of another	Modifying a `private` field via reflection	**Worst (Severe)**
2	**Common (Global)**	Multiple modules read/write shared global mutable state	Sharing mutable global flags across threads	**High Risk**
3	**Control**	Caller dictates callee's internal execution flow via flags	Passing `mode = 3` to select internal branch	**Moderate Risk**
4	**Stamp (Data-Struct)**	Passes a whole composite object when only 1 field is needed	Passing entire `Customer` to read `zipCode`	**Acceptable**
5	**Data**	Communicates exclusively via needed primitive parameters	`calculateArea(width, height)`	**Best (Direct)**
6	**Message / Event**	Communicates asynchronously via events with zero reference	Publishing `OrderPlacedEvent` via EventBus	**Ideal (Loosest)**

Concept Check Question 1 (CCQ 1)

In software system design, what is the primary practical benefit of combining **High Cohesion** with **Low Coupling**?

- **A.** Maximizes raw CPU execution speed by inlining all helper methods into one monolithic binary executable.
- **B.** Isolates internal class changes behind clean boundaries so modifications cause minimal ripple effects.
- **C.** Mandates storing all shared domain data structures inside a single globally mutable memory namespace.
- **D.** Eliminates the need to run automated integration test suites or continuous regression checks in CI/CD.



5.3 Stage 1 — Architectural Design: Patterns, Trade-offs & Macro UML

> *"There are no solutions, only trade-offs."*
> *— Thomas Sowell*

What is Software Architecture?

- **Formal Definition (IEEE 1471 / ISO 42010):**

> *Software architecture is the fundamental organization of a system embodied in its components, their relationships to each other and the environment, and the principles guiding its design and evolution.*


- **The Bridge Role of Architecture:**
  - **Requirements (What)**: Stakeholder needs, user stories, and constraints.
  - **Implementation (How)**: Source code, data schemas, and unit tests.
  - **Architecture (The Bridge)**: Transforms messy requirements into structured sub-systems, communication boundaries, and deployment topology.
- **Architecture in the Small vs. in the Large:**
  - **In the Small**: Internal design of individual applications (classes, modules, local interfaces).
  - **In the Large**: Enterprise-scale structures (distributed services, cloud platforms, event buses, multi-tier databases).

What is an Architectural Pattern?

- **Definition of Architectural Patterns:**
  - An architectural pattern is a **reusable, established solution to a commonly occurring structural problem** in software system design.
  - While design patterns (e.g., Factory, Strategy) operate at the class level, architectural patterns govern the **entire macro-system topology**.
- **Three Key Elements of an Architectural Pattern:**
  - **1. Context**: The recurring design situation and engineering environment.
  - **2. Problem & Forces**: Competing requirements (e.g., decoupling UI from business logic vs. minimizing latency).
  - **3. Solution & Consequences**: Structural partitioning, communication topology, and resulting trade-offs.
- **Why Patterns Matter:**
  - Establishes a shared architectural vocabulary across engineering teams.
  - Codifies decades of engineering experience, avoiding recurring structural failures.


Visual Roadmap: The 6 Architectural Patterns in 5.3


Centralized & Structural Patterns



2. Layered (N-Tier) Architecture


(Strict Downward Calls)






1. Model-View-Controller (MVC) Architecture


(Decoupled UI & State)







3. Repository (Blackboard) Architecture

(Central Shared Data Store)





Monolithic Architecture




Modular Component Design


Distributed, Routing & Flow Patterns



4. Client-Server Architecture


(Edge Clients ↔ Central Tier)






5. Pipe-and-Filter Stream Architecture


(Sequential Stateless Filters)






6. Microservices (MSA) Architecture

(Database-per-Service Pods)





Event–Driven Bus Topology

Real–World System Composition


Client–Server + MVC (Frontend)
+ Microservices + Layered (Services)
+ Pipe–Filter + Repository (Dispatch)

Multi–Pattern Hybrid Architecture

Architectural Patterns: Comprehensive Overview Matrix

Pattern Name	Visual Topology	Core Mechanism	Best Used For	Primary Risk & Trade-off
1. MVC	Triangular Cycle (`C → M → V`)	Separates UI presentation from data models	Interactive Web / mobile apps with rich UIs	Overkill for simple data display (CRUD)
2. Layered	Vertical Stack (`N → N-1`)	Strict hierarchy with one-way downward calls	Enterprise information systems & CRUD apps	Performance overhead; sinkhole anti-pattern
3. Repository	Hub-and-Spoke Central Store	Passive central data store with active agents	Compilers, IDEs, and shared data analysis	Central DB bottleneck & single point of failure
4. Client-Server	Distributed Network (`C ↔ S`)	Clients request services from central servers	Web apps, file servers, centralized services	Network latency & server overloading
5. Pipe-Filter	Linear Sequential Stream	Discrete transform filters connected via pipes	Data processing, compilers, ETL pipelines	Inefficient for interactive systems; parsing cost
6. Microservices	Decentralized Mesh (`S ↔ S`)	Independently deployable domain services	Large-scale, rapidly evolving cloud platforms	High operational, network & transactional complexity


1. Model-View-Controller (MVC) Pattern — Visual Topology



1. Model-View-Controller (MVC): Responsibilities & Trade-offs

- **Core Structural Responsibilities:**
  - **Model**: Encapsulates core business data, validation rules, and authoritative domain state; remains completely ignorant of UI presentation.
  - **View**: Renders visual representations (HTML, mobile screens, charts) to users and listens for Model state change notifications.
  - **Controller**: Intercepts user inputs and HTTP requests, orchestrates business workflows, updates the Model, and selects the target View.
- **When Used & Real-World Scenarios:**
  - Interactive Web and mobile applications where the same underlying data must be presented in multiple visual formats (e.g., dashboard tables, charts, and mobile views).
- **Engineering Advantages & Trade-offs:**
  - **Strengths**: Clean separation of concerns; UI designers and backend engineers can evolve presentation and business logic in parallel.
  - **Weaknesses**: Introduces extra indirection and boilerplate for simple CRUD screens; tight coupling arises if Views bypass Controllers to mutate state.


2. Layered Architecture Pattern — Visual Topology



2. Layered Architecture: Responsibilities & Trade-offs

- **Core Structural Responsibilities:**
  - Organizes the system into horizontal abstraction tiers: **Presentation** → **Application/Service** → **Business/Domain** → **Persistence**.
  - **Strict Layering Rule**: Each layer depends solely on the layer immediately below it (`Layer N → Layer N-1`), forbidding upward or skipped-layer calls.
- **When Used & Real-World Scenarios:**
  - Standard enterprise information systems, e-commerce backends, and banking applications requiring clear team boundaries and multi-level security isolation.
- **Engineering Advantages & Trade-offs:**
  - **Strengths**: High modularity and change isolation—swapping MySQL for DynamoDB in the Persistence layer leaves core Business Logic completely untouched.
  - **Weaknesses**: Susceptible to the **"Architecture Sinkhole Anti-Pattern"**, where requests merely pass through multiple layers without processing, adding latency and object-mapping overhead.

3. Repository Architecture Pattern — Visual Topology



Key Characteristics

Hub-and-Spoke Topology:
Subsystems never call each other directly; all data is exchanged via the repository.


Primary Strength:
Fast sharing of large data models; easy to plug in tools.

Single Point of Failure:
Repository crash or lock halts all connected tools.

3. Repository Architecture: Responsibilities & Trade-offs

- **Core Structural Responsibilities:**
  - **Central Repository**: A passive, authoritative data store maintaining all shared persistent state and schema invariants.
  - **Active Subsystems**: Independent tools or processing agents that never call each other directly, interacting exclusively through the central store.
- **When Used & Real-World Scenarios:**
  - Data-intensive environments where multiple specialized tools process the same complex data representation: **IDEs, compilers (shared AST), CAD systems, and AI Blackboard systems**.
- **Engineering Advantages & Trade-offs:**
  - **Strengths**: Eliminates direct inter-tool coupling; new analysis tools can be plugged into the repository effortlessly without modifying existing subsystems.
  - **Weaknesses**: The central repository is a **Single Point of Failure (SPOF)** and a major contention bottleneck under heavy concurrent writes; schema evolution affects all connected tools.

4. Client-Server Architecture Pattern — Visual Topology




4. Client-Server Architecture: Responsibilities & Trade-offs

- **Core Structural Responsibilities:**
  - **Client Tier**: Distributed consumer nodes responsible for user interaction, local rendering, and initiating network service requests.
  - **Server Tier**: Centralized provider nodes enforcing authentication, business rules, concurrent access control, and persistent data storage.
- **When Used & Real-World Scenarios:**
  - Web applications, mobile banking, multiplayer online services, and enterprise systems where shared data must be accessed securely from diverse locations.
- **Engineering Advantages & Trade-offs:**
  - **Strengths**: Centralizes security governance, data backups, and server-side upgrades; stateless application servers can scale horizontally behind load balancers.
  - **Weaknesses**: Vulnerable to network latency, packet loss, and connection drops; centralized server endpoints face DDoS and traffic-surge overload risks.

5. Pipe-and-Filter Architecture Pattern — Visual Topology

ARCHITECTURAL PATTERN 05 / PIPE & FILTER



Terminal (Unix Shell Pipe Analogy)

```
$ cat access.log | grep "500" | sort | uniq -c
```

Each filter is stateless and decoupled from upstream/downstream stages.

High Composability: Filters can be recombined or parallelized freely.

Best Used For: ETL pipelines, compilers, stream processing


Key Strength: High reuse & easy multi-core concurrency

Trade-off: Unfit for interactive UIs; parsing overhead

5. Pipe-and-Filter Architecture: Responsibilities & Trade-offs

- **Core Structural Responsibilities:**
  - **Filters**: Independent, stateless transformation units that consume an input stream, apply a single focused transformation, and emit an output stream.
  - **Pipes**: Unidirectional connectors that buffer and transport data streams between adjacent filters without the filters knowing each other's identity.
- **When Used & Real-World Scenarios:**
  - Multi-stage data processing pipelines: **Unix shell pipelines (`cat | grep | sort`), compiler front-ends, audio/video media encoding, and Big Data ETL workflows**.
- **Engineering Advantages & Trade-offs:**
  - **Strengths**: Exceptional composability and reuse—filters can be reordered, added, or executed concurrently across CPU cores.
  - **Weaknesses**: Ill-suited for interactive event-driven GUIs; incurs data parsing/serialization overhead at every pipe boundary and requires a common stream format.

6. Microservices Architecture Pattern (MSA) — Visual Topology




6. Microservices Architecture (MSA): Responsibilities & Trade-offs

- **Core Structural Responsibilities:**
  - **Autonomous Domain Services**: Small, business-capability-aligned services running in isolated processes with independent CI/CD deployment pipelines.
  - **Database-per-Service**: Each microservice strictly encapsulates its own private database; inter-service communication occurs solely via APIs (REST/gRPC) or Event Brokers (Kafka).
- **When Used & Real-World Scenarios:**
  - Large-scale cloud platforms (e.g., Netflix, Uber, Amazon) with dozens of autonomous engineering teams requiring rapid, independent release cycles and elastic scaling per domain.
- **Engineering Advantages & Trade-offs:**
  - **Strengths**: Superior **fault isolation (blast-radius containment)**, independent scaling of bottleneck services, team autonomy, and polyglot technology freedom.
  - **Weaknesses**: High distributed systems complexity—network latency, eventual consistency (Saga transactions), distributed tracing, and heavy Kubernetes/DevOps operational cost.

Monolithic vs. Microservices: Deep Dive

Comparison Dimension	Monolithic Architecture	Microservices Architecture
Deployment Unit	Single unified binary / WAR / container	Dozens/hundreds of independent containers
Data Storage	Single shared relational database	**Database-per-Service** (strict data encapsulation)
Communication	Fast in-memory function calls	Network RPC / REST / gRPC / Event Bus
Fault Isolation	**Poor**: Memory leak in Module A crashes entire app	**Superior**: Payment service crash leaves Browse active
Team Scalability	Merge conflicts; coordination bottlenecks	Independent feature teams deploying autonomously
Operational Cost	Simple (single CI/CD pipeline, standard logs)	High (Kubernetes, distributed tracing, service mesh)
Architectural Sweet Spot	Startups, MVP stage, small teams (<15 devs)	Large organizations (>50 devs), complex domains

Case Study: Food Delivery System — Multi-Pattern Topology



Case Study Synthesis: 6 Patterns in a Food Delivery System

- **Multi-Pattern Composition:** Real systems combine patterns by **zoom level** and **problem domain**:

Pattern	Food Delivery Subsystem / Zoom Level	Core Engineering Problem Solved
1. MVC	**Customer App & Merchant Portal UI**	One `OrderModel` simultaneously updates Live Map View & Progress Bar View
2. Layered	**Inside `Order Service` (`Controller → Domain → Repo`)**	Isolates delivery fee & promo pricing rules from PostgreSQL persistence
3. Repository	**AI Dispatch Blackboard (`Geo-State Store`)**	Route solver, order batcher & surge pricer share live city map state
4. Client-Server	**Customer / Merchant / Rider Apps ↔ Cloud**	Centralizes menu pricing, auth & payment verification on secure servers
5. Pipe-Filter	**Live Rider GPS Stream (`Denoise → Match → ETA`)**	Processes 100k+ GPS pings/sec through stateless, parallelizable stages
6. Microservices	**Backend Domains (`Menu`, `Order`, `Pay`, `Dispatch`)**	Scales GPS dispatch 20x during rainstorms; isolates promo crashes from checkout

Architecture Directly Shapes Quality Attributes

- **Quality Attributes Cannot Be Retrofitted Later:**
  - You cannot build a tightly coupled monolith and hope a few unit tests will magically make it scalable.
- **How Architectural Decisions Determine Quality Attributes:**
  - ⚡ **Performance**: Dictated by network hops, in-memory caching layers, and database partitioning.
  - 🛡️ **Security**: Dictated by zero-trust network zones, API gateways, and isolation of sensitive databases.
  - 🦺 **Safety**: Dictated by structural isolation of safety-critical functions (e.g., flight control vs. in-flight entertainment).
  - 🔄 **Availability & Fault Tolerance**: Dictated by redundancy, health checks, circuit breakers, and automated failover replicas.
  - 🔧 **Maintainability & Modifiability**: Dictated by strict adherence to High Cohesion and Low Coupling boundaries.

Architectural Trade-off Analysis & ATAM

- **The Inevitable Conflict Matrix (No Silver Bullet):**
  - **Performance vs. Security**: Deep packet inspection, TLS, and fraud checks add latency.
  - **Availability vs. Consistency (CAP Theorem)**: Strict distributed locks block orders during network partitions.
  - **Modularity vs. Performance**: Fine-grained layers and microservice RPCs add serialization overhead.
- **ATAM (Architecture Trade-off Analysis Method — Carnegie Mellon SEI):**
  - Evaluates how architectural decisions satisfy or conflict across **Quality Attribute Scenarios**:
    - **Sensitivity Points**: Decisions critical to a single quality attribute (e.g., *Circuit breakers on* `Payment Service` *directly govern checkout* ***Availability***).
    - **Trade-off Points**: Decisions where improving one quality attribute directly penalizes another.
    - **Risks & Non-Risks**: Unmitigated architectural bottlenecks vs. validated safe design choices.

ATAM Case Study: Food Delivery Architecture Trade-offs


- **Applying ATAM to 4 Critical Decisions in a Food Delivery Platform:**

Architectural Decision	Competing Quality Attributes (Trade-off Point)	ATAM Architectural Resolution
1. Rider GPS Ping Rate (`1s` vs. `15s` interval)	**Map Accuracy (Usability) ↔ Rider Battery & Bandwidth (Efficiency)**	**Adaptive Pinging**: Ping every `2s` near drop-off; throttle to `15s` when waiting at restaurant
2. Checkout & Dispatch (`Sync 2PC` vs. `Async Saga`)	**Strict Data Consistency ↔ Peak Surge Availability & Latency (CAP)**	**Hybrid Saga**: Sync pre-auth for payment, then async Kafka `OrderPlacedEvent` for dispatch
3. AI Dispatch Repository (`Central Store` vs. `Sharded`)	**Global Route Optimality ↔ Single Point of Failure Risk (SPOF)**	**Geo-Sharded In-Memory Cluster**: Partition Redis repository by city zone with active replicas
4. Promo & Fraud Check (`Deep ML` vs. `Fast Rule`)	**Anti-Fraud Security ↔ Checkout Throughput (<200ms Latency)**	**Two-Stage Pipeline**: Fast `<15ms` rule check inline at Gateway; async ML audit post-order

Modeling Macro Structure (1): UML Package Diagram

UML Package Diagram Notation Legend

1. Package Symbol (Tabbed Folder)



Groups logically cohesive classes, interfaces & sub-packages into a single namespace boundary.

Name in top tab or body center.

2. Element Visibility Specifiers

`+ Public Element`
Accessible by external packages

`- Private Element`
Hidden internal implementation

3. Dependency Arrow & Stereotypes



- Dashed open arrow: changes in Supplier may break Client.
- *«import»*: adds supplier public names to client namespace.
- *«access»*: private import (does not re-export elements).


4. Acyclic Dependencies Principle (ADP)

- Package dependency graph must be a **Directed Acyclic Graph**.
- **UI & Infrastructure** depend on **Domain** (never reverse!).



No Cycles!

Food Delivery System — UML Package Diagram (Module & Dependency Structure)



UML Package Diagram: Meaning, Notation & Food Delivery

> ***Architectural Meaning (Compile-Time View):*** *Models* ***source code organization, subsystem boundaries,*** *and* ***dependency direction governance.***

Core UML Notations & Rules

- **Tabbed Folder (`Package`)**: Groups cohesive classes and interfaces into a single namespace (`domain.order`).
- **Visibility (`+` Public vs. `-` Private)**: `+OrderService` & `+IOrderRepository` are exported; `-SurgePricingPolicy` is hidden inside the package.
- **Dependency Arrow (`- - ->`)**: Dashed open arrow with `«import»` or `«access»`; changes in the target package may force recompilation of the source package.
- **Acyclic Dependencies Principle (ADP)**: Package dependency graphs must never form a cycle (`A → B → A` is forbidden).

Food Delivery Design Insights

- **Bounded Context Partitioning**: Separate core domain packages for `domain.order`, `domain.dispatch`, and `domain.payment`.
- **Inward Dependency Governance**:
  - `ui.customer_app` imports `domain.order` downward.
  - `infra.persistence` (`PostgresOrderRepoImpl`) imports `domain.order` (`IOrderRepository`) **upward**!
- **Result**: The entire `domain.*` core has **zero compile-time dependencies** on PostgreSQL, Redis, Kafka, or Stripe SDKs.

Peer Discussion: Chess Game in MVC — UML Package Diagram (PlantUML)

Hands-On Modeling: Architecting a Chess Game in MVC (4 Mins)


- **Scenario:** Your team is designing a desktop/web **Chess Game** using the **Model-View-Controller (MVC)** architectural pattern.
- **1. Partition Classes into 3 Cohesive Packages (`package` syntax):**
  - `chess.model`: `+Board`, `+Piece`, `+MoveValidator`, `-BitboardEngine` (pure chess rules & state).
  - `chess.view`: `+BoardCanvasUI`, `+MoveHistoryPanel`, `+SoundEffectPlayer` (UI rendering).
  - `chess.controller`: `+GameController`, `+TurnClockHandler` (user input routing).
- **2. Draw the Package Diagram in PlantUML (PlantText):**
  - Use `package "chess.model" { ... }` and connect packages via `..> : «import»`.
  - **Audit Question:** Which direction do the dependency arrows point? Does `chess.model` import `chess.view`? Does your diagram satisfy the **Acyclic Dependencies Principle (ADP)**?



Modeling Macro Topology (2): UML Deployment Diagram

UML Deployment Diagram Notation Legend

1. Node (3D Cube: Hardware or Runtime Env)




- **«device»**: Physical compute resource (Server, Phone, IoT).
- **«executionEnvironment»**: OS, Docker Container, K8s Pod, JVM, or DBMS nested inside.

2. Deployable Artifact («artifact»)



Concrete physical file deployed onto a Node (e.g., `.jar`, `.war`, `.ipa`, Docker image, SQL schema) that *«manifest»* a component.

3. Communication Path & Multiplicity




- Solid line = network link + transport protocol & cardinality.

4. Why Deployment Diagrams Are Vital

- Bridges **software binaries** to **cloud infrastructure**.
- Reveals **Single Points of Failure (SPOF)**, firewall boundaries, replication topology & auto-scaling pools that are 100% invisible in Class or Package diagrams!

Food Delivery System — UML Deployment Diagram (Cloud Infrastructure)



UML Deployment Diagram: Meaning, Notation & Food Delivery

> ***Architectural Meaning (Runtime Infrastructure View):*** *Models* ***physical hardware nodes, cloud runtime containers, deployable binary artifacts, and network protocols.***

Core UML Notations & Rules


- **3D Node Cube (`«device»` / `«executionEnv»`)**:
  - `«device»`: Physical compute host (Mobile phone, AWS EC2, Load Balancer).
  - `«executionEnvironment»`: Nested runtime container (Kubernetes Pod, Docker, JVM, PostgreSQL Engine).
- **Artifact (`«artifact»` + 📄 Icon)**: Concrete deployable binary/file (`order-service:v2.4.jar`, `rider-gps.apk`) that `«manifest»` a logical component.
- **Communication Path & Multiplicity**: Solid line labeled with network protocol (`«gRPC / HTTP2»`, `«JDBC / TLS»`) and node cardinality (`[5..20]`).

Food Delivery Design Insights

- **Exposes High-Availability & Scaling Policies**:
  - `Dispatch Engine Pod [5..20]` scales wider than `Payment Pod [2..6]` to handle 6 PM dinner GPS spikes.
- **Eliminates Single Points of Failure (SPOF)**:
  - Shows `RDS PostgreSQL [1 Primary + 2 Replica]`, `Redis ElastiCache [6 Shards]`, and `Kafka [3 Nodes]`.
- **Makes Network Boundaries Explicit**:
  - External traffic uses `«HTTPS / REST & WSS»`, internal east-west traffic uses `«gRPC»`, and Payment uses `«HTTPS / mTLS»` to `Stripe Cloud`.


Section 5.3 Visual Recap: Structural vs. Distributed Patterns


Centralized & Structural Patterns



2. Layered (N-Tier) Architecture


(Strict Downward Calls)






1. Model-View-Controller (MVC) Architecture


(Decoupled UI & State)







3. Repository (Blackboard) Architecture

(Central Shared Data Store)





Monolithic Architecture




Modular Component Design


Distributed, Routing & Flow Patterns



4. Client-Server Architecture


(Edge Clients ↔ Central Tier)






5. Pipe-and-Filter Stream Architecture


(Sequential Stateless Filters)






6. Microservices (MSA) Architecture

(Database-per-Service Pods)





Event–Driven Bus Topology

Real–World System Composition

Client–Server + MVC (Frontend)

+ Microservices + Layered (Services)

+ Pipe–Filter + Repository (Dispatch)

Multi–Pattern Hybrid Architecture

Concept Check Question 2 (CCQ 2)

When comparing a Monolithic architecture with a Microservices architecture, what is the primary structural reason that Microservices provide superior **fault isolation** (blast radius containment)?

- **A.** All services read and write to a single shared enterprise SQL database instance with global table locks.
- **B.** Each service runs in an isolated process with a private database, containing the blast radius of crashes.
- **C.** Distributed service calls completely eliminate network serialization overhead and inter-node TCP latency.
- **D.** Decomposing a monolith into microservices drastically reduces DevOps infrastructure and monitoring costs.



5.4 Stage 2 — Interface & Contract Specification: DbC & Component UML

> *"Treat every software module boundary as a formal legal contract with explicit rights and obligations."*
> *— Bertrand Meyer (Creator of Design by Contract)*

Formal Interface Specification & Design by Contract (DbC)

How to Specify an Interface Contract: Design by Contract (DbC)

Example: Food Delivery Checkout Interface — IOrderCheckoutAPI.placeOrder(cart, paymentToken) : OrderReceipt

CLIENT (Caller)

Customer App / API Gateway

Invokes operation:

```
placeOrder(cart, token)
```

Must satisfy Precondition before calling!

1. PRECONDITION (requires)

Client's Obligation Before Call

- `cart != null`
- `cart.items.size() >= 1`
- `paymentToken.isValid()`
- `restaurant.isOpenNow()`

If violated → Caller is at fault!

SUPPLIER (Callee)

«component» OrderService

Executes business logic (Internal implementation hidden behind interface)

Assumes Precondition holds; delivers Postcondition!

2. POSTCONDITION (ensures)

Supplier's Guarantee on Return

- `receipt.status == CONFIRMED`
- `stock_after == stock_pre - qty`
- `payment.isCaptured() == true`
- `OrderPlacedEvent emitted`

If violated → Supplier has a bug!

3. CLASS INVARIANT (invariant — Domain Integrity Rules That Must Hold Before AND After Every Method Call)

Financial Integrity Invariant

`order.totalAmount >= 0`

(Order total can never be negative)

Order Structural Invariant

`sum(items.price) + fee == total`

(Line items always reconcile to total)

Dispatch Capacity Invariant

`rider.activeOrders <= 3`

(A courier never holds > 3 active orders)

Design by Contract (DbC): Rights, Obligations & API Specs

> ***Core Principle (Bertrand Meyer):*** *If the* ***Client*** *fulfills the* ***Precondition****, the* ***Supplier*** *is contractually bound to deliver the* ***Postcondition*** *while preserving the* ***Class Invariant****.*

The 3 Pillars of Design by Contract (DbC)

- **1. Precondition (`requires` — Client Obligation)**:
  - What must be true *before* invocation (`!cart.isEmpty() && token.isValid()`).
  - *Benefit to Supplier*: No need to litter internal code with redundant defensive checks; if violated, fail fast!
- **2. Postcondition (`ensures` — Supplier Guarantee)**:
  - What the Supplier guarantees *after* execution (`order.status == CONFIRMED && stock_after == stock_before - qty`).
  - *Benefit to Client*: Guaranteed outcome without inspecting Supplier internals.
- **3. Class Invariant (`invariant` — Domain Integrity)**:
  - Always true before and after any operation (`order.totalAmount >= 0`).

Industrial Interface Specification Standards

- **Eliminating Ambiguity Across Teams**:
  - Frontend, Mobile, and Backend teams lock interface specs in the **SDS** on Day 1 to enable **parallel development & contract testing**.
- **Modern Machine-Readable Contract Formats**:
  - **REST APIs**: **OpenAPI 3.1 (Swagger)** — specifies endpoints, JSON schemas, status codes (`201`, `400`, `422`), and validation bounds.
  - **RPC Services**: **Protocol Buffers (`.proto`)** — strongly-typed binary contracts for east-west `gRPC` calls.
  - **Event Streams**: **AsyncAPI / Apache Avro** — versioned schemas for Kafka `OrderPlacedEvent` payloads + **Idempotency Keys** (`idempotency_key: UUID`) to prevent duplicate payment charging!

Peer Discussion: Formal Design Specification for `bubbleSort(int[] arr)`

Pair Challenge: Specify the Complete DbC Contract for Bubble Sort (4 Mins)

- **Scenario:** Anyone can code `void bubbleSort(int[] arr)`, but writing a **mathematically airtight Design by Contract (DbC) specification** is surprisingly tricky!
- **1. Precondition (`requires` — Client Obligation):**
  - What must the caller guarantee about `arr` before calling? (`arr != null`? Is `arr.length == 0` valid?)
- **2. Postcondition (`ensures` — Supplier Guarantee):**
  - *The Classic Trap:* Suppose a developer writes only: `∀ i ∈ [0, n-2] : arr[i] <= arr[i+1]`.
  - *Critique:* If a buggy `bubbleSort` overwrites every element with zeros (`[0, 0, 0, 0]`), does it pass that postcondition? **YES!** What **second postcondition** is missing? *(Hint: Permutation / Multiset preservation!)*
- **3. Loop Invariant (`invariant`):** After outer pass `k`, what is guaranteed about the last `k` elements?



Modeling Interface Contracts: UML Component Diagram

UML Component Diagram Notation Legend

1. Component Classifier («component»)

«component»
OrderService

A modular, replaceable unit that encapsulates state & behavior behind explicit interfaces.
Icon: 2-tabbed box in top-right.

2. Provided Interface — "Lollipop / Ball" (—○)

Provider —○ IPaymentAPI

Contract that the component **realizes & exposes** to clients (e.g., REST/gRPC/Service API).

3. Required Interface — "Socket" (—( )

Consumer —(IPaymentAPI


Contract that the component **requires / depends on** from an external provider to operate.

4. Assembly Connector (Ball-and-Socket) & Port (□)

Order —○ IPayment —(StripePay Plug & Play!

- **Assembly Connector —(○—**: Wires consumer socket to provider lollipop. Consumer never knows provider's concrete class!
- **Port (□ on edge)**: Explicit boundary endpoint isolating external traffic & delegating (`-->`) to internal parts.

Food Delivery System — UML Component Diagram (Interface Contracts)



UML Component Diagram: Meaning, Notation & Food Delivery

> ***Stage 2 Modeling Purpose:*** *Models* ***modular, replaceable software components*** *wired strictly through* ***plug-and-play interface contracts*** *(visualizing* ***Design by Contract****).*

Core UML Notations & DbC Mapping

- **Component (`«component»` + ⧉ Icon)**: Encapsulated, replaceable unit whose internal classes are hidden behind explicit interfaces.
- **Provided Interface (`—○` Lollipop / Ball)**: Contract realized by a Supplier component (`IOrderCheckoutAPI` — guarantees DbC **Postconditions**).
- **Required Interface (`—(` Socket)**: Contract demanded by a Client component (`IPaymentGateway` — must satisfy DbC **Preconditions**).
- **Assembly Connector (`—(○—` Ball & Socket)**: Mates a required socket to a provided lollipop with zero implementation coupling.
- **Port (`□`) & Delegation (`- - ->`)**: Boundary endpoint forwarding external calls to internal sub-components.

Food Delivery Design Insights

- **Composite Subsystem Decomposition**: `Order Management` encapsulates internal `OrderStateEngine` and `MenuPricingCalc` behind an external boundary Port (`□`).
- **Hot-Swappable Plug-and-Play**:
  - `Order Management` only binds to socket `IPaymentGateway`.
  - Whether the lollipop is provided by `Stripe`, `ApplePay`, or an in-memory `MockPaymentStub` during CI testing, `Order Management` requires **zero code changes**!
- **Geo-Dispatch Contract**: `Rider Dispatch Engine` queries `Rider Geo-Location Tracker` strictly via `IGeoSpatialIndex`.

Concept Check Question 3 (CCQ 3)

In Stage 2 (**Interface & Contract Specification**), how do Bertrand Meyer's **Design by Contract (DbC)** and the **UML Component Diagram** work together when `Order Management` calls `Payment Component` via the `IPaymentGateway` interface?

- **A.** `Order Management` exposes a Lollipop (`—○`) and may freely pass negative order amounts without validation.
- **B.** Client Socket (`—(`) must satisfy the **Precondition**, while Supplier Lollipop (`—○`) guarantees the **Postcondition**.
- **C.** Component diagrams use 3D hardware node cubes (`«device»`) to bypass runtime Precondition and Postcondition checks.
- **D.** Design by Contract requires the caller component to directly mutate private SQL tables inside the supplier module.

5.5 Stage 3 — Component & Detailed OO Design: Patterns, SOLID & Class UML

> *"Clean code always looks like it was written by someone who cares."*
> *— Robert C. Martin (Uncle Bob)*

What Are Design Patterns? From GoF to SOLID Foundations


- **What Is a Software Design Pattern?**
  - While **Architectural Patterns** (Section 5.3) define system-wide macro topology, **Design Patterns** provide reusable, proven micro-level solutions to recurring class and object design problems within a specific context.
- **The Vast Landscape of Design Patterns (e.g., Gang of Four — GoF 23 Patterns):**
  - **Creational Patterns (5)**: *Factory Method, Abstract Factory, Builder, Singleton, Prototype* (decouple object creation).
  - **Structural Patterns (7)**: *Adapter, Decorator, Facade, Proxy, Composite, Bridge* (compose classes & interfaces).
  - **Behavioral Patterns (11)**: *Strategy, Observer, Command, State, Template Method, Iterator* (manage object collaboration).
- **Our Focus Here — The 5 SOLID Design Principles (Robert C. Martin):**
  - Rather than memorizing 23 GoF patterns by rote, we focus on **SOLID**—the **foundational "first principles"** upon which nearly all GoF patterns are built (e.g., *Strategy* realizes **OCP**; *Adapter* realizes **DIP**)!

Overview: The 5 SOLID Design Principles in UML

- **How SOLID Shapes Class & Interface Topologies:**
  - **S — Single Responsibility Principle (SRP)**: Partition bloated "God Classes" so each class serves **1 Actor / 1 Reason to Change**.
  - **O — Open / Closed Principle (OCP)**: Replace rigid concrete dependencies with **polymorphic** `«interface»` **abstractions** (`- - -|>`).
  - **L — Liskov Substitution Principle (LSP)**: Ensure every subclass (`——|>`) or realization (`- - -|>`) honors the **behavioral contract** of its base type.
  - **I — Interface Segregation Principle (ISP)**: Split bloated "Fat Interfaces" into **lean, role-specific** `«interface»` **contracts**.
  - **D — Dependency Inversion Principle (DIP)**: Invert dependency arrows **upward** so both high-level policies and low-level details depend on abstractions.

S — Single Responsibility Principle (SRP): UML Comparison


✘ Violating SRP: God Class with 3 Reasons to Change



Why This UML Design Fails (Coincidental / Logical Cohesion):

- **3 Orthogonal Axes of Change** collide inside one class file.
- A routine UI tweak by Marketing (`renderHtmlInvoice`) forces recompiling and redeploying mission-critical CFO tax calculation & SQL persistence!
- Frequent Git merge conflicts across Finance, Frontend, and Backend teams.

✓ Following SRP: 1 Cohesive Class per Actor



Why This UML Design Excels (Functional Cohesion + Data Coupling):

- **1 Class = 1 Stakeholder = 1 Reason to Change**.
- UI changes in `InvoiceHtmlRenderer` have **zero blast radius** on tax calculations or SQL persistence; each class can be unit-tested in isolation!

S — Single Responsibility Principle (SRP): Design Analysis

> ***Definition (Robert C. Martin):*** *"A class should have one, and only one, reason to change (i.e., be responsible to one, and only one, actor/stakeholder)."*

❌ UML Anti-Pattern: The "God Class"


- **Tangled Axes of Change**: `OrderInvoiceReport` combines **Financial Rules** (`calculateTaxAndSurge`), **Presentation Formatting** (`renderHtmlInvoice`), and **Database I/O** (`saveToPostgresDb`).
- **Fragility & Merge Collisions**:
  - When UX designers tweak receipt CSS inside `OrderInvoiceReport`, they risk breaking CFO tax logic or triggering SQL regressions.
  - achieves low **Coincidental / Logical Cohesion**.

✅ UML Refactoring: 1 Class per Actor

- **Cohesive Decomposition**:
  - `InvoiceTaxCalculator` ➔ Serves **CFO / Finance**.
  - `InvoiceHtmlRenderer` ➔ Serves **UX / Marketing**.
  - `InvoiceSqlRepository` ➔ Serves **DBA / Infra**.
- **Architectural Payoff**:
  - Achieves **Level 1 Functional Cohesion** and **Data Coupling** (passing only `OrderInvoice`).
  - Each class can be modified, tested, and deployed independently with zero cross-team interference.

O — Open / Closed Principle (OCP): UML Comparison


✘ Violating OCP: Rigid Concrete Coupling & Switch Chains



Why This Violates OCP (Not Closed for Modification):

- `OrderNotificationService` is directly coupled to every concrete channel.
- Every time business adds a new channel (LINE, WhatsApp, Discord), engineers must **cut open and modify** the tested core service class.
- High risk of breaking existing Email/SMS logic during routine extensions!

✓ Following OCP: Open for Extension, Closed for Modification



Why This UML Design Excels (Polymorphic Strategy / Plugin Pattern):

- `OrderNotificationService` depends solely on the stable `INotificationChannel`.
- To support **LINE Notify** or **Discord**, we simply add a new class that realizes (- - -|>) the interface—**0 lines modified** in the core service!
- Eliminates regression bugs in existing battle-tested notification channels.

O — Open / Closed Principle (OCP): Design Analysis

> ***Definition (Bertrand Meyer):*** *"Software entities (classes, modules, components) should be* ***open for extension****, but* ***closed for modification****."*

❌ UML Anti-Pattern: Direct Concrete Coupling


- **Hardwired Fan-Out (`⟶`)**: `OrderNotificationService` directly depends on concrete `EmailSender` and `SmsSender` classes via `if / else if` type-switching.
- **Violation of "Closed for Modification"**:
  - Adding `LineNotifySender`, `WhatsApp`, or `Discord` forces engineers to **open and edit** the core `OrderNotificationService` class.
  - Every edit risks breaking existing, production-tested notification channels!

✅ UML Refactoring: Polymorphic Interface Pivot

- **Stable Abstraction (`«interface» INotificationChannel`)**:
  - `OrderNotificationService` depends **only** on `INotificationChannel.send(msg)` (🔒 **Closed for Modification**).
- **Plug-in Realization (`- - -▷`)**:
  - `EmailChannel`, `SmsChannel`, and the new `LineNotifyChannel` independently realize `INotificationChannel` (🔓 **Open for Extension**).
- **Zero-Touch Expansion**: New channels are added as standalone classes with zero impact on core orchestration.

L — Liskov Substitution Principle (LSP): UML Comparison


✘ Violating LSP: Subclass Breaks Base Class Postcondition



Why This Violates Liskov Substitution Principle (LSP):

- **Rectangle Postcondition Contract**: `setHeight(h)` modifies `height` while leaving `width` invariant.
- `Square` violates this postcondition! Mathematical "IS-A" does NOT imply behavioral substitutability when mutable state setters are involved.

✓ Following LSP: Substitutable Contract via Shared Abstraction



Why This UML Design Excels (100% Behavioral Substitutability):

- `Rectangle` and `Square` are independent siblings realizing `IShape`.
- Any `IShape` instance can substitute for another without hidden side effects, broken invariants, or `UnsupportedOperationException`!
- **Design by Contract Rule**: Subtypes never weaken preconditions or violate postconditions & invariants of the base contract.

L — Liskov Substitution Principle (LSP): Design Analysis

> ***Definition (Barbara Liskov):*** *"Subtypes must be behaviorally substitutable for their base types without altering any desirable correctness properties of the program."*

❌ UML Anti-Pattern: The "IS-A" Inheritance Trap


- **Broken Postcondition in `Square ——|> Rectangle`**:
  - Base `Rectangle` promises that `setHeight(10)` mutates `height` while keeping `width` invariant.
  - Subclass `Square` breaks this contract by silently mutating **both** `width` and `height` (`getArea()` yields `100 != 50`).
- **Other Common LSP Violations in Food Delivery**:
  - `CashOnDeliveryPayment ——|> OnlinePayment` throwing `UnsupportedOperationException` inside `autoRefundCard()`!

✅ UML Refactoring: Behavioral Subtyping

- **Sibling Realization (`- - -|> IShape`)**:
  - Eliminate invalid inheritance between `Square` and `Rectangle`.
  - Both classes independently realize the pure contract `«interface» IShape` (`+ getArea(): int`) with immutable dimensions.
- **Design by Contract (DbC) Rules for LSP**:
  - A subtype must **never strengthen preconditions**, **never weaken postconditions**, and **never throw unexpected exceptions**.

I — Interface Segregation Principle (ISP): UML Comparison


✘ Violating ISP: Bloated "Fat" Interface Pollutes Clients



Why This Violates Interface Segregation Principle (ISP):

- `KitchenThermalPrinter` only prints restaurant receipts, yet is forced to implement dummy `scan` and `fax` methods that throw runtime exceptions!
- **Phantom Coupling**: If the `Tel` parameter in `sendVendorFax()` changes, `KitchenThermalPrinter` is forced to recompile & redeploy for no reason!

✓ Following ISP: Lean, Role-Specific Interfaces



Why This UML Design Excels (Cohesive Role Contracts):

- Each interface represents a single capability (`IPrintable`, `IScannable`).
- `KitchenThermalPrinter` implements only `IPrintable`—no dummy stubs!
- Multi-function devices compose multiple interfaces via multiple realization (`implements IPrintable, IScannable, IFaxable`).

I — Interface Segregation Principle (ISP): Design Analysis

> ***Definition (Robert C. Martin):*** *"Clients should not be forced to depend on interfaces or methods that they do not use."*

❌ UML Anti-Pattern: The "Fat Interface"


- **Polluted Contract (`IMultiFunctionDevice`)**: Bundles unrelated capabilities (`printOrderTicket`, `scanInvoicePdf`, `sendVendorFax`) into one monolithic `«interface»`.
- **Two Severe Consequences**:
  - **1. Dummy Stubs & Liskov Violations**: `KitchenThermalPrinter` must implement `scan()` and `fax()` by throwing runtime exceptions.
  - **2. Phantom Recompilation Coupling**: Changing a parameter in `sendVendorFax()` forces `KitchenThermalPrinter` to recompile!

✅ UML Refactoring: Role-Specific Interfaces

- **Granular Role Contracts**:
  - Decompose into `«interface» IPrintable`, `«interface» IScannable`, and `«interface» IFaxable`.
- **Selective Realization (`- - -|>`)**:
  - `KitchenThermalPrinter` realizes **only** `IPrintable`.
  - `CorporateOfficeMFP` composes capabilities by realizing all three (`IPrintable`, `IScannable`, `IFaxable`).
- **Result**: Zero unused methods and zero phantom coupling across unrelated clients.

D — Dependency Inversion Principle (DIP): UML Comparison


✘ Violating DIP: High-Level Policy Coupled to Low-Level Detail



Why This Violates Dependency Inversion Principle (DIP):

- **High-level business policy** directly imports low-level MySQL JDBC details.
- **Immobility**: Cannot reuse `OrderCheckoutService` with PostgreSQL or DynamoDB without rewriting core business classes.
- **Untestable**: Cannot run fast unit tests without booting a real MySQL DB!

✓ Following DIP: Both Layers Depend on Domain Abstraction



Why This UML Design Excels (Inversion of Control & Clean Architecture):

- **Rule 1**: High-level `OrderCheckoutService` and low-level `PostgresOrderRepo` both depend on the `IOrderRepository` abstraction.
- **Rule 2**: Low-level DB adapters point **UPWARD** into the Domain package; injected via Constructor Dependency Injection (DI) for 1ms unit testing!

D — Dependency Inversion Principle (DIP): Design Analysis

> ***Definition (Robert C. Martin):*** *"1. High-level modules should not depend on low-level modules; both should depend on abstractions. 2. Abstractions should not depend on details; details must depend on abstractions."*

❌ UML Anti-Pattern: Downward Source Dependency

- **High-Level Bound to Low-Level (`domain ——> infra`)**:
  - `OrderCheckoutService` directly references concrete `MySqlOrderDatabase`.
- **Why This Cripples Architecture**:
  - **Immobility**: Core business policy cannot be reused with PostgreSQL without editing domain classes.
  - **Untestability**: Running unit tests on `OrderCheckoutService` requires booting a physical MySQL database server.

✅ UML Refactoring: Upward Arrow Inversion

- **Domain Owns the Interface (`IOrderRepository`)**:
  - `OrderCheckoutService` depends only on `«interface» IOrderRepository` inside `domain.order`.
- **Infrastructure Realizes Upward (`infra - - -|> domain`)**:
  - `PostgresOrderRepo` and `InMemoryMockRepo` point **upward** across the layer boundary to realize `IOrderRepository`.
- **Constructor Dependency Injection (DI)**: Inject `PostgresOrderRepo` in production and `InMemoryMockRepo` for **1ms isolated unit tests**!

Peer Discussion: Exploring the GoF Observer Pattern (Motivation & Structure)

Web Search & Pair Analysis: The GoF Observer Design Pattern (4 Mins)

- **1. Search Online:** Look up the **Observer Design Pattern** (e.g., on *Refactoring.Guru* or *GoF Catalog*).
- **2. Design Motivation (What problem does it solve?):**
  - When one **Subject** changes state (e.g., a Food Delivery `Order` transitions to `READY_FOR_PICKUP`), multiple **Dependents** (`CustomerApp`, `RiderApp`, `MerchantDisplay`) must update automatically—**without hardcoding concrete class calls inside `Order`**!
- **3. UML Structure & SOLID Mapping (Discuss with Your Partner):**
  - Sketch the 4 UML roles: `Subject (Publisher)`, `«interface» IObserver (Subscriber)`, and `ConcreteObserverA / B`.
  - How does the Observer Pattern embody **OCP** (adding new subscribers without editing `Subject`) and **DIP** (`Subject` depends only on `«interface» IObserver`)?



Concept Check Question 4 (CCQ 4)

Which SOLID object-oriented design principle explicitly advocates that when introducing new system capabilities, developers should extend functionality by adding new classes rather than modifying existing, battle-tested code?

- **A.** Single Responsibility Principle (SRP)
- **B.** Open / Closed Principle (OCP)
- **C.** Interface Segregation Principle (ISP)
- **D.** Liskov Substitution Principle (LSP)



5.6 Stage 4 — Data & Persistence Design: ERD, Caching & Polyglot Storage

> *"Bad programmers worry about the code. Good programmers worry about data structures and their relationships."*
> *— Linus Torvalds (Creator of Linux & Git)*

3-Level Data Modeling, ERD & Polyglot Storage in Food Delivery



1. Three-Level Data Modeling, ERD Notation & Normalization

> ***Stage 4 Modeling Purpose:*** *Translates domain objects into* ***integrity-enforced relational schemas*** *and* ***high-speed physical indexes***.

3-Level Data Modeling & UML ERD Notation

- **1. Conceptual → 2. Logical ERD → 3. Physical Schema**:
  - Progresses from business concepts to normalized table columns, and finally to DBMS-specific indexes and partitions.
- **Core UML Data / ERD Notations**:
  - `«PK»` **(Primary Key)**: Unique immutable identifier (`order_id: UUID`).
  - `«FK»` **(Foreign Key)**: Referential integrity link (`customer_id` referencing `customers.customer_id`).
  - **Multiplicity (`1 ── 0..*`, `1 ◆── 1..*`)**: Distinguishes optional associations from lifecycle-bound composition (`Order` ◆—— `OrderItem`).

3NF Normalization vs. Physical Optimization

- **Third Normal Form (3NF — Write Integrity)**:
  - Every non-key column depends *only* on the Primary Key (e.g., store `restaurant_id` on `orders`, never duplicate restaurant address strings across millions of orders).
  - **Benefit**: Eliminates update anomalies and guarantees single source of truth.
- **Physical Indexing & Partitioning (Read Speed)**:
  - **Composite Index (`«idx»`)**: `(customer_id, created_at DESC)` accelerates "*My Order History*" from `800ms` full-table scan to `< 2ms` B-Tree lookup.
  - **Table Partitioning**: Partitioning `orders` monthly by `created_at` keeps active working sets small in RAM.

2. Polyglot Persistence, Caching & Distributed Consistency

> ***Architectural Reality:*** *Modern cloud systems pair* ***ACID Relational Databases*** *with* ***In-Memory Caches*** *and* ***Event Logs*** *(Polyglot Persistence).*

Matching Storage Engines to Workloads

- **1. Relational OLTP (`PostgreSQL` — ACID)**:
  - *Food Delivery Use*: `orders`, `order_items`, `payments`.
  - *Design Rule*: Use `«UQ» idempotency_key` and row-level locking to guarantee zero double-charging.
- **2. In-Memory Key-Value / Spatial (`Redis` — Ephemeral)**:
  - *Food Delivery Use*: Live rider GPS (`rider:geo:{city}`) & restaurant menu **Cache-Aside** (`TTL = 5 min`).
  - *Design Rule*: High write/read velocity (`< 5ms`), auto-evicted via `TTL = 30s` if a rider goes offline.
- **3. Append-Only Event Log (`Kafka` — Stream)**:
  - *Food Delivery Use*: High-throughput immutable audit log of domain events partitioned by `order_id`.

Managing Consistency: ACID vs. BASE & Outbox

- **Inside a Single Service (`ACID`)**:
  - Atomicity, Consistency, Isolation, Durability via local SQL transactions.
- **Across Distributed Services (`BASE` & Saga)**:
  - *Problem*: How to commit an `Order` in PostgreSQL and publish `OrderPlacedEvent` to Kafka without dual-write data loss?
  - *Solution — **Transactional Outbox Pattern***:
    1. Insert `orders` row AND `outbox_events` row in the **same local ACID transaction**.
    2. A background relay publishes `outbox_events` to Kafka (`At-Least-Once`), while downstream consumers enforce idempotency!

Concept Check Question 5 (CCQ 5)

In Stage 4 (**Data & Persistence Design**), why does a Food Delivery Platform store `orders` and `payments` in **PostgreSQL (Relational OLTP)** while storing 50,000 real-time courier GPS coordinates in **Redis (** `GeoHash` **+** `TTL = 30s` **)**?

- **A.** PostgreSQL lacks primary key support for tables, whereas Redis enforces Third Normal Form (3NF) foreign keys.
- **B.** Redis archives historical financial ledgers on disk, whereas PostgreSQL evicts all unpaid orders after 30 seconds.
- **C.** PostgreSQL ensures ACID financial integrity, while in-memory Redis serves high-frequency GPS queries in `< 5ms`.
- **D.** Writing live courier GPS streams into PostgreSQL eliminates all wireless network latency on mobile client devices.

5.7 AI-Augmented Software Design

> *"AI will not replace software architects, but architects who use AI—while grounded in solid engineering principles—will replace those who do not."*

AI as a Copilot Across the 4 Stages of Software Design

- **The "Copilot, Not Autopilot" Paradigm:**
  - AI excels at **generating candidate models, drafting contracts, detecting smells, and writing schemas**; human architects own **context, budget, security, and accountability**.
- **4 High-Impact Applications Mapped to Our 4 Design Stages:**
  - **Stage 1 (Arch Design — 5.3)**: Simulating **ATAM failure scenarios** ("*What happens if Redis crashes during dinner surge?*"), drafting **ADRs**, and generating **UML Package/Deployment** PlantUML code.
  - **Stage 2 (Interface Spec — 5.4)**: Generating **OpenAPI 3.1 / Protobuf** contracts and deriving **DbC Preconditions, Postconditions, and boundary test cases**.
  - **Stage 3 (OO Design — 5.5)**: Scanning for God Classes / cyclic dependencies and refactoring `switch/case` blocks into **SOLID / GoF Strategy** patterns.
  - **Stage 4 (Data Design — 5.6)**: Translating domain models into **3NF SQL DDL**, recommending composite **B-Tree indexes**, and spotting `N+1` query bottlenecks.

Human-in-the-Loop: Mitigating AI Blind Spots

- **Risks of Unchecked AI Adoption:**
  - **Premature Distributed Complexity:** AI frequently over-engineers, recommending microservices, Kubernetes, and Kafka for simple internal tools that 3 engineers could finish in a fortnight with a monolith.
  - **Context Blindness:** AI is blind to your team's tech-stack familiarity, cloud hosting budgets, and internal security compliance constraints.
  - **Superficial Refactoring:** Renaming variables without resolving fundamental architectural bottlenecks or data coupling.
- **The Golden Rule of System Architecture:**

> ***"AI Proposes Trade-offs; Lead Architects Make Decisions!"***
> *Human engineers must evaluate organizational context and bear ultimate responsibility for system viability.*

5.8 Conceptual Synthesis & References

> *"Simplicity is prerequisite for reliability."*
> *— Edsger W. Dijkstra*

Core Curriculum Self-Assessment & Key Takeaways

Chapter Section	Design Stage & UML / Model	Golden Engineering Heuristic
5.1 Design Process & Specs	4-Stage Workflow, **SDS & ADRs**	Catch flaws early ($1 vs. $100); document the *How* (SDS) and *Why* (ADR).
5.2 Universal Principles	**Cohesion & Coupling** (UML Compare)	**Maximize Cohesion, Minimize Coupling!** Hide internal secrets.
5.3 Stage 1: Arch Design	6 Patterns, ATAM, **Package & Deploy UML**	Synthesize patterns; enforce acyclic imports & cloud fault isolation.
5.4 Stage 2: Interface Spec	**Design by Contract (DbC) & Component UML**	Specify `Pre`, `Post` & `Invariant`; wire via Lollipop (`—o`) & Socket (`—(`).
5.5 Stage 3: OO Design	GoF 23, **5 SOLID & Class UML**	Depend on abstractions (DIP); subclasses must honor DbC contracts (LSP).
5.6 Stage 4: Data Design	**3-Level ERD**, 3NF & Polyglot Storage	Use ACID SQL for money, Redis TTL for live Geo-cache, Outbox for Kafka.
5.7 AI in Design	Copilot Across Stages 1–4	AI proposes options; human architects own trade-offs & context!

Classic Literature & Essential References

- **Foundational Software Architecture & Design Specifications:**
  - Len Bass, Paul Clements, Rick Kazman (SEI): *Software Architecture in Practice*, 4th Edition, Addison-Wesley.
  - Bertrand Meyer: *Object-Oriented Software Construction* (Origin of Design by Contract — DbC), Prentice Hall.
  - IEEE Std 1016: *IEEE Standard for Information Technology—Systems Design—Software Design Descriptions (SDD / SDS)*.
  - Michael Nygard: *Documenting Architecture Decisions (ADR)*, 2011.
- **Classic Design Principles, UML, Data & Patterns Literature:**
  - Robert C. Martin (Uncle Bob): *Clean Architecture: A Craftsman's Guide to Software Structure and Design*, Prentice Hall.
  - Erich Gamma, Richard Helm, Ralph Johnson, John Vlissides: *Design Patterns: Elements of Reusable Object-Oriented Software (GoF)*, Addison-Wesley.
  - Martin Fowler: *UML Distilled* & *Patterns of Enterprise Application Architecture*, Addison-Wesley.
  - Martin Kleppmann: *Designing Data-Intensive Applications (DDIA)*, O'Reilly Media.

Thank You for Listening!

Questions & Discussion

Prof. Nien-Lin Hsueh
Department of Information Engineering and Computer Science
Feng Chia University