Software Engineering

Chapter 4: System Modeling & Unified Architecture

Prof. Nien-Lin Hsueh
Department of Information Engineering and Computer Science
Feng Chia University

Chapter 4: Roadmap & Core Curriculum

Part 1: Foundations & Core Models

- **4.1 Foundations of Modeling:** Abstraction, 4 perspectives, 5 essential diagrams, and the elephant parable.
- **4.2 The UML:** The Method Wars, Three Amigos trinity (Jacobson, Rumbaugh, Booch), and OMG standardization.
- **4.3 Functional & Use Case Models:** Actor goals, system boundaries, include vs. extend, and AI prompt guidelines.
- **4.4 Structural & Class Models:** Domain classes, visibility, multiplicity, whole-part coupling, and AI prompt guidelines.
- **4.5 Interaction & Sequence Diagrams:** Chronological messages, lifelines, activations, and AI prompt guidelines.

Part 2: Workflows, Architecture & Synthesis

- **4.6 Process & Activity Diagrams:** Concurrent workflows, decisions, forks/joins, swimlanes, and AI prompt guidelines.
- **4.7 Behavioral & State Machines:** Reactive systems, event triggers, actions vs. activities, and AI prompt guidelines.
- **4.8 Text-Based Modeling with PlantUML:** Code-as-architecture, syntax quick reference, and multi-diagram pipelines.
- **4.9 Conceptual Recap & Synthesis:** Core principles review, fill-in-the-blank quiz, and references.

4.1 Foundations of System Modeling

> *"A language that doesn't affect the way you think about programming is not worth knowing."*
> *— Alan Perlis*

What is System Modeling?

> *"System modeling is the process of developing abstract models of a system, with each model presenting a different view or perspective of that system."*
> *— Ian Sommerville, Software Engineering (10th ed.)*

- **Essential Principles of Modeling:**
  - **Abstraction: Hides** non-essential implementation details to highlight critical architectural structures, data flows, and dependencies.
  - **Multiple Perspectives:** No single diagram can explain a complex software system. Different stakeholders require different views.
  - **Communication & Verification:** Serves as a universal **visual** grammar between product managers, system architects, software developers, and QA engineers.
  - **Blueprint for Implementation:** Provides the formal structural and behavioral specification from which executable code and database schemas are developed.

The Parable of the Elephant & Multiple Perspectives

The Blind Men and the Elephant: Why Multi-Perspective Modeling is Essential



① Feeling Trunk: "It's like a water pipe!"

Interaction Perspective

- Focus: Message timing & invocation flows
- Blind Spot: Misses static data schemas

UML Model: Sequence Diagram

② Feeling Leg: "It's like a solid pillar!"

Structural Perspective

- Focus: Class attributes, methods & relations
- Blind Spot: Misses dynamic runtime behavior

UML Model: Class Diagram

③ Feeling Body: "It's like a high wall!"

External / Context Perspective

- Focus: System boundary, actors & external APIs
- Blind Spot: Cannot see internal decomposition

UML Model: Context Diagram

④ Feeling Tail: "It's like a swinging rope!"

Behavioral Perspective

- Focus: Business workflows & state transitions
- Blind Spot: Cannot capture static entity models

UML Model: Activity / State Diagram

Takeaway: Every model is a partial projection; only multi-perspective modeling reveals the full architecture!

4 Core System Modeling Perspectives

- **1. External Perspective:**
  - Models the environment, external partners, and operational context of the system.
  - Defines the strict system perimeter: what is built internally vs. what is delegated to third parties.
- **2. Interaction Perspective:**
  - Models dynamic communications between external actors and the system, or message exchanges between internal collaborating objects.
- **3. Structural Perspective:**
  - Models the static architecture of system data, object classes, attributes, methods, and relationships independent of runtime execution order.
- **4. Behavioral Perspective:**
  - Models the dynamic execution behavior, sequential business workflows, and reactive discrete state transitions in response to external events.

5 Essential UML Models in Modern Practice

Model / Diagram	Section	Perspective	Nature	Primary Engineering Role
1. Use Case Model	4.3	External	Functional Contract	Defines system boundary, actor goals, and scope
2. Class Model	4.4	Structural	Static Backbone	Specifies domain entities, attributes, and relationships
3. Sequence Diagram	4.5	Interaction	Dynamic Chronology	Traces runtime message passing and BCE responsibilities
4. Activity Diagram	4.6	Behavioral	Dynamic Workflow	Models business processes, fork/join concurrency & swimlanes
5. State Machine Diagram	4.7	Behavioral	Reactive Lifecycle	Captures event-driven states, transitions & invariants

> ***Implementation & Acceleration:*** *Unified via* ***4.8 PlantUML*** *(Code-as-Architecture) with* ***AI Prompt Guidelines*** *integrated in each model.*

Concept Check Question 1

A software architect wants to define **how domain entity data is structured and how classes inherit and associate with each other**, completely independent of runtime execution order. Which modeling perspective should the architect adopt?

- **A.** External Perspective
- **B.** Interaction Perspective
- **C.** Structural Perspective
- **D.** Behavioral Perspective

4.2 The Unified Modeling Language (UML)

> *"A standardized visual grammar transformed software engineering from proprietary silos into a global discipline."*

The Need for Standardization: The 1990s "Method Wars"

- **The Rise of Object-Oriented Programming (Late 1980s – Early 1990s):**
  - The software industry transitioned from procedural code (C, Pascal) to object-oriented paradigms (C++, Smalltalk).
  - Software engineers urgently needed visual notations to represent classes, objects, and relationships.
- **The "Method Wars" Era:**
  - Over **50 competing OO modeling notations** flooded the commercial market.
  - Engineers argued fiercely over whether classes should be clouds, rectangles, or ovals; whether inheritance should be an open triangle, filled arrow, or dashed line.
  - **Severe Industry Fragmentation:** Companies could not exchange models, CASE tools were incompatible, and developers had to relearn notation whenever they switched jobs.

Unification & Standardization: From Rational to OMG

- **1994 – Unification Begins at Rational Software:**
  - Jim Rumbaugh joined Grady Booch at Rational to merge the Booch Method and OMT into the "Unified Method" (v0.8).
- **1995 – The Three Amigos Assemble:**
  - Ivar Jacobson joined Rational, bringing his revolutionary **Use Case** methodology (OOSE).
- **1997 – OMG International Standardization:**
  - Submitted to the **Object Management Group (OMG)**; unanimously adopted as **UML 1.1** in November 1997.
- **2005 – UML 2.0 Major Architecture Overhaul:**
  - Expanded from 9 to 13 (and later 14) diagram types with formal execution metamodels.

Pioneers of UML: Grady Booch

- **Role & Distinctions:**
  - Chief Scientist, Rational Software; IBM Fellow; ACM Fellow.
- **Pioneered Methodology:**
  - **The Booch Method** and seminal text: *Object-Oriented Analysis and Design with Applications*.
- **Core Contribution to UML:**
  - Focused heavily on **concrete software design**, module decomposition, class abstractions, and architectural patterns.
  - Championed visual expressiveness for implementation-level object structures and code mapping.
- **Famous Architectural Maxim:**

> *"Clean code always looks like it was written by someone who cares."*
>
> ”



Grady Booch
Rational Software / IBM Fellow

Pioneers of UML: James Rumbaugh

- **Role & Distinctions:**
  - Lead Researcher, General Electric (GE) Global R&D; Rational Software; IBM.
- **Pioneered Methodology:**
  - **Object Modeling Technique (OMT)** and book: *Object-Oriented Modeling and Design*.
- **Core Contribution to UML:**
  - Emphasized rigorous **domain analysis**, semantic data modeling, and entity-relationship mapping.
  - Pioneered the synthesis of object structure with David Harel's **Statecharts** to model dynamic reactive systems.
- **Famous Architectural Maxim:**

> *"You cannot build great software without understanding domain truth."*



James Rumbaugh
GE Research / Rational Software

Pioneers of UML: Ivar Jacobson

- **Role & Distinctions:**
  - Lead Architect, Ericsson; Founder, Objectory AB; Rational Software; SEMAT Pioneer.
- **Pioneered Methodology:**
  - **Object-Oriented Software Engineering (OOSE)**.
- **Core Contribution to UML:**
  - **Inventor of Use Cases (1986):** Revolutionized requirements by anchoring system architecture to measurable user goals.
  - Introduced the **Boundary–Control–Entity (BCE)** robustness analysis pattern and component-based architecture.
- **Famous Architectural Maxim:**

> *"A system that has no users has no reason to exist. Model user goals first."*

Ivar Jacobson
Ericsson / Objectory / Rational

The Three Amigos: The Trinity of Software Modeling

Ivar Jacobson

The "Why" (Goal / User)

- **Use Case Driven:** What goals do external actors achieve?
- **BCE Robustness:** Separating UI boundaries from data entities.
- **Component Contracts:** Reusable subsystem architectures.

James Rumbaugh

The "What" (Domain Data)

- **Domain Analysis:** What real-world concepts exist?
- **Class & Data Schemas:** Structural entity relationships.
- **State Machines:** Reactive event-driven lifecycles.

Grady Booch

The "How" (Design & Code)

- **Object-Oriented Design:** How do classes collaborate?
- **Macro Architecture:** Layered module decomposition.
- **Implementation Map:** Direct code translation into OOP.

> 📌 ***Architectural Synthesis:*** *Jacobson captures* ***Why*** *the system exists; Rumbaugh models* ***What*** *domain concepts exist; Booch designs* ***How*** *components execute in code.*

Concept Check Question 2

Which of the "Three Amigos" was specifically renowned for inventing **Use Cases (1986)** to anchor software architecture to tangible user goals?

- **A.** Grady Booch
- **B.** James Rumbaugh
- **C.** Ivar Jacobson
- **D.** Martin Fowler

4.3 Functional & Use Case Models

> *"A use case is a contract for behavior between the system and its actors to achieve a measurable business goal."*
> *— Alistair Cockburn*

Focus: Business Value & User Goals



Actor Taxonomy & System Boundaries



Use Case Relationship Matrix

Relationship	UML Notation	Behavior	Real-World Analogy
Association		Actor participates in a use case.	A customer walks into a store.
<<include>>		Mandatory, reusable logic. Runs at a specific point.	Calling a function: `checkout()` → `calculateTax()`
<<extend>>		Optional/conditional logic. Might run during certain steps.	A pop-up coupon or conditional error check.
Generalization		Is a relationship. Child inherits logic from parent.	International Student is like a Student, but with extra steps.

Clear Use Case Naming



Rules of Building Use Case Models

NESTING LIMIT

Max 2 Levels of Nesting

Avoid functional decomposition (e.g., A includes B includes C).
Keep it requirements-focused, not design-focused.

ACTOR INTERACTIONS

No Actor-to-Actor Lines

Actors do not interact directly on the diagram.
Detail these interactions in your text specifications.

SYSTEM BOUNDARIES

Use Boundaries with Purpose

Only use the boundary box to define system scope or distinct release phases (Phase 1, Phase 2). Omit if redundant.

Note: Call out external systems with <<system>> and use a Time actor (clock icon) for scheduled triggers.

Case Study: University Enrollment System



Case Study: Actor Generalization & Relationship Synthesis



Blueprint Legend

[1] Generalization: Int'l Student inherits base student logic.

[2] <<include>>: Enrolling always requires a seminar (Mandatory).

[3] <<extend>>: Security check only runs for certain students (Conditional).

[4] Time Actor: Triggers the monthly tuition report.

Common Anti-Patterns of Use Case Models

The Mistake (Symptom)	Why It Fails (Diagnosis)	The Fix (Cure)
✗ Technical names (`Process_DB_Transaction`)	Stakeholders don't understand implementation details.	✓ Use domain-friendly names (`Withdraw Funds`, `Generate Report`).
✗ Drawing arrows showing data flow	Associations show initiation, not data movement.	✓ Remove arrowheads unless showing passive actors.
✗ Overusing `<<extend>>` lines	Creates messy, unreadable diagrams.	✓ Move optional/conditional logic into textual use-case specs.
✗ Connecting Customer to Admin directly	Actors don't interact on use-case diagrams.	✓ Describe human interaction in the text scenario.

Best Practices Checklists



Use Case Specification: UC-01 Enroll Student

Field	Specification Details
Use Case ID / Name	**UC-01: Enroll Student in Course**
Primary Actor	Student (authenticated via campus Single Sign-On)
Preconditions	Student is matriculated with active status; enrollment registration window is open
Postconditions	Student is officially enrolled in course section; seat quota decremented by 1
Main Success Scenario	**1.** Student searches for open course sections by department or course code. **2.** System displays matching course sections, schedules, and remaining seat quotas. **3.** Student selects target section and submits an enrollment request. **4.** System executes `<<include>> Verify Prerequisites` against academic transcript. **5.** System reserves seat, updates enrollment ledger, and generates confirmation notice. **6.** Student views updated schedule and receives confirmation notification.
Extensions (Alternate)	**4a. Prerequisite Deficiency:** System displays missing prerequisite courses and halts. **4b. Schedule Conflict:** System alerts student of timeslot overlap with existing class. **5a. Section at Capacity:** System offers `<<extend>> Add to Waitlist` queue.

Concept Check Question 3

In our Food Delivery Use Case Model, why does `Apply Promo Voucher` point to `Place Food Order` with `<<extend>>`, while `Place Food Order` points to `Process Payment` with `<<include>>`?

- **A.** Voucher application is mandatory for all orders; payment is optional.
- **B.** Vouchers are conditional optional behavior; payment is mandatory shared execution.
- **C.** Vouchers are executed by supporting actors; payment is executed by primary actors.
- **D.** Vouchers represent class inheritance; payment represents object composition.

Diagnostic Exercise: Spot the 3 Flaws in this Use Case Model



Audit this student's draft diagram:
Can you spot the **3 critical modeling mistakes (anti-patterns)**?

- **1. Granularity & Workflow:**
  - What is wrong with connecting `Enter Delivery Address` → `Click Submit Button` → `Place Food Order`?
- **2. Relationship Direction:**
  - Look closely at `Process Payment` and `Place Food Order`. What is wrong with the `<<include>>` arrow?
- **3. Boundary & Actor Placement:**
  - Examine `Chef` and `MySQL Database`. What violates UML system boundary principles?

Diagnostic Solution: 3 Flaws in Use Case Model Explained



Audit Findings & Architectural Corrections:

- **1. Granularity & Workflow (Anti-pattern: Flowcharting):**
  - `Enter Address` & `Click Submit` are UI steps inside `Place Order`, not standalone value-yielding use cases.
- **2. Inverted Include Relationship:**
  - Base use cases include child subroutines. The `<<include>>` arrow must point: `Place Food Order` ➔ `Process Payment`.
- **3. Boundary & Actor Violations:**
  - `Chef` is an actor and must remain outside the boundary box; `MySQL Database` is internal storage, not an external actor.

AI Assistance: Guidelines for Use Case Modeling

- **1. Define Clear System Boundaries:**
  - Clearly separate what is inside the system from external users and third-party services (e.g., payment gateways).
- **2. Identify Real User Goals (Actors & Use Cases):**
  - Focus on complete, meaningful user goals (e.g., `Place Order`, `Track Delivery`).
  - Avoid breaking steps down into trivial UI interactions (no "Click Button" or "Enter Password").
- **3. Clarify Relationship Semantics:**
  - **Mandatory Sub-flows:** Identify common steps that occur every single time (shared building blocks).
  - **Optional or Conditional Steps:** Explicitly distinguish optional extensions (e.g., applying vouchers) from normal flows.
- **4. Human Review & Reality Check:**
  - Are use cases named with clear active verbs?
  - Are external partner systems kept outside the core system boundary?

AI Prompt Example: Food Delivery Use Case Model

1. Role & Task Instruction:

```
Act as a Lead Systems Analyst.
Generate a clean PlantUML Use Case
diagram for a Food Delivery System.
```

2. Modeling Guidance:

- Clearly define system boundary vs. external services.
- Focus on meaningful user goals (avoid trivial UI button clicks).
- Separate mandatory sub-flows from optional extensions.
- Identify primary human actors and external partner systems.

3. Input Requirements Statement:

> *"Our platform allows **Customers** to browse restaurants, add food items to cart, and place orders.*
> *When placing an order, the system must always authorize payment through an external **Payment Gateway** and validate delivery address.*
> *A customer may optionally enter a discount coupon code (`Apply Promo Voucher`) or select contactless doorstep delivery.*
> ***Restaurant Staff** review incoming orders, accept or reject them, and update kitchen prep status.*
> ***Delivery Couriers** accept available delivery tasks, pick up orders, and complete deliveries."*
>
> ”

Generated PlantUML & Diagram: Food Delivery Use Case Model

Generated PlantUML Specification:

```
@startuml
left to right direction
actor Customer
actor "Restaurant Partner" as Restaurant
actor "Payment Gateway\n«Supporting»" as Payment
actor "Delivery Courier" as Courier

rectangle "Food Delivery System" {
  usecase "Browse Menus" as UC_Browse
  usecase "Place Food Order" as UC_PlaceOrder
  usecase "Apply Promo Voucher" as UC_Voucher
  usecase "Track Delivery Live" as UC_Track
  usecase "Manage Menu" as UC_Menu
  usecase "Accept / Reject Order" as UC_AcceptOrder
  usecase "Process Payment" as UC_Payment
  usecase "Accept Delivery Task" as UC_AcceptTask
}

Customer -- UC_Browse
Customer -- UC_PlaceOrder
Customer -- UC_Track
Restaurant -- UC_Menu
Restaurant -- UC_AcceptOrder

UC_PlaceOrder ..> UC_Payment : <<include>>
UC_Voucher .> UC_PlaceOrder : <<extend>>
UC_Payment -- Payment
```

Rendered Diagram Output:



Interactive Activity: Evolving Use Cases with AI (Pair Hands-On)

Hands-on Experiment: Mutate Requirements & Audit AI Output (4 Mins)

- **1. Add ONE New Feature to the Use Case Prompt:**
  - *Scheduled Ordering:* Allow `Customer` to pre-order food for future delivery.
  - *Live Chat Support:* Connect `Customer` with `Support Agent` or `Courier`.
  - *Group Ordering:* Multiple users add items into a single pooled order.
- **2. Ask AI to Generate:** Prompt an LLM to update the PlantUML use case diagram.
- **3. Render & Critique:** Paste into PlantText and audit:
  - Did AI keep external actors/gateways **outside** the system boundary?
  - Did AI correctly distinguish **mandatory steps** from **optional extensions**?
  - Did AI avoid trivial button clicks (e.g., no "Click Confirm")?

4.4 Structural & Class Models

> *"Classes are the static building blocks; objects are the living runtime instances."*

The Anatomy of UML Class Diagrams

A visual reference guide to mapping object-oriented systems, syntax, and relationships.





UML SYNTAX & RELATIONSHIPS

- Generalization (Inheritance)
- Realization (Interface)
- Aggregation (Shared) — Shared Ownership
- Composition (Composite) — Strong Ownership
- Association

ARCHITECTURAL MAPPING

CLASS → COMPONENT/ROOM
ATTRIBUTE → SPECIFICATION/DIMENSION
OPERATSON → FUNCTION/ACTIVITY
RELATIONSHIP → STRUCTURAL CONNECTION/PATH

Blueprint vs. Instance: The Foundation of OOD



A **Class** is a blueprint. It describes the type of objects and encapsulates state (**attributes**) and behavior (**operations**). It is not the object itself.



Objects are usable instances of classes. Built from the same blueprint, they contain the same components but hold distinct, real-world states.

The Three Perspectives of Class Modeling



Anatomy of the UML Class Box



The Member Visibility Matrix (+, -, #, ~)

Symbol	Label	Meaning	Code Snippet
+	Public	Accessible from anywhere.	`public String name;`
-	Private	Accessible only within the class itself.	`private int id;`
#	Protected	Accessible within the class and its subclasses.	`protected double balance;`

Taxonomy of Class Relationships



Class A uses Class B temporarily (e.g., as a parameter). No structural ownership.

Classes know about each other. Can be unidirectional or bidirectional. Loose coupling.

A whole-part relationship, but parts can exist independently. E.g., a library has books.

Composition: Strict whole-part; parts die with the whole.
Inheritance: Structural `is-a` hierarchy.

UML precisely conveys how code should be implemented. Connections range from temporary usage to strict structural life-and-death bindings.

UML Connector & Arrowhead Cheat Sheet

Inheritance (Generalization)



Represents an “is-a” relationship. Subclass inherits features.

Realization



Relationship between interface and implementation.

Dependency

A “uses” relationship. Object used in a method, not stored in a field.

Simple Association

A structural link between two peer classes.

Lifecycle Diagnostic: Aggregation vs. Composition

Aggregation	Composition
• **Concept:** A ‘part of’ relationship. • **Lifespan:** Separate lifetimes. • **Analogy:** Team ◇— Player (If the team disbands, players still exist)	• **Concept:** Strict containment. • **Lifespan:** Live and die together. Part cannot stand alone. • **Analogy:** House ◆— Room (If the house is demolished, rooms cease to exist)

Cardinality, Multiplicity & Business Constraints



Syntax to System: The E-Commerce Order Model



Comprehension Check: Reading the Order Model



Evaluate whether each statement about the diagram is Correct or Incorrect:

- **1.** A customer "Nick" can have 3 orders in the system.
- **2.** If an `Order` is deleted, all its associated `LineItem`s are still kept.
- **3.** An `Order` can exist in the system without being associated with any `Customer`.
- **4.** External classes can directly modify `customer.customerID` via dot notation.
- **5.** `LineItem` realizes the contract and operations defined by `PaymentInterface`.
- **6.** A newly registered `Customer` can exist in the system with zero orders.
- **7.** A single `Order` can be jointly owned and shared by two different `Customer`s.

Concept Check Question 4

In our Food Delivery Class Diagram, why is the relationship between `Order` and `OrderItem` modeled as **Composition (◆)**, whereas `Order` and `Courier` is modeled as **Aggregation (◇)**?

- **A.** An `OrderItem` can exist independently, but a `Courier` cannot exist without an `Order`.
- **B.** An `OrderItem` is destroyed with its parent `Order`, whereas a `Courier` maintains an independent lifecycle.
- **C.** Composition represents inheritance between classes, while aggregation represents method invocation.
- **D.** Composition requires zero-to-one multiplicity, while aggregation requires one-to-many multiplicity.

Diagnostic Exercise: Spot the Flaws in this Baseball Class Model



Audit this student's draft model of a Baseball Game:
Can you spot the critical modeling flaws across **encapsulation, inheritance, and relationships**?

- **1. Whole-Part & Lifecycle (Aggregation vs. Composition):**
  - Why is `BaseballGame` linked to `Team` with a solid diamond (`◆`)? What happens when a game record is deleted?
- **2. Inheritance vs. Membership (is-a vs. has-a):**
  - Look closely at `Player` and `Team`. What is fundamentally wrong with `Team <|-- Player`?
- **3. Multiplicity & Cardinality:**
  - Can a game have only `1` team and `1` inning? How many teams and innings does a baseball game actually have?
- **4. Encapsulation & Responsibility Distribution:**
  - Why are all attributes `+` public? Does `pitchBall()` belong in `BaseballGame` or `Player`? Should a single `Team` declare who won?

Diagnostic Solution: Flaws in Baseball Class Model Explained



Audit Findings & Architectural Corrections:

- **1. Composition vs. Aggregation (`BaseballGame` & `Team`):**
  - Solid diamond (◆) destroys `Team` if a game is deleted! Teams outlive games; use aggregation (◇). A game has `2` teams and `9` innings.
- **2. Inheritance Abuse (is-a vs. has-a):**
  - `Team <|-- Player` is invalid. A Player is a member (has-a) of a Team, not a subtype of a Team.
- **3. Broken Encapsulation & Responsibility Misplacement:**
  - All attributes must be private (`-`). `pitchBall()` belongs in `Player`. A single Team cannot decide `calculateWinner()` unilaterally.

AI Assistance: Guidelines for Class Modeling

- **1. Define Core Domain Entities:**
  - Instruct AI to identify key business concepts (e.g., `Order`, `Customer`, `Item`) rather than raw database tables or UI widgets.
- **2. Clarify Object Relationships:**
  - **Whole vs. Part:** Guide AI to distinguish tight lifecycle ownership from loosely shared parts.
  - **Multiplicity:** Ensure AI specifies cardinality on both ends (e.g., 1 customer, many orders).
  - **Prefer Composition over Inheritance:** Prevent AI from creating deep "is-a" class hierarchies where simple composition fits better.
- **3. Encapsulation & Responsibilities:**
  - Keep internal state private; expose meaningful domain operations as methods.
- **4. Human Reality Check:**
  - Verify AI didn't hallucinate extra classes, invert arrows, or lazily draw plain associations.

AI Prompt Example: Food Delivery Class Model

1. Role & Task Instruction:

```
Act as a Principal Software Architect.
Generate a formal PlantUML Class Diagram
for a Food Delivery Domain Model.
```

2. Modeling Guidance:

- Identify core entities: `Customer`, `Restaurant`, `Order`, `OrderItem`, `Courier`.
- Distinguish whole-part relationships (an `Order` tightly owns its items).
- Clarify multiplicities on both ends of connections.
- Apply encapsulation (hide attributes, expose business operations).
- Keep external payment processing decoupled via an interface.

3. Input Requirements Statement:

> *"A **Customer** has customerId, name, email, phone, and deliveryAddress.*
> *A **Restaurant** has restaurantId, name, address, and owns a collection of **MenuItems** (itemId, name, price, isAvailable).*
> *A Customer can place multiple **Orders**. Each **Order** has orderId, orderStatus (OrderStatus enum: Placed, Preparing, Delivered), orderTime, and totalAmount.*
> *An Order consists of one or more **OrderItems** (quantity, itemPrice, subtotal). If an Order is deleted, its OrderItems must be cascade-deleted immediately.*
> *A **Courier** (courierId, name, phone, vehicleType) can be assigned to deliver an Order.*
> *An Order delegates credit card charging to a **PaymentProcessor** interface."*

Generated PlantUML & Diagram: Food Delivery Class Model

Generated PlantUML Specification:

```
@startuml
class Customer {
  - customerId: String
  - deliveryAddress: String
  + placeOrder(): Order
}
class Restaurant {
  - restaurantId: String
  - address: String
  + acceptOrder(): Boolean
}
class MenuItem {
  - itemId: String
  - price: Double
}
class Order {
  - orderId: String
  - totalAmount: Double
  + calculateTotal(): Double
  + assignCourier(c: Courier): void
}
class OrderItem {
  - quantity: Integer
  - subtotal: Double
}
class Courier {
  - courierId: String
  - vehicleType: String
}
interface PaymentProcessor {
  + chargeCreditCard(amount: Double): Boolean
}
```

Rendered Diagram Output:



Interactive Activity: Evolving Food Delivery with AI (Pair Hands-On)

Hands-on Experiment: Mutate Requirements & Audit AI Output

- **1. Add ONE New Rule to the Food Delivery Prompt:**
  - *Multi-Vendor:* Allow `Order` to bundle items from multiple `Restaurant`s.
  - *Tipping:* Allow `Customer` to tip and rate the assigned `Courier`.
  - *VIP Membership:* Add subscription tier (`Customer` gets free delivery).
- **2. Ask AI to Generate:** Prompt an LLM to update the PlantUML class diagram.
- **3. Render & Critique:** Paste into PlantText and audit:
  - Did AI preserve **Composition** (`*--`) vs. **Aggregation** (`o--`)?
  - Are **multiplicities** (`1..*`, `0..1`) logically sound for the new rule?
  - Did AI hallucinate redundant classes or violate `- private` fields?

4.5 Interaction & Sequence Diagrams

> *"Interaction modeling shows how objects collaborate chronologically over time to fulfill the promise of a use case."*

Sequence Diagrams: The Architectural Blueprint

A visual reference for modeling system interactions and logic.



Static Structure vs. Dynamic Collaboration

STATIC MODEL



DYNAMIC MODEL



UML Sequence Diagrams detail how operations are carried out over time. Unlike class or object diagrams that provide static views, sequence diagrams capture the dynamic flow of messages sent and received within a collaboration.

The Requirements-to-Code Pipeline: From Story to Code



Upstream Models: Use Case, Scenario & Class Architecture

1. Use Case Model



- **Primary Actor:** Customer
- **Secondary Actor:** Payment Gateway
- **System Boundary:** Order System
- **Business Goal:** Checkout and purchase items

2. Use Case Description

UC-01: Checkout Order

Precondition: Cart confirmed by customer

Main Success Scenario:

1. Customer submits checkout with payment.
2. System validates order items and availability.
3. System requests payment from Payment Gateway.
4. Payment Gateway confirms and issues receipt.
5. System marks order status as `PAID`.
6. System returns confirmation to Customer.

Postcondition: Order saved as `PAID`

3. Design Class Model



The Interaction Canvas: Code to Sequence Mapping

UML Sequence Diagram: 3 Objects & 7 Events



Source Code (Java): Execution Flow

```java
class OrderService {
    private PaymentGateway gateway;

    // [1] Controller invokes checkout
    public OrderResult checkout(String id, double amount) {
        // [2] Internal validation (self-call)
        boolean ok = this.validate(id); // [3] returns true

        // [4] Call payment gateway
        Receipt receipt = gateway.charge(amount);
        // [5] Gateway returns receipt

        // [6] Record paid status (self-call)
        this.saveStatus(OrderStatus.PAID);

        // [7] Return result to Controller
        return new OrderResult(true, receipt);
    }
}
```

Structural Anatomy: Lifelines, Activations & Events



Actor

External entity interacting with the subject. A role, not necessarily a physical person.

Lifeline

An individual participant in the interaction.

Focus of Control

The period during which an element performs an operation. Visualized by the activation rectangle.

Event

Any precise point where an occurrence happens (e.g., sending or receiving a message).

The Messaging Matrix: Synchronous, Asynchronous & Lifecycle

The Messaging Matrix

Message Type	Visual Notation	Semantic Meaning
`Call`		Invokes an operation on a target lifeline.
`Return`		Passes information back to the caller of a former message.
`Self`		Invokes a message on the same lifeline.
`Recursive`		Invokes a message targeting a new activation stacked on the caller.
`Create`		Instantiates a new target lifeline.
`Destroy`		Requests the destruction of the target lifeline's lifecycle.
`Duration`		Shows the distance between two time instants for an invocation.

Note: A comment carries no semantic force but attaches useful remarks.

UML 2.0 Combined Fragments: alt, opt, loop, par

Combined Fragments enclose a portion of the interaction to capture branching, loops, and parallel execution, moving beyond single linear paths.



Fragment Operators to Production Code Logic

Operator	Definition	Code Equivalent
`alt`	**Alternative:** Multiple fragments; only the one with a true condition executes.	`if / else if / else`
`opt`	**Optional:** Executes only if the supplied condition is true. Single trace.	`if (without else)`
`loop`	**Loop:** Executes multiple times based on a guard condition.	`while / for loop`
`par`	**Parallel:** Each fragment runs concurrently.	`multi-threading / async`
`region`	**Critical Region:** Only one thread can execute this fragment at once.	`Mutex lock / sync`
`neg`	**Negative:** Shows an explicitly invalid interaction.	`Error path / Exception`
`ref`	**Reference:** Refers to an interaction defined on another diagram.	`Function / Module call`
`sd`	**Sequence Diagram:** Surrounds an entire root sequence diagram.	`Root program`

Case Study: Hotel Reservation Interaction Flow



Concept Check Question 5

In a Boundary-Control-Entity (BCE) sequence diagram, which object should receive the customer's `submitOrder()` event from the checkout UI boundary?

- **A.** The `Order` entity object to immediately save database state.
- **B.** The `PaymentGatewayAPI` boundary object to process payment immediately.
- **C.** The `OrderController` control object to orchestrate business validation and service calls.
- **D.** The `Restaurant` entity object to confirm kitchen capacity.

Diagnostic Exercise: Spot the Flaws in this Sequence Diagram



Audit this student's draft Sequence Diagram for room booking:
Can you identify the critical mistakes across **layering, message syntax, and chronological flow**?

- **1. Architecture Layering & Encapsulation:**
  - Examine `BookingUI` and `MySQL_DB`. What architectural rule is broken by message `[2]` (`SELECT ...`)?
- **2. Synchronous vs. Asynchronous Syntax:**
  - Look at message `[6]`. Why is a synchronous return drawn with a dashed arrow while `[5]` is blocking?
- **3. Combined Fragment (`alt`) Logic:**
  - Inspect the guards on the `alt` block. Why are `[Room Available]` and `[else Payment Successful]` semantically invalid?
- **4. Chronological Causality & Activations:**
  - In what order do `showSuccessMessage()` and `INSERT INTO bookings` occur? Does the DB activation ever close?

Diagnostic Solution: 4 Flaws in Sequence Diagram Explained



Audit Findings & Architectural Corrections:

- **1. Architecture Layering Violation:**
  - `BookingUI` must never send raw SQL (`SELECT ...`) directly to `MySQL_DB`. Interactions must route through the Controller/Service layer.
- **2. Invalid `alt` Combined Fragment Guards:**
  - Branches in an `alt` block must evaluate the same domain condition (e.g., `[Room Available]` vs. `[else / Room Unavailable]`).
- **3. Chronological Paradox / Premature Confirmation:**
  - Database write (`INSERT INTO bookings`) must complete *before* `showSuccessMessage()` confirms booking to the user.
- **4. Dangling Lifeline Activation:**
  - The activation bar on `MySQL_DB` must terminate immediately when the DB query completes.

AI Assistance: Guidelines for Sequence Modeling

- **1. Enforce Architectural Layering:**
  - Instruct AI to follow a clean layered structure (UI → Controller / Business Logic → Entities & Databases).
  - Prevent AI from taking shortcuts like connecting UI directly to database storage.
- **2. Capture Interaction Dynamics:**
  - **Synchronous Requests & Replies:** Clearly show calls and corresponding response acknowledgments.
  - **Branching (Success vs. Failure):** Require AI to handle both normal success and alternative exception scenarios (e.g., payment failure).
  - **Decoupled / Asynchronous Tasks:** Distinguish immediate blocking actions from background notifications (e.g., alert queues).
- **3. Human Reality Check:**
  - Did AI bypass business logic layers?
  - Are alternate scenarios mutually exclusive with clear conditions?

AI Prompt Example: Food Delivery Sequence Model

1. Role & Task Instruction:

```
Act as a Backend Systems Architect.
Generate a clean PlantUML Sequence Diagram
for a Food Delivery Checkout flow.
```

2. Modeling Guidance:

- Follow layered architecture (UI → Controller → Entities / External APIs).
- Explicitly model both paths: **Payment Approved** vs. **Payment Declined**.
- Show asynchronous handoff for background kitchen notification.
- Show active execution lifespans during processing.

3. Input Requirements Statement:

> *"A Customer initiates checkout by clicking 'Pay Now' on the **CheckoutUI**.*
> *The **CheckoutUI** forwards* `submitOrder(cartItems, paymentInfo)` *to the **OrderController**.*
> *The **OrderController** calls **PaymentGateway*** `authorizeCharge(amount, token)`.
>
> ***If payment is approved:***
>
> - *PaymentGateway returns* `chargeToken`.
> - *OrderController persists **Order** as* `PLACED`*, publishes async* `orderPlacedEvent` *to **KitchenOrderQueue**, and returns* `orderSuccess(orderId)` *to CheckoutUI.*
>
> ***If payment is declined:***
>
> - *PaymentGateway returns* `declinedError`.
> - *OrderController logs failure and returns* `paymentFailed()` *to CheckoutUI without creating an order."*
>
> ”

Generated PlantUML & Diagram: Food Delivery Sequence Model

Generated PlantUML Specification:

```
@startuml
autonumber
actor Customer
boundary CheckoutUI
control OrderCtrl
boundary StripeAPI
entity OrderEntity
queue KitchenQueue

Customer -> CheckoutUI: clickPayNow()
activate CheckoutUI
CheckoutUI -> OrderCtrl: submitOrder(cart, payment)
activate OrderCtrl
OrderCtrl -> StripeAPI: authorizeCharge(amount, token)
activate StripeAPI

alt Payment Approved
  StripeAPI --> OrderCtrl: chargeToken
  deactivate StripeAPI
  OrderCtrl -> OrderEntity: create(PLACED)
  OrderCtrl ->> KitchenQueue: orderPlacedEvent
  OrderCtrl --> CheckoutUI: orderSuccess(orderId)
  CheckoutUI --> Customer: displaySuccess()
else Payment Declined
  StripeAPI --> OrderCtrl: declinedError
  OrderCtrl --> CheckoutUI: paymentFailed()
  deactivate OrderCtrl
  CheckoutUI --> Customer: displayError()
```

Rendered Diagram Output:



Interactive Activity: Evolving Sequences with AI (Pair Hands-On)

Hands-on Experiment: Mutate Flow & Audit AI Output (4 Mins)

- **1. Add ONE Edge Case to the Checkout Flow:**
  - *Gateway Timeout:* Payment gateway takes >5s to respond (trigger retry or fallback).
  - *Split Payment:* Allow customer to pay with partial Wallet Balance + Credit Card.
  - *Out of Stock:* Restaurant runs out of an item during checkout.
- **2. Ask AI to Generate:** Prompt an LLM to update the PlantUML sequence diagram.
- **3. Render & Critique:** Paste into PlantText and audit:
  - Did AI preserve **layering** (UI → Controller) without UI querying DB directly?
  - Are **success vs. failure branches** clearly partitioned with return messages?
  - Are **background alerts** (e.g., kitchen notifications) properly decoupled?

4.6 Process & Activity Diagrams

> *"Activity diagrams map the dynamic flow of control, concurrency, and data across collaborating participants."*

Visual Logic: Beyond Static Structures

An Activity Diagram is a crucial behavioral diagram in the Unified Modeling Language (UML). It is an advanced version of a flowchart designed to describe the dynamic aspects of a system, mapping the precise flow from one activity to the next.

The Chaos: Text-Based Processes

Process starts when the user opens the package and then needs to initialize the system, following which they must create must create a new file and ensure all settings are correct, after which they proceed to type the document, remembering to format it according to the guidelines, and finally, after reviewing, they must save the file in the appropriate directory before closing the application and moving on to the next task.

The Clarity: Visual Logic



Three Triggers for Activity Modeling



When to Reach for UML Activity Diagrams:

- **1. Business Workflows:**
  - **Cross-Boundary Value Streams:** Coordinate how multiple independent use cases chain together to fulfill end-to-end organizational goals.
  - **Macro-Level Alignment:** Aligns business stakeholders and engineering teams on broad operational lifecycles.
- **2. Complex Coordination:**
  - **Intra-Use-Case Orchestration:** Track overlapping operations, branching paths, and precise chronological timing within a single feature.
  - **Concurrency Management:** Safely handle simultaneous actions without thread race conditions.
- **3. Contextual Mapping:**
  - **Pre/Post-Condition Contracts:** Identify exact state invariants required before actions start and verified upon completion.
- **Core Value:** Activity models bridge high-level use cases and low-level code implementation.

Flowcharts vs. UML Activity Diagrams

Modeling Capability	Standard Flowchart	UML Activity Diagram
Sequential Logic	✓	✓
Conditional Splits (Branching)	✓	✓
Parallel / Concurrent Processes (Fork & Join)	✗	✓
Actor Accountability (Swimlanes / Partitions)	✗	✓
Object States & Transformation (Data Flow)	✗	✓

Core Vocabulary of System Flow



Conditional Logic: Decision & Merge Nodes



Handling Mutually Exclusive Paths in Workflows:

- **Decision Node (Top Diamond ◇):**
  - **Branching Point:** Evaluates guards on outgoing flows (e.g., `[Graphics Necessary? / Yes]` vs. `[No]`).
  - **Strict Mutual Exclusion:** Exactly **ONE** path receives the execution token based on runtime evaluation.
- **Merge Node (Bottom Diamond ◇):**
  - **Reconvergence Point:** Brings alternative paths back into a single continuing flow (e.g., before `Save File`).
  - **No Synchronization Waiting:** Does **NOT** wait for multiple tokens; whichever branch arrives first continues immediately.
- **Key Takeaway:** Diamonds handle **if-else** choices, safely dividing and reuniting mutually exclusive logic.

Concurrency: Fork & Join Nodes



Orchestrating Parallel Threads & Synchronization:

- **Fork Node (Top Solid Bar —):**
  - **1-to-Many Concurrency:** Takes one incoming control flow and splits it into **concurrent parallel threads**.
  - **Simultaneous Execution:** Both `Handle Billing` and `Fill and Send` execute concurrently without blocking each other.
- **Join Node (Bottom Solid Bar —):**
  - **Synchronization Barrier:** All incoming parallel branches must finish before outgoing flow (`Close Order`) can proceed.
  - **Waiting Guarantee:** If billing takes 1s and packing takes 10s, billing halts at the join bar until packing arrives.
- **Key Takeaway:** Forks spawn parallel concurrent threads; joins synchronize and wait for all threads to complete.

The Multi-Actor Accountability Problem



Clear Ownership Eliminates Workflow Ambiguity:

- **The Problem: Process Ambiguity (Left):**
  - **Unassigned Spaghetti Tasks:** Knowing *what* tasks occur is useless if no one knows *who* is responsible for each step.
  - **Lost Handoffs:** Complex arrow webs obscure role transitions between employees and managers, causing dropped tasks.
- **The Solution: Swimlane Accountability (Right):**
  - **Boundary Separation:** Clear vertical columns partition responsibilities (e.g., `Employee` vs. `Manager`).
  - **Explicit Crossing Points:** Cross-partition arrows explicitly define handoffs (e.g., employee submits → manager reviews & approves).
- **Core Principle:** Swimlanes transform tangled process spaghetti into crisp, legally unambiguous operational boundaries.

Swimlanes & Partitions: Grouping Activities



Mapping Seamless Actor Handoffs in Practice:

- **Actor Partitions (Swimlanes):**
  - Groups activities by performer: `Applicant` on the left, `Registrar` on the right.
  - Visualizes organizational, departmental, or subsystem boundaries cleanly.
- **Handoff Lifecycle (University Enrollment):**
  - **1. Action Initiation:** Applicant hands in the enrollment form (`Hand in Enrollment Form`).
  - **2. Boundary Crossing:** Flow crosses to the Registrar for validation (`Inspect Forms` → `Determine Proper Fill`).
  - **3. Notification & Return:** Registrar informs student (`Inform Student`), returning control to the Applicant to `Pay Initial Tuition`.
- **Key Takeaway:** Every cross-lane arrow is a formal contract interface between two distinct actors or architectural components.

Visual Taxonomy of Activity Diagrams

The Actors

Swimlane / Partition

Groups activities by actor or execution thread.

The Actions

Action Node

A single task to be performed.

Object Node

Represents a connected physical or digital artifact.

The Directors



Initial & Final Nodes

Start and stop all system flows.

Control & Object Flows

Sequence execution and data movement.

Decision & Merge Nodes

Split and return conditional paths.



Fork & Join Nodes

Split and return concurrent parallel paths.

The Unified Workflow Model



Combining Swimlanes, Concurrency, & Logic:

- **1. Cross-Actor Handoff:**
  - `Actor A` initiates an `Initial Request`; control flows across the partition to `Actor B` to `Review Request`.
- **2. Concurrent Processing & Object Flow:**
  - **Fork Bar:** Splits execution simultaneously into `Actor B` (perform analysis) and `Actor C` (execute sub-process).
  - **Object Transformation:** `Actor B` produces a tangible `[Analysis Report]` data object.
- **3. Decision Loop & Synchronization Barrier:**
  - **Retry Diamond:** In `Actor C`, `[Success?]` loops on failure and proceeds on success.
  - **Join Bar:** Waits for both the `Analysis Report` and successful sub-process before compiling output and delivering result.
- **Key Takeaway:** Unifies roles, parallel tasks, stateful objects, and conditional loops into an enterprise-grade blueprint.

Concept Check Question 6

In a UML Activity Diagram, what is the critical behavioral difference between a **Fork/Join** synchronization bar and a **Decision/Merge** diamond?

- **A.** Fork/Join splits and synchronizes concurrent parallel threads; Decision/Merge evaluates guards to pick exactly one mutually exclusive branch.
- **B.** Fork/Join is used for sequential database transactions; Decision/Merge is used for swimlane partitioning.
- **C.** Fork/Join models class inheritance; Decision/Merge models object creation.
- **D.** Fork/Join requires human operator approval; Decision/Merge is executed by automated timers.

Diagnostic Exercise: Spot the Flaws in this Activity Diagram



Audit this student's draft Activity Diagram for food fulfillment:
Can you identify the critical mistakes across **concurrency, branching, and swimlane roles**?

- **1. Concurrency vs. Conditional Branching:**
  - Look closely at the `fork` bar in the Kitchen swimlane. Why is placing `[Card Payment]` and `[Cash on Delivery]` guards on a fork fundamentally wrong?
- **2. Swimlane Accountability & Partitioning:**
  - Examine the actions assigned to `Customer` and `Kitchen`. Which responsibilities are absurdly reversed?
- **3. Dangling Control Flow & Termination:**
  - Follow the `[Out of Stock]` path after `Cancel Order`. What essential UML node is missing before flow terminates?
- **4. Deadlock vs. Synchronization:**
  - If concurrent threads do not properly converge with matching join semantics, what runtime failure occurs?

Diagnostic Solution: 4 Flaws in Activity Diagram Explained



Audit Findings & Architectural Corrections:

- **1. Fork Bar vs. Decision Diamond:**
  - A `fork` bar spawns parallel threads running *simultaneously*. Mutually exclusive paths (`[Card]` vs. `[Cash]`) require a Decision diamond.
- **2. Swimlane Responsibility Inversion:**
  - Roles are absurdly reversed: `Customer` enters delivery address; `Kitchen` cooks food and packages the meal.
- **3. Dangling Control Flow:**
  - The `[Out of Stock]` path after `Cancel Order` terminates into thin air; it must reach an explicit Activity Final node (◉).
- **4. Deadlock Hazard on Join:**
  - Feeding mutually exclusive decision branches into a Join bar causes deadlock waiting for non-existent concurrent tokens.

AI Assistance: Guidelines for Activity Modeling

- **1. Establish Clear Role Boundaries (Swimlanes):**
  - Partition actions by role or system (e.g., Customer, Kitchen, Courier, Dispatch) so every action has an explicit owner.
- **2. Identify True Concurrency & Synchronization:**
  - **Parallel Workflows:** Guide AI to recognize independent steps that happen at the same time (e.g., cooking food while dispatching a driver).
  - **Synchronization Milestones:** Explicitly specify where parallel branches must wait and join before the workflow can proceed.
- **3. Explicit Decision Points:**
  - Ensure branch conditions are clear and cover all possible outcomes.
- **4. Human Reality Check:**
  - Did AI collapse parallel work into a purely sequential list?
  - Does every split path properly reunite at a synchronization point?

AI Prompt Example: Food Delivery Activity Model

1. Role & Task Instruction:

```
Act as a Workflow & Process Architect.
Generate a clean PlantUML Activity Diagram
using swimlanes and parallel processing.
```

2. Modeling Guidance:

- Divide workflow into 4 roles: Customer, Kitchen, Dispatch, Courier.
- Identify parallel steps after order payment (cooking meal while matching courier).
- Synchronize branches: courier cannot pick up meal until both cooking is finished and courier has arrived.
- Clearly show process start, decision points, and completion.

3. Input Requirements Statement:

> *"Workflow begins in the **Customer** swimlane when the user confirms and pays for an order.*
> *Once confirmed, two parallel processes initiate:*
>
> - *In **Restaurant Kitchen**: Staff receive order ticket, prepare food items, and package the meal into a delivery bag.*
> - *Simultaneously, in **Dispatch Engine**: The system calculates transit route, queries nearby available couriers, and dispatches a delivery offer.*
>
> *In the **Delivery Courier** swimlane, the courier accepts the assignment and drives to the restaurant.*
> ***Synchronization Milestone:** The courier cannot pick up the order until BOTH the food packaging is complete AND the courier has arrived at the store.*
> *Once synchronized, kitchen hands off food to courier.*
> *Courier transports meal to customer address, customer verifies delivery with OTP, and the process ends."*

Generated PlantUML & Diagram: Food Delivery Activity Model

Generated PlantUML Specification:

```
@startuml
|Customer|
start
:Confirm & pay for order;

fork
  |Restaurant Kitchen|
  :Receive order ticket;
  :Prepare food items;
  :Package meal into delivery bag;
fork again
  |Dispatch Engine|
  :Calculate transit route;
  :Query nearby couriers;
  :Dispatch assignment offer;
  |Delivery Courier|
  :Accept assignment;
  :Drive to restaurant;
end fork

|Restaurant Kitchen|
:Hand off packaged meal to Courier;

|Delivery Courier|
:Transport meal to customer address;
```

Rendered Diagram Output:



Interactive Activity: Evolving Workflows with AI (Pair Hands-On)

Hands-on Experiment: Mutate Process & Audit AI Output (4 Mins)

- **1. Add ONE Process Rule to the Activity Prompt:**
  - *Courier Reassignment:* If matched courier declines, re-dispatch to another courier.
  - *Quality Check:* Kitchen inspects food; if burnt, redo cooking before packaging.
  - *Customer Self-Pickup:* If customer chooses takeaway, bypass courier swimlane.
- **2. Ask AI to Generate:** Prompt an LLM to update the PlantUML activity diagram.
- **3. Render & Critique:** Paste into PlantText and audit:
  - Did AI maintain clear **swimlanes** for all participating roles?
  - Are **parallel splits and joins** properly paired without deadlocks?
  - Are **decision diamonds** fully labeled with complete branch conditions?

4.7 Behavioral & State Machine Models

> *"A system in dynamic execution is defined by the states it occupies and the events that trigger transitions."*

Same Event, Different Results Based on State



Context-Dependent Behavioral Execution:

- **Identical Stimulus, Divergent Outcome:**
  - Sending the exact same input event (`pressSwitch()`) triggers opposite results depending on current system state.
- **State Evaluation:**
  - **Current State = Off (Blue Path):** The switch closes the circuit and transitions light to `On`.
  - **Current State = On (Red Path):** The switch breaks the circuit and transitions light to `Off`.
- **Core Architectural Invariant:** In reactive systems, runtime behavior is a function of `(Current State, Event) → (Next State, Action)`.

Positioning State Machines in the UML Ecosystem



Complementary Behavioral Perspectives:

- **Sequence Diagram (Inter-Object Chronology):**
  - **Scope:** Multiple objects collaborating across lifelines.
  - **Coverage:** Traces a **single execution scenario** (happy path or specific edge case).
- **State Machine (Intra-Object Lifecycle):**
  - **Scope:** A **single key entity** (e.g., `Order`, `Connection`).
  - **Coverage:** Exhaustively captures **all possible states, events, and transitions** over its entire lifetime.
- **Architectural Rule:** Use Sequence Diagrams for inter-service protocols; use State Machines for complex entity integrity.

Defining the State: A Lifecycle Interval



The Formal Lifecycle Interval:

- **1. Initial Pseudo-State (●):**
  - Not a true state; marks the default starting entry point of an object lifecycle.
- **2. The State (Rounded Box):**
  - **Sustained Interval:** A period during which the object satisfies an invariant, executes an ongoing activity, or waits for an event.
  - **State vs. Action:** A state is durational, unlike an instantaneous atomic action.
- **3. Final State (◉):**
  - Bullseye notation marking lifecycle termination and resource deallocation.
- **Core Rule:** Continuous/server processes omit final states; workflow entities terminate at final states.

The Four Triggers of State Transitions



The Four Event Stimuli in UML:

- **1. Signal Event (⚡ Lightning):**
  - Asynchronous message or event packet arriving from an external actor or subsystem.
- **2. Call Event (⚙ Gears):**
  - Synchronous invocation of an operation or method on the object's interface.
- **3. Time Event (⏳ Hourglass):**
  - Temporal trigger based on elapsed time (e.g., `after(30s)` or deadline expiration).
- **4. Change Event ([≥] Condition):**
  - Continuous monitoring trigger firing when a boolean expression transitions from false to true (e.g., `when(temp > 100)`).
  - **Key Takeaway:** Every state transition must be driven by exactly one of these four event types.

The Mechanics of a Transition: Event, Guard, Action



Anatomy of the Transition Pipeline:

- **The Transition Equation:**
  - Standard UML syntax: `Event [Guard] / Action`.
- **Step-by-Step Execution Mechanics:**
  - **1. Event Stimulus:** Incoming event drops into the state handler funnel.
  - **2. Guard Evaluation:** Boolean guard condition controls the gate; if false, the transition does not fire.
  - **3. Action Execution:** Atomic, instantaneous action effect runs in zero logical time.
  - **4. State Change:** System transitions out of Source State into Target State.
- **Completion Transitions:** Transitions without triggers fire automatically when internal state activities finish.

Transition in Action: Food Delivery Order Example



Applying the Transition Pipeline to Food Delivery:

- **Concrete Transition Syntax:**
  - `cancelOrder(reason) [elapsedTime <= 120s] / processFullRefund(); notifyKitchen()`
- **1. Event Stimulus (`cancelOrder`):**
  - Customer triggers cancellation from the mobile app.
- **2. Guard Condition (`[elapsedTime <= 120s]`):**
  - Order allows cancellation strictly within 2 minutes of placement. If `elapsedTime > 120s`, the guard evaluates to **false**, blocking transition to `Cancelled`.
- **3. Action Effect (`/ processFullRefund()`):**
  - Atomic side-effect executes immediately during the transition to refund the payment.
- **Target State (`Cancelled`):**
  - State enters `Cancelled` and executes `entry / logCancellation()`.

Execution Engines: Actions vs. Activities

Feature	Action	Activity
Nature	Atomic Computation (Operation call, destroy object)	Non-atomic computation
Duration	Instantaneous	Ongoing (Runs to completion or indefinitely)
Interruptibility	NEVER interruptible	YES, can be interrupted by events
Triggers	On Entry, Do, On Event, On Exit	Sustained state presence

Atomic Execution vs. Durational Behavior:

- **Action (Atomic Computation):**
  - **Duration:** Instantaneous (zero logical execution time).
  - **Interruptibility: Non-interruptible**; once triggered, runs to completion before any event is processed.
  - **Placement:** On transitions, `entry /`, or `exit /`.
- **Activity (Ongoing Computation):**
  - **Duration:** Sustained over time; continues while state is active.
  - **Interruptibility: Immediately interruptible** if an outgoing transition event fires.
  - **Placement:** Declared as `do / [activity]`.
- **Crucial Rule:** Never put long-running I/O or background loops inside an Action.

Boundary Executions: Entry and Exit Actions



Guaranteed Lifecycle Hooks in Food Delivery:

- **Entry Action (`entry / startGPSTracking()`):**
  - Guaranteed to fire immediately whenever entering `OutForDelivery` from `courierPickUp()`.
  - Starts real-time rider GPS tracking and alerts customer "Rider En Route".
- **Ongoing Activity (`do / streamRiderGPSCoordinates()`):**
  - Continues streaming GPS location throughout the delivery journey; immediately interruptible upon arrival or timeout.
- **Exit Action (`exit / stopGPSTracking()`):**
  - Guaranteed to execute regardless of whether delivery succeeds (`Delivered`) or fails (`DeliveryFailed`).
  - Stops battery-heavy GPS tracking and logs drop-off timestamp.
- **Architectural Value:** Encapsulates initialization and cleanup inside `OutForDelivery`, eliminating duplicate code across multiple exit arrows.

Scaling Architecture: Composite & Concurrent States



Taming Order Lifecycle Complexity via Hierarchy:

- **1. Simple State (`Placed`):**
  - Single atomic state awaiting restaurant acceptance.
- **2. Composite State (`OrderFulfillment`):**
  - An outer super-state encapsulating multi-step preparation and dispatch.
  - Outer transitions (e.g., `emergencyCancel() / fullRefund()`) uniformly govern all substates, drastically reducing arrow clutter.
- **3. Concurrent Regions (`||` Orthogonal Tracks):**
  - **Kitchen Pipeline (Region 1):** `Cooking` → `Packaged` → `AwaitingPickup`.
  - **Courier Logistics (Region 2):** `FindingCourier` → `CourierAssigned` → `CourierAtRestaurant`.
  - Both pipelines execute simultaneously and independently in parallel!

Composite States and History Memory (H)



Preserving Order Progress Across Interruptions:

- **Default Composite Entry:**
  - Standard orders entering `OrderExecution` always begin from initial startup (`Cooking`).
- **The History State Pseudo-Node `(H)`:**
  - **State Caching:** Remembers the active substate when an unexpected suspension occurs (e.g., `paymentDispute()` or address verification hold).
  - **Direct Restoration:** When the dispute is resolved (`disputeResolved()`), the transition enters `(H)`, which directs execution directly back to `OutForDelivery`!
- **Real-World Business Impact:**
  - **Without `(H)`:** Order would restart at `Cooking`, forcing the kitchen to re-cook the meal from scratch!
  - **With `(H)`:** The courier simply resumes delivery of the already-prepared meal.

The Unified Blueprint: Food Delivery Order Architecture



Comparing Dynamic Models: State Machine vs. Activity Diagram

> *Both diagrams capture behavioral dynamics in UML, but answer fundamentally different architectural questions.*

Comparison Dimension	State Machine Diagram (Statechart)	Activity Diagram (Workflow)
Core Perspective	**Entity-Centric / Reactive:** Models the complete lifecycle of a *single entity* over time.	**Process-Centric / Procedural:** Models the end-to-end *workflow* across multiple actors and systems.
Primary Node	**State:** Quiescent condition where an object waits for events or performs continuous work.	**Action / Activity:** An active computational step or business operation being executed.
Transition Driver	**Event-Driven:** Transitions wait for triggers (`Event [Guard] / Action`).	**Completion-Driven:** Flows advance automatically upon task completion (`Control / Object Flow`).
Concurrency Model	**Orthogonal Regions:** Parallel sub-states within a composite state (parallel tracks).	**Fork & Join Nodes:** Explicit parallel flow splitting and synchronization across swimlanes.
Optimal Use Case	Entity lifecycle (e.g., Order, Account, TCP socket), IoT devices, and status machines.	Business process modeling (e.g., checkout pipeline), ETL batch jobs, and use case elaboration.

Concept Check Question 7

In a UML State Machine, what is the critical architectural difference between an **Action** (such as `/ refundCharge()` or `entry / startTimer()`) and an **Activity** (`do / playAudio()`)?

- **A.** Actions are instantaneous, atomic, and non-interruptible; Activities are ongoing computations that take time and can be interrupted by incoming events.
- **B.** Actions are written in Python code; Activities are written in SQL queries.
- **C.** Actions only apply to class diagrams; Activities only apply to sequence diagrams.
- **D.** Actions represent manual human tasks; Activities are executed by database servers.

Diagnostic Exercise: Spot the Flaws in this State Machine Model



Audit this student's draft State Machine for an Order Lifecycle:
Can you identify the critical mistakes across **state semantics, transitions, and terminal nodes**?

- **1. State vs. Transient Action:**
  - Examine `DeductCreditCard`. Why is it semantically incorrect to model an instantaneous action as a persistent state?
- **2. Black Hole (Trap) State:**
  - Look at `RiskReview`. What happens once an order enters this state?
- **3. Non-Deterministic Transition Conflict:**
  - Inspect the two `cancelOrder` transitions leaving `Paid`. If `amount == 150`, which transition fires?
- **4. Final State Invariants:**
  - What fundamental UML rule is violated by the `reopenOrder()` transition leaving the final state `[*]`?

Diagnostic Solution: Flaws in State Machine Model Explained



Audit Findings & Architectural Corrections:

- **1. State vs. Transient Action:**
  - `DeductCreditCard` is an instantaneous action, not a state. It should be an effect on a transition (`pay / deductCard()`), not a state box.
- **2. Black Hole (Trap) State:**
  - `RiskReview` has an entry transition but zero outgoing paths, trapping orders permanently with no resolution path.
- **3. Non-Deterministic Transition Conflict:**
  - Leaving `Paid`, two transitions share `cancelOrder` where one lacks a guard. When `amount == 150`, both fire, causing runtime race conflict.
- **4. Illegal Outgoing Transition from Final State:**
  - `reopenOrder()` extends from `[*]`. UML strictly forbids transitions leaving a final state; terminal state is permanent.

AI Assistance: Guidelines for State Machine Modeling

- **1. Focus on Entity Lifecycle (States vs. Activities):**
  - Name states as discrete conditions or adjectives (`Placed`, `Preparing`, `Delivered`), never verbs or temporary actions (e.g., avoid "Cooking Meal").
- **2. Define Clear Triggers & Guard Rules:**
  - **Triggers:** Specify the exact business events that cause a state change (e.g., `acceptOrder`, `paymentConfirmed`).
  - **Business Guards:** Explicitly enforce rules that allow or block transitions (e.g., "cancellation allowed only before kitchen starts").
- **3. Account for Terminal & Exception States:**
  - Ensure every lifecycle has a clear starting point, successful completion, and failure/cancellation outcomes.
- **4. Human Reality Check:**
  - Did AI confuse an activity flow with a state machine?
  - Are there dead-end or unreachable states?

AI Prompt Example: Food Delivery State Machine Model

1. Role & Task Instruction:

```
Act as a Systems Verification Architect.
Generate a clean PlantUML State Machine
for a Food Delivery Order lifecycle.
```

2. Modeling Guidance:

- Model discrete lifecycle states: `Placed`, `Accepted`, `Preparing`, `ReadyForPickup`, `OutForDelivery`, `Delivered`, `Cancelled`.
- Enforce business rules: cancellation allowed only while in `Placed` or `Accepted` before cooking begins.
- Trigger automatic actions upon entering `OutForDelivery` (start GPS tracking).
- Ensure clear initial state and terminal states (Delivered, Cancelled).

3. Input Requirements Statement:

> *"An **Order** lifecycle begins at `[*]` and enters **Placed** upon customer payment.*
> *While in **Placed**, the restaurant receives an `acceptOrder` event moving it to **Accepted**, or a `rejectOrder` event moving it to **Cancelled** `/ issueFullRefund()`.*
> *The customer may trigger `cancelOrder` only while in **Placed** or **Accepted** with guard `[timeElapsed <= 120s]`, transitioning to **Cancelled**.*
> *From **Accepted**, the kitchen fires `startCooking`, transitioning to **Preparing**. Cancellation is now strictly blocked.*
> *When cooking finishes, `packagingComplete` moves order to **ReadyForPickup**.*
> *When the courier scans the pickup QR code, `courierPickedUp` moves order to **OutForDelivery**, which executes `entry / startGPSTracking()`.*
> *Upon arrival and OTP entry, `confirmDropoff` moves order to **Delivered**, which transitions to `[*]`."*
>
> ”

Generated PlantUML & Diagram: Food Delivery State Machine Model

Generated PlantUML Specification:

```
@startuml
[*] -right-> Placed : customerPays()

state Placed {
  Placed : entry / startAcceptTimer()
}
state OutForDelivery {
  OutForDelivery : entry / startGPSTracking()
}

Placed -right-> Accepted : acceptOrder()
Accepted -right-> Preparing : startCooking()
Preparing -down-> ReadyForPickup : packagingComplete()
ReadyForPickup -left-> OutForDelivery : courierPickedUp()
OutForDelivery -left-> Delivered : confirmDropoff()
Delivered -down-> [*]

Placed -down-> Cancelled : rejectOrder() / refund()
Placed -down-> Cancelled : cancelOrder [t <= 120s]
Accepted -down-> Cancelled : cancelOrder [t <= 120s]
Cancelled -left-> [*]
@enduml
```

Rendered Diagram Output:



Interactive Activity: Evolving State Lifecycles with AI (Pair Hands-On)

Hands-on Experiment: Mutate Lifecycle & Audit AI Output (4 Mins)

- **1. Add ONE Lifecycle Invariant to the State Machine Prompt:**
  - *Driver Reassignment:* If courier abandons delivery, transition back to `ReadyForPickup`.
  - *Customer Reschedule:* Allow postponing delivery while in `Preparing`.
  - *Delivery Failed:* If customer unreachable at drop-off, move to `FailedDelivery` and return meal.
- **2. Ask AI to Generate:** Prompt an LLM to update the PlantUML state machine.
- **3. Render & Critique:** Paste into PlantText and audit:
  - Did AI preserve **state naming** (adjectives/conditions, no action verbs)?
  - Are **illegal transitions** (e.g., cancelling hot food en route) strictly blocked?
  - Are **guard conditions and exit/entry actions** logically consistent?

4.8 Text-Based Modeling with PlantUML

> *"Stop dragging boxes. Start writing architecture."* „

ONLINE EDITOR **PlantText Live Playground (planttext.com) →**

PlantUML: Code-Driven Architecture



Diagrams as Code (Text to Architecture):

- **Declarative Architecture:**
  - Write concise, human-readable text scripts to specify system components and data flows.
- **PlantUML Syntax Snippet:**

```
component "Order Service" as OS
database "Order DB" as ODB
OS --> ODB : Stores Order Data
```

- **Automated Layout Engine:**
  - Graphviz computes coordinates, routing, and alignment automatically without manual layout friction.
- **Core Value:** Replaces brittle drawing tools with version-controlled, pull-request-friendly architecture files.

Stop Dragging Boxes. Start Writing Architecture



Eliminating Visual Friction & Maintenance Debt:

- **The Traditional GUI Way (Left - Mouse Fatigue):**
  - Whiteboard and GUI dragging tools are slow, manual, and permanently disconnected from source code.
  - Adding a single box requires tedious repositioning of dozens of connectors.
- **The PlantUML Way (Right - Instant & Standardized):**

```
class User { +name : String }
class Order { +id : Int }
User "1" -- "*" Order
```

- **Engineering Advantage:**
  - Focus 100% on software abstractions and relationships rather than pixel-pushing alignment.

Frictionless Setup: VS Code & Live Preview



Three Steps to Local Diagramming Velocity:

- **1. Install Extension:**
  - Add the official **PlantUML** extension from the VS Code Marketplace.
- **2. Write Architecture:**
  - Create any `.puml` file with full syntax highlighting & intelligent auto-completion.
- **3. Instant Rendering:**
  - Press `Alt + D` (Mac: `Option + D`) to toggle live side-by-side preview.
- **Multi-Format Export:**
  - Export production diagrams directly to **SVG**, high-res **PNG**, or terminal-friendly **ASCII art**.

The Architect's Blueprint: 5 Essential Lenses



Unified Syntax Across All Architectural Perspectives:

- **Structure Diagrams (Static Backbone):**
  - **Class Diagram:** Specifies domain entities, attributes, operations, and relationships.
- **Behavior Diagrams (Dynamic Motion):**
  - **Use Case Diagram:** High-level actor interactions and system boundaries.
  - **Activity Diagram:** Process workflows, concurrency, and swimlanes.
  - **Sequence Diagram:** Message chronology across lifelines.
  - **State Diagram:** Entity lifecycle states and event transitions.
- **Core Value:** One unified text syntax covers all five essential UML models.

Use Case Diagrams in PlantUML Syntax



Capturing Functional Requirements in Plain Text:

- **Intuitive Language Elements:**
  - `actor Customer`: Declares external actors (rendered as stick figures).
  - `usecase Login`: Declares system capabilities inside boundary ovals.
  - `Customer --> Login`: Establishes communication associations.
- **PlantUML Script Example:**

```
actor Customer
usecase Login
usecase Checkout
Customer --> Login
Customer --> Checkout
```

- **Agile Advantage:** Perfect for user story mapping and stakeholder scoping before coding.

Class Diagrams in PlantUML Syntax



Mirroring Object-Oriented Code Structure:

- **3-Compartment Class Box:**
  - Top: Class name (`class Animal`).
  - Middle: Attributes (`int id`, `String name`).
  - Bottom: Operations (`+int getId()`, `+void makeSound()`).
- **Visibility Modifiers:**
  - `+` Public | `-` Private | `#` Protected | `~` Package
- **PlantUML Script Example:**

```
class Animal {
  int id
  String name
  +int getId()
  +void makeSound()
}
```

The Class Relationship Matrix in PlantUML

Relationship Type	Definition	PlantUML Syntax	Visual Output
Inheritance	Subclass inherits attributes/operations of a superclass.	`<|--`	
Association	One class uses the services of another.	`--`	
Aggregation	A whole/part relationship where the part can exist independently.	`o--`	
Composition	Strong ownership; the part cannot exist without the whole.	`*--`	

Mnemonic Connector Symbols for Class Relations:

- **Inheritance (`<|--`):**
  - Subclass inherits attributes/operations (hollow triangle `<|`).
- **Association (`--`):**
  - Structural relationship where one class references another.
- **Aggregation (`o--`):**
  - Shared "has-a" relationship; parts exist independently (hollow diamond `o`).
- **Composition (`*--`):**
  - Strict ownership; parts live and die with the whole (solid diamond `*`).
- **Mnemonic Design:** PlantUML symbols visually mirror UML standard connector shapes.

Sequence Diagrams in PlantUML Syntax



Chronological Interactions Over Time:

- **Core Interaction Rules:**
  - Time flows downwards vertically.
  - Participants are declared with `participant Name`.
  - Solid arrow `->` represents synchronous request call.
  - Dashed arrow `-->` represents return response.
- **PlantUML Script Example:**

```
participant User
participant OrderService
User -> OrderService : Request to place order
OrderService --> User : Confirm order placement
```

- **Automatic Layout:** Lifelines, activations, and alignments are computed automatically.

Anatomy of Sequence Syntax: Lifelines & Messages



Key Visual Building Blocks in PlantUML:

- **1. Lifelines:**
  - Vertical dashed tracks representing collaborating participants.
- **2. Messages:**
  - Horizontal communication arrows (`->` synchronous, `->>` asynchronous).
- **3. Activation Boxes (`activate` / `deactivate`):**
  - Thin rectangles showing active execution periods on a lifeline.
- **4. Lifecycle Events (`create` / `destroy`):**
  - Specialized messages that instantiate new participants or terminate lifelines.
- **Core Value:** Clean text syntax generates pixel-perfect sequence diagrams.

Activity Diagrams & Swimlanes in PlantUML



Workflow & Process Modeling (Beta Syntax):

- **Workflow Control Markers:**
  - `start`: Renders solid black initial node.
  - `:Action Name;`: Colon and semicolon wrap action state boxes.
  - `stop`: Renders bullseye final termination node.
- **PlantUML Script Example:**

```
start
:Customer Login;
:Add to Cart;
stop
```

- **Advanced Capabilities:**
  - Decision diamonds via `if (...) then (...) else (...) endif`.
  - Swimlanes via `|Lane Name|` partition markers.

State Diagrams in PlantUML Syntax

While Activity diagrams show multi-actor processes, State diagrams focus strictly on the lifecycle of a single object in response to external events.

```
[*] --> NewOrder
NewOrder --> Paid : Payment Processed
Paid --> Shipped : Order Sent
Shipped --> [*]
```

Format: `StateA --> StateB : Event String`



Single-Object Reactive Lifecycle Modeling:

- **Standard State Transition Syntax:**
  - Format: `StateA --> StateB : Event String`
- **PlantUML Script Example:**

```
[*] --> NewOrder
NewOrder --> Paid : Payment Processed
Paid --> Shipped : Order Sent
Shipped --> [*]
```

- **Lifecycle Markers:**
  - `[*]`: Represents both initial pseudo-state and final state.
- **Core Value:** Model complex finite state machines in seconds with clear transition event labels.

Concept Check Question 8

What is the primary engineering advantage of using text-based diagramming tools like **PlantUML** over traditional proprietary GUI drawing software?

- **A.** PlantUML eliminates the need to understand software architecture and UML principles.
- **B.** Text markup can be version-controlled in Git, diffed in Pull Requests, and automated in CI/CD pipelines.
- **C.** PlantUML automatically generates full production databases and microservices without writing code.
- **D.** PlantUML is strictly limited to class diagrams and cannot model dynamic workflows.

4.9 Conceptual Recap & Synthesis

> *"Models are the lingua franca of software engineering."* „

Conceptual Recap: Fill-in-the-Blank Quiz (Part 1)

Word Bank: Interaction | Ivar Jacobson | Boundary-Control-Entity (BCE) | <<include>> | <<extend>> | Composition (◆) | Aggregation (◇)

1. The "Three Amigos" who unified UML at Rational Software were Grady Booch, Jim Rumbaugh, and [_____].
2. In system modeling, the 4 foundational perspectives are External, [_____], Structural, and Behavioral.
3. In use case modeling, mandatory shared functionality factored out across use cases uses the [_____] relationship.
4. Optional or conditional behavior triggered under specific conditions connects via the [_____] relationship.
5. The architectural analysis pattern separating user interfaces, business logic, and persistent domain entities is [_____].
6. In a UML class diagram, a filled black diamond (◆) represents [_____], where part lifetimes strictly depend on the whole.
7. In a UML class diagram, an open hollow diamond (◇) represents [_____], where parts maintain independent lifecycles.

Interactive Mode: Click any blank slot to reveal or hide the answer!

Conceptual Recap: Fill-in-the-Blank Quiz (Part 2)

Word Bank: Solid Arrow (→) | alt fragment | Swimlanes | Join Node | Guard Condition | Orthogonal Regions (||) | History State [H*]

8. In a sequence diagram, a synchronous call that blocks execution until the target responds is drawn with a [_____].
9. In a sequence diagram, conditional branching with mutually exclusive execution alternatives is enclosed in an [_____].
10. In an activity diagram, responsibilities of departments, business roles, or architectural tiers are partitioned by [_____].
11. In an activity diagram, a thick synchronization bar that merges multiple concurrent execution paths before continuing is a [_____].
12. In a UML state machine transition label, the boolean check condition enclosed in square brackets `[ ]` is the [_____].
13. In a composite state, concurrent parallel sub-states operating side-by-side are modeled inside [_____].
14. The pseudo-state that caches and restores the most recently active sub-state upon recovery from an interruption is the [_____].

Interactive Mode: Click any blank slot to reveal or hide the answer!

Activity Solution 1: Use Case Model Extensions

BACK Activity Prompt (p. 34)

> *"Extending use case models requires guarding system boundaries and distinguishing optional extensions from mandatory subroutines."*

Architectural Mutation Solutions

- **Scheduled Ordering (`<<extend>>`):**
  - `(Place Food Order) <.. (Schedule Future Delivery) : <<extend>>`
  - Guard condition: `[delivery_type == scheduled]`. Optional feature that hooks into standard checkout without polluting the base case.
- **Live Chat Support (Base Use Case):**
  - Standalone `(Live Order Chat)` use case. Primary actor `Customer` connects with secondary actors `Support Agent` and `Courier`.
  - Secondary actors remain strictly **outside** the system boundary rectangle.
- **Group Ordering (`<<extend>>`):**
  - Base use case `(Place Food Order)` extended by `(Pool Group Cart)` before payment.

PlantUML Delta & Quality Audit

```
rectangle "Food Delivery Platform" {
  usecase "Place Food Order" as UC_Order
  usecase "Schedule Future Order" as UC_Sched
  usecase "Live Order Chat" as UC_Chat
  UC_Order <.. UC_Sched : <<extend>>
}
Customer --> UC_Order
Customer --> UC_Chat
UC_Chat --> Agent : <<assists>>
```

- **[Pass] Boundary Discipline:** External partner `Support Agent` is positioned outside system boundary.
- **[Pass] Semantic Integrity:** Scheduled delivery is an optional extension, not a mandatory `<<include>>`.
- **[Pass] Goal Orientation:** Avoids low-level UI button clicks.

Activity Solution 2: Class Model Refinements

BACK Activity Prompt (p. 53)

> *"Domain class evolution tests whether lifecycles are autonomous (aggregation) or bounded by whole-part destruction (composition)."*

Structural Solutions & Semantics

- **Multi-Vendor Sub-Orders:**
  - Master `Order` splits into restaurant-specific sub-orders.
  - `Order` `"1"` `*--` `"1..*"` `SubOrder` (Composition: sub-orders cannot exist without the master order).
  - `SubOrder` `"1..*"` `o--` `"1"` `Restaurant` (Aggregation: restaurant survives order deletion).
  - `SubOrder` `"1"` `*--` `"1..*"` `OrderItem`.
- **Courier Tipping & Rating:**
  - `DeliveryTask` `"1"` `o--` `"0..1"` `CourierReview` (Aggregation / weak reference; review is optional).
- **VIP Membership Plan:**
  - `Customer` `"1"` `o--` `"0..1"` `MembershipPlan` (Decoupled subscription strategy pattern).

PlantUML Delta & Quality Audit

```
class Order { - orderId: UUID; - total: Money }
class SubOrder { - subTotal: Money; - status: Status }
class Restaurant { - name: String; - address: String }
class CourierReview { - rating: int; - tip: Money }
Order "1" *-- "1..*" SubOrder : aggregates
SubOrder "1..*" o-- "1" Restaurant : fulfills
SubOrder "1" *-- "1..*" OrderItem
DeliveryTask "1" o-- "0..1" CourierReview
```

- **[Pass] Multiplicity Logic:** 1 master order contains `1..*` sub-orders; 1 sub-order targets exactly 1 restaurant.
- **[Pass] Relationship Precision:** Solid diamond (`*--`) for lifecycle dependency; hollow diamond (`o--`) for weak associations.
- **[Pass] Strict Encapsulation:** Private attributes with explicit types.

Activity Solution 3: Sequence Interaction Edge Cases

BACK Activity Prompt (p. 71)

> *"Robust sequence diagrams isolate failure domains with explicit alternative fragments and strict architectural layering."*

Dynamic Edge Cases & Semantics

- **Payment Gateway Timeout (>5s):**
  - Boundary `CheckoutUI` invokes Controller `submitPayment()`.
  - Controller coordinates external `PaymentGateway.processPayment()`.
  - `alt [Gateway Response < 5s]`: Normal confirmation; updates `Order` entity and dispatches order.
  - `else [Timeout > 5s]`: Controller triggers `cancelTransaction()`, logs audit trail, and returns `PaymentTimeoutError` with retry options.
- **Split Payment Workflow:**
  - Two-phase execution: First deduct `Wallet Balance`. If successful, charge balance to `PaymentGateway`. If gateway fails, compensating rollback refunds wallet.

PlantUML Delta & Quality Audit

```
UI -> Controller : submitOrder(cart)
activate Controller
Controller -> Gateway : charge(amount)
activate Gateway
alt #LightGreen Response within 5s
  Gateway --> Controller : 200 OK (txnId)
  Controller -> Order : markPaid()
  Controller --> UI : OrderSuccess
else #Pink Timeout > 5s
  Gateway --> Controller : [Timeout Error]
  Controller -> Gateway : voidTransaction()
  Controller --> UI : PaymentFailed(retryOption)
end
deactivate Gateway
```

- **[Pass] Layering Integrity:** UI communicates exclusively with Controller, never directly accessing DB or external Gateway.
- **[Pass] Failure Partitioning:** Mutually exclusive paths enclosed in `alt` with clear guard expressions.

Activity Solution 4: Activity Workflow Evolution

BACK Activity Prompt (p. 89)

> *"Workflow evolution demands rigorous token balancing across swimlanes, explicit loop termination, and clean branching."*

Process Solutions & Control Logic

- **Courier Decline & Re-dispatch Loop:**
  - Inside `|Dispatch Engine|` swimlane: query nearest couriers in a `repeat` loop.
  - Dispatch notification passes control token to `|Courier|` swimlane.
  - Decision diamond in Courier swimlane:
    ```
    if (Accept?) then (yes) -> Confirm; else (no) -> Log Decline; repeat while (Couriers Available)
    ```
    .
  - Exhaustion branch routes to `Activity Final Node` or escalation.
- **Customer Self-Pickup Bypass:**
  - Decision diamond in `|Platform|`:
    ```
    if (Order Type?) then (Delivery) -> Fork to Kitchen & Courier; else (Self-Pickup) -> Notify Kitchen only; |Customer| :Pick Up at Counter; -> Merge
    ```
    .

PlantUML Delta & Quality Audit

```
|Dispatch System|
repeat
  :Find Available Courier;
  |Courier|
  :Receive Dispatch Ping;
backward:Log Rejection;
repeat while (Courier accepts?) is (no)
->yes;
:Confirm Courier Assignment;
|Kitchen|
:Hand Off Sealed Package;
|Courier|
:Deliver to Customer;
stop
```

- **[Pass] Swimlane Ownership:** Every action node resides in its responsible actor/system lane.
- **[Pass] Loop Integrity:** `repeat...repeat while` constructs have definitive termination paths.
- **[Pass] Zero Dangling Tokens:** All terminating branches reach explicit `stop` nodes.

Activity Solution 5: State Machine Lifecycle Exceptions

BACK Activity Prompt (p. 109)

> *"State machine integrity rests on protecting lifecycle invariants: once physical resources are committed, rollback rules must be absolute."*

Lifecycle Exceptions & Invariant Rules

- **Courier Abandonment & Reassignment:**
  - `OutForDelivery → ReadyForPickup : courier_abandoned [retries < 3] / unassign()`
  - Re-triggers courier dispatch without forcing kitchen to re-cook meal.
- **Delivery Failed & Return to Store:**
  - `OutForDelivery → FailedDelivery : unreachable [wait >= 10m] / markFailed()`
  - `FailedDelivery → ReturnedToStore : return_package / recordDisposal()`
  - Terminal transition: `ReturnedToStore → [*]`
- **Strict Invariant Enforcement:**
  - Direct transition `OutForDelivery → Cancelled` is **forbidden** without compensation.

PlantUML Delta & Quality Audit

```
state OutForDelivery {
  [*] --> InTransit
}
OutForDelivery --> ReadyForPickup : courier_dropped \n [retries < 3] / reassign()
OutForDelivery --> FailedDelivery : unreachable \n [wait >= 10m] / logFailed()
FailedDelivery --> ReturnedToStore : return_meal \n / auditWaste()
ReturnedToStore --> [*]
```

- **[Pass] State Naming Discipline:** States represent passive conditions (`FailedDelivery`, `ReturnedToStore`), never active verb actions.
- **[Pass] Tripartite Syntax:** Transitions declare Event `trigger`, `[guard]`, and `/action`.
- **[Pass] Finite Lifecycles:** Exceptional flows lead to explicit terminal state `[*]`.

References & Further Reading

- **Foundational Textbooks & Standards:**
  - Sommerville, I. (2016). *Software Engineering* (10th ed.). Chapter 5: System Modeling. Pearson.
  - Booch, G., Rumbaugh, J., & Jacobson, I. (2005). *The Unified Modeling Language User Guide* (2nd ed.). Addison-Wesley.
  - Fowler, M. (2003). *UML Distilled: A Brief Guide to the Standard Object Modeling Language* (3rd ed.). Addison-Wesley.
  - Cockburn, A. (2000). *Writing Effective Use Cases*. Addison-Wesley.
  - Object Management Group (OMG). (2017). *OMG Unified Modeling Language (OMG UML) Specification*, Version 2.5.1.
- **Modern Declarative Diagramming & AI Tooling:**
  - PlantUML Open-Source Standard: plantuml.com
  - Mermaid.js JavaScript Diagramming Documentation: mermaid.js.org