Software Engineering

Chapter 6: User Experience (UX) Engineering & Interaction Design

From Cognitive Foundations & Quantitative Laws to Empirical Usability Engineering

Prof. Nien-Lin Hsueh

Department of Information Engineering and Computer Science

Feng Chia University

Chapter 6: Roadmap & Core Curriculum

Part 1: Foundations, Cognition, Laws & Research

- **6.1 Foundations of HCI, UX & Usability:** ISO 9241-210, UI vs. UX, Garrett's 5 Planes, and Nielsen's 5 usability dimensions.
- **6.2 Cognitive Psychology & Mental Models:** Model Human Processor, Norman's 7 Stages of Action, Gulfs, and Cognitive Load.
- **6.3 Quantitative Laws & Visual Perception:** Fitts's Law, Hick's Law, Tesler's Law, Gestalt grouping, and WCAG accessibility.
- **6.4 Human-Centered Design & User Research:** Double Diamond lifecycle, empirical research, Personas, JTBD, and Journey Maps.

Part 2: Architecture, Evaluation, Testing & AI UX

- **6.5 Information Architecture & Prototyping:** Taxonomies, Card Sorting, Tree Testing, Wireframing, and Atomic Design Systems.
- **6.6 Analytical Evaluation (Heuristics):** Heuristic Evaluation workflow, Nielsen's 10 Usability Heuristics, and Cognitive Walkthroughs.
- **6.7 Empirical Testing, Metrics & Ethics:** Think-Aloud testing, N=5 model, SUS score, HEART metrics, A/B testing, and Dark Patterns.
- **6.8 AI-Augmented UX & Synthesis:** AI for UX vs. UX for AI, interactive concept recap, self-assessment, and reference solutions.

6.1 Foundations of HCI, UX & Usability Engineering

> *"Design is not just what it looks like and feels like. Design is how it works."*
> *— Steve Jobs (Co-founder of Apple)*

What is User Experience (UX)? Formal Definitions

> ***ISO 9241-210 Definition:*** *User Experience is "a person's perceptions and responses resulting from the use and/or anticipated use of a system, product or service."*


1. HCI vs. UX vs. UI vs. CX


- **Human-Computer Interaction (HCI)**:
  - The academic discipline uniting computer science, cognitive psychology, and ergonomics to study interactive computing systems.
- **User Interface (UI — The Conduit)**:
  - The concrete visual, auditory, or tactile presentation layer (buttons, typography, layouts, voice prompts) through which users interact.
- **User Experience (UX — The Holistic Outcome)**:
  - The end-to-end cognitive, behavioral, and emotional journey before, during, and after interacting with the system.
- **Customer Experience (CX)**:
  - The broader organizational umbrella encompassing marketing, pricing, retail support, and multi-channel brand interactions.

2. Why UI Alone Cannot Save a Broken UX

- **[Case Study] The Food Delivery Checkout Paradox**:
  - Suppose a Food Delivery app features award-winning gradients and smooth 120Hz animations (**Great UI**).
  - However, it hides delivery surge fees until the final step, loses the cart when switching payment methods, and offers no cancel button (**Broken UX**).
- **Engineering Insight**:
  - **UI** is the saddle, the stirrups, and the reins; **UX** is whether the rider actually reaches their destination safely and comfortably.
  - A beautiful UI on top of a flawed task workflow only accelerates user frustration.

Visual Comparison: UI vs. UX in Real-World Products





Why UX Engineering Matters in Software Engineering

- **1. The Economic ROI of Early UX Engineering (Boehm's Law Applied to UX):**
  - Fixing a workflow or mental-model flaw during **UX Prototyping** costs **$1** (moving a wireframe box in 5 minutes).
  - Fixing that same flaw after **Backend API & UI Coding** costs **$10–$20**; fixing it after **Production Release** costs **$50–$100+** in rework, support tickets, and user churn.
- **2. Operational Efficiency & Error Reduction in Enterprise Systems:**
  - Every extra click or ambiguous label multiplied across 50,000 daily courier dispatches wastes thousands of labor hours and inflates operational error rates.
- **3. Safety-Critical Systems: When Poor UX Becomes Fatal:**
  - **[Case 1] Therac-25 Radiation Therapy (1985–1987)**: Cryptic error codes (`Malfunction 54`) and mode-confusion UI contributed to lethal radiation overdoses.
  - **[Case 2] Hawaii Ballistic Missile False Alarm (2018)**: Ambiguous dropdown links (`PACOM (CDW) - STATE ONLY` vs. `Test Missile Alert`) with no confirmation dialog triggered statewide panic.

Structural Frameworks: Garrett's 5 Planes & Morville's Honeycomb

> ***Architectural View of UX:*** *UX is built from the* ***bottom up****—from abstract business/user strategy to concrete visual pixels.*

1. Jesse James Garrett's 5 Planes of UX (Bottom → Top)

1. **Surface Plane (Concrete)**: Visual sensory design—color palettes, typography, icons, and micro-animations.
2. **Skeleton Plane**: Interface layout, wireframes, navigation bars, and information presentation placement.
3. **Structure Plane**: **Interaction Design (IxD)** (system behavior over time) and **Information Architecture (IA)** (taxonomy).
4. **Scope Plane**: Functional specifications (feature set) and content requirements (*aligns with SRS!*).
5. **Strategy Plane (Abstract)**: User needs (Personas/JTBD) + Business objectives (ROI/KPIs).

2. Peter Morville's 7 Facets (The UX Honeycomb)

- **Useful**: Does the system solve a real, meaningful problem?
- **Usable**: Is the interface easy and intuitive to operate?
- **Findable**: Can users locate features and content when needed?
- **Credible**: Do users trust the system's security and accuracy?
- **Accessible**: Can users with diverse abilities (visual, motor, auditory, cognitive) use it effectively?
- **Desirable**: Does the aesthetic and brand evoke positive emotion?
- **Valuable**: Does it deliver measurable value to users and sponsors?

ISO 9241-11 & Jakob Nielsen's 5 Quality Components of Usability

> ***ISO 9241-11 Definition:*** *Usability is the extent to which a system can be used by* ***specified users*** *to achieve* ***specified goals*** *with* ***effectiveness, efficiency, and satisfaction*** *in a* ***specified context of use****.*

Nielsen's 5 Usability Dimensions	Core Engineering Question	Empirical Measurement Metric (Quantitative)
1. Learnability	How easily can a **first-time novice** accomplish basic tasks upon first encounter?	First-attempt **Task Completion Rate (%)** & time to complete onboarding without assistance.
2. Efficiency	Once users have learned the system, **how quickly** can they perform frequent tasks?	**Time-on-Task (seconds)**, number of clicks/keystrokes, or orders processed per minute.
3. Memorability	After returning from a hiatus (weeks/months), how easily can users **re-establish proficiency**?	Task completion time & error count after a **30-day non-use interval**.
4. Errors	How many errors do users make, how **severe** are they, and how easily can they **recover**?	**Error Rate per Task**, frequency of critical dead-ends, and mean time to recover.
5. Satisfaction	How pleasant, comfortable, and frustration-free is the subjective experience?	Post-study standardized scales: **SUS (0–100)**, **CSAT**, or **Net Promoter Score (NPS)**.

The Aesthetic-Usability Effect & Norman's 3 Levels of Emotional Design

> ***Empirical Finding (Kurosu & Kashimura, 1995):*** *Users perceive* ***aesthetically pleasing interfaces as more usable*** *than they objectively are—up to a critical threshold!*

1. The Aesthetic-Usability Effect

- **Origin (ATM Study, 1995)**:
  - Researchers tested 26 layouts of an ATM with identical functionality and number of buttons.
  - Layouts rated higher in visual beauty were consistently rated significantly **easier to use** (`r = 0.589`), even when actual task speed was identical.
- **Engineering Implications & Limits**:
  - **[Benefit]**: Visual polish builds initial trust and makes users more tolerant of **minor** usability hiccups.
  - **[Boundary Limit]**: Aesthetics **cannot** mask **severe** task failures (e.g., broken checkout or lost data).

2. Don Norman's 3 Levels of Emotional Processing

- **1. Visceral Level (Pre-conscious / First Impression)**:
  - Instantaneous (`< 50ms`) gut reaction to visual symmetry, color harmony, typography, and tactile feel.
- **2. Behavioral Level (In-Use / Functional Usability)**:
  - Subconscious experience while performing tasks—governed by **usability, feedback speed, and feel of control**.
- **3. Reflective Level (Post-Use / Conscious Meaning)**:
  - Intellectual rationalization, personal identity, brand pride, and whether the user recommends the product to peers.

Concept Check Question 1 (CCQ 1)

A hospital deploys a new Emergency Room Triage System. First-time nursing interns complete training in 10 minutes (**high novice learnability**), but veteran ER nurses require **14 mouse clicks across 5 modal dialogs** to register a single critical patient during mass-casualty surges. According to **Jakob Nielsen's 5 Quality Components of Usability**, which specific usability dimension is severely compromised?

- **A. Memorability**, because veteran nurses must re-learn the triage taxonomy after returning from annual leave.
- **B. Efficiency**, because expert users face excessive interaction steps when executing high-frequency tasks.
- **C. Learnability**, because first-time nursing interns cannot complete basic triage registration without manuals.
- **D. Visceral Aesthetics**, because the modal dialogs lack modern gradient styling and smooth micro-animations.

6.2 Cognitive Psychology & Human Information Processing

> *"What information consumes is rather obvious: it consumes the attention of its recipients. Hence a wealth of information creates a poverty of attention."*
> *— Herbert A. Simon (Nobel Laureate & Turing Award Winner)*

The Model Human Processor (MHP) & Perceptual Response Thresholds

> ***Foundational HCI Model (Card, Moran & Newell, 1983):*** *Models the human user as three coupled subsystems—**Perceptual**, **Cognitive**, and **Motor**—each with measurable cycle times.*

1. The 3 Subsystems of MHP

- **Perceptual System (`τ_p ≈ 100 ms`)**:
  - Sensory buffers (Visual Iconic Store & Auditory Echoic Store) that capture raw stimuli from the screen.
  - Events occurring within `< 100 ms` fuse into a single instantaneous perception (perceived causality).
- **Cognitive System (`τ_c ≈ 70 ms`)**:
  - Compares perceived symbols in **Working Memory** against **Long-Term Memory** schemas to make decisions.
- **Motor System (`τ_m ≈ 70 ms`)**:
  - Translates cognitive intentions into physical muscle movements (finger tap, mouse drag, eye saccade).

2. Jakob Nielsen's 3 Response-Time Thresholds

- `0.1 Second (100 ms)` **— Instantaneous Manipulation**:
  - The user feels they are **directly manipulating** the object (e.g., button press state, scrolling, cursor tracking).
- `1.0 Second (1,000 ms)` **— Uninterrupted Flow of Thought**:
  - The user notices a slight delay, but their **train of thought remains unbroken** without needing a progress bar.
- `10 Seconds (10,000 ms)` **— Maximum Attention Span**:
  - Beyond `10s`, working memory context breaks down; the UI **must** provide a **percent-done progress indicator**, time estimate, and a safe **Cancel / Background** option!

Don Norman's 7 Stages of Action & The Two Gulfs

> ***Core Interaction Cycle (Don Norman, The Design of Everyday Things):*** *Every human interaction bridges the gap between* ***Internal Psychological Goals*** *and* ***External Physical System State****.*

1. The 7 Stages of Action Cycle

- **Goal (1)**: Formulate the high-level objective ("*Order dinner for $15*").
- **Execution Bridge (Stages 2 → 4)**:
  - **2. Plan**: Choose an action strategy.
  - **3. Specify**: Determine the exact sequence of UI inputs.
  - **4. Perform**: Execute physical clicks/taps on the world.
- **Evaluation Bridge (Stages 5 → 7)**:
  - **5. Perceive**: Sense what changed on the screen.
  - **6. Interpret**: Decode the meaning of that visual change.
  - **7. Compare**: Verify if the new system state matches the **Goal**.

2. The Two Gulfs of Interaction Failure

- **The Gulf of Execution ("*How do I make it do what I want?*")**:
  - The gap between the user's **intentions** and the **actions allowed** by the interface.
  - *Bridged by*: Clear **Signifiers**, **Affordances**, **Natural Mapping**, and **Constraints**.
- **The Gulf of Evaluation ("*What happened? Did it work?*")**:
  - The effort required to perceive and interpret the **system's current state** after acting.
  - *Bridged by*: Immediate **Status Feedback (`< 100ms`)**, clear **Conceptual Models**, and informative state indicators.

Affordances, Signifiers, Mappings & Feedback

> ***Bridging the Gulfs:*** *Don Norman refined his framework to distinguish* ***Affordances*** *(what actions are possible) from* ***Signifiers*** *(the perceptible clues showing where and how to act).* ”

Core Design Concept	Formal Definition in HCI / UX	Software UI Engineering Application
1. Affordance	The relationship between a physical/digital object and a user that defines **what actions are possible**.	A scrollable viewport *affords* vertical panning; a text input box *affords* typing characters.
2. Signifier	Any **perceptible visual, auditory, or tactile clue** that communicates *where* and *how* an action should be taken.	An underlined blue label, a raised button shadow, a `[Search]` icon, or a visible scrollbar thumb.
3. Natural Mapping	The spatial or logical relationship between **controls and their effects** in the world.	Pressing the **Right Arrow** `→` advances to the next slide; dragging a slider up increases volume.
4. Feedback	Communicating the **results of an action** back to the user immediately and clearly.	Button ripple (`< 100ms`), toast confirmation (`"Added to Cart"`), or inline red validation text.
5. Constraints	Limiting possible actions (Physical, Cultural, Semantic, Logical) to **prevent invalid states**.	Disabling the `"Place Order"` button until a valid delivery address and payment method are selected.

Case Study: Norman's Door & Natural Mapping in Controls



Mental Models vs. Conceptual Models (The System Image)

> ***Norman's Triad of Models:*** *Designers* ***never talk directly to users****; they communicate exclusively through the* ***System Image*** *(the UI, feedback, behavior, and documentation).*

1. The Three Models in Software Systems

- **1. The Designer's Conceptual Model**:
  - How the software architect and developer conceive the system (e.g., Git commits as a Directed Acyclic Graph of SHA-1 blobs and trees; file deletion as unlinking an inode pointer).
- **2. The User's Mental Model**:
  - The internal belief system formed in the user's mind based on prior real-world experience (e.g., folders on a desktop, a shopping cart, a trash can).
- **3. The System Image (The Bridge)**:
  - Everything the user actually interacts with: UI layout, metaphors, labels, feedback, and error messages.

2. Engineering Consequences of Model Mismatch

- **[Anti-Pattern] Implementation Model Leak**:
  - Exposing database foreign-key stack traces (`ORA-02292: integrity constraint violated`) or internal microservices jargon directly to end users.
- **[Case Study] Cloud Sync vs. Local Save**:
  - If a web editor auto-saves to the cloud every keystroke, but displays a prominent `"Save"` icon thatActually downloads a `.json` backup, users with a traditional desktop Mental Model will repeatedly click `"Save"` and clutter their disk!
- **Design Rule**: Align the **System Image** with the **User's Mental Model**, hiding internal implementation mechanics.

Working Memory, Attention & Cognitive Load Theory

> ***Sweller's Cognitive Load Theory (1988):*** *Human* ***Working Memory*** *has severely limited capacity (`4 ± 1` active chunks, decaying within `~20 seconds`); exceeding it triggers cognitive overload and task abandonment.*

1. The 3 Types of Cognitive Load (John Sweller)

- **Intrinsic Cognitive Load (Task Inherent)**:
  - The unavoidable mental effort required by the domain task itself (e.g., filing corporate taxes vs. ordering a coffee).
  - *Managed by*: Breaking complex workflows into **progressive step-by-step wizards**.
- **Extraneous Cognitive Load (Bad UI Overhead)**:
  - Wasted mental effort caused by **poor interface design**—visual clutter, inconsistent navigation, cryptic jargon, or forcing users to memorize codes across screens.
  - *Engineering Goal*: **Eliminate Extraneous Load to near zero!**
- **Germane Cognitive Load (Schema Building)**:
  - Productive mental effort invested in learning reusable patterns and mastering the system's conceptual model.

2. Memory & Attention Constraints in UI Design

- **Working Memory Capacity (Miller `7 ± 2` → Cowan `4 ± 1`)**:
  - Modern cognitive research (Nelson Cowan, 2001) shows humans actively hold only **3 to 5 chunks** in working memory while multitasking.
- **Recognition Over Recall**:
  - Showing recent addresses, visual menu thumbnails, and search autocomplete (`Recognition`) requires far less cognitive load than typing from memory (`Recall`).
- **Inattentional & Change Blindness**:
  - Users tunnel-focus on their goal; subtle status changes placed outside their **foveal fixation zone** (`~2°` visual angle) go completely unnoticed!

Concept Check Question 2 (CCQ 2)

In a cloud deployment dashboard, an engineer clicks the **"Deploy to Production"** button. Because the frontend lacks a loading spinner, toast message, or state change for 8 seconds, the engineer assumes the click failed and clicks the button three more times, triggering conflicting deployments. In **Don Norman's Action Cycle**, which specific breakdown caused this error?

- **A.** A wide **Gulf of Execution**, because the engineer could not locate the deployment button on the screen.
- **B.** Excess **Intrinsic Cognitive Load**, because cloud deployment inherently requires memorizing Linux kernel flags.
- **C.** A wide **Gulf of Evaluation**, because the interface failed to provide immediate feedback on the system's new state.
- **D.** A **Natural Mapping** violation, because the deployment button was positioned on the right side of the toolbar.

6.3 Quantitative Laws of Interaction & Visual Perception

> *"Design is a science as much as an art: human motor movement, choice reaction time, and visual grouping obey mathematical laws."*

Mathematical Laws of Pointing & Choice: Fitts's Law & Hick's Law

> ***Predictive HCI Modeling:*** *Human motor targeting and decision-making speed follow* ***logarithmic information-theoretic equations*** *(bits per second).*

1. Fitts's Law (1954 — Motor Targeting Speed)

- **Shannon Formulation (MacKenzie, 1992)**:
  - $MT = a + b \cdot \log_2(D / W + 1)$
  - MT: Movement Time; D: Distance to target; W: Width (size) of target along the axis of motion.
  - $\log_2(D / W + 1)$: **Index of Difficulty (ID, in bits)**.
- **4 Core UI Engineering Applications**:
  1. **Enlarge Primary Targets ($\uparrow W$)**: Make frequent CTAs at least 44×44 px (Apple iOS) / 48×48 dp (Android).
  2. **Minimize Travel Distance ($\downarrow D$)**: Context menus (right-click) pop up at $D \approx 0$ right under the cursor!
  3. **Infinite Screen Edges ("Magic Corners")**: macOS top menu bar & Windows bottom-left Start corner have $W = \infty$ because the cursor is stopped by the screen bezel.
  4. **Separate Destructive Actions**: Never place "Delete Account" 2px next to "Save"!

2. Hick-Hyman Law (1952 — Choice Reaction Time)

- **Mathematical Formulation**:
  - $RT = a + b \cdot \log_2(n + 1)$ (for n equally probable choices)
  - $RT = a + b \cdot \Sigma\, p_i \log_2(1 / p_i + 1)$ (general entropy form)
- **Core UI Engineering Applications**:
  1. **Progressive Disclosure**: Do not dump 40 settings onto one screen; display the **3–5 primary options** and tuck advanced settings behind "Advanced...".
  2. **Categorized & Scannable Grouping**: Group long lists into clear semantic categories so users scan k headers instead of reading n unsorted items.
  3. **Smart Defaults & Highlighted Recommendations**: Highlighting a [Recommended] plan reduces choice entropy (H), slashing decision paralysis!

Behavioral & Workflow Laws: Jakob's, Tesler's, Postel's & Doherty

> ***Systems Laws of UX:*** *Great interaction design leverages* ***existing user habits****, absorbs* ***accidental complexity*** *into code, and accepts* ***flexible human input****.*

1. Jakob's Law & The Doherty Threshold

- **Jakob's Law of Internet User Experience (Jakob Nielsen)**:
  - "*Users spend most of their time on* ***other sites****. This means that users prefer your site to work the same way as all the other sites they already know.*"
  - **Design Rule**: Follow established platform conventions (top-right shopping cart `[Cart]`, top-left logo home link, standard `Ctrl+Z` undo) so users spend **0% cognitive load** learning navigation!
- **The Doherty Threshold (`< 400 ms`, Walter Doherty, 1982)**:
  - Productivity soars when computer and human interact at a pace `< 400 ms`, ensuring neither waits on the other.
  - *Technique*: Use **Optimistic UI Updates** & **Skeleton Screens** to keep perceived response under `400 ms`.

2. Tesler's Law & Postel's Law in UI Engineering

- **Tesler's Law (Law of Conservation of Complexity)**:
  - Every application has an inherent amount of irreducible complexity. The only question is: **Who bears it—the User or the Software Engineer?**
  - *Example*: Instead of forcing users to type City, State, and County manually, the engineer spends 20 lines of code auto-filling them from a 5-digit **Postal/ZIP Code**!
- **Postel's Law (The Robustness Principle)**:
  - "*Be conservative in what you send, be liberal in what you accept.*"
  - *Example*: Accept credit card or phone numbers whether the user types `0912-345-678`, `(0912) 345 678`, or `0912345678`—strip formatting characters in code instead of throwing a red syntax error!

Gestalt Principles of Visual Perception in UI Layout

> ***Gestalt Psychology ("The whole is other than the sum of its parts"):*** *The human visual cortex automatically groups screen elements into coherent structures based on* ***6 perceptual laws.***

Gestalt Principle	Perceptual Mechanism	UI / Frontend Engineering Application
1. Proximity	Elements placed **closer together** are perceived as belonging to the same functional group.	Keep a form **Label** `4px` above its **Input Box**, but leave `20px` **margin** before the next field—zero border lines needed!
2. Similarity	Elements sharing visual attributes (**color, shape, size, font**) are perceived as having similar behavior.	Style all primary actions in solid brand blue (`#2563eb`) and all secondary actions in subtle outline gray.
3. Common Region (Enclosure)	Elements enclosed within a **visible boundary or shaded card** are perceived as a unified unit.	Group an order card's restaurant title, item list, and `"Track Order"` button inside a subtle `.card` container.
4. Continuity	The human eye naturally follows **smooth, aligned lines and curves** rather than abrupt jagged jumps.	Align form labels and inputs along a **single clean vertical left axis** to accelerate visual scanning.
5. Closure	The brain automatically fills in missing gaps to perceive **complete, familiar shapes**.	Partially clipping the 4th card at the right edge of a horizontal carousel naturally signals "*Scroll right for more!*"
6. Figure-Ground	The visual system instantly separates the **foreground focal object (Figure)** from the **background (Ground)**.	Dimming the background (`rgba(0,0,0,0.5)` backdrop blur) behind a **Modal Dialog** focuses 100% attention on the modal.

Visual Hierarchy, Typography, Contrast & Accessibility (WCAG 2.2)

> ***Inclusive Engineering Mandate:*** *Accessibility (**a11y**) is not an optional edge case—roughly **15% of the global population** lives with visual, motor, auditory, or cognitive disabilities (plus situational impairments like bright sunlight!).*

1. Visual Hierarchy & Scanning Patterns

- **F-Pattern & Z-Pattern Eye Tracking (NN/g)**:
  - Users **do not read** interfaces word-for-word; they **scan** in an **F-shaped pattern** (text-heavy lists) or **Z-shaped pattern** (landing pages).
- **3 Pillars of Scannable Typography**:
  - **Size & Weight Scale**: Clear ratio between `H1` (`28–32px`), `H2` (`20–24px`), Body (`16px`), and Caption (`13–14px`).
  - **Line Length (Measure)**: Keep body text paragraphs between **50 and 75 characters per line** (`max-width: 65ch`).
  - **Whitespace (Negative Space)**: Active breathing room that prevents visual crowding and isolates focal points.

2. W3C WCAG 2.1 / 2.2 Accessibility (POUR)

- **The 4 POUR Principles**: **P**erceivable, **O**perable, **U**nderstandable, **R**obust.
- **Concrete Frontend Engineering Requirements**:
  1. **Color Contrast (Level AA)**: Minimum `4.5 : 1` luminance contrast ratio for normal text (`3.0 : 1` for large text `>= 18pt` or UI icons).
  2. **Never Rely on Color Alone**: ~8% of males have red-green color deficiency (Deuteranopia/Protanopia). Pair red error borders with **an icon (`[!]`) + text message**!
  3. **Keyboard & Screen Reader Support**: Full `Tab` focus ring order, semantic HTML (`<button>`, `<nav>`, `<main>`), and `aria-label` attributes.

Peer Discussion 6.3: Diagnosing a High-Friction Checkout Screen

UX Engineering Audit: Refactoring the Food Delivery Checkout UI (4 Mins)

- **Scenario:** A junior developer built the checkout screen for our **Food Delivery App**, and cart abandonment jumped to **62%**. An inspection reveals four design flaws:
  1. The **"Place Order"** button is a tiny `24×18 px` text link at the top-left corner of the mobile screen, right next to **"Empty Entire Cart"** (`2px` gap).
  2. The payment selector displays all **28 supported banks and wallets** in a single unsorted radio-button list.
  3. The phone number field rejects `0912-345-678` with a red popup: "*Error: Numeric digits only! Re-enter all 8 address fields.*"
  4. Required fields are marked *only* by changing their border color from green to red (`#ef4444` on `#e5e7eb` gray background, contrast `2.1:1`).
- **Discussion Tasks:**
  - **Q1.** Identify which specific **Law of UX or Accessibility Standard** (Fitts's, Hick's, Tesler's/Postel's, WCAG) is violated by each of the 4 flaws (`#1` to `#4`).
  - **Q2.** Propose the concrete **UI refactoring fix** for each flaw!



Concept Check Question 3 (CCQ 3)

According to the Shannon formulation of **Fitts's Law** ($MT = a + b \cdot \log_2(D / W + 1)$), why do desktop operating systems place critical global menus (such as the macOS Menu Bar or the Windows Start button) flush against the **extreme edges or corners of the screen**?

- **A.** Screen edges reduce the number of menu items n, lowering cognitive choice reaction time under Hick's Law.
- **B.** The monitor bezel blocks the cursor from overshooting, giving edge targets an effectively infinite width W.
- **C.** Placing menus at the screen edge increases luminance contrast ratios to satisfy WCAG 2.2 Level AAA standards.
- **D.** Peripheral vision processes corner pixels in $< 20ms$, bypassing the Model Human Processor's motor stage.

6.4 The Human-Centered Design (HCD) Process & User Research

> *"You are not the user! Every assumption you make about how people will use your software is a hypothesis waiting to be tested."*
> *— Jakob Nielsen & Don Norman*

The Double Diamond Model & ISO 9241-210 Iterative Lifecycle

> ***Design Before Solutioning:*** *Engineers must first* ***design the right thing*** *(Problem Space) before* ***designing the thing right*** *(Solution Space).*


1. The Double Diamond (4 Phases: Diverge ↔ Converge)

- **Diamond 1 — Understanding the Problem Space**:
  1. **Discover (Diverge <)**: Conduct field observations, contextual inquiry, and user interviews to uncover real pain points.
  2. **Define (Converge >)**: Synthesize findings into Personas, Journey Maps, and a focused **Problem Statement (HMW — How Might We)**.
- **Diamond 2 — Engineering the Solution Space**:
  3. **Develop (Diverge <)**: Brainstorm alternative IA flows, sketch low-fidelity wireframes, and explore interactive prototypes.
  4. **Deliver (Converge >)**: Run usability tests, refine high-fidelity designs, validate metrics, and hand off to agile sprints.

2. ISO 9241-210 Core Principles of HCD

- **1. Explicit Understanding of Users, Tasks & Environments**:
  - Grounded in empirical observation, not stakeholder guesswork.
- **2. Users Involved Throughout Design & Development**:
  - Continuous feedback from early paper sketches to beta releases.
- **3. Driven & Refined by User-Centered Evaluation**:
  - Prototypes are tested early and often to catch mental-model flaws.
- **4. Iterative Process**:
  - Every evaluation round feeds insights back into requirements and design until usability benchmarks are met.

Visual Overview: The Iterative UX Engineering Lifecycle



Empirical User Research: The 2×2 Landscape (NN/g)

> ***Triangulation Principle:*** *What users* ***say they do*** *in interviews often differs from what they* ***actually do*** *in the wild! Combine* ***Attitudinal*** *and* ***Behavioral*** *methods.*

Research Dimension	Qualitative ("*Why & How to Fix*") Small Sample (`N = 5–12`), Deep Insights	Quantitative ("*How Many & How Much*") Large Sample (`N = 100–10,000+`), Statistical
Behavioral *(What Users Actually Do)*	• **Contextual Inquiry (Field Observation)** • **Moderated Usability Testing (Think-Aloud)** *Insight*: Uncovers workarounds, environmental distractions, and mental-model breakdowns.	• **Product Telemetry & Clickstream Funnel Analytics** • **Controlled A/B Testing & Eye-Tracking Heatmaps** *Insight*: Pinpoints exact drop-off rates (`62% at step 3`) and task completion times at scale.
Attitudinal *(What Users Say & Feel)*	• **Semi-Structured User Interviews** • **Diary Studies & Focus Groups** *Insight*: Reveals underlying motivations, domain goals, anxieties, and unmet emotional needs.	• **Standardized Questionnaires (SUS, SUPR-Q, NPS)** • **Large-Scale Intercept Surveys & Kano Surveys** *Insight*: Benchmarks subjective satisfaction and feature priority across customer segments.

Synthesizing Research: Affinity Diagrams, Personas & JTBD

> ***Data-Driven Synthesis:*** *Raw interview transcripts must be distilled into actionable engineering models—**Personas** (Who) and **Jobs-to-be-Done** (Why).*

1. Affinity Diagramming & Evidence-Based Personas

- **Affinity Diagramming (KJ Method)**:
  - Clustering hundreds of field observation notes bottom-up into thematic insight groups (`Pain Points`, `Workarounds`, `Trust Barriers`).
- **Alan Cooper's Goal-Directed Personas (*The Inmates Are Running the Asylum*)**:
  - An archetype representing a distinct **behavioral pattern cluster** derived from real user research (never made-up marketing stereotypes!).
  - **Core Anatomy of an Engineering Persona**:
    1. **Context & Tech Proficiency** (e.g., "*Rider Wei, operates one-handed on a scooter in rain*").
    2. **End Goals & Motivations** (maximize deliveries/hour safely).
    3. **Pain Points & Frustrations** (small tap targets, GPS drift).

2. Jobs-to-be-Done (JTBD — Clayton Christensen)

- **Focus on the "Job", Not Demographic Labels**:
  - People don't buy products because of their age bracket; they "*hire*" a product to get a specific **Job** done in a specific situation.
- **Standard JTBD Statement Template**:
  - **When** `[Situation / Context]`,
  - **I want to** `[Motivation / Action]`,
  - **So I can** `[Expected Outcome / Value]`.
- **Food Delivery JTBD Example**:
  - *"When I am working overtime with 4 colleagues at 8 PM (**Situation**), I want to share a single group cart link where everyone picks their own meal in 3 minutes (**Action**), so I can order dinner without collecting cash or passing my phone around (**Outcome**)."*

Modeling Context & Tasks: Journey Maps & Task Analysis (HTA)

> ***End-to-End Temporal Modeling:*** *While Personas capture user traits,* ***Customer Journey Maps*** *and* ***Hierarchical Task Analysis (HTA)*** *model actions, emotions, and pain points* ***over time****.*

1. Customer Journey Map (Macro Experience Flow)

- **Horizontal Stages (Timeline)**:
  - `Discovery` → `Onboarding` → `Ordering` → `Waiting` → `Delivery & Support`.
- **Vertical Swimlanes Across Each Stage**:
  1. **User Actions & Touchpoints**: Mobile app, SMS, push notifications, physical handoff.
  2. **Thoughts & Questions**: "*Is the restaurant still open? Where is my rider?*"
  3. **Emotional Curve (`Delight (+) ↔ Frustration (−)`)**: Visualizes emotional peaks and **valleys of anxiety** (e.g., the 25-minute "black box" wait after paying!).
  4. **Pain Points & Engineering Opportunities**: Adding a live kitchen status tracker (`Preparing → Packing → Picked Up`) directly heals the post-payment anxiety valley!

2. Hierarchical Task Analysis (HTA — Micro Task Tree)

- **Origin (Annett & Duncan, 1967)**:
  - Decomposes a high-level user **Goal (`0`)** into a tree of **Sub-tasks (`1, 2, 3...`)** and execution **Plans** (specifying sequence, selection, or loops).
- **Food Delivery HTA Example**:
  - **Goal `0`**: Complete Group Meal Order
    - `1.` Create Group Session & Share Link
    - `2.` Collect Member Selections (`Plan 2`: wait until all members click "*Ready*" OR host clicks "*Lock Cart*")
    - `3.` Select Split-Bill vs. Host-Pays Mode
    - `4.` Authorize Payment (`3.1` Verify address → `3.2` Confirm total → `3.3` Authenticate biometrics)
- **Engineering Value**: Directly maps to **UI screen flows, UML Activity Diagrams, and test scenarios**!

Bridging UX Artifacts to Software Requirements (SRS)

> ***Closing the SE ↔ UX Gap:*** *Every UX research artifact translates directly into a formal* ***Software Engineering Requirements or Design Specification*** *artifact!*

UX Engineering Artifact (Ch 06)	Corresponding SE / UML Artifact (Ch 03–05)	Concrete Traceability Example in Food Delivery
1. Evidence-Based Persona *(e.g., Rider Wei — Scooter Context)*	**UML Actor & Non-Functional Requirements (NFRs)** in SRS	**Usability NFR-01**: Courier Order Accept/Decline screen must have tap targets `>= 56×56 dp` and contrast `>= 7:1` for one-handed outdoor glare use.
2. Jobs-to-be-Done (JTBD)	**Agile Epic & User Stories** (`As a... I want... So that...`)	**US-204**: *As an office team host, I want to generate a shareable group-cart link with a $25/person cap so colleagues can pick meals within budget.*
3. Customer Journey Map *(Post-Payment Anxiety Valley)*	**Functional Requirements & Event-Driven Architecture**	**FR-108**: System shall push real-time `OrderStateChanged` WebSocket updates within `< 2s` of kitchen tablet and courier status transitions.
4. Hierarchical Task Analysis (HTA)	**UML Use Case Scenarios, Activity Diagrams & Acceptance Tests**	Maps HTA `Plan 2` branches (`All Members Ready` vs. `Host Timeout Override`) directly into **Given-When-Then (BDD)** acceptance criteria.

6.5 Information Architecture, Wireframing & Prototyping

> *"If a user can't find it, it doesn't exist."*
> *— Steve Krug (Author of Don't Make Me Think)*

Information Architecture (IA): Organization, Labeling & Navigation

> ***Information Architecture (Rosenfeld, Morville & Arango — The "Polar Bear Book"):*** *The structural design of shared information environments to maximize* ***findability*** *and* ***understandability****.*

1. The 4 Core Systems of Information Architecture

- **1. Organization Systems (How we categorize)**:
  - **LATCH Principle (Wurman)**: Information can only be organized by **L**ocation, **A**lphabet, **T**ime, **C**ategory, or **H**ierarchy (Magnitude).
  - **Structural Topologies**: **Hierarchy (Tree)**, **Sequential (Linear Wizard)**, **Matrix (Multi-faceted Filter)**, and **Organic (Hypertext Graph)**.
- **2. Labeling Systems (How we name things)**:
  - Using user-centric vocabulary (`"Track My Order"`) instead of internal DB table names (`"Query Dispatch_Log_V2"`).

2. Navigation & Search Systems

- **3. Navigation Systems (How users move through space)**:
  - **Global Navigation**: Persistent top/bottom bar present across the entire app (`Home | Search | Orders | Account`).
  - **Local Navigation**: Sub-navigation within a specific category (e.g., Restaurant Menu tabs: `Popular | Mains | Drinks`).
  - **Contextual & Breadcrumb Navigation**: `"Where am I?"* trail (`Home > Taiwanese > Din Tai Fung > XiaoLongBao`) + inline related links.
- **4. Search Systems**:
  - Autocomplete, typo tolerance, and faceted filtering when repositories grow too large to browse.

Empirical IA Validation: Card Sorting & Tree Testing

> ***Testing Navigation Before Drawing Screens:*** *Never let backend database schemas dictate your UI menu hierarchy—validate user mental models empirically with* ***Card Sorting*** *and* ***Tree Testing****!*

1. Card Sorting (Generative — Building the Taxonomy)

- **How It Works**:
  - Write 30–60 content items or app features on index cards (or digital tools like OptimalSort). Ask `15–20` users to group them into piles that make sense to them.
- **Two Variants**:
  - **Open Card Sort**: Users create their own groupings AND invent their own **category names** (*discovers how users naturally classify and label concepts*).
  - **Closed Card Sort**: Users sort cards into **pre-defined top-level categories** (*tests whether existing menu labels are unambiguous*).
- **Analysis**: **Dendrograms** & **Similarity Matrices** reveal consensus clusters vs. orphan items.

2. Tree Testing (Evaluative — "Reverse Card Sorting")

- **How It Works**:
  - Strip away all visual styling, layout, and graphics—present **only the pure text menu hierarchy (the "Tree")**.
  - Give users realistic findability tasks: "*Where would you go to request a refund for a missing drink?*"
- **Quantitative IA Metrics**:
  1. **Success Rate (%)**: Did they reach the correct leaf node?
  2. **Directness (%)**: Did they navigate straight there on the **first path without backtracking** (`First-Click Accuracy`)?
  3. **Time Spent**: Seconds required to locate the item.

The Prototyping Fidelity Spectrum: Sketch → Wireframe → Prototype

> ***Bill Buxton's Dual Mandate (Sketching User Experiences):*** *Early low-fidelity sketches focus on* ***"Getting the Right Design"*** *(exploring alternatives cheaply); late high-fidelity prototypes focus on* ***"Getting the Design Right"*** *(refining micro-interactions).*

Fidelity Tier	Visual & Interactive Characteristics	Primary Engineering Purpose & Cost to Change
1. Low-Fidelity (Lo-Fi) *Paper Sketches & Balsamiq*	Hand-drawn boxes, rough lines, zero color/fonts; static or wizard-of-oz paper flipping.	**Divergent Ideation (`Cost: Minutes`)**: Explore 5 radically different workflows in 30 mins. Encourages honest user critique (*nobody hesitates to criticize a pencil sketch!*).
2. Mid-Fidelity (Mid-Fi) *Grayscale Wireframes*	Strict grid layout, real hierarchy & copy labels, grayscale boxes (`[Image]`), no brand colors.	**Skeleton & IA Alignment (`Cost: Hours`)**: Lock down screen density, Gestalt grouping, content priority, and edge-case states (`Empty`, `Loading`, `Error`).
3. High-Fidelity (Hi-Fi) *Interactive Figma / Code Prototype*	Pixel-accurate UI tokens, real food photos, clickable state transitions, and micro-animations.	**Usability Testing & Dev Handoff (`Cost: Days`)**: Validate realistic task flows, visual contrast, and exact component specs prior to sprint implementation.

Design Systems, Atomic Design & UI Engineering Consistency

> ***Bridging UX Design & Frontend Architecture (Brad Frost, 2013):*** *A* ***Design System*** *is not a static PDF style guide; it is a* ***versioned, single-source-of-truth component library*** *shared between Figma and production code (React/Vue/iOS/Android).*

1. Brad Frost's 5-Level Atomic Design Hierarchy

1. **Atoms (Primitives)**: Indivisible UI building blocks—`<Button>`, `<Input>`, `<Icon>`, `<Badge>`, plus **Design Tokens** (`--color-primary-600`, `--space-4`).
2. **Molecules (Simple Compounds)**: A small functional unit combining 2–3 atoms—e.g., a **`<SearchBar>`** (`<Label>` + `<Input>` + `<Button>`).
3. **Organisms (Complex Sections)**: Self-contained interface regions—e.g., **`<RestaurantCard>`** or **`<GlobalNavbar>`**.
4. **Templates (Page Skeletons)**: Content-agnostic layout grids assembling organisms into a page structure.
5. **Pages (Concrete Instances)**: Templates populated with real runtime data (`"Din Tai Fung Menu"`), used to test edge cases (e.g., 80-character dish names!).

2. Why Software Engineers Love Design Systems

- **1. Enforces Nielsen's Heuristic #4 (Consistency)**:
  - Guarantees every modal, toast, and primary button behaves identically across 50 microservices and frontend squads.
- **2. Design Tokens as the Contract (`JSON → CSS/Swift/Kotlin`)**:
  - Semantic tokens (`color.bg.danger.subtle`, `spacing.md = 16px`) enable instant **Dark Mode** switching and WCAG contrast compliance from a single JSON source!
- **3. Built-In Accessibility (a11y Once, Everywhere)**:
  - Baking keyboard `Tab` focus traps and `aria-*` attributes into the base `<DialogAtom>` automatically makes every modal in the enterprise accessible!

Peer Discussion 6.5: IA & Wireframe States for Group Ordering

UX Architecture Exercise: Designing the "Office Group Order" Flow (4 Mins)

- **Scenario:** You are designing the **Group Order (Shared Cart)** feature for our Food Delivery App based on the JTBD from Section 6.4 (*Host invites 4 colleagues via link; budget cap $25/person*).
- **1. Information Architecture & Labeling:**
  - Where in the app's hierarchy should `"Start Group Order"` live so users find it on their **first click** (Restaurant Menu header vs. Account Settings vs. Checkout Screen)?
- **2. Mid-Fidelity Wireframe & The 4 UI States:**
  - Sketch or specify the **Host's Shared Cart Wireframe**, explicitly addressing the **4 Mandatory UI States**:
    - **Empty State**: Host just created the link; 0 colleagues have joined yet. What signifiers/actions are shown?
    - **Loading / Active State**: 3 colleagues have added items; 1 colleague is still "*Choosing...*".
    - **Error / Edge State**: A colleague adds a $32 item exceeding the $25 cap, OR abandons their phone without clicking "*I'm Ready*". How does the UI prevent the Host from getting stuck?



Concept Check Question 4 (CCQ 4)

Before designing any visual screens for a banking portal, a UX engineer presents 30 participants with a **plain-text collapsible menu hierarchy** (stripped of all graphics, colors, and page layouts) and asks: "*Where would you click to freeze a lost debit card?*" Which specific UX evaluation method is being conducted, and what does it measure?

- **A. Open Card Sorting**, which discovers how users invent new category names from unorganized feature cards.
- **B. Tree Testing**, which evaluates menu findability and first-click accuracy within an existing hierarchy.
- **C. A/B Split Testing**, which measures live production conversion rates between two visual button styles.
- **D. Atomic Design Auditing**, which verifies that UI molecules inherit CSS tokens from primitive atoms.

6.6 Analytical Evaluation: Nielsen's 10 Usability Heuristics

> *"Heuristic evaluation is a discount usability engineering method: 3 to 5 independent evaluators can identify 75% to 80% of major usability problems before a single user test is run."*
> *— Jakob Nielsen (1994)*

Heuristic Evaluation: Protocol, Evaluators & Severity Rating

> ***Why Multiple Evaluators? (Nielsen & Landauer, 1993):*** *A single evaluator finds only* `~35%` *of usability problems; aggregating* ***3 to 5 independent evaluators*** *uncovers* `75%–80%` *of issues at minimal cost!*

1. The 4-Step Heuristic Evaluation Protocol

1. **Briefing & Task Scenarios**: Evaluators receive the target Persona, domain context, and core task flows to inspect.
2. **Independent Inspection (Crucial Rule!)**:
   - Each of the **3–5 evaluators** inspects the interface **alone** (two passes: Pass 1 for overall flow, Pass 2 auditing each screen against the 10 Heuristics) to prevent groupthink bias!
3. **Aggregation & Debriefing**: Combine duplicate findings into a master defect log, citing the specific **Heuristic (** `#1–#10` **)** violated.
4. **Severity Rating & Action Plan**: Score each defect (`0–4`) to prioritize engineering sprint fixes.

2. Nielsen's 0–4 Usability Severity Scale

- **Severity = f (** `Frequency` **,** `Impact` **,** `Persistence` **)**:
  - `0` **— Not a Problem**: Disagreement; no UX impact.
  - `1` **— Cosmetic Problem**: Fix only if extra time remains in the sprint (e.g., `2px` icon misalignment).
  - `2` **— Minor Usability Problem**: Low priority; causes brief hesitation but users recover quickly.
  - `3` **— Major Usability Problem**: High priority; causes significant confusion, delay, or repeated errors.
  - `4` **— Usability Catastrophe**: **Blocker!** Must be fixed before release (causes data loss, double-charging, or task abandonment).


Nielsen's Heuristics #1 – #3: Status, Real World & User Control

> ***Cluster 1 (Transparency & Agency):*** *Keep the user informed, speak their language, and always provide an* ***emergency exit****.*


Heuristic (`#1 – #3`)	Core Principle & Cognitive Rationale	Software UI Engineering Examples (`[Good]` vs. `[Violation]`)
#1 Visibility of System Status	Always keep users informed about **what is going on**, through appropriate feedback within a reasonable time (`100ms / 1s / 10s`).	**[Good]**: Live Food Delivery steps (`Order Confirmed → Kitchen Preparing → Rider 3 mins away`) + upload `%` bar. **[Violation]**: Clicking `"Pay"` shows a frozen button for 9 seconds.
#2 Match Between System & Real World	Speak the **users' language** (words, phrases, familiar concepts) rather than system-oriented engineering terms; follow real-world conventions.	**[Good]**: Checkout uses a familiar receipt layout and says "*Card declined by bank*". **[Violation]**: Throwing `"Error 0x80040E14: RPC Payment Shard NullPointer"`.
#3 User Control & Freedom	Users often choose functions by mistake and need a clearly marked **"Emergency Exit"** to leave the unwanted state without an extended dialogue.	**[Good]**: Gmail's `"Message Sent – [Undo] (5s)"` toast; Food Delivery `"Cancel Order (Free within 60s)"` button. **[Violation]**: Accidentally tapping an item immediately charges the card with no cancel/back option.

Visual Examples: Visibility of System Status & Real-World Mapping


1. DETERMINISTIC PROGRESS



2. MULTI-STEP STEPPER



3. LIVE STATE & SYNC



Nielsen's Heuristics #4 – #7: Consistency, Errors, Memory & Speed

> ***Cluster 2 (Cognitive Efficiency & Error Prevention):*** *Leverage conventions, prevent* ***Slips & Mistakes*** *before they happen, minimize memory load, and provide* ***Accelerators*** *for experts.*

Heuristic (`#4 – #7`)	Core Principle & Cognitive Rationale	Software UI Engineering Examples (`[Good]` vs. `[Violation]`)
#4 Consistency & Standards	Users should not have to wonder whether different words, situations, or actions mean the same thing (**Internal & External Consistency**).	**[Good]**: Using standard platform navigation and consistent button terminology (`"Place Order"` everywhere). **[Violation]**: Calling the cart `"Basket"` on screen 1, `"Tray"` on screen 2, and `"Bag"` on screen 3.
#5 Error Prevention	Better than a good error message is a **careful design that prevents a problem from occurring** in the first place (eliminate **Slips** & **Mistakes**).	**[Good]**: Graying out past calendar dates; Gmail warning "*You wrote 'attached' but attached no file.*" **[Violation]**: Letting users type `"Feb 31"` in a plain text box and failing only after form submission.
#6 Recognition Rather Than Recall	Minimize user memory load by making **objects, actions, and options visible**; users should not have to remember info from one screen to another.	**[Good]**: Showing recent delivery addresses, dish thumbnails, and inline promo-code selector. **[Violation]**: Forcing users to memorize a 10-digit order ID from Page A to type into Support Page B.

Nielsen's Heuristics #8 – #10: Minimalism, Recovery & Help

> ***Cluster 3 (Signal-to-Noise & Graceful Recovery):*** *Every extra unit of irrelevant information competes with relevant units and* ***diminishes their relative visibility****.*

Heuristic (`#8 – #10`)	Core Principle & Cognitive Rationale	Software UI Engineering Examples (`[Good]` vs. `[Violation]`)
#8 Aesthetic & Minimalist Design	Interfaces should **not contain irrelevant or rarely needed information**; maximize the **Signal-to-Noise Ratio** (Edward Tufte's *Data-Ink Ratio*).	**[Good]**: Restaurant card shows only Name, Photo, Rating (`4.8★`), ETA (`25 min`), and Delivery Fee. **[Violation]**: Cluttering every menu card with 14 promotional badges, legal disclaimers, and full address strings.
#9 Help Users Recognize, Diagnose & Recover from Errors	Error messages must be expressed in **plain language** (no error codes), precisely **indicate the problem**, and **constructively suggest a solution**.	**[Good]**: "*Card expired (08/25). Please update your expiration date or choose Apple Pay.*" **[Violation]**: A red banner saying simply `"Invalid Input (Code 422)"` without highlighting which field failed.
#10 Help & Documentation	Even though it is best if the system can be used without documentation, provide **searchable, task-focused, concise contextual help**.	**[Good]**: Inline `[?]` tooltip explaining "*Service Fee covers packaging & insurance*" right at checkout. **[Violation]**: Forcing users to download a 120-page PDF manual to learn how to split a bill.

Cognitive Walkthrough: Task-Focused Analytical Inspection

> ***Complementing Heuristic Evaluation (Wharton, Rieman, Lewis & Polson, 1994):*** *While Heuristic Evaluation audits a UI broadly against 10 principles, a* ***Cognitive Walkthrough*** *steps through a specific* ***task action-by-action*** *to evaluate* ***first-time Learnability****.*

1. The 4 Standard Questions Asked at Every Action Step

- For each micro-step `k` in a novice user's task sequence, evaluators ask **4 cognitive questions** (mapped to Norman's Action Cycle!):
  1. **Goal Formation**: Will the user realistically **try to achieve the right effect** at this step?
  2. **Visibility (Affordance)**: Will the user **notice that the correct UI control is available** on the screen?
  3. **Label Association (Signifier)**: Will the user **associate the control's label/icon with their intended goal**?
  4. **Feedback Evaluation**: After performing the action, will the user **see clear feedback confirming progress** toward their goal?

2. Heuristic Evaluation vs. Cognitive Walkthrough

Comparison Dimension	Heuristic Evaluation	Cognitive Walkthrough
Inspection Scope	Holistic screen-by-screen audit against **10 Heuristics**.	Step-by-step trace of **specific task flows**.
Primary Focus	Overall usability (`#1-#10`), consistency & error handling.	**First-time Learnability** & exploratory discovery.
Theoretical Root	Empirical usability principles (Nielsen, 1994).	**CE+ Theory of Exploratory Learning** & Norman's Action

Concept Check Question 5 (CCQ 5)

When a user attempts to register an account on a web portal, typing an already-registered email and clicking **"Submit"** clears the entire 12-field form and displays a banner reading: `"SQLSTATE[23505]: Unique violation on key idx_users_email"`. Which pair of **Jakob Nielsen's 10 Usability Heuristics** is most directly violated by this behavior?

- **A. #7 Flexibility and Efficiency of Use** and **#8 Aesthetic and Minimalist Design**.
- **B. #2 Match Between System and Real World** and **#9 Help Users Recognize, Diagnose, and Recover from Errors**.
- **C. #1 Visibility of System Status** and **#10 Help and Documentation**.
- **D. #4 Consistency and Standards** and **#6 Recognition Rather Than Recall**.

6.7 Empirical Usability Testing, Metrics & Ethical UX

> *"Testing one user early in the project is better than testing 50 near the end."*
> *— Steve Krug (Rocket Surgery Made Easy)*

Formative vs. Summative Testing & The Think-Aloud Protocol

> ***Why Test with `N = 5` Users Per Iteration? (Nielsen & Landauer, 1993):*** *The proportion of usability problems discovered by `n` users follows `P = 1 - (1 - L)^n` (where average problem discoverability `L ≈ 0.31`). Testing **5 users uncovers** `~85%` of usability flaws!*

1. Formative vs. Summative Usability Testing

- **Formative Evaluation (*During Design — "Find & Fix"*)**:
  - Conducted iteratively on **wireframes and prototypes** before code is locked.
  - **Sample Size**: **5 users per iteration** (`3 rounds × 5 users = 15 users` catches far more bugs than `1 round × 15 users`!).
  - **Focus**: Qualitative behavioral diagnosis (*Why did they get stuck?*).
- **Summative Evaluation (*Post-Build — "Benchmark & Compare"*)**:
  - Conducted on working builds or against competitors.
  - **Sample Size**: `20–30+` **users** for tight confidence intervals on quantitative metrics (`Task Success %`, `Time-on-Task`, `SUS`).

2. The Think-Aloud Protocol (Ericsson & Simon, 1984)

- **How Concurrent Think-Aloud Works**:
  - Ask participants to complete realistic scenario tasks while **continuously verbalizing their thoughts, expectations, and confusion out loud** ("*I'm looking for a way to split the bill... I'm clicking this icon because it looks like two people...*").
- **3 Strict Moderator Rules (Preventing Bias)**:
  1. **Test the System, Never the User**: Explicitly reassure participants "*We are testing the app, not you; any confusion is the software's fault.*"
  2. **Never Lead the Witness**: Never ask "*Do you see the green button at the top?*" Ask open prompts: "*What are you thinking right now?*"
  3. **Observe Actions Over Polite Compliments**: Users often say "*It's nice!*" out of politeness after failing a task for 4 minutes!

Quantitative Usability Metrics & Standardized Questionnaires

> ***Objective UX Benchmarking:*** *Combine* ***Behavioral Task Metrics*** *(what happened during the test) with* ***Standardized Psychometric Scales*** *(validated post-task / post-test questionnaires).*

Metric Category	Specific Engineering Metric / Scale	Formula, Benchmark Threshold & Interpretation
1. Effectiveness *(Behavioral)*	**Task Completion Rate (Success %)** & **Error Count**	`Success % = (Completed Accurately / Total Attempts) × 100%`. *Target*: `>= 80%–90%` for consumer apps; `100%` for safety-critical flows.
2. Efficiency *(Behavioral)*	**Time-on-Task (s)** & **Lostness Metric (`L`, Smith 1996)**	`L = sqrt((N/S − 1)² + (R/N − 1)²)` (`R`=min nodes, `S`=total visited, `N`=unique visited). *Threshold*: `L < 0.4` indicates clear navigation; `L > 0.5` indicates severe user disorientation!
3. Post-Task Ease *(Attitudinal)*	**SEQ (Single Ease Question)** & **NASA-TLX (Cognitive Workload)**	**SEQ**: 1-item 7-point rating right after each task ("*Overall, how difficult or easy was this task?*", Benchmark `>= 5.5 / 7`). **NASA-TLX**: 6-dimension workload index.
4. Overall Usability *(Post-Study Scale)*	**SUS (System Usability Scale — John Brooke, 1986)**	10 alternating positive/negative items (`1–5` Likert), scored `0 to 100` (percentile rank, *not* a percentage!). *Industry Historical Average*: `68` (`>= 80.3` is Grade **A** / Top 10%; `< 50` is Grade **F**).

Large-Scale Production Experiments: A/B Testing & Google HEART

> ***Continuous UX Telemetry:*** *After launch, product engineering teams pair* ***Controlled Online Experiments (A/B Testing)*** *with* ***Google's HEART Framework*** *(Kerry Rodden, Hilary Hutchinson & Xin Fu, 2010).*

1. Controlled A/B Testing & Guardrail Metrics

- **Randomized Controlled Trial (RCT) in Production**:
  - Randomly split live traffic (`50% Control A` vs. `50% Variant B` via feature flags) to test a specific **UX Hypothesis**.
- **Statistical Rigor & Guardrail Metrics**:
  - Require pre-calculated **Sample Size (Statistical Power `1 - β >= 80%`)** and `p < 0.05` significance (never "peek and stop early"!).
  - **Guardrail Metrics**: When testing if a larger checkout button increases conversion (`Primary Metric`), monitor **Cancel/Refund Rate** and **Page Latency** (`Guardrail Metrics`) to ensure you didn't just cause accidental clicks!

2. Google's HEART Framework + Goals-Signals-Metrics

- **5 UX Quality Dimensions at Scale (`H-E-A-R-T`)**:
  - **H — Happiness**: Subjective satisfaction (`SUS`, in-app CSAT, App Store rating).
  - **E — Engagement**: Depth & frequency of voluntary interaction (`orders/week`, active sessions).
  - **A — Adoption**: New users adopting the product or a new feature (`% using Group Order within 14 days`).
  - **R — Retention**: Cohort survival rate (`D7 / D30 / D90` returning active users; inverse of **Churn**).
  - **T — Task Success**: Behavioral efficiency & error rates in telemetry (`Search-to-Cart %`, checkout completion time).

Ethical UX Engineering: Dark Patterns vs. Transparent Design

> ***ACM Code of Ethics & EU Digital Services Act (DSA):*** *Software engineers have a professional and legal duty to reject* ***Deceptive Design (Dark Patterns)*** *that exploit human cognitive biases against the user's best interest.*

Dark Pattern (Harry Brignull, 2010)	Deceptive Cognitive Manipulation Mechanism	Ethical & Legal UX Engineering Alternative
1. Roach Motel *(Asymmetric Friction)*	Signing up for a monthly subscription takes **1 tap**, but canceling requires calling a phone hotline during business hours and navigating 8 retention screens.	**Symmetric Click-to-Cancel (FTC Rule)**: Make subscription cancellation just as fast, visible, and self-service as sign-up.
2. Confirmshaming *(Emotional Manipulation)*	Phrasing the decline button to guilt or insult the user: "*No thanks, I hate saving money and prefer paying full price.*"	**Neutral, Respectful Labeling**: Use clear, objective choices: `"Apply Annual Pass"` vs. `"Continue with Standard Order"`.
3. Sneak into Basket & Drip Pricing	Automatically pre-checking optional insurance/tips in the cart, or hiding mandatory `"Platform + Service Fees"` until the final payment click.	**Upfront All-In Price Transparency & Opt-In Consent**: Display total estimated fees upfront; require explicit user **Opt-In** (never pre-checked boxes!).
4. Misdirection & Disguised Cancel	Making `"Keep My Subscription"` a giant bright blue button while hiding `"Confirm Cancellation"` as tiny low-contrast gray text (`Fitts + Visual Hierarchy abuse`).	**Honest Visual Hierarchy**: Style primary confirmation and secondary back actions clearly without inverting button semantics to trick users.

Peer Discussion 6.7: Designing a Usability Test Plan & Ethical Audit

Empirical UX Lab: Testing & Auditing "FoodPass" Subscription (4 Mins)

- **Scenario:** The business team wants to launch **FoodPass** (a $9.99/month free-delivery membership) inside our Food Delivery App.
- **Part 1 — Formative & Summative Usability Test Plan:**
  - You have **2 weeks** before launch. How many participants (`N`) will you recruit for your **Formative Think-Aloud** wireframe rounds vs. your final **Summative Benchmark**?
  - Write **1 concrete, non-leading Task Scenario** (without using the exact button label `"Manage FoodPass"`) to test whether users can pause or cancel their membership, and list **2 Quantitative Metrics** you will record.
- **Part 2 — Dark Pattern Ethical Audit:**
  - A PM proposes: *(a)* Pre-checking `"Add FoodPass ($9.99/mo)"` at checkout by default, and *(b)* Requiring users to go through 5 screens where `"Keep FoodPass"` is bright green and `"Cancel"` is a tiny gray link.
  - **Task:** Name the **2 Dark Patterns** present and rewrite the flow to achieve high ethical conversion without deception!



6.8 AI-Augmented UX Engineering, Synthesis & References

> *"In the era of Generative AI, the paradigm shifts twice: we use AI to accelerate UX workflows (AI for UX), and we invent new interaction paradigms for probabilistic AI systems (UX for AI)."*

The Dual Paradigm: "AI for UX" vs. "UX for AI" (Human-AI Interaction)

> ***Deterministic GUI vs. Probabilistic AI:*** *Traditional GUIs are* ***100% deterministic*** *(`Click Button A → State B`); Generative AI interfaces are* ***probabilistic, latency-variable, and fallible****, requiring new UX engineering patterns!*

1. AI for UX (Accelerating the HCD Lifecycle)

- **Discover & Define**:
  - Using LLMs to transcribe interviews, cluster **Affinity Diagrams** with verbatim citations, and spot themes across 10,000 support tickets.
- **Develop (Ideation & Wireframing)**:
  - Rapidly generating multi-variant wireframe layouts, realistic domain microcopy (eliminating `"Lorem ipsum"`), and WCAG-compliant color palettes.
- **Evaluate (Synthetic Pre-Inspection)**:
  - Running automated **Heuristic & WCAG pre-audits** before human usability testing (*Warning: Synthetic AI personas never replace real human observation!*).

2. UX for AI (Designing Human-AI Interaction — HAI)

- **Microsoft's 18 HAI Guidelines (Amershi et al., CHI 2019)**:
  1. **Calibrate Trust Initially (`G1–G2`)**: Make clear *what the AI can do* and *how well it can do it* (avoid false anthropomorphism).
  2. **Hybrid Intent Input (Prompt + GUI Controls)**: Pure chat boxes have a wide **Gulf of Execution** ("Blank Canvas Paralysis"); pair natural language with **clickable prompt chips & parameter sliders**!
  3. **Explainability & Source Grounding (`G11`)**: Show *why* the AI recommended a dish or route, with clickable citations/provenance.
  4. **Graceful Hallucination Recovery & Human-in-the-Loop**: Stream tokens progressively (`< 400ms` first token), show confidence levels, and require **explicit human confirmation** (`Diff Preview + Undo`) before executing destructive actions!

Conceptual Recap: Fill-in-the-Blank Quiz (Part 1)

Word Bank: Gulf of Execution | Gulf of Evaluation | Fitts's Law | Extraneous Cognitive Load

1. In Don Norman's 7 Stages of Action, the gap between a user's intention and the actions allowed by the interface ("*How do I work this?*") is the [_____].
2. When a user clicks a button and cannot tell whether the system registered the action due to missing status feedback, they face a wide [_____].
3. In John Sweller's Cognitive Load Theory, unnecessary mental effort caused by cluttered layouts, inconsistent navigation, or cryptic jargon is called [_____].
4. The logarithmic predictive model $MT = a + b \cdot \log_2(D / W + 1)$ governing pointing time as a function of target distance and size is [_____].

Interactive Mode: Click any blank slot to reveal or hide the answer!

Conceptual Recap: Fill-in-the-Blank Quiz (Part 2)

Word Bank: Tree Testing | Recognition Rather Than Recall | Think-Aloud Protocol | Roach Motel

5. The empirical IA evaluation method ("reverse card sorting") that tests findability and first-click accuracy using a plain-text menu hierarchy is [_____].
6. Showing recent delivery addresses and visual autocomplete suggestions instead of forcing users to memorize codes applies Nielsen's Heuristic #6: [_____].
7. The formative usability testing method in which participants continuously verbalize their thoughts and expectations while performing tasks is the [_____].
8. A deceptive Dark Pattern that makes subscribing take 1 click while burying cancellation behind phone calls and 8 retention screens is a [_____].

Interactive Mode: Click any blank slot to reveal or hide the answer!

Core Curriculum Synthesis & Classic Academic Literature

Section	Core UX / HCI Models & Frameworks	Golden Engineering Takeaway
6.1 Foundations	**ISO 9241-210 / 9241-11**, Garrett's 5 Planes, **Nielsen's 5 Dimensions**	UX is built bottom-up (`Strategy → Surface`); quantify Learnability, Efficiency, Memorability, Errors & Satisfaction.
6.2 Cognition	**Model Human Processor (`100ms/1s/10s`)**, **7 Stages & 2 Gulfs**, **Cognitive Load**	Narrow the **Gulfs of Execution & Evaluation**; align the **System Image** with the **User's Mental Model**; cut extraneous load.
6.3 Laws & a11y	**Fitts's Law**, **Hick's Law**, **Tesler/Postel**, **Gestalt**, **WCAG 2.2 (`4.5:1`)**	Maximize target `W`, minimize `D` & choice entropy `n`; absorb complexity in code; enforce `4.5:1` contrast & non-color cues.
6.4 HCD Research	**Double Diamond**, **2×2 Research Matrix**, **Personas**, **JTBD**, **Journey Maps & HTA**	"*You are not the user!*" Triangulate behavioral & attitudinal research; trace Personas/JTBD/HTA directly to the **SRS**.
6.5 IA & Prototyping	**LATCH**, **Card Sorting & Tree Testing**, **Lo-Fi → Hi-Fi**, **Atomic Design**	Validate taxonomy findability first; sketch Lo-Fi to get the *right design*; scale UI via **Atoms → Organisms** & Tokens.
6.6 Heuristics	**Nielsen's 10 Usability Heuristics (`0–4` Severity)**, **Cognitive Walkthrough**	Run 3–5 independent inspections (`~80%` bug discovery); prevent Slips & Mistakes; audit novice steps via `Q1–Q4`.
6.7 Testing & Ethics	**Think-Aloud (`N = 5`)**, **SUS (`68` avg)**, **HEART & A/B**, **Anti-Dark Patterns**	Test 5 users per round; benchmark via **SUS & HEART**; reject **Roach Motel / Confirmshaming** Dark Patterns.
6.8 AI & UX	**AI for UX** vs. **UX for AI (Microsoft 18 HAI Guidelines)**	Pair natural language with GUI controls, ground sources, and require **Human-in-the-Loop Preview + Undo**.

- **Essential References:** Don Norman (*The Design of Everyday Things*); Jakob Nielsen (*Usability Engineering*); Stuart Card, Thomas Moran & Allen Newell (*The Psychology of HCI*); Steve Krug (*Don't Make Me Think*); Jesse James Garrett (*The Elements of User Experience*); ISO 9241-210 & W3C WCAG 2.2

Appendix A: Suggested Answers for CCQ 1 – CCQ 5

Question	Ans	Core UX / HCI Principle & Concise Engineering Rationale
CCQ 1 (Sec 6.1) *Usability Dimensions*	**B**	**Efficiency vs. Learnability (Nielsen's 5 Components)**: Novice interns learn in 10 mins (high *Learnability*), but requiring 14 clicks across 5 modals for experienced daily nurses bottlenecks expert task speed (**Efficiency**).
CCQ 2 (Sec 6.2) *Norman's Two Gulfs*	**C**	**Wide Gulf of Evaluation**: The engineer executed the click easily (narrow *Gulf of Execution*), but the lack of immediate visual feedback (`< 100ms` button state / `< 1s` spinner) prevented perceiving the new system state, causing duplicate clicks.
CCQ 3 (Sec 6.3) *Fitts's Law (`D` & `W`)*	**B**	**Infinite Target Width (`W = ∞`) at Screen Edges**: Under `MT = a + b · log2(D/W + 1)`, pinning global menus flush against screen edges/corners uses the display boundary to stop cursor overshoot, dramatically lowering the Index of Difficulty.
CCQ 4 (Sec 6.5) *IA Empirical Testing*	**B**	**Tree Testing (Reverse Card Sorting)**: Evaluates an existing text hierarchy stripped of visual layout to measure **Findability Success Rate (%)** and **First-Click Directness (%)** prior to wireframing.
CCQ 5 (Sec 6.6) *Nielsen's 10 Heuristics*	**B**	**#2 Match Real World & #9 Error Recovery**: Exposing raw SQL error codes (`SQLSTATE[23505]`) violates **#2** (system-oriented jargon); wiping out 12 user-typed fields with no constructive fix violates **#9** (and **#5 Error Prevention**).

Appendix B: Suggested Solutions for Peer Discussions 6.3, 6.5 & 6.7

1. Solution — Peer Discussion 6.3 (Checkout Audit) & 6.5 (Group IA)

- **Peer Discussion 6.3 (4 Checkout Flaws & Fixes)**:
  1. **Fitts's Law + Heuristic #5**: Enlarge `"Place Order"` to full-width `52px` bottom bar (`↑ W`, `↓ D` in thumb zone); move `"Empty Cart"` into a top-right overflow menu with confirmation.
  2. **Hick-Hyman Law**: Replace 28 flat radio buttons with the user's **last-used payment method** as default + `3` top categories (`Card | Apple/Google Pay | Bank`).
  3. **Postel's & Tesler's Laws + Heuristic #9**: Auto-strip `-`/`()` spaces in JS; preserve all 8 address fields on validation error!
  4. **WCAG 2.2 Level AA (`1.4.1` & `1.4.3`)**: Increase contrast to `>= 4.5:1` (`#b91c1c` on `#fef2f2`) and add `[!] Required` icon + text below each missing field.
- **Peer Discussion 6.5 (Group Order IA & 4 States)**:
  - **IA Placement**: Place `"[+ Group Order]"` button directly in the **Restaurant Menu Header** (matches user mental model when browsing a restaurant).
  - **Edge State Override**: Show per-member status (`Adding...` vs. `Ready ✓`), auto-cap items at `$25` with inline split-pay option, and give Host a **"Lock Cart & Checkout Now"** override so 1 away coworker never blocks the order!

2. Solution — Peer Discussion 6.7 (Usability Test & Ethics)

- **Part 1 — Test Plan & Non-Leading Scenario**:
  - **Sample Plan**: Run **2 formative rounds × 5 users (`N = 10`)** using **Think-Aloud** on Figma prototypes to fix flows, then **1 summative round (`N = 25`)** to benchmark.
  - **Non-Leading Prompt**: "*Imagine you subscribed to FoodPass last month, but you are traveling abroad for 3 weeks and want to stop being billed next month. Show me what you would do.*" (Never say the word `"Manage"` or `"Cancel"`!).
  - **Metrics**: **Task Completion Rate (%)**, **Time-on-Task (s)**, **First-Click Accuracy (%)**, and post-task **SEQ / SUS**.
- **Part 2 — Dark Pattern Audit & Ethical Redesign**:
  - **Violations**: `(a)` **Sneak into Basket** (pre-checked opt-out box); `(b)` **Roach Motel + Visual Misdirection** (5 retention screens with inverted button colors).
  - **Ethical Fix**: Show transparent math ("*Save $4.50 on this order with FoodPass — [Add Free Trial]*" explicit Opt-In) and provide a symmetric **1-Click Pause / Cancel** button in Account Settings!