

Software Engineering

Lecture 4: Requirements Engineering

Prof. Nien-Lin Hsueh

Department of Information Engineering and Computer Science
Feng Chia University

Focus Questions

- What is **Requirements Engineering (RE)** and why is fixing requirements errors early so critical?
- What is the fundamental difference between **User Requirements** and **System Requirements**?
- How do **Functional**, **Non-Functional**, and **Domain Requirements** differ?
- What are the 4 main stages of the **Requirements Elicitation & Analysis** process?
- How can non-functional goals be transformed into **testable, verifiable metrics**?
- How are requirements **validated** and **managed** when changes occur?
- How can **Artificial Intelligence (LLMs & Generative AI)** assist in Requirements Engineering?

The Exponential Cost of Ambiguity



Fixing a requirements error after software delivery can cost up to 100 times more than catching it during the initial blueprint phase. A late change forces cascading redesigns of architecture, database schemas, code, and test suites.

What is Requirements Engineering?

- **Definition:**

The systematic process of establishing the services that a customer requires from a system and the operational/developmental constraints under which it operates.

- **Dual Function of Requirements:**

- Contract Bidding:** High-level abstract statements open to contractor interpretation.
- Contract Basis:** Detailed functional specification defining exact system implementation.

The Ultimate High-Stakes Translation



Requirements Engineering (RE) bridges the gap between informal customer language and formal technical specifications.

The Dual Legal Function

Contract Bidding

High-level, abstract statements that leave room for contractor interpretation and negotiation.

Contract Basis

The exhaustive, highly detailed functional specification that dictates the exact system implementation.

User vs. System Requirements

- **User Requirements:**

- High-level statements in natural language and intuitive diagrams outlining system services and operational constraints. Written primarily for **customers and end-users**.

- **System Requirements:**

- Structured document setting out detailed descriptions of system functions, services, and operational constraints. Forms the basis of the **contract between client and contractor**.

User vs. System Requirements Example

User Requirement Definition:

The Mentcare system shall generate monthly management reports showing the cost of drugs prescribed by each clinic during that month.

System Requirements Specification (Detailed):

- 1. On the last working day of each month, a summary of drugs prescribed, cost, and clinics shall be generated.*
- 2. The report shall be automatically generated after 17:30 on the last working day.*
- 3. Access to all cost reports shall be restricted to authorized users on an access control list.*

The Audience & Scope Matrix

Dimension	User Requirements	System Requirements
Target Audience	Customers, End-Users, non-technical stakeholders.	Developers, System Architects, Client technical leads.
Level of Abstraction	High-level system services and operational constraints.	Granular, exhaustive functional and operational descriptions.
Format / Language	Natural language with intuitive, broad diagrams.	Structured documents, formal technical notation, strict schema.
Example (Mentcare)	Generate monthly reports of clinic drug costs.	At 17:30 on the last working day, generate an access-controlled summary of drugs, costs, and clinics.

System Stakeholders

- **Definition:** Any person or organization affected by the system who has a legitimate interest.
- **Types of Stakeholders:**
 - **End Users:** Patients, Doctors, Nurses, Receptionists.
 - **System Managers:** Clinic Managers, IT Staff.
 - **System Owners:** Hospital Board, Health Authority.
 - **External Stakeholders:** Medical Ethics Board, Government Regulators.

Types of Requirements

1. Functional Requirements:

- Statements of specific services the system should provide, how it reacts to particular inputs, or what it must *not* do.

2. Non-Functional Requirements:

- Constraints on system services or functions (e.g., performance, response time, security, reliability).

3. Domain Requirements:

- Constraints derived directly from the operational domain (e.g., medical safety regulations, banking standards).

The Triad of Requirements



Functional

Definition

Specific services provided, reactions to inputs, or behaviors to avoid.

Failure Impact

A specific feature breaks.



Non-Functional

Definition

Broad constraints on system services (performance, security, reliability).

Failure Impact

The entire system becomes unusable.



Domain

Definition

Constraints derived directly from the operational environment.

Real-World Example

Medical safety regulations or HIPAA compliance dictating data handling, regardless of user requests.

Functional Requirements: Challenges


- **Requirements Imprecision:**

- Ambiguous natural language requirements cause misunderstandings.
- *Example:* "Search appointment list" — does it mean across *all* clinics (user intent) or within an *individual* clinic (developer assumption)?

- **Completeness vs. Consistency:**

- **Complete:** Includes descriptions of all required facilities.
- **Consistent:** Contains no conflicting or contradictory specifications.
- *In practice, complete and consistent requirements are extremely difficult to achieve for complex systems.*

The Imprecision Trap



Core Principle: Achieving both Completeness (all facilities described) and Consistency (no conflicting specs) is nearly impossible in complex systems using only natural language.

Non-Functional Requirements (NFR)


- **System-Wide Impact:**

- NFRs often apply to the system as a **whole** rather than individual features.
- Failing to meet an NFR can render the entire system useless (e.g., a slow or insecure medical database).

- **Architectural Influence:**

- Performance NFRs dictate module communication patterns; security NFRs introduce authentication infrastructure.

The Structural Base of NFRs




If a functional block falls out, you lose a feature.

If a foundational NFR pillar crumbles (e.g., the database is fundamentally insecure or unbearably slow), the entire system collapses, rendering every functional block above it useless.

NFRs dictate the **core module communication patterns**.

Classification of Non-Functional Requirements



Goals vs. Verifiable NFRs

- **Goal (Imprecise Intention):**

"The system should be easy to use by medical staff and minimize user errors."


- **Verifiable NFR (Testable Metric):**

"Medical staff shall be able to use all core functions after 4 hours of training. After training, the average user error rate shall not exceed 2 errors per hour of use."

- **Goal-Question-Metric (GQM) Approach:**

- Define **Goals** → Ask key **Questions** → Specify measurable **Metrics**.

Forging Metrics from Ambiguity



Goal: The system needs to be fast.

Question: How quickly must a user see data after clicking?

Metric: Screen refresh time < 2 seconds for 95% of queries.

The Metric Taxonomy

	Speed: Transactions/sec
	Reliability: Mean Time Between Failures (MTBF)
	Portability: Number of supported OS platforms

Metrics for Specifying NFRs

Property	Measurable Metric Examples
Speed	Transactions/second, User response time (<2s), Screen refresh time.
Size	Mbytes storage, Memory footprint.
Ease of Use	Training time (hours), Number of help screens required.
Reliability	Mean Time Between Failures (MTBF), Availability percentage (99.9%).
Robustness	Time to restart after failure, Probability of data corruption.
Portability	Percentage of target-dependent statements, Number of supported OS platforms.

Concept Check Question 1

Which category of requirements specifies constraints on system performance, reliability, and security across the system as a whole?

- **A.** Functional Requirements
- **B.** User Requirements
- **C.** Non-Functional Requirements
- **D.** Domain Requirements



Concept Check Question 1: Answer

Which category of requirements specifies constraints on system performance, reliability, and security across the system as a whole?


- **Correct Answer: C**
- **Explanation:** Non-functional requirements specify constraints (timing, reliability, security, compliance) that apply to the system overall.




The Requirements Engineering Process

- **Four Interleaved Activities:**
 - i. **Elicitation & Analysis:** Discovering requirements from stakeholders.
 - ii. **Specification:** Documenting requirements formally.
 - iii. **Validation:** Checking that requirements meet customer needs.
 - iv. **Management:** Managing requirements change over time.

The Engine of Clarity



Requirements Elicitation Loop




Elicitation Techniques

- **Interviews:**
 - **Closed Interviews:** Fixed set of pre-determined questions.
 - **Open Interviews:** Exploratory discussions around user goals and workflows.
- **Ethnography (User Observation):**
 - Observing users in their actual working environment to discover implicit/unspoken requirements and operational nuances.
- **Stories & Scenarios:**
 - Real-life narrative examples detailing initial state, normal flow, exception handling, and concurrent tasks.

Use Case Diagram Notation (UML)

- **Actors:** External entities (users or systems) interacting with the application.
- **Use Cases:** Ellipses representing high-level functional interactions.
- **System Boundary:** Box defining scope of the system.

Anatomy of a Use Case



UML (Unified Modeling Language) forces early structural thinking, moving elicitation away from messy narrative paragraphs.

Requirements Validation

- **High Cost of Requirements Errors:**
 - Fixing a requirements error after system delivery can cost **up to 100 times** more than fixing a coding bug!
- **5 Requirements Checks:**
 - i. **Validity:** Does it reflect the true needs of stakeholders?
 - ii. **Consistency:** Are there any conflicting requirements?
 - iii. **Completeness:** Are all mandatory features specified?
 - iv. **Realism:** Can it be built within budget and technical constraints?
 - v. **Verifiability:** Can it be objectively tested?

The 5 Pillars of Validation



Validity: Does this reflect the true needs of the stakeholders?



Consistency: Are there any hidden contradictions or logical conflicts?



Completeness: Are all mandatory facilities explicitly specified?



Realism: Can this actually be built within budget and technical limits?



Verifiability: Can an objective test be written to prove this was achieved?

Requirements Change & Management

- **Why Requirements Change:**
 - Business goals shift, new regulations emerge, payors and actual system users have conflicting demands.
- **Requirements Management Planning:**
 - **Unique Identification:** Tagging every requirement (e.g., SRS-3.3.2).
 - **Traceability Matrix:** Tracking dependencies between requirements and architecture modules.
 - **Change Control Board (CCB):** Formal process to evaluate cost, impact, and priority of proposed changes.

Architecting for Inevitable Change

The Catalyst

Why change happens:
Shifting business goals,
new regulations, and
conflicting stakeholder
demands.

Unique Identification

Tagging every requirement (e.g., SRS-3.3.2) to prevent ambiguity.

Traceability Matrix

A grid visualization showing how a single requirement links down to specific architecture modules and test cases.

Change Control Board (CCB)

A human governance node representing the formal process to evaluate the cost, impact, and priority of proposed changes.

AI in Requirements Engineering: Overview

- **The Generative AI Paradigm Shift:**
 - LLMs and Generative AI tools serve as an **intelligent RE Copilot** across the software engineering lifecycle.
 - Bridges the gap between informal customer language and formal technical specifications.
- **Key Benefit:** Accelerates elicitation, eliminates ambiguities early, and reduces requirements debt.

The Modern Catalyst

The Generative AI Paradigm Shift. LLMs serve as an Intelligent RE Copilot across the software engineering lifecycle.

By bridging the gap between informal customer language and formal technical specifications, AI accelerates elicitation, eliminates ambiguities early, and drastically reduces long-term requirements debt.

4 Core AI Applications in RE

1. Automated User Story & Specification Generation:

- Converts raw client interview transcripts into structured `Given-When-Then` Gherkin acceptance criteria.

2. Ambiguity & Inconsistency Detection:

- Scans SRS documents to flag non-verifiable adjectives ("*user-friendly*", "*fast*") and logical contradictions.

3. NFR Metric Derivation & GQM Assistance:

- Translates abstract goals into quantitative metrics (e.g. "*System must be responsive*" → `p95 latency < 200ms`).

4. Automated Requirements Traceability Matrix (RTM):

- Dynamically links user stories to code components and test cases to predict change impact.

The AI-Enhanced RE Loop



Human-in-the-Loop: Risks & Best Practices

- **Risks of Unchecked AI in RE:**
 - **Hallucinations:** Inventing non-existent business rules or domain constraints.
 - **Privacy & IP Leaks:** Accidentally leaking proprietary business logic to public LLMs.
 - **Superficial Specs:** AI lacks deep organizational domain intuition and stakeholder empathy.
- **The Golden Rule:**

AI is an Assistant, Not an Approver!

Human Domain Experts and Product Managers MUST review, validate, and sign off on all AI-generated requirements.

The Human-in-the-Loop Imperative

The Risks of Unchecked AI

Hallucinations: AI inventing non-existent business rules or domain constraints.

IP Leaks: Exposing proprietary business logic to public LLM models.

Superficial Specs: AI fundamentally lacks organizational intuition and stakeholder empathy.

AI generates the blueprint, but human engineers must verify the structural integrity.

Generative AI accelerates the translation process, but the ultimate responsibility for a verifiable, structurally sound system rests on human oversight.

Concept Check Question 2

Why is fixing a requirements error after software delivery significantly more expensive than fixing an error during development?

- **A.** Requirements documents cannot be edited after signing.
- **B.** Post-delivery fixes require re-designing, re-coding, and re-testing dependent modules across the entire system.
- **C.** Stakeholders refuse to approve requirements changes.
- **D.** Non-functional requirements do not apply after deployment.



Concept Check Question 2: Answer

Why is fixing a requirements error after software delivery significantly more expensive than fixing an error during development?

- **Correct Answer: B**
- **Explanation:** A late requirements change impacts architecture, component design, database schemas, code, and test suites, cascading costs up to 100x.



Recap: Fill-in-the-blank Quiz

Test your understanding of the core concepts in this chapter:

1. ____ requirements describe what the system should do, while ____ requirements specify system constraints.
2. High-level requirements written for customers are called ____ requirements.
3. The Goal-Question-Metric (GQM) approach turns general goals into verifiable ____.
4. The ____ Control Board evaluates the impact and cost of proposed requirements changes.



Recap: Answers & Summary

Here are the completed concepts:

1. **Functional** requirements describe what the system should do, while **non-functional** requirements specify system constraints.
2. High-level requirements written for customers are called **user** requirements.
3. The Goal-Question-Metric (GQM) approach turns general goals into verifiable **metrics**.
4. The **Change** Control Board evaluates the impact and cost of proposed requirements changes.



References

- **Sommerville Software Engineering Book (Chapter 4)**
 - [IEEE 830 Recommended Practice for Software Requirements Specifications](#)
 - [UML Use Case Specification Standard](#)