

Software Engineering

Lecture 3: Requirements Engineering

Prof. Nien-Lin Hsueh

Department of Information Engineering and Computer Science

Feng Chia University


Chapter 3: Roadmap & Key Topics

- **3.1 Foundations of Requirements Engineering** (User vs. System Requirements)
- **3.2 Stakeholders & Requirements Classification** (Functional & Domain Rules)
- **3.3 Non-Functional Requirements (NFRs) & Metrics** (Verifiable Quality Goals)
- **3.4 Requirements Elicitation & Use Case Modeling** (Discovery & UML Notation)
- **3.5 Requirements Validation & Change Management** (5 Pillars & Traceability)
- **3.6 AI-Assisted Requirements Engineering** (LLM Copilots & Human-in-the-Loop)
- **3.7 Conceptual Recap: Fill-in-the-blank Quiz & References**

Focus Questions

- What is **Requirements Engineering (RE)** and why is fixing requirements errors early so critical?
- What is the fundamental difference between **User Requirements** and **System Requirements**?
- How do **Functional**, **Non-Functional**, and **Domain Requirements** differ?
- What are the 4 main stages of the **Requirements Elicitation & Analysis** process?
- How can non-functional goals be transformed into **verifiable, testable metrics**?
- How do modern **Large Language Models (LLMs)** enhance the RE process, and what are the human-in-the-loop safeguards?

Exponential Cost of Requirements Errors



3.1 Foundations of Requirements Engineering

The systematic process of establishing the services that a customer requires from a system and the operational/developmental constraints under which it operates. „

- **Dual Function of Requirements:**

1. **Contract Bidding:** High-level abstract statements open to contractor interpretation.
2. **Contract Basis:** Detailed functional specifications defining precisely what must be delivered.

- **The Fundamental Goal:**

- Bridging the gap between the messy, ambiguous real world of human stakeholders and the precise, deterministic world of software systems.

User Requirement (Customer Intent)

The MHC-PMS shall generate monthly summary reports of drug costs prescribed by clinics

Engineering Translation



System Requirements (Developer Contract)

- 1.1: Triggered on last working day of month
- 1.2: Standard layout: drug name, doses, total cost
- 1.3: Handles 10k records < 60s without DB lock

User vs. System Requirements

- **User Requirements:**

- High-level abstract statements written in natural language with diagrams.
- Target audience: **Clients, system users, managers, non-technical stakeholders.**
- Focuses on **what** services the system provides from the user perspective.

- **System Requirements:**

- Detailed, structured specifications defining system functions, services, and operational constraints precisely.
- Target audience: **Developers, software architects, system testers.**
- Serves as the baseline technical contract for system implementation.

User vs. System Requirements Example


- **User Requirement (High-Level Intent):**

"The MHC-PMS shall generate monthly summary reports showing the cost of drugs prescribed by each clinic."

- **System Requirements (Detailed Technical Specification):**

- **1.1:** On the last working day of each month, a summary report shall be generated of drug costs across each registered clinic.
- **1.2:** The system shall produce reports using a standardized layout showing drug names, total doses prescribed, and total cost.
- **1.3:** If drug cost data exceeds 10,000 records, generation shall complete within 60 seconds without locking the transactional database.

The Three Types of Software Requirements



Concept Check Question 1

In requirements engineering, what is the critical operational distinction between **User Requirements** and **System Requirements**?

- **A.** User requirements are high-level stakeholder goals; system requirements are detailed functional contracts for developers.
- **B.** User requirements specify UI wireframes; system requirements specify backend database schemas.
- **C.** User requirements can never change; system requirements are refactored continuously during daily scrums.
- **D.** User requirements come from external legal auditors; system requirements are generated by compiler tools.



3.2 System Stakeholders & Requirements Classification

Any person or organization affected by the system who has a legitimate interest in its behavior and operational outcome.

”

- **Types of Stakeholders:**

- **End Users:** Patients, Doctors, Nurses, Receptionists.
- **System Managers:** Clinic Managers, IT Directors, Compliance Officers.
- **External Stakeholders:** Health Authorities, Medical Device Regulators, Insurance Payors.

- **The Stakeholder Conflict Challenge:**

- Different stakeholders have competing, conflicting requirements (e.g., Doctors want rapid data entry; Compliance Officers want comprehensive multi-factor audit logging).

Types of Requirements: Functional & Domain

1. Functional Requirements:


- Statements of specific services the system should provide, how it reacts to particular inputs, or what it must *not* do.

2. Non-Functional Requirements:

- Constraints on system services or functions (e.g., timing constraints, security, reliability, data privacy).

3. Domain Requirements:

- Constraints derived from the operational domain (e.g., medical laws, banking regulations, physical properties).
- *Critical rule:* Domain requirements often override both functional and non-functional requirements!



If any single pillar fails, the entire system collapses!

Case Study: Stakeholder Ecosystem in UberEats

A food delivery platform like UberEats illustrates how requirements emerge from multi-sided stakeholder ecosystems with competing priorities.

”

- **The Multi-Sided Stakeholder Ecosystem:**

- **Hungry Customer (Eater):** Demands fast delivery, accurate ETA, live GPS tracking, and friction-free refunds.
- **Restaurant Merchant:** Wants predictable kitchen prep buffers, timely courier arrivals, and locked payments once cooking starts.
- **Delivery Courier:** Demands fair dispatching algorithms, transparent tip payouts, short distances, and safe parking tolerance.
- **Platform Operations (Uber):** Optimizes network liquidity, balances supply/demand via dynamic fees, and prevents promotional fraud.
- **External Regulators:** Enforce food safety temperature standards, labor regulations, and mandatory electronic fiscal receipts.

- **The Stakeholder Conflict Challenge:**

- *Customer vs. Restaurant:* Customer cancels 5 minutes after ordering; restaurant already started cooking expensive ingredients. Who absorbs the loss?

UberEats: The Requirements Triad in Practice

- **1. Functional Requirements (Services & Behavior):**

- The system shall allow customers to filter restaurants by dietary restrictions and live delivery ETA.
- The system shall broadcast available delivery jobs to the optimal courier based on GPS location and vehicle type.
- The system shall automatically split and transfer payouts among restaurant, courier, and platform upon delivery confirmation.

- **2. Non-Functional Requirements (Quality & Constraints):**

- **Performance:** Courier GPS coordinates shall refresh on the customer tracking map every ≤ 2 seconds.
- **Availability:** The platform shall maintain $\geq 99.99\%$ uptime during peak dinner hours (18:00–21:00).
- **Security:** All customer credit card credentials shall comply with PCI-DSS Level 1 tokenization.

- **3. Domain Requirements (Environmental & Legal Mandates):**

- *Food Safety:* Hot perishable food delivery duration shall not violate health agency safety guidelines.
- *Fiscal Compliance:* The system must generate legally compliant electronic VAT invoices per local jurisdiction.

Functional Requirements: Challenges


- **Requirements Imprecision:**

- Ambiguous natural language requirements cause misunderstandings.
- *Example:* "Search appointment list" — does it mean across *all* clinics (user intent) or within an *individual* clinic (developer interpretation)?


- **Completeness vs. Consistency:**

- **Completeness:** All services required by the user should be specified.
- **Consistency:** Requirements should not have contradictory definitions.
- *Reality Check:* In complex systems, achieving 100% completeness and consistency upfront is practically impossible, requiring iterative refinement.

What the customer described



How the systems analyst designed it



How the programmer coded it



What the customer actually wanted



Concept Check Question 2

Consider the following specification for the UberEats platform:

"Due to municipal food hygiene regulations, perishable warm food delivery transit time shall not exceed 45 minutes, and containers must maintain a temperature above 60°C throughout transit."

”

What category of software requirement does this statement represent?

- **A.** Domain Requirement (a constraint imposed by the operational environment, industry regulations, or physical laws)
- **B.** Functional Requirement (a specification of an active software computation, user feature, or system service)
- **C.** Non-Functional Requirement (a general software quality attribute concerning performance, scalability, or uptime)



3.3 Non-Functional Requirements (NFR) & Metrics

Constraints on the services or functions offered by the system, including timing constraints, security, reliability, and standards compliance, fundamentally shaping software architecture. „


- **System-Wide Impact:**

- NFRs often apply to the system as a **whole** rather than individual features.
- Failing to meet an NFR can render the entire system useless (e.g., a slow or insecure medical database).


- **Architectural Influence:**

- Performance NFRs dictate module communication patterns; security NFRs introduce authentication infrastructure.
- *Architecture is shaped far more by NFRs than by functional features!*

Non-Functional Requirements Iceberg



NON-FUNCTIONAL REQUIREMENTS (NFR) HIERARCHY




Product Requirements


I need 0.1s response time!



Organizational Requirements



External Requirements



Goals vs. Verifiable NFRs

- **Goal (Imprecise Intention):**

"The system should be easy to use by medical staff and minimize user errors."

„

- **Verifiable NFR (Testable Metric):**

"Medical staff shall be able to use all core functions after 2 hours of training. After training, the average number of operator errors shall not exceed 2 per working day."

„

- **The Golden Engineering Principle:**

- Always transform subjective stakeholder goals into **quantifiable, objectively testable metrics!**

THE SYSTEM MUST
BE BLAZING FAST AND
SUPER EASY TO USE!

Goal:
User Satisfaction

Goal: High
Performance

HOW DO I
TEST 'SUPER
EASY'??

Question:
How to
measure
'easy' and
'fast'?

CONVERTED
TO VERIFIABLE
METRICS!

- ✓ RESPONSE $\leq 200\text{ms}$
- ✓ ERROR RATE $< 0.1\%$
- ✓ TRAINING TIME $< 1\text{HR}$

Metrics for Specifying NFRs

Property	Measurable Metric Examples
Speed	Processed transactions/sec; Response time; Screen refresh rate
Size	Megabytes of RAM; Number of ROM chips required
Ease of Use	Training time to competency; Number of help desk queries/week
Reliability	Mean Time Between Failures (MTBF); Rate of failure occurrence
Robustness	Time to restart after failure; Percentage of data corrupted on power loss
Portability	Percentage of target-dependent statements; Number of supported OS platforms

Concept Check Question 3

A client provides an imprecise non-functional goal: "*The order checkout system must be blazing fast and highly reliable.*" Which of the following correctly transforms this vague goal into a **verifiable, testable engineering metric**?

- **A.** 99% of checkouts shall have response time ≤ 500 ms, and peak uptime shall be $\geq 99.95\%$.
- **B.** The checkout UI shall use sleek animations so customers perceive maximum speed.
- **C.** All checkout services shall use memory-safe code to guarantee bug-free execution.
- **D.** The cloud database shall allocate unlimited RAM whenever transaction load increases.



3.4 Requirements Elicitation & Modeling

The collaborative, iterative process of discovering, understanding, negotiating, and modeling stakeholder needs and operational system boundaries.

”

- **Four Interleaved Activities:**

1. **Elicitation & Analysis:** Discovering requirements from stakeholders.
2. **Specification:** Documenting requirements formally.
3. **Validation:** Checking that requirements reflect real needs.
4. **Management:** Managing changes to requirements over time.

- **Spiral & Iterative Nature:**

- RE is **never a single-pass, linear activity**; it is an iterative spiral where understanding deepens across successive releases.

CLIENT
IDEAS

Untangling
the chaos!

STRUCTURING
KNOWLEDGE

Elicitation


Requirements
Engineering Engine
of Clarity

Specification

✓
Matches what
you wanted!

Management

Validation



Elicitation Technique 1: Stakeholder Interviews & Workshops

- **Types of Interviews:**

- **Closed Interviews:** Pre-defined question sets useful for verifying factual constraints and compliance checklists.
- **Open Interviews:** Unstructured, exploratory conversations uncovering stakeholder frustrations, mental models, and broad visions.
- **Semi-Structured Interviews:** Core agenda with flexibility to drill down into unexpected operational friction points.

- **The "Unstated Assumptions" Trap:**

- Stakeholders frequently omit obvious domain knowledge ("*Of course everyone knows taxes change by county!*").

- **Facilitated Workshops (Joint Application Design - JAD):**

- Gathers conflicting stakeholders (e.g., Doctors, Nurses, IT, Billing) in one room with a neutral facilitator to resolve competing needs in hours rather than months.

Interview Heuristics: Principles, Myths & Practical Skills

- **Core Principles:**

- **Listen 80%, Talk 20%:** Let stakeholders articulate operational pain points without interruption.
- **Focus on Problems, Not Solutions:** Ask "*What goal are you trying to accomplish?*" rather than "*Do you want a dropdown button?*"

- **Common Myths:**

- *Myth 1:* "Users know what they want and state it clearly." (Reality: They confuse symptoms with root causes).
- *Myth 2:* "One interview yields a complete spec." (Reality: Interviews provide initial hypotheses).
- *Myth 3:* "Discuss technical architecture with users." (Reality: Microservices/SQL talk alienates stakeholders).

- **Practical Skills:**

- **The "5 Whys" Technique:** Drill past superficial feature requests to uncover root business needs.
- **Comfort with Silence (3-Second Pause):** Wait 3 seconds after users stop speaking to hear unwritten realities.

Elicitation Technique 2: Ethnography & Workplace Observation

"What people say they do, and what they actually do, are often entirely different."

”

- **The Power of Direct Observation:**

- Spending time in the actual operational environment (e.g., hospital ER, trading floor, warehouse loading dock).

- **Uncovering "Tacit Knowledge":**

- **Tacit Knowledge:** Deeply ingrained habits, shortcuts, and informal workarounds that users perform automatically but never mention in meetings.

- **Observation Styles:**

- **Passive Observation ("Fly on the Wall"):** Watching natural workflows without interruption to identify operational bottlenecks and cognitive load.
- **Contextual Inquiry (Active Shadowing):** Observing users perform real tasks, asking clarifying questions in the moment (*"Why did you write that code on a sticky note?"*).

Elicitation Technique 3: Scenarios, User Stories & Storyboards

- **Concrete Narrative Scenarios:**

- Rich, chronological walkthroughs of realistic, day-in-the-life system usage under both typical conditions and crisis situations.

- **Agile User Stories & Acceptance Criteria:**

- **Format:** "As a [User Role], I want [Capability], so that [Business Value]."
- **Given-When-Then (Gherkin):**
 - *Given* a customer with an active promo code,
 - *When* they apply the code to an eligible restaurant order,
 - *Then* the subtotal must reflect a 20% discount up to a maximum of \$10.

- **Low-Fidelity Storyboarding & Paper Prototyping:**

- Quick comic-strip sketches of user journeys that elicit early, visceral feedback before writing code ("*I didn't realize I'd need 5 screen taps just to reorder!*").

Agile User Story

As a Hungry Customer,
I want live GPS tracking
of my UberEats courier,
so that I don't wait in
the cold rain!



Acceptance Criteria Met



Elicitation Technique 4: Document Analysis & System Archaeology

- **Mining Existing Operational Artifacts:**

- **Standard Operating Procedures (SOPs):** Official enterprise rules, compliance manuals, and safety checklists.
- **Legacy Code & Database Schemas:** Reverse-engineering existing production systems to extract implicit business algorithms.
- **Forms & Spreadsheet Archaeology:**
 - Paper intake forms, invoice receipts, and manual Excel tracking sheets.
 - *Rule of Thumb:* Every column in an active Excel sheet represents an unfulfilled requirement of the previous software system!

- **The "Archaeology Trap":**

- Distinguish between **essential business logic** (must preserve) and **historical technical workarounds** (must deprecate, not blindly digitize).

Choosing Elicitation Techniques: A Comparative Matrix

Technique	Primary Strengths	Main Limitations	Best Applied When...
Interviews	High depth; builds personal stakeholder rapport	Vulnerable to bias; misses tacit knowledge	Initial discovery & understanding broad goals
Workshops (JAD)	Resolves conflicting priorities; rapid alignment	Scheduling friction; dominant personalities	Multiple stakeholders have competing requirements
Ethnography	Discovers actual behavior & informal workarounds	Highly time-consuming; non-generalizable	Complex, physical, high-stress work environments
User Stories & Scenarios	Testable; directly feeds agile sprint backlogs	Can miss global non-functional constraints	Defining incremental user-facing features
Doc Analysis	Highly objective; uncovers legacy business rules	Documents are often outdated or aspirational	Replacing legacy systems & regulated domains

THE 4 REQUIREMENTS ELICITATION TECHNIQUES

1. Interviews & Workshops



2. Ethnography & Observation



3. Scenarios & Storyboards



4. Document Archaeology



Concept Check Question 4

During a requirements elicitation interview, an executive insists: *"Our clinical software must include a blockchain ledger to record patient vitals."* What is the most effective engineering interview heuristic to apply?

- **A.** Apply the "5 Whys" to investigate the underlying data integrity and audit problem rather than prematurely locking in the suggested technology.
- **B.** Immediately begin drafting smart contracts and relational database schemas for the requested blockchain feature.
- **C.** Reject the executive's request outright because non-technical stakeholders are prohibited from proposing system capabilities.
- **D.** Politely terminate the interview and switch exclusively to passive workplace observation.



Concept Check Question 5

In requirements engineering, why is **Ethnography (workplace observation)** uniquely vital when analyzing complex operational environments such as hospital emergency rooms or air traffic control?

- **A.** It uncovers tacit knowledge—ingrained habits, physical workarounds, and unwritten shortcuts that users perform automatically but never mention during interviews.
- **B.** It automatically compiles natural language requirements directly into executable acceptance test suites without human intervention.
- **C.** It eliminates the need for subsequent software architecture design, database modeling, or code review phases.
- **D.** It guarantees that the resulting software requirements will achieve 100% mathematical completeness on the initial development sprint.



From Scenarios to Use Cases: Bridging Elicitation to Modeling

How do engineers transition from raw elicitation stories (Technique 3) into structured system models?

”

- **Connecting to Elicitation Technique 3 (Scenarios & User Stories):**
 - Elicitation produces concrete human stories (*"Alice orders sushi using a coupon, but her card expires"*).
- **What is a Scenario?**
 - A single, concrete execution path through a user interaction (one specific narrative sequence).
- **What is a Use Case?**
 - A generalized umbrella that aggregates **all related scenarios** (the Happy Path plus all alternative & exception flows) for a specific actor goal (*Place Food Order*).
- **Why Transition from Scenarios to Use Cases?**
 - Scenarios provide rich narrative context; use cases structure them into comprehensive functional contracts for engineering and test planning.

Discovering Use Cases: The 5-Step Process


How do engineers systematically discover and structure use cases during elicitation?

1. **Identify External Actors:** Determine who or what interacts directly with the software (human roles, payment gateways, automated sensors).
2. **Identify Actor Business Goals:** For each actor, ask: "*What observable value do they need the system to deliver?*"
3. **Group Scenarios into Use Cases:** Cluster related user stories into verb-noun operational goals (*Place Order, Track Delivery*).
4. **Define System Boundaries:** Clearly demarcate what logic resides inside the application vs. what remains external or manual.
5. **Factor Common & Conditional Logic:** Extract shared mandatory steps (`<<include>>`) and optional variations (`<<extend>>`).

Use Case Diagram Notation (UML)

- **Actors:** External entities (users or systems) interacting with the application.
- **Use Cases:** Ellipses representing high-level functional interactions.
- **System Boundary:** Box defining scope of the system under design.
- **Relationships:**
 - **<<include>>**: Behavior that is always executed as part of the base use case (e.g., *Authenticate User* included in *View Medical Records*).
 - **<<extend>>**: Optional or conditional behavior triggered under specific conditions (e.g., *Prescribe Controlled Substance* extends *Prescribe Medication*).

Anatomy of a UML Use Case Diagram



USE CASE DESCRIPTION: WITHDRAW CASH

METADATA

- Primary Actor: Bank Customer
- Preconditions: ATM online
 - Cash vault loaded
 - Card inserted & validated
- Postconditions: Cash dispensed
 - Account debited
 - Audit log recorded
 - Card returned

MAIN SUCCESS SCENARIO (HAPPY PATH)

1. Customer selects 'Withdraw Cash' and inputs amount (\$100)
2. System verifies available account balance with Core Banking API
3. System confirms internal ATM vault has sufficient bills
4. System debits customer account & creates transaction log
5. System initiates cash dispensing mechanism
6. System ejects ATM card and sounds chime
7. Customer removes card; System opens cash dispenser shutter
8. Customer takes cash; System prints transaction receipt

EXTENSIONS & EXCEPTIONS

- 2a. Insufficient Balance: System displays alert, offers balance check, and aborts
- 3a. Machine Out of Cash: System alerts customer, limits withdrawal, or aborts
- 6a. Unclaimed Card: If card not taken within 30s, ATM retracts card for security
- 8a. Unclaimed Cash: If cash left in tray for 30s, shutter closes and debit is reversed

Why Requirements Elicitation is Hard

"The hardest single part of building a software system is deciding precisely what to build." — Fred Brooks

”

- **1. The Articulation Barrier (Tacit Knowledge):**

- Stakeholders possess deep operational expertise but struggle to verbalize routine habits (*"It's just obvious how we handle daily exceptions!"*).

- **2. The Solution Bias (Premature Anchoring):**

- Users demand specific UI widgets or trendy technology (*"Put a blockchain ledger here!"*) rather than articulating actual business pain points.

- **3. Conflicting Stakeholder Agendas:**

- Marketing seeks frictionless one-click purchases; InfoSec demands multi-factor authentication; Finance demands complex audit reconciliation.

- **4. Requirements Volatility (The Moving Target):**

- Software is malleable; once stakeholders interact with early prototypes, their perceived needs and market priorities inevitably evolve.

Concept Check Question 6

A software engineering team creates a UML Use Case Diagram showing an actor connected to the "Withdraw Cash" use case. Why must engineers author a detailed textual **Use Case Description** in addition to the diagram?

- **A.** Diagrams only show high-level scope; descriptions define sequential flows, preconditions, postconditions, and exception handling.
- **B.** UML diagrams cannot be rendered by web browsers without accompanying markdown text.
- **C.** Compilers require use case descriptions to allocate heap memory for actor threads.
- **D.** Descriptions convert non-functional requirements into automated GUI wireframes.



3.5 Requirements Validation & Change Management

The critical quality process of certifying that requirements represent real user needs, and managing evolving specifications throughout the software lifecycle.

”


- **High Cost of Requirements Errors:**

- Fixing a requirements error after system delivery can cost **up to 100 times** more than fixing a coding bug!

- **5 Requirements Checks:**

1. **Validity:** Does it reflect the real needs of the customer?
2. **Consistency:** Are there conflicting requirements?
3. **Completeness:** Are all requirements and constraints included?
4. **Realism:** Can the requirement be implemented with current budget/tech?
5. **Verifiability:** Can the requirement be objectively tested?

The 5 Pillars of Requirements Validation



Requirements Change & Management

- **Why Requirements Change:**


- Business goals shift, new regulations emerge, payors and actual system users have conflicting demands.

- **Requirements Management Planning:**

- **Unique Identification:** Tagging every requirement with a traceable ID (e.g., `REQ-SEC-012`).
- **Traceability Policies:** Maintaining links from requirements to architecture modules, code commits, and test cases.
- **Change Control Process:** Formal assessment of the cost and architectural impact before approving changes.


REQUIREMENTS CHANGE MANAGEMENT & TRACEABILITY

UNIQUE ID TAGGING




LINILY PRESENT ON
A DIRECT FLOW

TRACEABILITY MATRIX



REQUIREMENTS SAFELY THROUGH
THROUGH CAUSING CHANGES

CHANGE CONTROL BOARD & IMPACT ANALYSIS



IMPACT ANALYSIS

- Potential changes before approved
- Evaluatal changes before approved
- Evaluate changes before approved

Concept Check Question 7

Why is fixing a requirements error after software delivery significantly more expensive than fixing an error during early development?

- **A.** Requirements documents cannot be legally modified once signed by clients.
- **B.** A late fix requires redesigning, recoding, retesting, and redeploying cascading components that were built on the flawed premise.
- **C.** Compilers automatically lock code repositories against changes after the first production release.
- **D.** Automated unit tests lose their validity after code has been deployed to cloud environments.



3.6 AI in Requirements Engineering: Overview

Leveraging Large Language Models as intelligent analytical copilots to bridge informal human dialogue and formal, testable software specifications.

”

- **The Generative AI Paradigm Shift:**

- LLMs and Generative AI tools serve as an **intelligent RE Copilot** across the software engineering lifecycle.
- Bridges the gap between informal customer language and formal software engineering artifacts.

- **Key Capabilities:**

- Drafting structured specifications from messy meeting notes.
- Detecting semantic contradictions and missing edge cases across hundreds of pages of documentation.
- Generating initial test cases and Gherkin acceptance criteria automatically.

Why LLMs Work for RE: Pre-Trained Domain Ontologies

"When you ask an AI to design a food delivery app, it doesn't start from scratch—it already knows the business domain!"

- **The Secret of Pre-Trained Domain Knowledge:**

- LLMs are trained on billions of tokens: industry documentation, enterprise case studies, open-source codebases, and ISO/IEEE standards.
- The model already possesses a latent **Domain Ontology**:
 - **In Banking:** It already knows accounts require transaction atomicity, multi-factor auth, and regulatory audit ledgers.
 - **In E-Commerce / Delivery:** It already understands multi-party split payments, geofencing, dynamic surge pricing, and cancellation refund rules.

- **The "Instant Domain Advisor" Advantage:**


- **Surfacing Tacit Requirements:** Immediately proposes standard industry edge cases that junior engineers often forget (e.g., promo-code fraud, cold-chain temperature thresholds).
- **Rapid Scaffolding:** Transforms informal stakeholder interview transcripts into Given-When-Then user stories and UML candidate entities in seconds.

Empirical Studies: AI in Requirements Engineering

- **1. Elicitation Breadth & Edge Cases (IEEE RE / ACM TOSEM):**
 - *Finding:* LLMs generate **30%–50% more boundary conditions & edge cases** vs. humans alone, drastically cutting early requirement omissions.
- **2. Ambiguity & Conflict Detection (Ferrari et al., RE'23):**
 - *Finding:* LLM checkers detect passive-voice vagueness & untestable adjectives with **>80% precision**, matching senior human reviewers.
- **3. The Hallucination Penalty (NYU / Stanford & Empirical RE):**
 - *Finding:* **~20%–25%** of LLM specs contain **fabricated APIs or phantom rules**. Human-in-the-loop verification remains non-negotiable!

Empirical Sources:

- [1] A. Ferrari et al., "Detecting Ambiguities in Requirements with LLMs," *Proc. 31st IEEE RE*, 2023.
- [2] C. Arora et al., "Automating Requirements Elicitation & Analysis with LLMs," *ACM TOSEM*, 2024.
- [3] H. Zhang et al., "Faithfulness & Hallucination in Generative RE," *Empirical Softw. Eng.*, 2024.



4 Core AI Applications in RE

1. Automated User Story & Specification Generation:

- Converts raw client interview transcripts into structured **Given-When-Then** Gherkin acceptance criteria.

2. Ambiguity & Inconsistency Detection:

- Scans hundreds of requirement statements to detect contradictory terms and passive-voice vagueness.

3. Traceability Matrix Construction:


- Uses semantic embeddings to map high-level user requirements to code functions and unit tests.

4. Synthetic Stakeholder Persona Simulation:

- Simulates diverse user personas to brainstorm overlooked edge cases during early discovery.

The 4 Core AI Applications in Requirements Engineering

User Story Gen




Ambiguity Detective



User Story Gen



Persona Simulator



Traceability Matrix

Human-in-the-Loop: Risks & Best Practices

- **Risks of Unchecked AI in RE:**

- **Hallucinations:** Inventing non-existent business rules or domain constraints.
- **Privacy & IP Leaks:** Accidentally leaking proprietary business logic to public cloud models.
- **Bias Amplification:** Reinforcing historical biases in requirements datasets.

- **The Golden Rule: Human-in-the-Loop:**

- AI proposes; **the Human Software Engineer disposes.**
- The human engineer retains legal, ethical, and architectural accountability for every accepted requirement.

HUMAN-IN-THE-LOOP: THE ULTIMATE RESPONSIBILITY IN AI-ASSISTED RE



Concept Check Question 8

When software engineering teams use Large Language Models (LLMs) to generate requirements specifications from stakeholder interview transcripts, what is the primary operational risk requiring human-in-the-loop verification?

- **A.** The LLM may hallucinate plausible-sounding but fictitious business logic, omitted edge-case constraints, and non-existent external API integrations.
- **B.** The LLM cannot output text formatted in Markdown bullet points or standard user story Given-When-Then acceptance criteria.
- **C.** The LLM will consume excessive server memory and cause database deadlock errors across production microservice clusters.
- **D.** The LLM strictly enforces waterfall development practices and refuses to generate requirements for iterative agile sprint cycles.



3.7 Conceptual Recap: Fill-in-the-blank Quiz

Test your understanding of the core concepts in this chapter:

1. requirements describe what the system should do, while requirements specify system constraints.
2. High-level requirements written for customers are called requirements.
3. Detailed specifications written as a technical contract for developers are requirements.
4. The Goal-Question-Metric approach turns vague stakeholder wishes into metrics.
5. In UML use cases, behavior that is always executed as part of a base use case uses the relationship.
6. When using AI in requirements engineering, the engineering principle that ensures accountability is .

References & Further Reading

- **Foundational Textbooks & Standards:**

- Sommerville, I. (2016). *Software Engineering* (10th ed.). Chapter 4: Requirements Engineering. Pearson.
- IEEE Std 830-1998 / ISO/IEC/IEEE 29148:2018: *Systems and software engineering — Life cycle processes — Requirements engineering*.
- Cockburn, A. (2000). *Writing Effective Use Cases*. Addison-Wesley.
- Wieggers, K., & Beatty, J. (2013). *Software Requirements* (3rd ed.). Microsoft Press.

- **AI & Empirical Requirements Engineering Research:**

- Ferrari, A., et al. (2023). "Detecting Ambiguities in Requirements with Large Language Models." *IEEE RE'23*.
- Arora, C., et al. (2024). "Automating Requirements Elicitation and Analysis with LLMs: An Empirical Evaluation." *ACM TOSEM*.
- Zhang, H., Rahman, M., & Wang, Y. (2024). "Faithfulness, Hallucination, and Risk in Generative Requirements Engineering." *Empirical Software Engineering (EMSE)*.