Data

MAGNETOM Avanto
Tim [76 x 18]
Q-engine

SIEMENS
medical

Tim – Total imaging matrix

[76 x 18]. 76 seamlessly integrated coil elements. 18 RF channels.

- Up to 76 simultaneously connected coil elements which can be seamlessly integrated into one examination
- 18 independent receiver channels (Analog/Digital Converters, ADCs)

Almost all receiving coils with up to 76 coil elements in total can be connected simultaneously. They can be seamlessly integrated into the examination without repositioning the patient or even changing a single coil.

iPAT – Advanced iPAT capabilities

- Full iPAT throughout the whole body – without patient repositioning or changing the coil setup
- Multi-directional, i. e. three dimensional, high-speed, high-resolution iPAT
- Flexible iPAT through use of multiple coils and Matrix Coil Mode
- iPAT with acceleration factors up to 4 (one direction) or 12 (with iPAT^2, optional)[1)]
- Tim Assistant ensures ease-of-use and optimized iPAT settings

1) With iPAT Extension Option

Gradients

General

Gradient duty cycle	100 %
Gradient performance for each axis	
Max. amplitude	33 mT/m
Min. rise time	264 µs from 0 to 33 mT/m
Max. slew rate	125 T/m/s
Vector gradient performance (vector summation of all 3 gradient axes)	
Max. eff. amplitude	57 mT/m
Max. eff. slew rate	216 T/m/s

Gradient Amplifier

Water-cooled, highly compact, modular design
Ultra-fast solid-state technology with very low switching losses

Max. output voltage[2)]	1250 V
Max. output current[2)]	460 A

2) Values for each of the 3 gradient axes

Resolution Parameters		
	Min. FoV	5 mm
	Max. FoV	500 mm
	Min. slice thickness 2D	0.1 mm
	Max. slice thickness 2D	200 mm
	Min. partition thickness 3D	0.05 mm
	Max. partition thickness 3D	20 mm
	Min. slab thickness 3D	6.8 mm
	Max. slab thickness 3D	500 mm
	Max. matrix	1024
	Highest in-plane resolution	11 µm

Spin Echo	Matrix	128	256
	Min. TR	6.9 ms	7.4 ms
	Min. TE	3.5 ms	4.0 ms

Inversion Recovery	Matrix	128	256
	Min. TR	28 ms	29 ms
	Min. TE	3.5 ms	4.0 ms
	Min. TI	22 ms	22 ms

2D GRE (TurboFLASH)	Matrix	128	256
	Min. TR	1.4 ms	1.8 ms
	Min. TE	0.55 ms	0.78 ms
	Min. measurement time	37 ms	49 ms

3D GRE (ceMRA)	Matrix	128	256
	Min. TR	1.4 ms	1.8 ms
	Min. TE	0.55 ms	0.78 ms

TrueFISP	Matrix	128	256
	Min. TR	2.2 ms	2.8 ms
	Min. TE	0.95 ms	1.2 ms
	Min. measurement time	86 ms	120 ms

TSE (HASTE)	Matrix	128	256
	Min. echo spacing	2.6 ms	2.8 ms
	Min. TR	6.9 ms	7.4 ms
	Min. TE	3.5 ms	4.0 ms
	Min. measurement time	98 ms	116 ms
	Max. Turbo factor	512	

TurboGSE	Matrix	128	256
	Min. echo spacing	1.1 ms	1.2 ms
	Min. TR	6.9 ms	7.4 ms
	Min. TE	3.5 ms	4.0 ms
	Max. Turbo factor	65	
	Max. EPI factor	21	

EPI (single-shot and multi-shot)	Matrix	64	128	256
	Min. echo spacing	0.34 ms	0.48 ms	0.74 ms
	Min. TR	10 ms	10 ms	10 ms
	Min. TE	2.2 ms	2.3 ms	2.7 ms
	Min. measurement time	13 ms	17 ms	25 ms
	Max. EPI factor	256		

Diffusion Imaging	Matrix	64	128	256
	Max. b-value [s/mm²]	10,000	10,000	10,000
	Min. TE with b = 1,000 [s/mm²]	57 ms	58 ms	63 ms

All matrices without interpolation.
Combinations of the stated parameters are not always possible; some parameters may require optional application packages.

Siemens AG, Medical Solutions
Magnetic Resonance
Henkestr. 127, D-91052 Erlangen
Germany
Telephone: +49 9131 84-0
www.SiemensMedical.com

Siemens **Medical Solutions** that help

Order-No. A91101-M2220-G10-1-7600
Printed in Germany
PA 09033.