




# Full data: eight-method comparison

















18,462 images × 50 epochs; three matched seeds. GRPO/RLOO configurations were selected by mean best validation MAE, without test outcomes. Moving means: 5 epochs (10 for 200-epoch runs); bands: between-seed sample SD where n=3. Axes emphasize later fit; the interactive viewer can show full training trajectories.


# Full data: scalar and categorical SL









Three matched seeds; all four settings use peak LR 0.001. Scalar label NLL is undefined and is omitted from that panel. Moving means: 5 epochs (10 for 200-epoch runs); bands: between-seed sample SD where n=3. Axes emphasize later fit; the interactive viewer can show full training trajectories.

# 1024 images × 200 epochs: eight tested methods


Validation mean-age MAE (years)





Validation mean-age RMSE (years)





Validation median Spearman (higher is better)





Validation label NLL (nats)










Seed 42. Adapted to the eight completed categorical settings: categorical MAE/MSE and both population GRPO rewards replace the unrun scalar, sampled-TailRL and RLOO settings. Moving means: 5 epochs (10 for 200-epoch runs); bands: between-seed sample SD where n=3. Axes emphasize later fit; the interactive viewer can show full training trajectories.



Statistical MaxRL: widths and estimators
Population
Validation mean-age MAE (years)
Population
Validation mean-age RMSE (years)
Population
Validation median Spearman (higher is better)
Population
Validation label NLL (nats)
64 samples
Validation mean-age MAE (years)
64 samples
Validation mean-age RMSE (years)
64 samples
Validation median Spearman (higher is better)
64 samples
Validation label NLL (nats)
Epoch
Stat MAE, w=2
Stat MSE, w=2
Stat MSE, w=5
CE
Stat MAE, w=5
Full data, three seeds per setting. Five shared legend entries control both estimator rows. Solid: width 2; dashed: width 5. The same exact CE reference appears in both rows. Rates are independently validation-selected; this is not a matched-LR intervention. Moving means: 5 epochs (10 for 200-epoch runs); bands: between-seed sample SD where n=3. Axes emphasize later fit; the interactive viewer can show full training trajectories.

# TailRL and supervised baselines













TailRL (64 samples)
TailRL (population)
Scalar MAE
CE


Full data × 50 epochs, three matched seeds: sampled TailRL, population TailRL, scalar MAE and CE. TailRL peak LR: population 0.0001; 64 samples 0.001. Rates are independently validation-selected. Moving means: 5 epochs (10 for 200-epoch runs); bands: between-seed sample SD where n=3. Axes emphasize later fit; the interactive viewer can show full training trajectories.


# Fixed training-label noise: four levels

























































4096 images × 50 epochs; optimization seed 42, noise seed 2026; held-out labels are clean. η = noise RMS / clean-age SD (about 0.05 at SD 1); conventional power SNR = 1/η². SD 3 replaces the unrun SD 2 by request. GRPO MAE is the best available clean-validation RL configuration; RLOO noise arms were not run. Moving means: 5 epochs (10 for 200-epoch runs); bands: between-seed sample SD where n=3. Axes emphasize later fit; the interactive viewer can show full training trajectories.


# Conditional two-digit policies: eight objectives




Seed 42. Eight conditional 10×10 objectives on full data × 50 epochs. No 1024 × 200 digit runs are available. All digit rates were selected on 4096 images; full-data digit runs reuse them. These panels contain digit policies only. Moving means: 5 epochs (10 for 200-epoch runs); bands: between-seed sample SD where n=3. Axes emphasize later fit; the interactive viewer can show full training trajectories.