

SCION Reference Manual

August 24, 2026

Title Spatiotemporal Clustering and Inference of Omics Networks

Version 5.0

Description Infers gene regulatory / omics networks from multi-omics data using random-forest based feature importance (a GENIE3-style approach), with optional pre-clustering of genes, permutation-based FDR thresholding of inferred edges, network visualization, and a Shiny app covering the full run / threshold / visualize workflow.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Depends R (>= 4.0.0)

Imports cluster,
doParallel,
dtw,
dtwclust,
fastICA,
ggplot2,
igraph,
parallel,
randomForest,
stats,
tools,
utils

Suggests cmapR,
htmltools,
htmlwidgets,
plotly,
shiny,
shinydashboard,
shinydashboardPlus,
shinyjs,
shinytest2,

shinyWidgets,
testthat (>= 3.2.0),
visNetwork

Config/testthat/edition 3

Contents

cluster_genes	2
compute_fdr_threshold	3
compute_outdegree	4
infer_network	5
launchApp	6
load_permutations	6
permute_network	7
plot_fdr_curve	9
plot_network	10
plot_outdegree_distribution	10
plot_weight_distribution	11
read_scion_inputs	12
RS.Get.Weight.Matrix	13
run_scion	14
save_diagnostic_plots	16
save_permutation	17
write_scion_network	18

cluster_genes	<i>Cluster genes prior to network inference</i>
---------------	---

Description

Computes a fixed gene-to-cluster assignment used by `infer_network()`. This assignment is computed once from the real, unpermuted data; when running permutations via `permute_network()`, the same assignment must be reused rather than recomputed, so that permuted networks are compared against the real network on identical gene groupings.

Usage

```
cluster_genes(  
  clustering_data = NULL,  
  method = c("none", "dtw", "ica", "kmeans", "upload"),  
  threshold = 0.5,  
  clusters_file = NULL,  
  target_data = NULL,  
  reg_data = NULL  
)
```

Arguments

clustering_data	data frame or matrix of expression data to cluster on (rows = genes, columns = samples). Ignored when method = "none". If NULL and method needs data ("dtw"/"ica"/"kmeans"), it is derived from target_data/reg_data – see Details.
method	clustering method: "none" (no clustering, one network for all genes), "dtw" (temporal, dynamic time warping), "ica" (non-temporal, independent component analysis), "kmeans" (non-temporal, k-means), or "upload" (use a pre-computed clusters file).
threshold	clustering threshold used by "dtw" and "ica"; ignored by "kmeans" and "upload".
clusters_file	path to a CSV of pre-computed clusters (first column = gene names, a clusters column with cluster numbers). Required when method = "upload".
target_data, reg_data	the processed target/regulator matrices (rows = genes, columns = samples). reg_data alone is also used by method = "kmeans" to pick a starting k (see Details); target_data is only used to derive clustering_data when it isn't supplied.

Details

When clustering_data is NULL and clustering is requested, it defaults to reg_data plus whatever rows of target_data aren't already in reg_data (regulator data takes precedence for genes that are both a target and a regulator) – i.e. the same genes that will be used for network inference, combined into one matrix. This matches the historical PANOPLY behavior of auto-deriving a clustering matrix from the target/regulator data when no separate clustering file is provided.

Value

a data frame with a clusters column (row names = gene names), or NULL when method = "none".

compute_fdr_threshold *Compute a permutation-based FDR and edge-weight cutoff*

Description

Ports the validated permutation-testing procedure exactly: for each rank position in the sorted, nonzero real network weights, computes an empirical p-value from how often permuted networks exceed the real weight at that rank, BH-adjusts across ranks, and picks the smallest real weight for which FDR is still below target_fdr.

Usage

```
compute_fdr_threshold(real_network, permuted_networks, target_fdr = 0.05)
```

Arguments

real_network	the real network's edge table (must have a Weight column), e.g. the network element of <code>run_scion()</code> 's result.
permuted_networks	a list of permuted edge tables, as returned by <code>permute_network()</code> , produced against the same real_network.
target_fdr	the FDR threshold to select a weight cutoff at (default 0.05).

Value

a list:	
curve	a data frame with one row per ranked real-network weight: weight, p_value, fdr – the input to <code>plot_fdr_curve()</code> .
threshold	the chosen edge-weight cutoff, or NA if no rank achieves target_fdr.
target_fdr	echoes the input.
thresholded_network	real_network filtered to Weight >= threshold.
permuted_weights	the rank x permutation matrix of (padded) permuted weights, useful for diagnostic plots.

compute_outdegree	<i>Compute each regulator's out-degree (number of edges) in a network</i>
-------------------	---

Description

Compute each regulator's out-degree (number of edges) in a network

Usage

```
compute_outdegree(network)
```

Arguments

network	an edge table with a Regulator column.
---------	--

Value

a data frame with Regulator and outdegree columns, one row per regulator that has at least one edge, sorted by decreasing out-degree.

infer_network

*Infer a (possibly clustered) network from target/regulator matrices***Description**

The core network-inference step of SCION, with no file I/O: given target and regulator expression matrices (genes as rows, samples as columns) and an optional, already-computed cluster assignment, infers one network per cluster (or a single network if `cluster_assignment` is `NULL`), optionally connects cluster hubs, and returns a single edge table. This function is called identically by `run_scion()` for the real network and by `permute_network()` for every permutation – it never recomputes clustering.

Usage

```
infer_network(
  target_data,
  reg_data,
  cluster_assignment = NULL,
  weightthreshold = 0,
  normalize = TRUE,
  connect_hubs = TRUE,
  num.cores = 1,
  ptm_sep = ".",
  seed = NULL,
  ...
)
```

Arguments

<code>target_data</code>	data frame/matrix, genes as rows, samples as columns.
<code>reg_data</code>	data frame/matrix, genes as rows, samples as columns.
<code>cluster_assignment</code>	optional data frame with a <code>clusters</code> column (row names = gene names), as returned by <code>cluster_genes()</code> . <code>NULL</code> means infer a single network across all genes.
<code>weightthreshold</code>	edges with weight below this value are dropped.
<code>normalize</code>	passed to <code>RS.Get.Weight.Matrix()</code> .
<code>connect_hubs</code>	if clustering, whether to additionally infer a network connecting each cluster's hub gene (highest out-degree regulator).
<code>num.cores</code>	passed to <code>RS.Get.Weight.Matrix()</code> .
<code>ptm_sep</code>	separator used to split a PTM-site regulator name into gene symbol + site (e.g. "." for <code>SOX2.S35</code> , "_" for <code>MEF2C_S453s</code>): when connecting cluster hubs and no hub gene is directly present in <code>target_data</code> 's row names, and always in the returned edge table (see <code>split_ptm_sites()</code>) so a PTM-annotated regulator and its plain-symbol target are recognized as the same gene.

seed	optional RNG seed set once, at the very start of this call (before clustering-aware seed draws or any inference). Without it, the result depends on the ambient global RNG state at call time – pass an explicit seed (or call <code>set.seed()</code> yourself right before calling) any time you need two calls to be comparable/reproducible.
...	additional arguments passed to <code>RS.Get.Weight.Matrix()</code> .

Value

a data frame with columns Regulator, Interaction, Target, Weight, or NULL if inference could not be run (e.g. no targets/regulators).

launchApp	<i>Launch the SCION Shiny app</i>
-----------	-----------------------------------

Description

A 3-tab app covering the full run -> permute/FDR -> visualize workflow. Requires shiny, shinydashboard, shinydashboardPlus, shinyjs, and plotly, which are Suggests (not hard dependencies) so that scripted/HPC use of the package doesn't require the Shiny stack to be installed.

Usage

```
launchApp(...)
```

Arguments

...	additional arguments passed to <code>shiny::shinyApp()</code> .
-----	---

Value

a shiny.appobj, as returned by `shiny::shinyApp()`.

load_permutations	<i>Read back permutation networks saved by save_permutation()</i>
-------------------	---

Description

Read back permutation networks saved by `save_permutation()`

Usage

```
load_permutations(dir = ".", prefix = "permutation")
```

Arguments

dir	directory to read from.
prefix	filename prefix used when saving (must match).

Value

a list of edge tables, named by permutation index (as a string) and ordered by increasing index – directly usable as the `permuted_networks` argument to `compute_fdr_threshold()`.

permute_network	<i>Generate permuted null networks for FDR thresholding</i>
-----------------	---

Description

Shuffles the target/regulator matrices and reruns `infer_network()` `n_permutations` times, reusing the SAME fixed `cluster_assignment` every time (clustering is never recomputed per permutation – see `cluster_genes()`). Ported from the validated lab procedure (`scion_data_processing.R`): each permutation `i` is seeded with `base_seed + i` before shuffling, which makes results independent of `num.cores` for the same reason the per-target-gene seeding in `RS.Get.Weight.Matrix()` does.

Usage

```
permute_network(
  target,
  reg,
  cluster_assignment = NULL,
  n_permutations = 100,
  indices = seq_len(n_permutations),
  permute_dim = c("col", "row"),
  base_seed = 0,
  num.cores = 1,
  weightthreshold = 0,
  normalize = TRUE,
  connect_hubs = TRUE,
  ptm_sep = ".",
  ...
)
```

Arguments

<code>target, reg</code>	the processed target/regulator matrices used for the real network (the <code>target/reg</code> elements of <code>run_scion()</code> 's result).
<code>cluster_assignment</code>	the fixed cluster assignment used for the real network (the <code>cluster_assignment</code> element of <code>run_scion()</code> 's result, or <code>NULL</code>).
<code>n_permutations</code>	number of permutations (typically 100). Ignored if <code>indices</code> is given explicitly.
<code>indices</code>	which permutation indices to run; each index <code>i</code> is seeded with <code>base_seed + i</code> , independent of every other index and of <code>num.cores</code> (see Details). Defaults to <code>seq_len(n_permutations)</code> , i.e. all of them in one call. Pass a single index – e.g. an HPC job array's task ID – to run just one permutation per job; see <code>save_permutation()/load_permutations()</code> for a file-based workflow built around exactly that pattern.

permute_dim	passed to <code>shuffle_matrix()</code> as dim; "col" (default) matches the validated lab scheme.
base_seed	permutation i uses seed base_seed + i. Default 0 reproduces the lab scheme (<code>set.seed(i)</code>).
num.cores	when > 2, the requested indices run across a FORK cluster (one permutation per worker at a time); each permutation's own <code>infer_network()</code> call is then forced to num.cores = 1 internally to avoid nesting parallelism. When num.cores <= 2, indices run serially (in this process or, for a single index, as whatever single HPC job called this) and their own num.cores is passed straight through to each <code>infer_network()</code> call.
weightthreshold	passed to <code>infer_network()</code> . Must match whatever was used for the real network (see normalize below), and should generally be 0: the FDR comparison in <code>compute_fdr_threshold()</code> needs the full, unthresholded network on both sides – a nonzero value applies the same manual cutoff before that comparison ever happens, biasing which edges get compared (see <code>run_scion()</code> , which enforces this automatically when calling this function with permute = TRUE).
normalize	passed to <code>infer_network()</code> . Must match whatever was used for the real network this permutation set will be compared against in <code>compute_fdr_threshold()</code> , and should generally be FALSE for both: normalizing rescales each network independently to [0, 1], forcing every permutation's top edge weight to exactly 1 regardless of its actual signal, which invalidates the rank-based FDR comparison (see <code>run_scion()</code> , which enforces this automatically when calling this function with permute = TRUE).
connect_hubs, ptm_sep	passed to <code>infer_network()</code> .
...	additional arguments passed to <code>infer_network()</code> .

Details

Emits a "SCION_STAGE: permutation testing progress <done>/<total>" message after every completed permutation (serial path) or every completed batch of num.cores - 1 permutations (parallel path – a single `parLapply()` call blocks until it returns, so there's no way to observe progress *within* one call; splitting the work into per-worker-sized batches trades a little dispatch overhead for a progress update roughly every num.cores - 1 permutations). The Shiny app's Run tab listens for these to drive its progress bar smoothly across the whole permutation phase instead of sitting still until it's all done.

Value

a list the same length as indices, each element an edge table as returned by `infer_network()`, named by its permutation index (as a string).

plot_fdr_curve	<i>Plot diagnostics from a permutation-based FDR result</i>
----------------	---

Description

Plot diagnostics from a permutation-based FDR result

Usage

```
plot_fdr_curve(
  fdr_result,
  type = c("curve", "fdr_hist", "weight_comparison"),
  permutation_index = 1,
  title = NULL,
  threshold = fdr_result$threshold,
  show_target_fdr_line = TRUE,
  label_lines = FALSE
)
```

Arguments

fdr_result	the output of compute_fdr_threshold() .
type	"curve" (default; weight vs. FDR scatter with the chosen threshold marked), "fdr_hist" (histogram of FDR values across ranks), or "weight_comparison" (real vs. one permuted network's weight distribution overlay).
permutation_index	which permuted network's weights to show for type = "weight_comparison" (default 1; matches permuted_networks[[1]] used to build fdr_result).
title	optional plot title – see plot_weight_distribution() 's title argument.
threshold	the edge-weight cutoff to mark on type = "curve" (a dashed vertical line, labeled with its value) – defaults to fdr_result\$threshold, but the caller can pass a different value (e.g. a manual cutoff that overrides the FDR-based one) so the marked line always reflects whichever cutoff is actually in effect. NULL/NA draws no line.
show_target_fdr_line	if TRUE (default), also draws a dashed horizontal line at fdr_result\$target_fdr. Set FALSE when threshold is a manual override, since the FDR target is no longer the criterion that produced it and showing it would be misleading.
label_lines	if FALSE (default), the threshold/target-FDR lines carry their value as plotly hover text only (via plotly::ggplotly()) – appropriate for the interactive app, where hovering is how you'd read a value off any other point on the plot too. If TRUE, also draws the value as permanent on-plot text, for contexts with no hover available (the static PDF export).

Value

a ggplot2 object.

plot_network	<i>Plot a SCION network</i>
--------------	-----------------------------

Description

A quick in-R sanity-check visualization – for anything beyond a few dozen nodes, or for a publication-quality figure, importing the edge table into Cytoscape (see [write_scion_network\(\)](#)) will still give better layout control. Both the static and interactive versions use the same visual encoding: regulators are blue squares, targets are orange circles, and edge width is proportional to weight.

Usage

```
plot_network(edge_table, interactive = FALSE, ...)
```

Arguments

edge_table	an edge table with Regulator, Target, Weight columns (e.g. the network element of run_scion() 's result, or a compute_fdr_threshold() result's thresholded_network).
interactive	if FALSE (default), plots via base igraph plotting (static). If TRUE, returns an interactive visNetwork HTML widget (requires the optional visNetwork package) with on-canvas zoom/pan controls.
...	additional arguments passed to <code>igraph::plot.igraph()</code> (static) or <code>visNetwork::visNetwork()</code> (interactive).

Value

for `interactive = FALSE`, invisibly returns the igraph object (after plotting it, with a legend, as a side effect); for `interactive = TRUE`, a visNetwork htmlwidget.

plot_outdegree_distribution	<i>Plot the distribution of regulator out-degrees in a network</i>
-----------------------------	--

Description

Plot the distribution of regulator out-degrees in a network

Usage

```
plot_outdegree_distribution(network, bins = 30, title = NULL)
```

Arguments

network	an edge table with a Regulator column.
bins	number of histogram bins.
title	optional plot title – see plot_weight_distribution() 's title argument.

Value

a ggplot2 object.

plot_weight_distribution

Plot the distribution of edge weights in a network

Description

Plot the distribution of edge weights in a network

Usage

```
plot_weight_distribution(
  network,
  bins = 100,
  cutoff = NULL,
  title = NULL,
  label_line = FALSE
)
```

Arguments

network	an edge table with a Weight column, e.g. the network element of run_scion() 's result. Always pass the full, unthresholded network here (not an already-filtered one) so cutoff is visible in context against the whole distribution.
bins	number of histogram bins.
cutoff	optional edge-weight cutoff (FDR-based or manual) to mark with a dashed vertical line. NULL (default) or NA draws no line.
title	optional plot title – NULL (default) omits it. The interactive app view skips this (its box header already names the plot); save_diagnostic_plots() and the app's PDF export set one, since an exported plot has no other title to identify it by.
label_line	if FALSE (default), the cutoff line carries its value as plotly hover text only (via plotly::ggplotly()) – appropriate for the interactive app. If TRUE, also draws the value as permanent on-plot text, for contexts with no hover available (the static PDF export).

Value

a ggplot2 object.

read_scion_inputs	<i>Read SCION input matrices from CSV or GCT files</i>
-------------------	--

Description

Reads target and regulator expression matrices (and, optionally, a separate clustering matrix), restricts each to a gene list if provided, and drops any row containing a missing value – SCION does not support missing values, so unlike the private-version `na.max` proportional filter, this is always an all-or-nothing drop.

Usage

```
read_scion_inputs(
  target_data_file,
  reg_data_file,
  target_genes_file = NULL,
  reg_genes_file = NULL,
  gene_list_header = TRUE,
  clustering_data_file = NULL,
  format = c("auto", "csv", "gct")
)
```

Arguments

target_data_file, reg_data_file	path to target/regulator expression matrices. CSV: first column = gene names, remaining columns = samples. GCT: a GCT(x) file, read via <code>cmapR::parse_gctx()</code> (requires the optional <code>cmapR</code> package – install with <code>BiocManager::install("cmapR")</code>).
target_genes_file, reg_genes_file	optional path to a file listing which genes to keep as targets/regulators (first column = gene names). NULL (default) keeps every gene present in the corresponding data file.
gene_list_header	whether target_genes_file/reg_genes_file have a header row. Default TRUE (matches this package's own tutorial data). Set to FALSE for a plain one-gene-symbol-per-line file with no header (e.g. PANOPLY's TF_file convention) – with the default TRUE, such a file would silently have its first gene misread as a column header and dropped.
clustering_data_file	optional path to a CSV clustering matrix (rows = genes, columns = samples), used by <code>cluster_genes()</code> . Restricted to genes that appear in target_genes_file or reg_genes_file when those are given.
format	"auto" (default), "csv", or "gct". "auto" detects GCT(x) from target_data_file's extension (.gct/.gctx) and falls back to CSV otherwise – pass "csv"/"gct" explicitly to override. Regulator gene names may use either a dot (SOX2.S35) or underscore (MEF2C_S453s) PTM-site convention; both are left as-is here (see

the `ptm_sep` argument of `infer_network()` for where the convention matters downstream).

Value

a list with `target` and `reg` data frames (genes as rows, samples as columns, row names made syntactically valid via `make.names()`), and `cluster_data` (or `NULL` if `clustering_data_file` was not given).

RS.Get.Weight.Matrix	<i>Infer a weighted regulator -> target network via random-forest importance</i>
----------------------	---

Description

For each target gene, fits a random forest predicting its expression from all regulator features, and records each regulator's importance as the edge weight. This is the GENIE3-style core of SCION's network inference, and is called identically for the real network and for every permutation generated by `permute_network()`.

Usage

```
RS.Get.Weight.Matrix(
  target.matrix,
  input.matrix,
  K = "sqrt",
  nb.trees = 10000,
  importance.measure = "%IncMSE",
  seed = NULL,
  trace = TRUE,
  normalize = TRUE,
  num.cores = 1,
  ...
)
```

Arguments

<code>target.matrix</code>	data frame/matrix of target expression, samples as rows, genes as columns.
<code>input.matrix</code>	data frame/matrix of regulator (input) expression, samples as rows, genes as columns.
<code>K</code>	number of candidate regulators considered at each tree split: "sqrt", "all", or an integer.
<code>nb.trees</code>	number of trees per random forest.
<code>importance.measure</code>	"IncNodePurity" or "%IncMSE".

seed	optional RNG seed for the top-level per-target seed draw. Must be set consistently between a real network and its permutations for the permutation seeding scheme in <code>permute_network()</code> to be reproducible.
trace	if TRUE, emit a progress message per target gene.
normalize	if TRUE, rescale the weight matrix to $[0, 1]$.
num.cores	number of cores to use: a <code>num.cores - 1</code> FORK cluster is used to parallelize across target genes (disabled when <code>num.cores <= 2</code>).
...	additional arguments passed to <code>randomForest::randomForest()</code> .

Value

a numeric matrix of edge weights (targets x regulators), or NULL if there are no targets or no regulators.

run_scion	<i>Run SCION: read inputs, cluster once, infer a network</i>
-----------	--

Description

User-facing wrapper around `read_scion_inputs()`, `cluster_genes()`, and `infer_network()`. Unlike the legacy `SCION()` function, this does not require a working directory or hardcode file output – it returns everything in memory, and optionally writes a Cytoscape-importable edge table if `output_file` is given. The returned list (particularly `target`, `reg`, and `cluster_assignment`) has everything `permute_network()` needs to run permutations against this same network without recomputing clustering.

Usage

```
run_scion(
  target_data_file,
  reg_data_file,
  target_genes_file = NULL,
  reg_genes_file = NULL,
  gene_list_header = TRUE,
  format = c("auto", "csv", "gct"),
  clustering_method = c("none", "dtw", "ica", "kmeans", "upload"),
  clustering_data_file = NULL,
  clustering_threshold = 0.5,
  clusters_file = NULL,
  connect_hubs = TRUE,
  weightthreshold = 0,
  normalize = TRUE,
  num.cores = 1,
  ptm_sep = ".",
  seed = 2020,
  permute = FALSE,
```

```

    n_permutations = 100,
    permute_dim = c("col", "row"),
    base_seed = 0,
    target_fdr = 0.05,
    output_file = NULL,
    ...
)

```

Arguments

target_data_file, reg_data_file, target_genes_file, reg_genes_file
 gene_list_header, format passed to [read_scion_inputs\(\)](#).

clustering_method
 passed to [cluster_genes\(\)](#) as method: "none" (default), "dtw", "ica", "kmeans", or "upload".

clustering_data_file
 path to a clustering matrix, required unless clustering_method is "none" or "upload".

clustering_threshold
 passed to [cluster_genes\(\)](#) as threshold.

clusters_file
 passed to [cluster_genes\(\)](#) as clusters_file, required when clustering_method = "upload".

connect_hubs, num.cores, ptm_sep
 passed to [infer_network\(\)](#).

weightthreshold
 passed to [infer_network\(\)](#). Forced to 0 (with a warning) whenever permute = TRUE, regardless of what's passed – the FDR comparison needs the full, unthresholded network on both sides; apply a cutoff to the result afterward instead (see [compute_fdr_threshold\(\)](#)).

normalize
 passed to [infer_network\(\)](#). Forced to FALSE (with a warning) whenever permute = TRUE, regardless of what's passed – normalizing rescales each network (real and every permutation) independently to [0, 1], which would force every permutation's top edge weight to exactly 1 and invalidate the rank-based FDR comparison.

seed
 RNG seed set once, before clustering and inference, so the same inputs produce the same network every run. Default matches the legacy SCION() behavior. Set to NULL to skip seeding.

permute
 if TRUE, also run [permute_network\(\)](#) and [compute_fdr_threshold\(\)](#) against the just-inferred network, in this same call. Runs n_permutations permutations using the SAME weightthreshold, normalize, connect_hubs, ptm_sep, num.cores, and ... used for the real network above – there is no separate way to set these for the permutations, since the FDR calculation requires them to match. For sharding permutations across an HPC job array instead of running them all in this one call, use permute = FALSE here and call [permute_network\(\)](#) / [save_permutation\(\)](#) / [load_permutations\(\)](#) directly against this call's target/reg/cluster_assignment.

n_permutations, permute_dim, base_seed
 passed to [permute_network\(\)](#) when permute = TRUE.

target_fdr	passed to <code>compute_fdr_threshold()</code> when <code>permute = TRUE</code> .
output_file	optional path to write the final edge table to (tab-separated, Cytoscape-importable). NULL (default) writes nothing. When <code>permute = TRUE</code> , writes the FDR-thresholded network, not the raw one. Also triggers <code>save_diagnostic_plots()</code> , saved alongside it (same directory, named from <code>output_file</code> 's base name) – there's no Shiny app to view/download them from interactively in this CLI/scripted path, so they're written automatically instead of requiring a separate call.
...	additional arguments passed to <code>infer_network() / RS.Get.Weight.Matrix()</code> (and, when <code>permute = TRUE</code> , to the internal <code>permute_network()</code> call as well, so e.g. <code>nb.trees</code> stays consistent between the real network and its permutations).

Value

a list with `network` (the real edge table), `target`, `reg` (the processed input matrices), `cluster_assignment` (or NULL), `params` (the arguments used, for reference / for feeding into `permute_network()` yourself), and – only when `permute = TRUE` – `permuted_networks` (the `permute_network()` result), `fdr_result` (the `compute_fdr_threshold()` result), and `network_thresholded` (shorthand for `fdr_result$thresholded_network`).

`save_diagnostic_plots` *Save SCION's diagnostic plots as publication-quality PDFs*

Description

Writes the edge weight distribution and regulator out-degree distribution (and, if permutations were run, the FDR curve and real-vs-permuted weight comparison) as separate single-plot PDFs via `ggplot2::ggsave()` – vector output, so resolution is never a concern. This is what `run_scion()` calls automatically whenever `output_file` is set (i.e. CLI/scripted use, where there's no app to view the interactive versions in); call it directly for any other `run_scion()` result you want plots from.

Usage

```
save_diagnostic_plots(
  result,
  dir,
  prefix = "diagnostics",
  width = 7,
  height = 5,
  units = "in"
)
```

Arguments

<code>result</code>	a <code>run_scion()</code> result list.
<code>dir</code>	directory to save into (created, recursively, if it doesn't exist).

prefix filename prefix for each saved plot.
width, height, units
 passed to `ggplot2::ggsave()`.

Value

invisibly, a character vector of the file paths written.

save_permutation	<i>Save one permutation's network to disk</i>
------------------	---

Description

Companion to [load_permutations\(\)](#) for an HPC job-array workflow: each array task runs one permutation (via `permute_network(..., indices = task_id)`) and saves its result with this function; a final job reads them all back with [load_permutations\(\)](#) and passes them to [compute_fdr_threshold\(\)](#).

Usage

```
save_permutation(network, index, dir = ".", prefix = "permutation")
```

Arguments

network a single permuted network (edge table), e.g. `permute_network(..., indices = task_id)[[1]]`.
index the permutation index this network corresponds to (e.g. the HPC job array task ID).
dir directory to save into (created if it doesn't exist).
prefix filename prefix; the file is saved as `<prefix>_<index>.rds`.

Value

the path written to, invisibly.

write_scion_network	<i>Write a SCION network to a Cytoscape-importable file</i>
---------------------	---

Description

Write a SCION network to a Cytoscape-importable file

Usage

```
write_scion_network(network, output_file)
```

Arguments

network	an edge table as returned in the network element of run_scion() 's result.
output_file	path to write to (tab-separated).