

Absolute-Value Threshold Preservation under Bounded Score Perturbations

Research Architecture Runtime

operator/absolute-value-threshold

2026-07-29

Abstract

`absolute-value-threshold` is a scalar region indicator preserved outside an ε -buffer under $|x' - x| \leq \varepsilon$. Lean `LEAN_FULL`.

This theorem is: Primitive

1 Problem

The `absolute-value-threshold` operator maps a scalar score to a discrete region label/bit.

2 Stability notion

Additive $|x' - x| \leq \varepsilon$; outputs agree when x is at least ε inside its region.

3 Definitions

Region boundaries are thresholds (sign at 0, abs-threshold at $T \geq 0$, interval $[L, U]$). Assumptions follow the Lean module.

4 Theorem

Theorem 1. *Under the module's buffer hypotheses, $|x' - x| \leq \varepsilon$ preserves the operator output; sharpness pushes across a boundary when the buffer fails.*

5 Intuition

Same one-dimensional buffer logic as thresholding, applied to the operator's cut set.

6 Examples

Example 2. For sign: $x = 2$, $\varepsilon = 0.5$ stays positive. For abs-threshold $T = 3$, $x = 5$, $\varepsilon = 0.2$ stays pass.

7 Proof

Write $|x' - x| \leq \varepsilon$. On the pass side of each cut, x is at least ε beyond the cut, so x' cannot cross it; on the fail side, x' cannot reach the cut. Sharpness uses a $\pm\varepsilon$ push from a point within ε of the boundary (Theorem ??), matching the Lean cases.

8 Formal statement

Lean module

`Research.Operators.AbsThreshold.Preservation`

Source file

`lean/Research/Operators/AbsThreshold/Preservation.lean`

Theorems

- `abs\_threshold\_preservation`
- `abs\_threshold\_sharpness`

Certificate

`lean/certificates/absolute-value-threshold/abs-threshold-preservation`

Status

`LEAN_FULL` on Mathlib $\mathbb{R}$ (`REAL_MATHLIB`)

9 Proof dependencies

- Interval arithmetic on $\mathbb{R}$.
- Threshold-style buffers.

10 Consequences

Scalar building block; related: thresholding, sign, multi-threshold.