

```
In [1]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.linear_model import LinearRegression
from sklearn.model_selection import train_test_split
from sklearn.metrics import r2_score
```

```
In [2]: df = pd.read_csv('house_price.csv')
df.head()
```

```
Out[2]:
```

	House Size	Bedrooms	Age of House	House Price
0	1500	3	10	350000
1	1800	3	8	400000
2	2000	4	5	450000
3	2200	4	2	475000
4	2500	5	15	525000

```
In [3]: X = df[['House Size', 'Bedrooms', 'Age of House']]
Y = df['House Price']
```

```
In [4]: X_train, X_test, Y_train, Y_test = train_test_split(X, Y, test_size=0.2, random_
```

```
In [5]: model = LinearRegression()
model.fit(X_train, Y_train)
```

```
Out[5]:
```

▼ LinearRegression ⓘ ?

► Parameters

```
In [6]: Y_pred = model.predict(X_test)
Y_pred
```

```
Out[6]: array([ 958198.91326438, 3084757.95178209, 2213923.0591368 ,
3676539.75229267, 1145827.56632132, 3989268.46066852,
1827657.81346492, 1706685.73548026, 2419439.6139755 ,
1275055.59897449])
```

```
In [7]: r2_score_value = r2_score(Y_test, Y_pred)
r2_score_value
print(f"R-squared Score: {r2_score_value}")
```

R-squared Score: 0.9987416757120748

```
In [ ]:
```